






DESCRIPTION OF SCENE

This view to the east shows a flat, rockstrewn landscape with a few small drifts of very fine-grained material scattered among the rocks (line 350, sample 2900). The rocks range from a centimeter to meters in size and are very similar to each other: subangular, equidimensional, and profusely pitted or vesicular. They have a narrower range of sizes (10-20 cm) than those of the Viking 1 site. The rocks appear to be evenly distributed out to the horizon. Barely visible in the far distance just above the horizon line 120, sample 3500) are several bright plateaus which may be ejecta lobes from the crater Mic, a large 160-km-diameter crater that lies about 170 km east of the lander. A trough 1 m wide and about 10 cm deep extends from left to right across the foreground 8 m in front of the lander (line 450, sample 2580; line 530, sample 3250). Several small drifts occur by the floor of the trough (line 430, sample 2600). The trough is part of a roughly polygonal network of troughs. A number of possible origins have been proposed for the troughs, some of which involve freezing and thawing, contraction cracks of cooling lava, or desiccation of clay soils.

The fine-grained material forming the surface between the blocks in the foreground is bound in a coherent crust 1 or 2 mm thick, that breaks into platy fragments when disturbed (line 1530, sample 2300).

The object at the right center of the scene (line 350, sample 2700) is the surface-sampler. The true form of the instrument is not apparent because its image is a mosaic of three pictures that were taken when the instrument was in different positions. These pictures were selected so that a minimum of the surface would be occulted. The box-like structure at the lower left (line 1150, sample 2300) is the housing or cover in which the meteorological instruments were stowed during the launch and transit to Mars. The meteorological boom and instrument were deployed after landing.

THE VIKING MISSION

Two Viking spacecraft, each consisting of an orbiter and lander, were launched from Kennedy Space Center on August 20 and September 9, 1975. The Viking 1 spacecraft arrived at Mars on June 19, 1976, and was placed in a highly elliptic orbit around the planet at a periastron altitude of nearly 1500 km. The orbiter camera was used in conjunction with other instrumental methods to find a suitable landing site for the lander. After about 30 days in orbit, the lander was separated from the orbiter, and on July 20, 1976, Viking Lander 1 touched down on the surface of Mars at lat. 22.483° N, and long. 47.968° W. (Morris and Jones, 1980) on the west edge of a large basin called Chryse Planitia. It landed in a stable position at a 3° tilt downward in the direction 284.9° clockwise from north.

The side of the lander on which the two cameras are mounted faces southeast. When the cameras are pointed in a direction normal to the front of the lander, the viewing direction is 141.6° clockwise from north along the horizon. The first picture from the surface of Mars, of an area near the lander's footpad 3, was taken immediately after landing by camera 2. During the ensuing 43 days, the camera responded to all commands and successfully carried out their assigned mission. On September 2, the activities of Lander 1 were reduced to accommodate the planned receipt of data from Viking Lander 2.

On September 3, 1976, Viking Lander 2 successfully landed on Utopia Planitia of Mars (47.966° N, 225.797° W), more than 6500 km northeast of Lander 1 (Mayo and others, 1977; Davies and others, 1978). Lander 2 faced approximately north and tilted 8.2° downward in the direction of 277.4° clockwise from north. The viewing direction of its camera when pointed in a direction normal to the front of the lander is 29.0° clockwise from north along the horizon. The camera on Viking Lander 2 operated successfully for 61 days until the primary mission of both landers was completed on November 15, 1976, at solar conjunction.

During the primary mission, 454 pictures of the martian surface were processed from Viking Lander 1 data and 582 pictures from Viking Lander 2 data. The extended mission of Viking began December 15, after solar conjunction, and ended in June 1978. During this period, an additional 1636 pictures were obtained from Lander 1 data and 1311 pictures from Lander 2 data. A comprehensive description of the Viking primary mission and the results of eight scientific experiments on board the landers were published in the Journal of Geophysical Research (v. 82, no. 28, Sept. 30, 1977; see References).

*Latitudes are geographic (see de Vaucouleurs and others, 1973).

VIKING LANDER MOSAICS

The Viking Lander cameras acquired many high-resolution pictures of the Chryse Planitia and Utopia Planitia landing sites. Each picture is the product of computer processing on Earth of digital-image data transmitted from Mars as a result of "camera events" initiated out by one of the lander camera systems. Further computer processing of data from a selected number of these events yielded a total of 10 mosaics. Two pairs of mosaics from Lander 1 data (one mosaic from each camera) consisted of one pair made from data taken in the morning (0700-0800 hours) and one pair made with data acquired in midafternoon (1400-1530 hours). Similarly, three pairs of mosaics for the Lander 2 site consisted of one pair between 0700 and 0800 hours, one pair at noon, and one pair between 1700 and 1800 hours.

Procedures used for processing the Viking Lander camera data were described by Levinthal and others (1977). The individual camera events used in each mosaic are identified in the outline of the accompanying camera view. Detailed descriptions and reproductions of these camera events were given by Tucker (1978). Copies of the Viking Lander pictures can be obtained from the National Space Science Data Center, Goddard Space Flight Center, Greenbelt, MD, 20771.

The Lander camera system (Huck and others, 1975a) has selectable focus settings for a depth of field from 1.2 m to infinity in the high-resolution (0.04° instantaneous field of view) mode. The survey (low-resolution) mode has an instantaneous field of view of 0.12°; this mode was used in the mosaics only where no high-resolution data were acquired. Each complete mosaic extends 342.2° in azimuth, from approximately 5° above the horizon to 60° below. A complete mosaic incorporates approximately 15 million picture elements (pixels). In order to manage the processing of such large data bases, each mosaic was compiled from four individual azimuthal sectors.

Most of the data used in the mosaics were selected from the primary mission. In some cases, extended-mission data were included where primary-mission coverage was absent or where the surface was obscured by the sampler arm. Further selection was made on the basis of optimum focus.

The image data were photometrically corrected (Huck and others, 1975b; Patterson and others, 1977; Wolfe and others, 1977) for differences caused by variations in exposure and for subsampling differences caused by minor timing delay variations in the pictures of the set. The geometry was then transformed to a local Mars horizon and corrected for geometric camera errors (Patterson and others, 1977; Wolfe, 1981). The corrected pixels composing a sector were then combined by the computer into a single image, and an optimum contrast correction was applied.

The mosaics are composites of the best pixels of all the Lander pictures used for each sector. In the computer mosaicking process, the image data derived from the camera events for each sector were assigned priorities on the basis of quality or detail. These data were examined by the computer in sequence according to the priorities, and the best pixels of each data set were used for the mosaic.

The computer formatting of the Viking Lander mosaics was done at the Image Processing Laboratories of the Jet Propulsion Laboratory of the California Institute of Technology, Pasadena, Calif., under the general supervision of Elliott C. Levinthal of the Department of Genetics, Stanford University, who represented the Viking Lander Imaging Team. A detailed description of the multiple steps involved in the construction of the Viking Lander mosaics and an acknowledgment of the many people who assisted in the project were given by Levinthal (1980).

GEOMETRY OF THE MOSAICS

The cameras on the Viking Lander acquire data by sampling in equal increments of elevation and azimuth angle. In the accompanying mosaic, 8 mm subtends a 1° horizontal or vertical angle, regardless of the place of measurement within the panorama. If the martian surface were flat, one pixel (0.04°) on the surface would be 1 mm wide at 60° camera elevation and 2 m wide at the horizon 3 km away. Characteristically for this type of imaging system, most straight lines in the scene appear curved in the reconstruction. This representation of the picture data differs from that of a conventional camera having "point perspective" picture geometry, in which rays are projected from object space, through the perspective point in the camera lens, to an image plane in the camera.

The geometry of the lander pictures is complicated by additional factors. Because both landers are tilted with respect to the horizon, on the uncorrected pictures the horizon resembles a sine curve. Computer rectification of the pictures results in a straight horizon along which vertical angles can be measured with respect to the local gravity vector, and horizontal angles can be measured from martian north. These angles are not related in any simple way to the azimuth and elevation angles given in "camera coordinates" for the uncorrected pictures.

There are other geometric distortions due to the camera: optic path distortion that affects a light ray after it passes the camera window; and camera-system distortions, or "bold-down" errors, that are caused by the way the cameras are mounted on the lander. The geometric transformation used in creating the mosaics took into account the optic path distortion but not the "bold-down" errors. However, along the horizon, the error in azimuth angle is equal to the rotational "bold-down" error for each camera to an accuracy of less than 1 pixel. The scale "azimuth angles from Mars" has been adjusted to take into account this correction.

The residual azimuth angle errors are less than 1 pixel along the horizon and become larger with steeper elevation angles and large lander tilts. For the worst case, Lander 2, camera 1, this error is a maximum of 5.7 ± 1 pixel at 60° elevation. The somewhat azimuthal-angle-dependent residual elevation error is a maximum of 3 ± 1 pixel for Lander 2, camera 1, and approximately 1 pixel for the other cameras.

REFERENCES

- Davies, M. E., Katayama, T. Y., and Roth, J. A., 1978, Control of Mars: February 1978. Rand Corp. R-2309, NASA, 91 p.
- Huck, F. O., McColl, H. F., Patterson, W. R., and Taylor, G. R., 1975a, The Viking Mars Lander camera: Space Science Instruments, v. 1, no. 2, p. 189-241.
- Huck, F. O., Burcher, E. L., Taylor, E. J., and Wall, S. D., 1975b, Radiometric performance of the Viking Mars Lander cameras. U. S. National Aeronautics and Space Administration Technical Memorandum TMX-73692.
- Levinthal, E. C., and Jones, K. L., 1980, The mosaics of Mars as seen by the Viking Lander cameras, NASA Contractors Report, 3326.
- Levinthal, E. C., Green, William, Jones, K. L., and Tucker, Robert, 1977, Processing the Viking Lander camera data. Journal of Geophysical Research, v. 82, no. 28, p. 4415-4420.
- Mayo, W. H., Jr., Kelly, G. M., Brenkle, J. P., and Kornick, J. A., 1977, Lander locations, Mars physical ephemeris, and solar system measurements. Determination from Viking Lander tracking data. Journal of Geophysical Research, v. 82, no. 28, p. 4391-4400.
- Tucker, R. B., 1978, Viking Lander imaging investigation—picture catalog of primary mission experiment data record: National Aeronautics and Space Administration Reference Publication 1007, 258 p.
- de Vaucouleurs, G. D., Davies, M. E., and Strum, F. M., Jr., 1973, The Mariner 9 stereographic coordinate system. Journal of Geophysical Research, v. 78, no. 20, p. 4395-4402.
- Wolfe, M. R., 1981, Viking Lander camera geometry calibration report. California Institute of Technology, Jet Propulsion Laboratory Publication 79-54, v. 1, 36 p.
- Wolfe, M. R., Atwood, D. L., and Morrill, M. E., 1977, Viking Lander camera radiometry calibration report. California Institute of Technology, Jet Propulsion Laboratory Publication 77-62, v. 1, 90 p.

VIKING LANDER 2 RECTIFIED PHOTOMOSAIC MORNING SCENE - CAMERA 1 - SECTOR 4