

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

TEXT TO ACCOMPANY:  
COAL RESOURCE OCCURRENCE  
AND  
COAL DEVELOPMENT POTENTIAL  
MAPS  
OF THE  
FORT RENO SE QUADRANGLE,  
JOHNSON AND CAMPBELL COUNTIES, WYOMING

BY

INTRASEARCH INC.

ENGLEWOOD, COLORADO

OPEN FILE REPORT 79-180

1980

This report was prepared under contract to the U.S. Geological Survey and has not been edited for conformity with Geological Survey standards and nomenclature. Opinions, and conclusions expressed herein do not necessarily represent those of the Geological Survey.

## TABLE OF CONTENTS

	<u>PAGE</u>
I. INTRODUCTION	1
II. GEOLOGY	3
III. DATA SOURCES	9
IV. COAL BED OCCURRENCE	10
V. GEOLOGICAL AND ENGINEERING MAPPING PARAMETERS	15
VI. COAL DEVELOPMENT POTENTIAL	18
Table 1.--Coal Reserve Base Data (in short tons) for Underground Mining Methods for Federal Coal Lands in the Fort Reno SE Quadrangle, Johnson and Campbell Counties, Wyoming.	21
Table 2.--Coal Reserve Base Data (in short tons) for in-Situ Gasification for Federal Coal Lands in the Fort Reno SE Quadrangle, Johnson and Campbell Counties, Wyoming.	22
SELECTED REFERENCES	23

TABLE OF CONTENTS (continued)

<u>MAPS</u>	<u>PLATES</u>
1. Coal Data Map	1
2. Boundary and Coal Data Map	2
3. Coal Data Sheet	3 A & B
4. Isopach Map of Smith Coal Bed	4
5. Structure Contour Map of Smith Coal Bed	5
6. Isopach Map of Overburden of Smith Coal Bed	6
7. Areal Distribution of Identified Resources of Smith Coal Bed	7
8. Identified Resources of Smith Coal Bed	8
9. Isopach Map of Local "A" Coal Bed	9
10. Structure Contour Map of Local "A" Coal Bed	10
11. Isopach Map of Overburden of Local "A" Coal Bed	11
12. Areal Distribution of Identified Resources of Local "A" Coal Bed	12
13. Identified Resources of Local "A" Coal Bed	13
14. Isopach Map of Upper-Middle Wyodak Coal Beds	14
15. Structure Contour Map of Upper-Middle Wyodak Coal Beds	15
16. Isopach Map of Overburden of Upper-Middle Wyodak Coal Beds	16
17. Areal Distribution of Identified Resources of Upper-Middle Wyodak Coal Beds	17
18. Identified Resources of Upper-Middle Wyodak Coal Beds	18
19. Isopach Map of Lower Wyodak Coal Bed	19
20. Structure Contour Map of Lower Wyodak Coal Bed	20

TABLE OF CONTENTS (continued)

<u>MAPS</u>	<u>PLATES</u>
21. Isopach Map of Overburden of Lower Wyodak Coal Bed	21
22. Areal Distribution of Identified Resources of Lower Wyodak Coal Bed	22
23. Identified Resources of Lower Wyodak Coal Bed	23
24. Isopach Map of Wall Coal Bed	24
25. Structure Contour Map of Wall Coal Bed	25
26. Isopach Map of Overburden of Wall Coal Bed	26
27. Areal Distribution of Identified Resources of Wall Coal Bed	27
28. Identified Resources of Wall Coal Bed	28
29. Isopach Map of Local "B" Coal Bed	29
30. Structure Contour Map of Local "B" Coal Bed	30
31. Isopach Map of Overburden of Local "B" Coal Bed	31
32. Areal Distribution of Identified Resources of Local "B" Coal Bed	32
33. Identified Resources of Local "B" Coal Bed	33
34. Isopach Map of Pawnee Coal Bed	34
35. Structure Contour Map of Pawnee Coal bed	35
36. Isopach Map of Overburden of Pawnee Coal Bed	36
37. Areal Distribution of Identified Resources of Pawnee Coal Bed	37
38. Identified Resources of Pawnee Coal Bed	38
39. Isopach Map of Wildcat-Moyer Coal Zone	39
40. Structure Contour Map of Wildcat-Moyer Coal Zone	40

TABLE OF CONTENTS (continued)

	<u>MAPS</u>	<u>PLATES</u>
41.	Isopach Map of Overburden of Wildcat-Moyer Coal Zone	41
42.	Areal Distribution of Identified Resources of Wildcat-Moyer Coal Zone	42
43.	Identified Resources of Wildcat-Moyer Coal Zone	43
44.	Coal Development Potential for In-Situ Gasification	44

CONVERSION TABLE

<u>TO CONVERT</u>	<u>MULTIPLY BY</u>	<u>TO OBTAIN</u>
inches	2.54	centimeters (cm)
feet	0.3048	meters (m)
miles	1.609	kilometers (km)
acres	0.40469	hectares (ha)
tons (short)	0.9072	metric tons (t)
cubic yards/ton	0.8428	cubic meters/ metric ton
acre-feet	0.12335	hectare-meters
British thermal units/pound (Btu/lb)	2.326	kilojoules/kilogram (kj/kg)
British thermal units/pound (Btu/lb)	0.55556	kilocalories/kilogram (kcal/kg)
Fahrenheit	5/9 (F-32)	Celsius

I. Introduction

This report and accompanying maps set forth the Coal Resource Occurrence (CRO) and Coal Development Potential (CDP) of coal beds within the Fort Reno SE Quadrangle, Johnson and Campbell Counties, Wyoming. This CRO and CDP map series includes 45 plates (U. S. Geological Survey Open-File Report 79-180). The project is compiled by IntraSearch Inc., 5351 South Roslyn Street, Englewood, Colorado, under KRCRA Eastern Powder River Basin, Wyoming, Contract Number 14-08-0001-17180. This contract is a part of a program to provide an inventory of unleased federal coal in Known Recoverable Coal Resource Areas (KRCRAs) in the western United States.

The Fort Reno SE Quadrangle is located in Johnson and Campbell Counties, Wyoming. It encompasses all or parts of Townships 44 and 45 North, Ranges 76 and 77 West, and covers the area: 43°45' to 43°52'30" north latitude; 106°00' to 106°07'30" west longitude.

Access to the Fort Reno SE Quadrangle is provided by unimproved roads which extend throughout much of the study area. Minor trails provide additional access to the more remote areas. A short segment of maintained road is located along the east-central boundary of the quadrangle, extending to Gillette, approximately 44 miles (71 km) to the northeast. The closest railroad is the Burlington Northern trackage approximately 32 miles (51 km) to the east near the Black Thunder coal mine.

The most significant drainage is provided by northwest-flowing Willow Creek which meanders across the north-central and eastern parts of

the study area. Willow Creek drains into the Powder River approximately 4.5 miles (7.2 km) to the northwest <sup>of the quadrangle.</sup> Minor streams supplement this drainage throughout the remainder of the quadrangle. Elevations attain heights of 5,060 feet (1,542 m) above sea level in the southern half of the quadrangle, and 550 to 650 feet (168 to 198 m) above the Willow Creek valley floor.

The 10 to 12 inches (25 to 30 cm) of annual precipitation falling in this semi-arid region accrue principally in the springtime. Summer and fall precipitation usually originates from thunderstorms, and infrequent snowfalls of 6 inches (15 cm) or less generally characterize winter precipitation. Although temperatures ranging from less than -25°F (-32°C) to more than 100°F (38°C) have been recorded near Arvada, Wyoming, average wintertime minimums and summertime maximums range from +5° to +15°F (-15° to -9°C) and 75° to 90°F (24° to 32°C), respectively.

Surface ownership is divided among fee, state, and federal categories with the state and federal surface generally leased to ranchers for grazing purposes. Details of surface ownership are available at the Johnson and Campbell County Courthouses in Buffalo and Gillette, Wyoming, respectively. Details of mineral ownership on federal lands are available from the U. S. Bureau of Land Management in Cheyenne, Wyoming. Federal coal ownership is shown on plate 2 of the Coal Resource Occurrence maps. The non-federal coal ownership comprises both fee and state coal resources.

The Coal Resource Occurrence and Coal Development Potential program pertains to unleased federal coal and focuses upon the delineation

of lignite, subbituminous coal, bituminous coal, and anthracite at the surface, and in the subsurface. In addition, the program identifies total tons of coal in place, <sup>(resources)</sup> as well as recoverable tons, <sup>(reserves)</sup> These coal tonnages are then categorized in measured, indicated, and inferred *parts of identified* resources, and hypothetical resources. Finally, recommendations are made regarding the potential for surface mining, underground mining, and in-situ gasification of the coal beds. This report evaluates the coal resources of all unleased federal coal beds in the quadrangle which are 5 feet (1.5 m) or greater in thickness and occur at depths down to 3,000 feet (914 m). No resources or reserves are computed for leased federal coal, state coal, fee coal, or lands encompassed by coal prospecting permits and preference-right lease applications.

Surface and subsurface geological and engineering extrapolations drawn from the current data base suggest the occurrence of approximately 8.9 billion tons (8.1 billion metric tons) of total, unleased federal coal-in-place in the Fort Reno SE Quadrangle.

The suite of maps that accompanies this report sets forth and portrays the coal resource and reserve occurrence in considerable detail. For the most part, this report supplements the cartographically displayed information with minimum verbal duplication of the CRO-CDP map data.

## II. Geology

Regional. The thick, economic coal deposits of the Powder River Basin in northeastern Wyoming occur mostly in the Tongue River Member of the Fort Union Formation, and in the lower part of the Wasatch

Formation. Approximately 3,000 feet (914 m) of the Fort Union Formation, including the Tongue River, Lebo, and Tullock Members of Paleocene age, are unconformably overlain by approximately 700 feet (213 m) of the Wasatch Formation of Eocene age. These Tertiary formations lie in a structural basin flanked on the east by the Black Hills uplift, on the south by the Hartville and Casper Mountain uplifts, and on the west by the Casper Arch and the Big Horn Mountain uplift. The structural configuration of the Powder River Basin originated in Late Cretaceous time, with episodic uplift thereafter. The Cretaceous Cordillera was the dominant positive land form throughout the Rocky Mountain area at the close of Mesozoic time.

Outcrops of the Wasatch Formation and the Tongue River Member of the Fort Union Formation cover most of the areas of the major coal resource occurrence in the Powder River Basin. The Lebo Member of the Fort Union Formation is mapped at the surface northeast of Recluse, Wyoming. The Lebo Member is east of the principal coal outcrops and associated clinkers (McKay, 1974), and it presumably projects into the subsurface beneath much of the basin. One of the principal characteristics for separating the Lebo and Tullock Members (collectively referred to as the Ludlow Member east of Miles City, Montana) from the overlying Tongue River Member is the color differential between the lighter-colored upper portion and the somewhat darker lower portion (Brown, 1958). Although geologists are trying to develop criteria for subsurface recognition of the Lebo-Tullock and Tongue River-Lebo contacts through use of subsurface data from geophysical logs, no definitive guidelines

are known to have been published. Hence, for subsurface mapping purposes, the Fort Union Formation is not divided into its member subdivisions for this study.

During the Paleocene epoch, the Powder River Basin tropical to subtropical depositional environment included broad, inland flood basins with extensive swamps, marshes, freshwater lakes, and a sluggish, but active, northeastward-discharging drainage system. These features were superimposed on an emerging sea floor, near base level. Much of the vast area where organic debris collected was within a reducing depositional environment. Localized uplifts began to disturb the near sea level terrain of northeastern Wyoming, following retreat of the Cretaceous seas. However, the extremely fine-grained characteristics of the Tongue River Member clastics suggest that areas of recurring uplift peripheral to the Powder River Basin were subdued during major coal deposit formation.

The uplift of areas surrounding the Powder River Basin created a structural basin of asymmetric character, with the steep west flank located on the eastern edge of the Big Horn Mountains. The axis of the Powder River Basin is difficult to specifically define, but it is thought to be located in the western part of the Basin, and to display a north-south configuration some 15 to 20 miles (24 to 32 km) east of Sheridan, Wyoming. Thus, the sedimentary section described in this report lies on the east flank of the Powder River Basin, with gentle dips of 2 degrees or less disrupted by surface structure thought to relate to tectonic adjustment and differential compaction.

Some coal beds in the Powder River Basin exceed 200 feet (61 m) in thickness. Deposition of these thick, in-situ coal beds requires a delicate balance between subsidence of the earth's crust and in-filling of these areas by tremendous volumes of organic debris. These conditions, in concert with a favorable ground water table, non-oxidizing clear water, and a climate amenable to the luxuriant growth of vegetation produce a stabilized swamp critical to the deposition of coal beds.

Deposition of the unusually thick coal beds of the Powder River Basin may be partially attributable to short-distance water transportation of organic detritus into areas of crustal subsidence. Variations of coal bed thickness throughout the basin relate to changes in the depositional environment. Drill hole data that indicate either the complete absence or extreme attenuation of a thick coal bed probably relate to location of the drill holes within the ancient stream channel system servicing this lowland area in Early Cenozoic time. Where thick coal beds thin rapidly from the depocenter of a favorable depositional environment, it is not unusual to encounter a synclinal structure over the maximum coal thickness due to the differential compaction between organic debris in the coal depocenter and fine-grained clastics in the adjacent areas.

The Wasatch Formation of Eocene age crops out over most of the central part of the Powder River Basin and exhibits a disconformable contact with the underlying Fort Union Formation. The contact has been placed at various horizons by different workers; however, for the

purpose of this report, the contact is positioned near the top of the Roland coal bed as mapped by Olive (1957) in northwestern Campbell County, Wyoming. It is considered to disconformably descend in the stratigraphic column to the top of the Wyodak-Anderson coal bed (Roland coal bed of Taff, 1909) along the eastern boundary of the coal measures. No attempt is made to differentiate the Wasatch and Fort Union Formations on geophysical logs or in the subsurface mapping program for this project.

Although Wasatch and Fort Union lithologies are too similar to allow differentiation in some areas, most of the thicker coal beds occur in the Fort Union section on the east flank of the Powder River Basin. Furthermore, orogenic movements peripheral to the basin apparently increased in magnitude during Wasatch time causing the deposition of friable, coarse-grained to gritty, arkosic sandstones, fine to very fine-grained sandstones, siltstones, mudstones, claystones, brown-to-black carbonaceous shales, and coal beds. These sediments are noticeably to imperceptibly coarser than the underlying Fort Union clastics.

The Fort Reno SE Quadrangle is located in an area where surface rocks are classified within the Wasatch Formation. Although the Wasatch Formation is reportedly up to 1,800 feet (549 m) thick (Denson and Horn, 1975), Olive (1957) mapped 700 to 800 feet (213 to 244 m). Only 600 to 700 feet (183 to 213 m) of Wasatch Formation are exposed in the quadrangle. Olive (1957) correlated coal beds in the Spotted Horse coal field with coal beds in the northward extension of the Sheridan coal field, Montana

(Baker, 1929), and Gillette coal field, Wyoming (Dobbin and Barnett, 1927), and with coal beds in the Ashland coal field (Bass, 1932) in southeastern Montana. This report utilizes, where possible, the coal bed nomenclature used in previous reports. The Smith coal bed was named by Taff (1909). Baker (1929) assigned the name to the Wall coal bed, and the Pawnee coal bed was named by Warren (1959). IntraSearch (1978, 1979), informally named the Wildcat and Moyer coal beds.

IntraSearch's correlation of thick coal beds from the Spotted Horse coal field to Gillette points out that the Wyodak coal bed, named the "D" coal bed by Dobbin and Barnett (1927), is equivalent to the Anderson, Canyon and all, or part, of the Cook coal beds to the north and west of Gillette, Wyoming. Correlation of this suite of coal beds with the Wyodak coal bed south and southwest of Gillette suggests that the Anderson and Canyon coal beds equate with the upper 10 to 25 percent of the thick Wyodak coal bed, and the Cook and Wall, or Upper Wall, coal beds are equivalent to the major part of the Wyodak coal bed. Due to problematic correlations outside of the Gillette area, the name Wyodak has been informally used by many previous authors to represent the coal beds in the area surrounding the Wyodak coal mine.

Local. The Fort Reno SE Quadrangle lies on the eastern flank of the Powder River Basin, where the strata dip gently westward. The Wasatch Formation crops out over the entire quadrangle and is composed of friable, coarse-grained to gritty, arkosic sandstones, fine to very fine-grained sandstones, siltstones, mudstones, claystones, brown-to-black carbonaceous shales, and coal beds.

III. Data Sources

Within the Fort Reno SE Quadrangle, no significant coal outcrops or associated clinker are mapped in any publications known to IntraSearch at the time of this report. It is presumed and highly possible that no significant coal outcrops exist at the surface in the Fort Reno SE Quadrangle.

Geophysical logs from oil and gas test bores and producing wells compose the source of subsurface control. Some geophysical logs are not applicable to this study, for the logs relate only to the deep, potentially productive oil and gas zones. More than 80 percent of the logs include resistivity, conductivity, and self-potential curves. Occasionally, the suite of geophysical logs includes gamma, density, and sonic curves. These logs are available from several commercial sources.

All geophysical logs available in the quadrangle and its 3-mile perimeter area were scanned to select those with data applicable to Coal Resource Occurrence mapping. Paper copies of the logs were obtained and interpreted, and coal intervals were annotated. Maximum accuracy of coal bed identification was accomplished where gamma, density and resistivity curves were available. Coal bed tops and bottoms were identified on the logs at the midpoint between the minimum and maximum curve deflections. The correlation of coal beds within and between quadrangles was achieved utilizing a fence diagram to associate local correlations with regional coal occurrences.

The reliability of correlations, set forth by IntraSearch in

this report, varies depending on: the density and quality of lithologic and geophysical logs; the details, thoroughness, and accuracy of published and unpublished surface geological maps, and interpretative proficiency. There is no intent on the part of IntraSearch to refute nomenclature established in the literature or used locally by workers in the area. IntraSearch's nomenclature focuses upon the suggestion of regional coal bed names applicable throughout the eastern Powder River Basin. It is expected and entirely reasonable that some differences of opinion regarding correlations, as suggested by IntraSearch, exist. Additional drilling for coal, oil, gas, water, and uranium, coupled with expanded mapping of coal bed outcrops and associated clinkers, will broaden the data base for coal bed correlations and allow continued improvement in the understanding of coal bed occurrences in the eastern Powder River Basin.

The topographic map of the Fort Reno SE Quadrangle is published by the U. S. Geological Survey, compilation date 1953. Land network and mineral ownership data are compiled from land plats available from the U. S. Bureau of Land Management in Cheyenne, Wyoming. This information is current to October 13, 1977.

IV. Coal Bed Occurrence

The Wasatch <sup>Formation</sup> and Fort Union Formation coal beds that are present in all or part of the Fort Reno SE Quadrangle include, in descending stratigraphic order: the Smith, Local "A", Upper Wyodak, Middle Wyodak, Lower Wyodak, Wall, local, Local "B", local, local, Pawnee, Wildcat, and Moyer coal beds. The Wildcat coal bed, and the Moyer coal beds are mapped together as a coal zone. A suite of maps composed of: coal isopach; structure; overburden isopach; areal distribution of identified resources; and identified resources is prepared for each of these coal beds or coal zones.

No physical or chemical analyses are known to have been published regarding the coal beds in the Fort Reno SE Quadrangle. For Campbell and eastern Johnson County coal beds, the "as received" proximate analysis; the Btu value computed on a moist, mineral-matter-free basis;\* and the coal rank are as follows:

COAL BED NAME	DATA SOURCE IDENTIFICATION	AS RECEIVED BASIS						MOIST, M-M-F BTU/LB	COAL RANK
		ASH %	FIXED CARBON %	MOISTURE %	VOLATILES %	SULFUR %	BTU/LB		
	Lab.No.								
Felix (**)	6432	5.6	35.7	25.8	32.9	0.39	8465	9010	Subbtm. C
	Lab.No.								
Smith Upper (**)	6460	4.7	34.0	28.8	32.5	0.46	7862	8280	Lignite A
	Hole								
Wyodak (U)	7310	5.9	33.9	29.1	31.2	0.44	8172	8722	Subbtm. C
	Hole								
Middle-Lower Wyodak (U)	7334	5.1	34.9	29.4	30.5	0.28	8329	8814	Subbtm. C
	Hole								
Pawnee (U)	7424	7.9	31.0	31.9	29.2	0.39	7344	8025	Lignite A
	Lab.No.								
"Wildcat" (1)	11447	4.3	29.4	27.8	29.4	0.27	8410	8818	Subbtm. C

\* The moist, mineral-matter-free Btu values are calculated in the manner stipulated in the publication by American Society for Testing and Materials (1971).

\*\* Stone and Lupton (1910).

(U) U. S. Geological Survey and Montana Bureau of Mines and Geology (1974 and 1976).

(1) Winchester (1912).

The proximate analyses presented above are from core hole or outcrop locations in excess of 20 miles (32 km) from this quadrangle. For simplification of tonnage computations, all coal beds in the Fort Reno SE Quadrangle are tentatively classified as subbituminous C rank.

The Coal Data sheets, plates 3A and 3B, shows the down-hole identification of coal beds within the quadrangle as interpreted from

U. S. Geological Survey and Montana Bureau of Mines and Geology drill holes and geophysical logs from oil and gas test bores and from producing sites. This portrayal is schematic by design; hence, no structural or coal thickness implications are suggested by the dashed correlation lines projected through No Record (NR) intervals. Inasmuch as the Upper Wyodak coal bed underlies the entire quadrangle, it is designated as datum for the correlation diagram. The Upper, Middle and Lower Wyodak coal beds show a thick coal bed occurrence throughout the study area. The remaining coal beds are relatively thin throughout the Fort Reno SE Quadrangle.

The Smith coal bed is a thin, lenticular coal bed occurring approximately 600 to 1,150 feet (183 to 351 m) beneath the surface. The coal bed thickness ranges from 0 to 7 feet (0 to 2.1 m) with maximum thicknesses located across the central part of the study area. The Smith coal bed is absent from approximately 6 percent of the quadrangle in the southern half. Structure contours drawn on top of the Smith coal bed show a small, west-plunging anticline extending across the southern half of the study area. In the northern half of the quadrangle, the Smith coal bed dips to the west with minor structural flexures.

The Local "A" coal bed lies approximately 375 to 585 feet (114 to 178 m) below the overlying Smith coal bed. The coal bed ranges from 0 to 26 feet (0 to 8 m) in thickness and exhibits a sporadic occurrence. Maximum thicknesses occur in the southeast quarter of the quadrangle. It is absent from approximately 75 percent of the quadrangle,

occurring primarily in the southeast and northwest quarters of the study area. The structure contours drawn on top of the Local "A" coal bed depict shallow southwest dip. The Local "A" coal bed occurs between 950 and 1,650 feet (290 and 503 m) beneath the surface.

The Upper-Middle Wyodak coal beds occur approximately 50 to 150 feet (15 to 46 m) below the Local "A" coal bed and approximately 350 to 650 feet (107 to 198 m) below the overlying Smith coal bed where the Local "A" coal bed is absent. The coal bed thickness varies from 72 to 122 feet (22 to 37 m) with maximum thicknesses occurring in the southeast quarter of the quadrangle. A non-coal interval ranging from 0 to 194 feet (0 to 59 m) separates the Upper Wyodak coal bed from the Middle Wyodak coal bed. These coal beds are separated throughout most of the western half of the study area. The dominant structural features in the Fort Reno SE Quadrangle are two, southeast-trending anticlines that occur in the southwest quarter and east-central area. A syncline separates these two anticlinal features. Another syncline is present in the northeast quarter of the quadrangle. The Upper-Middle Wyodak coal beds occur between 1,050 and 1,700 feet (320 and 518 m) beneath the surface.

The Lower Wyodak coal bed lies approximately 0 to 145 feet (0 to 44 m) beneath the Middle Wyodak coal bed. The Lower Wyodak coal bed and Middle Wyodak coal bed are together in the southeast quarter of the quadrangle. The coal bed thickness ranges from 22 to 43 feet (7 to 13 m) with maximum thicknesses occurring along the northern border

and southeast quarter of the study area. A non-coal interval ranging from 0 to 67 feet (0 to 20 m) separates two parts of the Lower Wyodak coal bed, primarily in the northwest quarter of the quadrangle.

Structure contours drawn on top of the Lower Wyodak coal bed indicate a westward dip with minor flexures. A broad, northwest-plunging syncline occurs in the western half of the quadrangle. The Lower Wyodak coal bed occurs from 1,300 to 1,900 feet (396 to 579 m) beneath the surface.

The Wall coal bed occurs approximately 35 to 110 feet (11 to 34 m) beneath the overlying Lower Wyodak coal bed. The coal bed thickness ranges from 4 to 12 feet (1.2 to 4 m) with maximum thickness occurring in the northwest, southeast, and southwest quarters of the quadrangle. A northwest-trending syncline occurs in the central area. The Wall coal bed lies between 1,400 and 1,900 feet (427 and 579 m) beneath the surface of the quadrangle.

The Local "B" coal bed occurs approximately 95 to 160 feet (29 to 49 m) below the overlying Wall coal bed. This thin coal bed varies from 1 to 9 feet (0.3 to 2.7 m) in thickness with maximum thicknesses occurring in the northwest and southwest quarters of the study area. Structure contours drawn on top of the Local "B" coal bed indicate a shallow, northwest-plunging syncline along the western boundary of the quadrangle. The Local "B" coal bed occurs between 1,550 and 2,100 feet (472 and 640 m) beneath the surface.

The Pawnee coal bed occurs approximately 190 to 235 feet (58 to 72 m) beneath the Local "B" coal bed, and ranges in thickness from

0 to 8 feet (0 to 2.4 m). Maximum thicknesses occur in the northeast quarter of the quadrangle. The Pawnee coal bed is absent from approximately 15 percent of the quadrangle in the southwest quarter. A shallow syncline is present along the western boundary of the quadrangle. The Pawnee coal bed lies between 1,800 and 2,350 feet (549 and 716 m) beneath the surface.

The Wildcat-Moyer coal zone occurs approximately 290 to 385 feet (88 to 117 m) below the overlying Pawnee coal bed, and is composed of a thin Wildcat coal bed overlying two, thin, lenticular Moyer coal beds. The total coal zone thickness ranges from 0 to 30 feet (0 to 9 m) with maximum thicknesses occurring in the central and south-central parts of the quadrangle. Both Wildcat and Moyer coal beds thin to the northwest and are absent in approximately 1 percent of the quadrangle in the northwest quarter. Structure contours drawn on top of the Wildcat coal bed indicate a rolling structure, gently dipping to the west. A small, westward-plunging anticline extends across the southern half of the study area. The Wildcat-Moyer coal zone lies between 2,100 and 2,700 feet (640 and 823 m) beneath the surface.

V. Geological and Engineering Mapping Parameters

The correct horizontal location and elevation of drill holes utilized in subsurface mapping are critical to map accuracy. IntraSearch plots the horizontal location of the drill hole as described on the geophysical log heading. Occasionally this location is superimposed

on or near to a drillsite shown on the topographic map, and the topographic map horizontal location is utilized. If the ground elevation on the geophysical log does not agree with the topographic elevation of the drillsite, the geophysical log ground elevation is adjusted to conformance. If there is no indication of a drillsite on the topographic map, the "quarter, quarter, quarter" heading location is shifted within a small area until the ground elevation on the heading agrees with the topographic map elevation. If no elevation agreement can be reached, the well heading or data sheet is rechecked for footage measurements and ground elevation accuracy. Inquiries to the companies who provided the oil and gas geophysical logs frequently reveal that corrections have been made in the original survey. If all horizontal location data sources have been checked and the information accepted as the best available data, the drillsite elevation on the geophysical log is modified to agree with the topographic map elevation. IntraSearch considers this agreement mandatory for the proper construction of most subsurface maps, but in particular, the overburden isopach, the mining ratio, and Coal Development Potential maps.

Subsurface mapping is based on geologic data within, and adjacent to, the Fort Reno SE Quadrangle area. Data from geophysical logs are used to correlate coal beds and control contour lines for the coal thickness, structure, and overburden maps. Structure contour maps are constructed on the tops of the main coal beds.

In preparing overburden isopach maps, no attempt is made to identify coal beds that occur in the overburden above a particular coal bed under study. Mining ratio maps for this quadrangle are constructed

utilizing a 95 percent recovery factor. Contours of these maps identify the ratio of cubic yards of overburden to tons of recoverable coal. Where ratio control points are sparse, interpolated points are computed using coal structure, coal isopach, and topographic control. On the Areal Distribution of Identified Resources Map (ADIR), coal bed reserves are not calculated where the coal is less than 5 feet (1.5 m) thick, where the coal occurs at a depth greater than 500 feet (152 m), and where non-federal coal exists, or where federal coal leases, preference-right lease applications, and coal prospecting permits exist.

Coal tonnage calculations involve the planimetry of areas of measured, indicated,<sup>and</sup> inferred *identified* resources, and hypothetical resources to determine their areal extent in acres. An Insufficient Data Line is drawn to delineate areas where surface and subsurface data are too sparse for CRO map construction. Various categories of resources are calculated in the unmapped areas by utilizing coal bed thicknesses mapped in the geologically controlled area adjacent to the insufficient data line. Acres are multiplied by the average coal bed thickness and 1,750, or 1,770--the number of tons of lignite A or subbituminous C coal per acre-foot, respectively (12,874 or 13,018 metric tons per hectare-meter, respectively)--to determine total tons in place. Recoverable tonnages<sup>(reserves)</sup> are calculated at 95 percent of the total tons in place. Where tonnages are computed for the CRO-CDP map series, resources and reserves are expressed in millions of tons. Frequently, the planimetry of coal resources on a sectionized basis involves complexly curvilinear lines (coal bed outcrop and 500-foot stripping limit designations) in relationship

with linear section boundaries and circular resource category boundaries. Where these relationships occur, generalizations of complex curvilinear lines are discretely utilized, and resources and/or reserves are calculated within an estimated 2 to 3 percent, plus or minus, accuracy.

VI. Coal Development Potential

Strippable Coal Development Potential. Areas where coal beds are 5 feet (1.5 m) or more in thickness and are overlain by 500 feet (152 m) or less of overburden are considered to have potential for surface mining and are assigned a high, moderate, or low development potential based on the mining ratio (cubic yards of overburden per ton of recoverable coal). The formula used to calculate mining-ratios for subbituminous coal is as follows:

$$MR = \frac{to (0.911)*}{tc (rf)}$$

where MR = mining ratio  
to = thickness of overburden  
tc = thickness of coal  
rf = recovery factor  
0.911 = conversion factor (cu. yds./ton)

\*A conversion factor of 0.922 is used for lignite.

A surface mining development potential map, when applicable, is prepared utilizing the following mining ratio criteria for coal beds 5 feet to 40 feet (1.5 to 12 m) thick:

1. Low development potential = 15:1 and greater ratio.
2. Moderate development potential = 10:1 to 15:1 ratio.
3. High development potential = 0 to 10:1 ratio.

The following mining ratio criteria are utilized for coal beds greater than 40 feet (12 m) thick:

1. Low development potential = 7:1 and greater ratio.
2. Moderate development potential = 5:1 to 7:1 ratio.
3. High development potential = 0 to 5:1 ratio.

There is no development potential for surface mining in the Fort Reno SE Quadrangle. The coal beds present within the study area occur at depths that exceed the 500-foot (152-m) stripping limit for surface mining. For this reason, no surface mining potential map was generated for this quadrangle.

Underground Mining Coal Development Potential. Subsurface coal mining development potential throughout the Fort Reno SE Quadrangle is considered low. Inasmuch as recovery factors have not been established for the underground development of coal beds in this quadrangle, reserves are not calculated for coal beds that occur more than 500 feet (152 m) beneath the surface. Table 2 sets forth the estimated coal resources in tons per coal bed.

In-Situ Gasification Coal Development Potential. The evaluation of subsurface coal deposits for in-situ gasification development potential relates to the occurrence of coal beds more than 5 feet (1.5 m) thick buried from 500 to 3,000 feet (152 to 914 m) beneath the surface. This categorization is as follows:

1. Low development potential relates to: 1) a total coal section less than 100 feet (30 m) thick that lies 1,000 feet (305 m) to 3,000 feet (914 m) beneath the surface, or 2)

a coal bed or coal zone 5 feet (1.5 m) or more in thickness that lies 500 feet (152 m) to 1,000 feet (305 m) beneath the surface.

2. Moderate development potential is assigned to a total coal section from 100 to 200 feet (30 to 61 m) thick and buried from 1,000 to 3,000 feet (305 to 914 m) beneath the surface.

3. High development potential involves 200 feet (61 m) or more of total coal thickness buried from 1,000 to 3,000 feet (305 to 914 m).

The coal development potential for in-situ gasification (plate 44) on the Fort Reno SE Quadrangle is moderate for approximately 90 percent of the study area. A high potential rating covers approximately 3 percent of the quadrangle in the southeast quarter. Both high and moderate development potential ratings can be attributed primarily to the massive, combined coal bed thicknesses of the Upper, Middle, and Lower Wyodak coal beds. The remaining area is classified as non-federal coal land, and therefore not evaluated in this study. None of the Fort Reno SE Quadrangle is classified as low development potential for in-situ gasification.

Table 1.-- Coal Reserve Base Data (in short tons) for Underground Mining Methods for Federal Coal Lands in the Fort Reno SE Quadrangle, Johnson and Campbell Counties, Wyoming.

Coal Bed Name	High Development Potential	Moderate Development Potential	Low Development Potential	Total
Smith	-	-	146,240,000	146,240,000
Local "A"	-	-	77,800,000	77,800,000
Upper-Middle Wyodak	-	-	5,417,530,000	5,417,530,000
Lower Wyodak	-	-	1,770,440,000	1,770,440,000
Wall	-	-	475,860,000	475,860,000
Local "B"	-	-	188,950,000	188,950,000
Pawnee	-	-	124,430,000	124,430,000
Wildcat Moyer	-	-	719,100,000	719,100,000
TOTAL	-	-	8,920,350,000	8,920,350,000

Table 2.--Coal Reserve Base Data (in short tons) for In-Situ Gasification for Federal Coal Lands in the Fort Reno SE Quadrangle, Johnson and Campbell Counties, Wyoming.

Coal Bed Name	High Development Potential	Moderate Development Potential	Low Development Potential	Total
	217,550,000	8,702,800,000	-	8,920,350,000
TOTAL	217,550,000	8,702,800,000	-	8,920,350,000

- American Society of Testing and Materials, 1971, Standard specifications for classification of coals by rank (ASTM Designation D 388-66) in Gaseous fuels, coal, and coke: American Society for Testing and Materials, pt. 19, p. 57-61.
- Baker, A. A., 1929, The northward extension of the Sheridan coal field, Big Horn and Rosebud Counties, Montana: U. S. Geological Survey Bull. 806-B, p. 15-67.
- Bass, N. W., 1932, The Ashland coal field, Rosebud, Powder River, and Custer Counties, Montana: U. S. Geological Survey Bull. 831-B, p. 19-105.
- Brown, R. W., 1958, Fort Union Formation in the Powder River Basin, Wyoming: Wyoming Geological Association Guidebook, Thirteenth Annual Field Conf., p. 111-113.
- Denson, N. M., and Horn, G. H., 1975, Geologic and structure map of the southern part of the Powder River Basin, Converse, Niobrara, and Natrona Counties, Wyoming: U. S. Geological Survey Miscellaneous Investigations Series, Map I-877, scale 1:125,000.
- Dobbin, C. E., and Barnett, V. H., 1927 (1928), The Gillette coal field, northeastern Wyoming: U. S. Geological Survey Bull. 796-A, 50 p.
- Glass, G. B., 1975, Review of Wyoming coal fields, 1975: Wyoming Geological Survey Public Information Circ. 4, p. 10.
- IntraSearch Inc., 1978, Coal resource occurrence and coal development potential <sup>maps</sup> of the Rocky Butte Quadrangle, Campbell County, Wyoming: U. S. Geological Survey Open-File Report 78-830, 22 p.
- \_\_\_\_\_ 1979, Coal resource occurrence and coal development potential *maps* of the Larey Draw Quadrangle, Campbell County, Wyoming: U. S. Geological Survey Open-File Report 79-023, 29 p.

- Jacob, A. F., 1973, Depositional environments of Paleocene Tongue River Formation: Am. Assoc. of Petroleum Geologists Bull., vol. 56, no. 6, p. 1038-1052.
- McKay, E. J., 1974, Preliminary geologic map of the Bertha 2 NW (Rocky Butte) Quadrangle, Campell County, Wyoming: U. S. Geological Survey Open-File Report 74-173, scale 1:24,000.
- Olive, W. W., 1957, The Spotted Horse coal field, Sheridan and Campbell Counties, Wyoming: U. S. Geological Survey Bull. 1050, 83 p.
- Stone, R. W., and Lupton, C. T., 1910, The Powder River coal field, Wyoming, adjacent to the Burlington Railroad: U. S. Geological Survey Bull. 381-B, p. 115-136.
- Taff, J. A., 1909, The Sheridan coal field, Wyoming: U. S. Geological Survey Bull. 341-B, p. 123-150.
- U. S. Bureau of Mines and U. S. Geological Survey, 1976, Coal resource classification system of the U. S. Bureau of Mines and U. S. Geological Survey: U. S. Geological Survey Bull. 1450-B, 7 p.
- U. S. Geological Survey and Montana Bureau of Mines and Geology, 1974, Preliminary report of coal drill-hole data and chemical analyses of coal beds in Campbell County, Wyoming: U. S. Geological Survey Open-File Report 74-97, 241 p.
- \_\_\_\_\_, 1976, Preliminary report of coal drill-hole data and chemical analyses of coal beds in Campbell and Sheridan Counties, Wyoming: Custer, Prairie, and Garfield Counties, Montana; and Mercer County, North Dakota: U. S. Geological Survey Open-File Report 76-319, 377 p.

Warren, W. C., 1959, Reconnaissance geology of the Birney-Broadus coal field, Rosebud and Powder River Counties, Montana: U. S. Geological Survey Bull. 1072-J, p. 561-585.

Weimer, R. J., 1977, Stratigraphy and tectonics of western coals in Geology of Rocky Mountain Coal, A Symposium, 1976: Colorado Geological Survey Resources Series 1, p. 9-27.

Winchester, D. E., 1912, The Lost Spring coal field, Converse County, Wyoming: U. S. Geological Survey Bull. 471-F, p. 472-515.