

RESERVOIRS IN CUMBERLAND RIVER BASIN

03413500 LAKE CUMBERLAND.--Lat 36°52'09", long 85°08'45", Russell County, KY, Hydrologic Unit 05130103, in pylon of Wolf Creek Dam on Cumberland River and 10 mi southwest of Jamestown, Ky. DRAINAGE AREA, 5,789 mi². PERIOD OF RECORD, April 1950 to current year. Prior to October 1954, published as Wolf Creek Reservoir. April to June 1950, published in WSP 1726. GAGE, water-stage recorder. Datum of gage is Sandy Hook datum. Prior to Dec. 6, 1950, nonrecording gage at same site at datum 545.0 ft higher.

REVISIONS.--WSP 1556: Drainage area.

REMARKS.--Reservoir is formed by earth embankment and concrete gravity dam surmounted by 10 taintor gates, each 37 high by 50 ft wide. Final closure of dam made Aug. 7, 1950. Total capacity at elevation 760.00 ft top of gates, is 3,070,000 cfs-days, of which 1,056,000 cfs-days above elevation 723.00 ft, crest of spillway, are reserved for flood control and 1,080,000 cfs-days between elevation 673.00 ft, minimum power pool, and 723.00 ft are used for power production. Figures given herein represent total contents, of which 934,000 cfs-days below elevation 673.00 ft is dead storage. Reservoir is used for flood control, power, navigation, and recreation.

COOPERATION.--Records furnished by U.S. Army Corps of Engineers.

EXTREMES FOR PERIOD OF RECORD.--Maximum contents, 2,811,000 cfs-days, May 13, 1984, elevation, 751.70 ft; minimum, first filling, 934,400 cfs-days, Jan. 1, 1956, elevation, 673.01 ft.

EXTREMES FOR CURRENT YEAR.--Maximum contents, 2,098,000 cfs-days, Dec. 14, elevation, 726.29 ft; minimum, 1,411,000 cfs-days, Sept. 30, elevation, 697.19 ft.

03416500 DALE HOLLOW LAKE.--Lat 36°32'19", long 85°27'05", Clay County, Hydrologic Unit 05130105, at Dale Hollow Dam on Obey River, 3.0 mi east of Celina, and 7.3 mi upstream from mouth. DRAINAGE AREA, 936 mi². PERIOD OF RECORD, August 1943 to current year. Prior to October 1965, published as Dale Hollow Reservoir. GAGE, water-stage recorder. Datum of gage is Sandy Hook datum. Prior to June 25, 1946, nonrecording gage at same site and datum.

REVISIONS.--WSP 1306: 1944. WSP 2110: Drainage area.

REMARKS.--Reservoir is formed by concrete gravity dam. Spillway is equipped with six taintor gates, each 12 ft high by 60 ft wide. Closure of dam was made Aug. 30, 1943; water in reservoir first reached minimum pool elevation May 7, 1944. Revised capacity table used after Sept. 30, 1970. Total capacity at elevation 663.0 ft, top of gates, is 859,800 cfs-days of which 177,500 cfs-days between elevations 663.00 ft and 651.00 ft, crest of spillway, are reserved for flood control, and 250,200 cfs-days between elevations 651.00 ft and 631.00 ft, ordinary minimum pool, are used for power production. Contents of 432,100 cfs-days below elevation 631.00 ft is dead storage. Reservoir is used for flood control, navigation, and power.

COOPERATION.--Records furnished by U.S. Army Corps of Engineers.

EXTREMES FOR PERIOD OF RECORD.--Maximum contents, 828,600 cfs-days, Mar. 15, 1975, elevation, 660.98 ft; minimum, first filling, 428,000 cfs-days, Sept. 11, 1944, elevation, 630.63 ft.

EXTREMES FOR CURRENT YEAR.--Maximum contents, 712,500 cfs-days, May 2, elevation, 653.14 ft; minimum, 515,100 cfs-days, Sept. 30, elevation, 638.17 ft.

03418400 CORDELL HULL RESERVOIR.--Lat 36°17'23", long 85°56'39", Smith County, Hydrologic Unit 05130108, at Cordell Hull Dam Cumberland River, 2.7 mi north of Carthage, and at mile 313.5. DRAINAGE AREA, 8,095 mi². PERIOD OF RECORD, October 1972 to current year. GAGE, water-stage recorder. Datum of gage is sea level.

REMARKS.--Reservoir is formed by concrete gravity dam with earth embankment. Spillway is equipped with five gates, each 41 ft high and 45 ft wide. Closure of dam was made Oct. 4, 1967; water in reservoir first reached ordinary minimum pool Mar. 13, 1973. Total capacity at elevation 508.0 ft, maximum surcharge pool, is 156,700 cfs-days, of which 53,400 cfs-days is controlled storage between elevations 508.0 ft and 499.0 ft, ordinary minimum pool. Contents of 5,000 cfs-days between elevation of 499.0 ft and 500.0 ft full winter pool, is available for power production. Contents of 48,400 cfs-days above 500.0 ft is available for flood control during the winter, and 26,100 cfs-days above 504.0 ft, full pool during spring to fall season, is available for flood control the rest of the year. Contents of 103,300 cfs-days below elevation 499.0 ft is dead storage. Reservoir is used for navigation, power, and flood control.

COOPERATION.--Records furnished by U.S. Army Corps of Engineers.

EXTREMES FOR PERIOD OF RECORD.--Maximum contents, 156,700 cfs-days, Mar. 13, 1975, May 8, 1984, elevation, 508.00 ft; minimum, after first filling to ordinary minimum pool, 96,700 cfs-days, Apr. 18, 1974, elevation, 497.65 ft.

EXTREMES FOR CURRENT YEAR.--Maximum contents, 136,300 cfs-days, Apr. 30, elevation, 504.91 ft; minimum, 103,400 cfs-days, Dec. 9, elevation, 499.03 ft.

MONTHEND ELEVATION AND CONTENTS AT 2400, WATER YEAR OCTOBER 2004 TO SEPTEMBER 2005

DATE	03413500 LAKE CUMBERLAND		03416500 DALE HOLLOW LAKE		03418400 CORDELL HULL RESERVOIR	
	Elevation (feet)	Contents (cfs-days)	Change in contents (cfs-days)	Elevation (feet)	Contents (cfs-days)	Change in contents (cfs-days)
Sept. 30...	712.39	1,753,900	-	645.02	601,400	-
Oct. 31...	701.20	1,498,200	-255,700	643.28	578,800	-22,600
Nov. 30...	701.17	1,497,500	-700	644.36	592,800	+14,000
Dec. 31...	718.60	1,903,900	+406,400	648.12	642,700	+49,900
CAL YR 2004	-	-	+328,400	-	-	+58,200
Jan. 31...	720.80	1,958,500	+54,600	647.00	627,600	-15,100
Feb. 28...	718.30	1,896,600	-61,900	649.49	661,400	+33,800
Mar. 31...	716.17	1,844,500	-52,100	650.60	676,700	+15,300
Apr. 30...	724.28	2,046,400	+201,900	652.82	708,000	+31,300
May 31...	721.24	1,969,600	-76,800	650.45	674,700	-33,300
June 30...	716.80	1,859,800	-109,800	647.71	637,100	-37,600
July 31...	712.54	1,757,400	-102,400	645.08	602,200	-34,900
Aug. 31...	704.44	1,570,300	-187,100	641.91	561,400	-40,800
Sept. 30...	697.19	1,411,000	-159,300	638.19	515,100	-46,300
WTR YR 2005	-	-	-342,900	-	-	-86,300

RESERVOIRS IN CUMBERLAND RIVER BASIN--CONTINUED

03422000 GREAT FALLS LAKE.--Lat 35°48'21", long 85°38'09", Warren County, Hydrologic Unit 05130108, at pen-stock inlet on Collins River, 700 ft southwest of powerhouse of Tennessee Valley Authority, 1.5 mi northwest of Rock Island, 1.8 mi upstream from mouth of Collins River, and 2.0 mi upstream from Great Falls Dam on Caney Fork. DRAINAGE AREA, 1,677 mi². PERIOD OF RECORD, January 1917 to current year. GAGE, remote indicator gage. Datum of gage is sea level. REVISIONS.--WSP 2110: Drainage area.

REMARKS.--Reservoir is formed by concrete gravity dam. Spillway is equipped with 18 taintor gates, each 14 ft high by 25 ft wide. Closure of dam was made in 1916; dam redesigned and crest raised 35 ft in 1925. Revised capacity table used after Sept. 30, 1970. Total capacity at elevation 805.3 ft top of gates, is 25,900 cfs-days, of which 18,700 cfs-days are controlled storage above elevation 780.0 ft, normal minimum pool. Contents of 1,500 cfs-days below elevation 762.0 ft is dead storage. Reservoir is used primarily for power.

COOPERATION.--Records furnished by Tennessee Valley Authority.

EXTREMES FOR PERIOD OF RECORD.--Maximum midnight elevation, 817.48 ft, Mar. 23, 1929, contents not determined; minimum midnight contents, 1,700 cfs-days, Aug. 19, 1918, elevation, 756.3 ft.

EXTREMES FOR CURRENT YEAR.--Maximum contents, 195,200 cfs-days, Jan. 26, elevation, 872.85 ft; minimum, 24,900 cfs-days, Apr. 4, elevation, 804.93 ft.

03424000 CENTER HILL LAKE.--Lat 36°05'48", long 85°49'38", DeKalb County, Hydrologic Unit 05130108, at Center Hill Dam on Caney Fork, 10 mi north of Smithville, 14 mi southeast of Carthage, and at mile 26.6. DRAINAGE AREA, 2,174 mi². PERIOD OF RECORD, October 1948 to current year. Prior to October 1965, published as Center Hill Reservoir. GAGE, water-stage recorder. Datum of gage is Sandy Hook datum. Prior to Mar. 14, 1949, nonrecording gage at site 1,320 ft upstream at same datum. REVISIONS.--WSP 1910: Drainage area.

REMARKS.--Reservoir is formed by earth embankment and concrete gravity dam. Spillway is equipped with eight taintor gates, each 37 ft high by 50 ft wide. Closure of dam was made Nov. 27, 1948; water in reservoir first reached minimum pool elevation Jan. 11, 1949. Revised capacity table used after Sept. 30, 1970. Total capacity at elevation 685.0 ft, top of gates, is 1,054,800 cfs-days, of which 384,500 cfs-days between 685.0 ft and 648.0 ft, crest of spillway, are reserved for flood control, and 248,000 cfs-days between elevations 648.0 ft and 618.0 ft, ordinary minimum pool, are used for power production. Contents of 422,300 cfs-days below 618.0 ft is dead storage. Reservoir is used for flood control, navigation, and power.

COOPERATION.--Records furnished by U.S. Army Corps of Engineers.

EXTREMES FOR PERIOD OF RECORD.--Maximum contents, 1,014,600 cfs-days, May 10, 1984, elevation, 681.52 ft; minimum, after first filling, 171,000 cfs-days, Dec. 1, 2, 1949, elevation, 576.1 ft.

EXTREMES FOR CURRENT YEAR.--Maximum contents, 794,400 cfs-days, Dec. 13, elevation, 660.91 ft; minimum, 529,800 cfs-days, Sept. 30, elevation, 631.83 ft.

03426300 OLD HICKORY LAKE.--Lat 36°17'50", long 86°39'20", Sumner County, Hydrologic Unit 05130201, at Old Hickory Dam on Cumberland River, 2.0 mi west of Hendersonville, 10 mi northeast of the State Capitol in Nashville, and at mile 216.2. DRAINAGE AREA, 11,673 mi². PERIOD OF RECORD, June 1954 to current year. GAGE, water-stage recorder. Datum of gage is sea level; gage readings have been reduced to elevations NGVD. Prior to Apr. 4, 1957, nonrecording gage at same site and datum. REVISIONS.--WSP 2110: Drainage area.

REMARKS.--Reservoir is formed by concrete gravity dam with earth embankment. Spillway is equipped with six taintor gates, each 41 ft high and 45 ft wide. Closure of dam was made in June 1954 and water in reservoir was raised sufficiently to maintain navigation through the lock. Water in reservoir first reached ordinary minimum pool elevation Dec. 30, 1956. Revised capacity table used after Sept. 30, 1970. Total capacity at elevation 450.0 ft, maximum surcharge pool, 274,600 cfs-days of which 63,000 cfs-days between elevations 450.0 ft and 445.0 ft, normal pool, are induced surcharge storage provided to compensate for loss of natural valley storage incurred by construction of the project, and 31,800 cfs-days between elevations 445.0 ft and 442.0 ft, ordinary minimum pool, are used for power production. Contents of 179,800 cfs-days below elevation 442.0 ft, is dead storage. Reservoir is used for navigation and power.

COOPERATION.--Records furnished by U.S. Army Corps of Engineers.

EXTREMES FOR PERIOD OF RECORD.--Maximum contents, 277,200 cfs-days, May 9, 1984, elevation, 450.18 ft; minimum, after first filling to ordinary minimum pool, 179,400 cfs-days, Oct. 22, 1957, Oct. 28, 1969, elevation, 441.96 ft.

EXTREMES FOR CURRENT YEAR.--Maximum contents, 230,400 cfs-days, Dec. 2, elevation, 446.60 ft, minimum, 198,900 cfs-days, Dec. 14, elevation, 443.85 ft.

MONTHEND ELEVATION AND CONTENTS AT 2400, WATER YEAR OCTOBER 2004 TO SEPTEMBER 2005

DATE	03422000 GREAT FALLS LAKE			03424000 CENTER HILL LAKE			03426300 OLD HICKORY LAKE		
	Elevation (feet)	Contents (cfs-days)	Change in contents (cfs-days)	Elevation (feet)	Contents (cfs-days)	Change in contents (cfs-days)	Elevation (feet)	Contents (cfs-days)	Change in contents (cfs-days)
Sept. 30...	799.55	20,100	-	639.64	595,700	-	444.50	206,000	-
Oct. 31...	786.91	11,000	-9,100	634.39	551,000	-44,700	444.80	209,400	+3,400
Nov. 30...	800.65	21,000	+10,000	637.85	580,200	+29,200	445.57	218,200	+8,800
Dec. 31...	785.52	10,200	-10,800	644.24	636,200	+56,000	445.65	219,100	+900
CAL YEAR 2004	-	-	-12,400	-	-	+68,300	-	-	+4,500
Jan. 31...	787.23	11,200	+1,000	638.71	587,600	-48,600	445.34	215,500	-3,600
Feb. 28...	801.96	22,100	+10,900	643.37	628,400	+40,800	444.55	206,600	-8,900
Mar. 31...	795.06	16,500	-5,600	637.89	580,600	-47,800	444.90	210,500	+3,900
Apr. 30...	793.66	15,500	-1,000	643.35	628,200	+47,600	445.10	212,800	+2,300
May 31...	800.14	20,600	+5,100	646.25	654,300	+26,100	444.50	206,000	-6,800
June 30...	799.64	20,200	-400	644.31	636,800	-17,500	444.51	206,100	+100
July 31...	800.03	20,500	+300	641.11	608,500	-28,300	444.60	207,100	+1,000
Aug. 31...	797.67	18,500	-2,000	635.52	560,500	-48,000	445.20	213,900	+6,800
Sept. 30...	794.72	16,200	-2,300	631.84	529,900	-30,600	444.67	207,900	-6,000
WTR YR 2005	-	-	-3,900	-	-	-65,800	-	-	+1,900

RESERVOIRS IN CUMBERLAND RIVER BASIN--CONTINUED

03430050 J. PERCY PRIEST RESERVOIR.--Lat 36°09'23", long 86°37'07", Davidson County, Hydrologic Unit 05130203, on upstream face of J. Percy Priest Dam on Stones River, 2.6 mi east of Donelson, and 6.8 mi above mouth. DRAINAGE AREA, 892 mi². PERIOD OF RECORD, September 1967 to current year. GAGE, water-stage recorder. Datum of gage is sea level. Prior to Dec. 15, 1967, nonrecording gage at same site and datum.

REMARKS.--Reservoir is formed by concrete gravity dam with earth embankments. Spillway is equipped with four taintor gates, each 41 ft high by 45 ft wide. Closure of dam was made Sept. 18, 1967; water in reservoir first reached ordinary minimum pool May 15, 1968. Revised capacity table used after Sept. 30, 1970. Total capacity at elevation 504.5 ft, maximum controlled pool, is 328,700 cfs-days of which 193,600 cfs-days is controlled storage between elevations 504.5 ft and 480.0 ft, ordinary minimum pool. Contents of 17,200 cfs-days between elevations 480.0 ft and 483.0 ft, full winter pool, is available for power production. Contents of 176,400 cfs-days above 483.0 ft is available for flood control during the winter, and 131,100 cfs-days above 490.0 ft, full pool during spring-to-fall season, is available for flood control the rest of the year. Contents of 135,100 cfs-days below elevation 480.0 ft is dead storage. Reservoir is used for flood control, power, recreation, and wildlife.

COOPERATION.--Records furnished by U.S. Army Corps of Engineers.

EXTREMES FOR PERIOD OF RECORD.--Maximum contents, 336,600 cfs-days, May 9, 1984, elevation, 505.18 ft; minimum, after first filling to ordinary minimum pool, 109,500 cfs-days, Dec. 5, 1968, elevation, 474.75 ft.

EXTREMES FOR CURRENT YEAR.--Maximum contents, 221,900 cfs-days, Dec. 10, elevation, 493.25 ft, minimum, 147,200 cfs-days, Jan. 28, elevation, 482.14 ft.

03434900 CHEATHAM LAKE.--Lat 36°18'56", long 87°13'10", Cheatham County, Hydrologic Unit 05130202, at Cheatham Dam on Cumberland River, 9.4 mi west of Ashland City, 16 mi southeast of the courthouse in Clarksville, and at mile 148.7. DRAINAGE AREA, 14,159 mi².

REMARKS.--Reservoir is formed by concrete gravity dam. Spillway is equipped with seven semi-submersible taintor gates, each 27 ft high by 60 ft wide. Total capacity at elevation 385.0 ft, normal pool, is 52,200 cfs-days, of which 9,800 cfs-days are controlled storage. Records of contents not published herein.

03438210 LAKE BARKLEY.--Lat 37°01'17", long 88°13'16", Lyon County, KY, Hydrologic Unit 05130205, in powerhouse of Barkley Dam on Cumberland River, 1.4 mi northeast of Grand Rivers, KY, and at mile 30.6. DRAINAGE AREA, 17,598 mi². PERIOD OF RECORD, July 1964 to current year. GAGE, water-stage recorder. Datum of gage is sea level, (levels by U.S. Army Corps of Engineers). Prior to Jan. 1, 1966, nonrecording gage, 1,200 ft upstream from Barkley Dam at same datum.

REMARKS.--Reservoir is formed by concrete gravity dam with earth embankments. Spillway is equipped with 12 taintor gates, each 50 ft high by 55 ft wide. Construction cofferdam was closed and limited storage began July 1, 1964; reservoir reached ordinary minimum pool elevation of 354.0 ft Feb. 16, 1966. Total level pool capacity at elevation 375.0 ft, top of gates, is 1,049,600 cfs-days, of which 742,000 cfs-days is controlled storage above 354.0 ft, ordinary minimum pool. Contents of 130,500 cfs-days between ordinary minimum pool elevation, 354.0 ft, and full pool elevation, 359.0 ft, is available for power during the spring-to-fall season. Minimum pool elevation in advance of floods is 346.0 ft, contents 171,000 cfs-days. Reservoir is used for navigation, flood control, power, and recreation. Barkley-Kentucky Canal opened June 13, 1966, for navigation and power use. Canal is 1.75 mi long and interconnects Lake Barkley and Kentucky Lake at a point 2.2 mi upstream from Barkley Dam. For daily discharges through the canal, see station 03438190, Kentucky reports.

COOPERATION.--Records furnished by U.S. Army Corps of Engineers.

EXTREMES FOR PERIOD OF RECORD.--Maximum elevation, 370.04 ft, May 13, 1984; minimum after reaching permanent pool elevation, 353.20 ft, Dec. 20, 1976.

EXTREMES FOR CURRENT YEAR.--Maximum contents, 489,300 cfs-days, Jan. 21, elevation, 360.70 ft; minimum content, 307,000 cfs-days, Dec. 23, minimum, 353.95 ft. Contents based on backwater profile.

MONTHEND ELEVATION AND CONTENTS AT 2400, WATER YEAR OCTOBER 2004 TO SEPTEMBER 2005

Date	Elevation (feet)	Contents (cfs-days)	Change in contents (cfs-day)	Elevation (feet)	Contents (cfs-days)	Change in contents (cfs-days)
	03430050	J. PERCY PRIEST LAKE		*03438210	LAKE BARKLEY	
Sept. 30.....	489.80	196,200	-	355.75	349,500	-
Oct. 31.....	487.25	178,700	-17,500	356.20	361,000	+11,500
Nov. 30.....	487.11	177,800	-900	356.05	357,100	-3,900
Dec. 31.....	482.40	148,700	-29,100	355.05	332,200	-24,900
CAL YR 2004	-	-	-6,800	-	-	+15,400
Jan. 31.....	483.39	154,600	+5,900	354.75	325,100	-7,100
Feb. 28.....	483.45	154,900	+300	356.40	366,200	+41,100
Mar. 31.....	485.52	167,600	+12,700	355.80	350,800	-15,400
Apr. 30.....	490.85	203,800	+36,200	360.15	472,400	+121,600
May 31.....	490.35	200,200	-3,600	358.95	436,600	-35,800
June 30.....	489.98	197,500	-2,700	359.05	439,500	+2,900
July 31.....	490.83	203,700	+6,200	358.00	409,500	-30,000
Aug. 31.....	490.55	201,600	-2,100	358.20	415,200	+5,700
Sept. 30.....	409.19	199,000	-2,600	355.15	334,700	-80,500
WTR YR 2005	-	-	+2,800	-	-	-14,800

* Contents based on backwater profile.

THIS PAGE IS INTENTIONALLY BLANK