

SANTEE RIVER BASIN

293

02168500 LAKE MURRAY NEAR COLUMBIA, SC

LOCATION.--Lat 34°03'07'', long 81°13'15'', Lexington County, Hydrologic Unit 03050109, in intake tower 500 ft upstream from dam on Saluda River and 10.4 mi upstream from confluence of Saluda and Broad Rivers at Columbia.

DRAINAGE AREA.--2,420 mi², approximately.

PERIOD OF RECORD.--August 1929 to current year.

GAGE.--Data collection platform. Datum of gage is 0.64 ft below NGVD of 1929. Prior to October 1966, mean gage height was published. Prior to Oct. 31, 1930, nonrecording gage at same site and datum.

REMARKS.--Lake is formed by earth dam; storage began Aug. 31, 1929; dam completed in 1930. Usable capacity, 68,210,000,000 ft³ between gage heights 300.0 ft (limit of drawdown) and 360.0 ft (maximum normal lake level). Dead storage, 15,590,000,000 ft³. Figures given herein represent usable contents. Gage height of one spillway crest (completed in 1946), 330 ft with top of gates at 362 ft; gage height of other spillway crest, 340 ft with top of gates at 365 ft. Water is used for generation of power. Prior to October 1, 1997, capacity computations were determined using the capacity curve prepared by Lexington Power Company.

EXTREMES FOR PERIOD OF RECORD.--Maximum gage height, 361.51 ft, Apr. 10, 1936; minimum gage height since generation of power was started, 320.96 ft, Dec. 23, 1941.

EXTREMES FOR CURRENT YEAR.--Maximum gage height, 352.87 ft, Sep. 30; minimum gage height, 345.30 ft, Nov. 16-19.

Gage height, feet
WATER YEAR OCTOBER 2003 TO SEPTEMBER 2004
DAILY OBSERVATION AT 2400 HOURS

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	345.65	345.53	345.99	345.78	345.98	346.81	346.99	347.03	347.02	348.50	349.29	349.95
2	345.59	345.52	345.98	345.77	346.00	346.90	347.02	347.14	347.02	348.63	349.39	349.94
3	345.51	345.52	346.00	345.80	346.03	346.98	347.03	347.19	347.00	348.69	349.44	349.93
4	345.45	345.51	346.06	345.83	345.99	347.02	347.04	347.26	346.98	348.75	349.47	349.93
5	345.47	345.50	346.05	345.90	345.97	347.03	347.06	347.27	346.97	348.82	349.48	349.94
6	345.51	345.49	346.05	345.95	345.96	347.08	347.06	347.26	346.95	348.86	349.47	349.95
7	345.66	345.47	346.06	345.95	346.04	347.13	347.06	347.24	346.93	348.89	349.44	350.36
8	345.71	345.46	346.06	345.95	346.08	347.11	347.08	347.11	346.97	348.93	349.41	351.04
9	345.72	345.43	346.08	345.99	346.07	347.09	347.08	347.09	346.99	348.95	349.39	351.24
10	345.80	345.40	346.21	346.02	345.99	347.08	347.09	347.08	347.02	348.95	349.39	351.58
11	345.85	345.39	346.17	346.01	345.89	347.06	347.08	347.05	347.01	348.97	349.37	351.99
12	345.85	345.38	346.19	345.97	346.02	347.05	347.11	347.13	347.18	348.98	349.67	352.12
13	345.84	345.36	346.31	345.90	345.98	347.02	347.21	347.14	347.19	348.98	349.72	352.09
14	345.88	345.32	346.43	345.88	346.04	347.01	347.21	347.12	347.23	348.97	349.86	352.07
15	345.80	345.31	346.54	345.88	346.06	347.02	347.21	347.14	347.23	348.97	349.90	351.97
16	345.86	345.32	346.55	345.88	346.08	347.05	347.24	347.12	347.25	348.97	349.92	351.97
17	345.87	345.31	346.60	345.90	346.27	347.07	347.24	347.12	347.21	348.99	349.96	352.14
18	345.84	345.30	346.62	345.93	346.25	347.09	347.25	347.11	347.22	348.99	349.96	352.08
19	345.83	345.42	346.53	345.96	346.28	347.08	347.25	347.11	347.28	348.98	349.95	352.03
20	345.82	345.44	346.47	346.00	346.31	347.09	347.23	347.13	347.24	349.00	349.94	352.03
21	345.71	345.57	346.41	346.03	346.38	347.13	347.15	347.15	347.42	349.02	349.93	352.02
22	345.62	345.71	346.36	346.01	346.37	347.06	347.12	347.21	347.49	349.04	349.93	352.03
23	345.56	345.76	346.30	346.04	346.42	346.99	347.07	347.21	347.50	349.03	349.93	352.01
24	345.48	345.82	346.25	346.04	346.47	346.96	347.06	347.11	347.56	349.01	349.96	352.05
25	345.43	345.83	346.21	346.06	346.50	346.98	347.04	347.05	347.61	348.99	349.96	352.07
26	345.43	345.88	346.16	346.08	346.52	346.98	347.09	347.04	347.62	349.04	349.94	352.10
27	345.40	345.91	346.11	346.20	346.57	346.99	347.09	347.03	347.93	349.13	349.93	352.26
28	345.52	346.02	346.06	346.17	346.59	346.99	347.06	347.02	348.08	349.14	349.93	352.46
29	345.50	345.97	345.99	346.14	346.69	346.98	347.05	347.02	348.17	349.16	349.93	352.37
30	345.51	345.96	345.94	346.09	---	346.90	347.05	347.03	348.36	349.18	349.89	352.87
31	345.53	---	345.86	346.03	---	346.98	---	347.05	---	349.21	349.95	---
MAX	345.88	346.02	346.62	346.20	346.69	347.13	347.25	347.27	348.36	349.21	349.96	352.87
MIN	345.40	345.30	345.86	345.77	345.89	346.81	346.99	347.02	346.93	348.50	349.29	349.93
	39.8	40.5	40.3	40.6	41.7	42.2	42.3	42.3	44.4	45.8	47.1	52.5
	-52.3	+274	-59.7	+105	+435	+179	+42.4	0.00	+833	+526	+455	+2090

CAL YR 2003 * -39.3 MAX 347.95 MIN 345.09
WTR YR 2004 * +397 MAX 352.87 MIN 345.30

(+) CONTENTS, IN BILLIONS OF CUBIC FEET, AT END OF MONTH.
(*) CHANGE IN CONTENT, EQUIVALENT IN CUBIC FEET PER SECOND.