

STATE BOARD OF CONSERVATION  
CONDENSED DRILLER'S LOG

WELL RECORD

INSTRUCTIONS: This record is to be filed with the Board within 30 days after completion of well.

0 - 515 Shale, sand, lime  
 515 - 769 Sand, lime  
 769 - 2275 shale, sand, streaks fullers earth  
 2275 - 2432 shale, chalk  
 2432 - 2552 soft grey shale  
 2552 - 3052 chalk  
 3052 - 3859 shale, sand  
 3859 - 4700 shale, sharp sand  
 4700 - 5160 grey shale  
 5160 - 5549 grey and brown shale  
 5549 - 6387 red and grey shale  
 6387 - 6691 red & grey shale, sand streaks  
 6691 - 7028 sand and shale, run log

OPERATOR: G. L. Prince  
 NAME OF CONTRACTOR: H. S. N. ...  
 DATE OR COMMENCING: ...  
 WELL LOCATION: ...  
 SURVEY: ...  
 COUNTY: ...

ELEVATION AT TOP OF OIL STRING CASINGHEAD: ...  
 DERRICK FLOOR: ...  
 GROUND: ...

CASING LINER AND TUBING RECORD

STRING	SIZE	WT. FT.	NAME AND TYPE	AMOUNT		DEPTH SET AT	PREPARED
				Feet	Inches		

CEMENT AND TESTING RECORD

SIZE OF HOLE	STRING	WHERE CEMENT PLACED	NUMBER BAGS OF CEMENT	METHOD USED	Pressure tested in Test	Remarks of Cement Drilled	KIND OF CEMENT
10"	Surface		100				Portland

DRILL STEM TEST

FROM	TO	CHOKES	TIME	W.P.	R.O.P.	R.C.P.	RESULTS

INITIAL PRODUCTION TEST

DATE TAKEN: ...  
 OIL: ...  
 GAS: ...  
 CORR: ...  
 WATER: ...