BACKWATER AT BRIDGES AND DENSELY WOODED FLOOD PLAINS, FLAGON BAYOU NEAR LIBUSE, LOUISIANA

By George J. Arcement, B. E. Colson, and C. O. Ming

Prepared in cooperation with the DEPARTMENT OF TRANSPORTATION FEDERAL HIGHWAY ADMINISTRATION

LOUISIANA DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT

HYDROLOGIC INVESTIGATIONS ATLAS Published by the U.S. Geological Survey, 1978

> BACKWATER AT BRIDGES AND DENSELY WOODED FLOOD PLAINS FLAGON CREEK NEAR LIBUSE, LOUISIANA

INTRODUCTION New techniques for predicting water-surface profiles, needed in the design of economical, structurally sound, and environmentally compatible stream crossings, are under investigation. The investigation has accelerated with the advent of digital computers capable of analyzing large quantities of data. Among the techniques is the development of two-dimensional (2-D) digital models. Field data are essential for development and evaluation of these techniques for predicting water-surface profiles. This atlas is one of a series that provide a wide range of field data.

Since 1969 the U.S. Geological Survey has been collecting backwater data where wide, densely vegetated flood plains are crossed by highway embankments and single-opening bridges. This work was done in cooperation with the Federal Highway Administration Department of Transportation, the Alabama State Highway Department, the Louisiana Department of Transportation and Development, and the Mississippi State Highway Department. The objective of this cooperative project is to present the data in a format conducive to the development of improved models for predicting hydraulic responses of flow at highway crossings of streams in complex hydrologic and geographic settings.

Backwater data were obtained at 22 sites for 35 floods; that is, 11 sites had 1 flood each; 9 sites, 2 floods each; and 2 sites, 3 floods each. Analysis of data (Schneider and others, 1976) showed that backwater and discharge at these sites computed by methods presently in use, would be inaccurate. The floodflow data are unique in the range and detail in which information was collected and provide a base for evaluating digital models relating to open-channel flow.

The data sites (fig. 1) are listed below. This atlas shows flood data obtained on Flagon Bayou near Libuse, Louisiana, one of the 22 sites.

HYDROLOGIC INVESTIGATIONS ATLAS NUME	BER
Buckhorn Creek near ShilohHA	-607*
Pea Creek near Louisville	608*
Poley Creek near Sanford	609
Yellow River near Sanford	610*
Whitewater Creek near Tarentum	611*
LOUISIANA	
Alexander Creek near St. Francisville	-600*
Beaver Creek near Kentwood	601*
Comite River near Olive Branch	602
Cypress Creek near Downsville	603*
Flagon Bayou near Libuse	604
Little Bayou de Loutre near Truxno	605*
Tenmile Creek near Elizabeth	606*
MISSISSIPPI	
Bogue Chitto near Johnston Station	
Bogue Chitto near Summit	592*
Coldwater River near Red Banks	593*
Lobutcha Creek at Zama	594*
Okatoma Creek east of Magee	595
Okatoma Creek near Magee	596
Tallahala Creek at Waldrup	590
Thompson Creek near Clara	597*
West Fork Amite River near Liberty	598*
Yockanookany River near Thomastown	599*

## DESCRIPTION OF DATA TYPE OF DATA

Data collected at all study sites consist of (1) depths, velocities, and discharges measured through the bridge openings, and (2) peak water-surface elevations along the highway embankment and along cross sections. A minimum of eight valley cross sections were surveyed at approximately one valley-width intervals in the vicinity of the bridge at each site. Locations of the cross sections were alined perpendicularly to the assumed direction of flow. Cross sections were extended to intersect the edge of the valley at equal water-surface elevations. Surveying procedures described in the U.S. Geological Survey Techniques of Water-Resources Investigations series (Matthai, 1967; Benson and Dalrymple, 1967) were followed.

HIGH-WATER MARKS

Water-surface elevations were determined from high-water marks identified along the cross sections and the edges of the valley after each flood. During peak discharge measurements, water-surface elevations were marked with standard surveying stakes along the upstream and downstreams sides of the highway embankment. For some floods additional high-water marks were identified in the valley adjacent to the bridge to define in detail the water surface in the approach and exit reaches.

BRIDGE GEOMETRY Detailed bridge geometry was obtained at each site. The bridge cross section was surveyed at the most contracted section. Piers, spur dikes, wingwalls, abutment slopes, and other pertinent geometry were measured.

MANNING'S ROUGHNESS COEFFICIENT Schneider and others (1976) used composite Manning's roughness coefficient values n where frequent changes in roughness occurred. In their study, composite values of n were verified by matching step backwater computations of the water surface with actual water-surface profiles for measured discharges. The range of n values used in this report is based on values used by Schneider and others (1976). Roughness

varies from open fields to dense forests. Roughness values or ranges of roughness values in different parts of the flood plain are shown on the maps. The values shown are based on water depth. The high value is the value where water depth is less than 0.6 meter and the low value applies where water depth is greater than 1.0 meter. A linear relation of roughness to water depth is assumed for water depths between 0.6 and 1.0 meter.

PRESENTATION OF DATA The data are presented on topographic maps enlarged from standard 1:24,000 or 1:62,500 scale U.S. Geological Survey topographic maps which comply with National Map Accuracy Standards. Accuracy limitations of the base maps are retained in the enlargements. Although positions may be scaled closely

on the enlargements, they are not defined with greater accuracy than positions on the base maps. Ground elevations are placed adjacent to solid squares. Elevations of floodmarks are indicated by numerical values adjacent to solid triangles. Floodmark elevations for separate floods are shown on separate sheets. Bridge geometry and road-embankment dimensions are shown with brief notations

of pier spacing and configuration. In addition to the data points shown on the maps, discharge measurements of selected floods, plots of cross sections, and velocity distribution diagrams are shown. Cross-section elevations are tabulated to define stream channels and flood-plain features in greater detail. Each cross section is referred to a zero station established at the extreme left edge (facing downstream) of the valley.

DATUM All elevations presented in this report are referred to

National Geodetic Vertical Datum of 1929 (NGVD).

FLOOD FREQUENCY Flood-frequency relations are presented graphically. Techniques for deriving flood-frequency relations are those described by the U.S. Water Resources Council (1977), and by

INTERNATIONAL SYSTEM OF UNITS (SI) The International System of Units (SI) is used throughout this report. All data were measured in the U.S. customary units and converted to SI units. Ground elevations which were originally determined to the nearest tenth of a foot are rounded to the nearest 0.01 meter. Water-surface elevations which were surveyed to hundredths of a foot are rounded to millimeters. The same criteria apply to all other dimensions, except contour elevations which are shown to the nearest

MULTIPLY SI UNITS	BY	TO OBTAIN U.S. CUSTOMARY UNITS
Meter (m)	<i>LENGTH</i> 3.281	Feet (ft)
Square meter (m²)	AREA 10.76	Square feet (ft²)
Cubic meter (m³)	<i>VOLUME</i> 35.31	Cubic feet (ft³)
Meter per second (m/s)	VELOCITY 3.281	Feet per second (ft/s)
Cubic meter per second (m <sup>3</sup> /s)	FLOW RATE 35.31	Cubic feet per second (ft <sup>3</sup> /s)

DATA FOR FLAGON BAYOU NEAR LIBUSE, LOUISIANA

Data for Flagon Bayou near Libuse obtained in a 4.6-kilometer reach crossed about midway by State Highway 116 are presented on 5 sheets (fig. 2). Sheet 1 contains tables showing cross-section data (table 1) and discharge data (table 2). An aerial view of the reach in the vicinity of the bridge is shown in figure 3. Relative magnitude of the flood is shown on

the frequency curve (fig. 4). The locations of representative ground elevations are shown on sheets 2A and 2B. These are points of significant changes in cross-section elevations or alinement of the axis. Plots of the cross sections are graphic presentations of the

Bridge geometry and road embankments are shown on sheet 2A as they existed at the time of the flood. The cross section surveyed at the downstream side of the bridge is tabulated on sheet 1. The cross section shown for velocity distribution was obtained by sounding from the upstream side of the bridge during the discharge measurement. Data for the flood of December 7, 1971, are presented. Eleven valley cross sections were surveyed after this flood (sheets 2A and 2B). Manning's roughness coefficients and the 1971 flood

boundaries are shown on sheets 2A, 2B, 3A, and 3B.

FLOOD OF DECEMBER 7, 1971 Peak water-surface elevations, measured cross section, and velocities for the flood of December 7, 1971, are shown on sheets 3A and 3B. The flood crested at an elevation of 23.308 meters at the reference point located on the downstream guardrail 34 meters from the left abutment. The peak discharge was 134 cubic meters per second, from a stage-discharge relation developed for the site. A discharge of 132 cubic meters per second was measured at an elevation of 23.265 meters at the reference point (table 2). The recurrence interval of the peak discharge is 4 years (Neely, 1976). See

**SUMMARY** Flood-flow data that will provide a base for evaluating digital models relating to open-channel flow were obtained at 22 sites

on streams in Alabama, Louisiana, and Mississippi. Thirty-five floods were measured. Analysis of the data indicated that backwater and discharges computed by standard indirect methods currently in use would be inaccurate where densely vegetated flood plains are crossed by highway embankments and single-opening bridges. This atlas presents flood information at the site on Flagon Bayou near Libuse, Louisiana. Water depths, velocities, and discharge through the bridge openings for the flood of December 7, 1971, on Flagon Bayou near Libuse were measured, together with peak water-surface elevations along embankments and along cross sections. Manning's roughness coefficients in different parts of the flood plain are shown on a map, and flood-frequency relations are shown on a graph.

ADDITIONAL INFORMATION Other information pertaining to floods in Alabama, Louisiana, and Mississippi may be obtained at the offices of the U.S. Geological Survey listed below: U.S. Geological Survey Room 202, Oil and Gas Board Building (P. O. Box V) University, Alabama 35486

U.S. Geological Survey 6554 Florida Boulevard (P. O. Box 66492) Baton Rouge, Louisiana 70896

U.S. Geological Survey 430 Bounds Street Jackson, Mississippi 39206


figure 4.

SELECTED REFERENCES Barnes, H. H., Jr., 1967, Roughness characteristics of natural channels: U.S. Geol. Survey Water Supply Paper 1849,

Benson, M. A., and Dalrymple, T., 1967, General field and office procedures for indirect discharge measurements: U.S. Geol. Survey Techniques Water-Resources Inv., book 3, Chap. A1, Bradley, J. N., 1970, Hydraulics of bridge waterways: Federal Highway Admin., Hydraulic Design Ser. No. 1, 111 p. Colson, B. E., and Hudson, J. W., 1976, Flood frequency of

Mississippi streams: Mississippi State Highway Dept., 34 p. Hains, C. F., 1973, Floods in Alabama, magnitude and frequency: Alabama Highway Dept., 37 p. Hedman, E. R., 1964, Effects of spur dikes on flow through constrictions: Am. Soc. Civil Engineers Proc., Jour. Hydraulics Div., v. 91, no. HY4, July 1965, p. 155-165. Matthai, H. F., 1967, Measurement of peak discharge at width contractions by indirect methods: U.S. Geol. Survey Techniques Water-Resources Inv., book 3, chap. A4, 44 p. Neely, B. L., Jr., 1976, Floods in Louisiana, magnitude and frequency, 3d ed.: Louisiana Dept. Highways, 340 p.

Schneider, V. R., Board, J. W., Colson, B. E., Lee, F. N., and Druffel, L., 1976, Computation of backwater and discharge at width constrictions of heavily vegetated flood plains: U.S. Geol. Survey Water-Resources Inv. 76-129, 64 p. U.S. Water Resources Council, 1977, Guidelines for determining flood flow frequency: Washington, D.C., U.S. Water Resources Council Bull. 17A, 163 p.



Prepared in cooperation with the

DEPARTMENT OF TRANSPORTATION FEDERAL HIGHWAY ADMINISTRATION

AND THE LOUISIANA DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT

FIGURE 1.—INDEX MAP OF STUDY SITES IN THE BRIDGE BACKWATER INVESTIGATION PROJECT, ALABAMA, LOUISIANA, AND MISSISSIPPI.




FIGURE 2—INDEX MAP SHOWING STUDY REACH, FLAGON BAYOU NEAR LIBUSE, LOUISIANA



FIGURE 3—AERIAL VIEW LOOKING UPSTREAM AT BRIDGE ON STATE HIGHWAY 116 NEAR LIBUSE, LOUISIANA

SECOND




TABLE 2—DISCHARGE MEASUREMENT OF DECEMBER 6, 1971. FLAGON BAYOU NEAR LIBUSE, LOUISIANA ZERO STATION IS AT THE EDGE OF THE LEFT ABUTMENT (FACING DOWNSTREAM). (WATER-SURFACE ELEVATION = 23.265 METERS) TOTAL DISCHARGE=132 CUBIC METERS PER

STATION (METERS)	DEPTH (METERS)	ANGLE (DEGREES)	OBSERVATION DEPTH <sup>1</sup>	VELOCITY (METERS PER SECOND)	
6.4	0.0	0	0.0	0.0	
12.2	1.01	0	0.6	0.037	
15.2	1.40	8	0.0		
15.2	1.40	0		0.037	
10.0	4.05	0.5	0.8	0.0	
18.3	1.95	25	0.2	0.954	
40.0	0.00		0.8	0.634	
19.8	2.96	24	0.2	1.000	
			0.8	0.725	
21.3	3.66	23	0.2	1.024	
			0.8	0.930	
22.9	4.79	23	0.2	1.094	
			0.8	0.975	
23.8	5.24	16	0.2	0.930	
			0.8	0.811	
25.0	5.55	0	0.2	1.216	
			0.8	0.911	
27.4	5.76	0	0.2	1.244	
			0.8	1.024	
29.0	5.79	0	0.2	1.305	
20.0	0.70	O	0.8	0.975	
29.9	5.94	0			
23.3	5.54	U	0.2	1.000	
21.1	6.00	0	0.8	0.930	
31.1	6.00	0	0.2	1.030	
20.0	F 70	0	0.8	1.000	
32.0	5.76	8	0.2	1.116	
			8.0	1.012	
33.5	5.67	16	0.2	1.094	
			8.0	1.094	
35.1	5.36	19	0.2	1.030	
			8.0	0.911	
36.0	5.39	19	0.2	0.826	
			0.8	1.116	
37.2	5.43	27	0.2	1.024	
			0.8	1.244	
38.1	4.94	29	0.2	1.024	
			0.8	1.189	
39.6	4.63	18	0.2	1.024	
			0.8	1.116	
41.1	4.15	11	0.2	1.030	
41.1	4.10		0.8	1.094	
44.2	3.23	0	0.2		
44.2	3.23	U	0.8	0.500	
47.2	2.35	0	0.8	0.872	
47.2	2.33	U		0.512	
E0.0	1.04	10	0.8	0.201	
50.3	1.01	16	0.6	0.177	
54.6	0.0	0	0.0	0.0	
<sup>1</sup> Observation depth is the ratio of the velocity observation depth to the total depth at the station.					

TABLE 1—VALLEY CROSS SECTION DATA FOR FLAGON BAYOU NEAR LIBUSE, LOUISIANA. ZERO STATION IS AT THE LEFT EDGE OF THE VALLEY (FACING DOWNSTREAM).

CROS	S SECTION 1	CPOSS S	ECTION 6 (Cont.)
ChOS	GROUND SURFACE	288	
STATION	ELEVATION	305	21.24 22.40
(METERS)	(METERS)	343	21.24
0	20.02	358	22.71
4	19.45	369	22.86
9	18.81	393	21.95
15 19	18.81 18.50	422	22.25
23	18.81	437	21.97
30	19.72	494	22.07
39	18.56	518	21.95
48	19.05	570	21.76
89	17.40	593	21.67
92 123	19.90	600	23.13
141	19.75 19.69	CPOS	S SECTION 7
166	19.72	Chos	GROUND SURFACE
206	19.90	STATION	ELEVATION
227	20.06	(METERS)	(METERS)
271 288	19.87 19.45	0	23.64
289	18.53	15	21.98
291	17.71	18	21.31
294	18.53	24	21.37
296	19.42	32 70	21.34 21.40
352	19.99	74	22.12
365 390	20.24 21.15	77	21.31
397	21.37	114	21.37
400	21.52	122	21.37
		137 139	21.76 20.54
CROS	S SECTION 2	140	21.85
	GROUND SURFACE	160	20.21
STATION	ELEVATION	169	20.18
(METERS)	(METERS)	177	22.70
0 12	21.72 21.43	186 204	22.52 22.16
20	20.42	255	22.45
24	19.42	287	22.68
30	20.21	334	22.30
37	19.42	338	21.88
40 55	21.15 20.85	357 364	21.88 21.88
61	20.82	378	23.44
91	22.25	0.0	20111
102	19.51	CROS	S SECTION 8
108 113	21.82 20.45		<b>GROUND SURFACE</b>
119	19.23	STATION	<b>ELEVATION</b>
122	20.39	(METERS)	(METERS)
140	20.76	0	23.37
154	20.79	37 183	23.60 22.85
183 189	20.21 19.51	204	22.95
197	19.93	221	22.80
203	20.82	227	22.10
210	20.96	230 235	21.85 22.13
233 237	20.76 18.26	258	22.16
243	17.25	262	20.51
249	18.17	271	20.54
255	19.75	273 297	21.76 22.28
256	20.60	305	22.80
258 263	21.00 21.03	323	22.13
276	20.63	334	21.92
293	20.67	340 341	23.10 21.61
311	20.97	351	21.73
321 335	20.72 21.43	370	23.06
351	21.03	387	22.86
376	20.60	408	22.62
430	20.51	427 443	22.89 22.83
435 437	18.99	452	22.83
439	18.38 18.99	463	22.28
441	20.42	468	22.07
449	21.46	474	22.31
453	21.67	507 520	22.18 22.10
CDOC	CECTION O	552	21.37
CROS	S SECTION 3	558	21.70
STATION	GROUND SURFACE ELEVATION	569	22.65
(METERS)	(METERS)	594	24.16
(IVIETERS)	21.39	CPOS	S SECTION 9
18	21.61	Chos	GROUND SURFACE
36	21.58	STATION	ELEVATION
41 47	20.79	(METERS)	(METERS)
47 53	19.87 20.79	0	24.22
71	20.79	4	23.93
91	21.64	27	23.75
102	21.91	35 52	22.25 23.38

102 126	21.91 21.49	52	23.38
164	21.49	62	23.59
242	21.36	68	23.38
292	21.24	75 86	22.43
304	20.82	93	21.85 22.46
309	21.54	103	23.86
317 335	21.09 20.67	125	24.02
340	21.18	128	22.86
362	21.76	142	23.44
378	21.55	146	22.16
408	21.49	148 155	23.32 23.53
422	21.49	160	23.90
454	21.85	180	23.87
457 461	20.97 20.30	198	23.58
464	19.72	274	23.58
475	20.15	280	23.26
476	21.18	302	23.80
537	20.99	319	23.71
574	22.62	323 326	22.56 23.16
00000	05071011	363	22.65
CROSS	S SECTION 4	363	20.70
Sameonia de Barrisosa e securi	GROUND SURFACE	366	19.17
STATION	ELEVATION	369	20.70
(METERS)	(METERS)	369	23.29
0	23.34	416	22.98
15	23.23	422 430	23.71 23.13
20 91	23.06 22.52	459	21.03
113	22.37	460	21.03
123	23.83	462	23.07
129	23.23	525	23.28
134	22.56	579	23.59
141	22.10	591	24.92
146 155	21.75 21.82	CPOSS	SECTION 10
190	21.88	CHOSS	GROUND SURFAC
194	21.09	STATION	ELEVATION
201	21.37	(METERS)	(METERS)
207	20.76	0	25.12
225	21.34	35	23.90
239 240	21.49	69	23.80
243	20.73 19.84	82	23.86
257	20.33	107	24.02
258	20.85	125	24.37
261	21.76	162 177	24.35 24.29
264	22.30	186	23.16
274	22.34	197	23.99
296 321	22.34	235	24.35
333	22.10 21.81	241	21.46
351	22.19	248	20.85
365	22.28	256 262	21.49 23.90
376	21.49	351	24.53
408	21.46	369	24.29
409 414	20.82	375	23.56
418	20.85 21.79	384	23.65
444	21.82	387	24.17
460	21.58	405	24.48
478	21.60	431 497	24.34 24.05
490	22.22	572	23.09
498	22.82	578	23.84
CROSS	SECTION 5	582	23.04
I KI I		000	04.00

444 460 478 490 498	21.82 21.58 21.60 22.22 22.82	405 431 497 572 578	24.48 24.34 24.05 23.09 23.84
CROS	SS SECTION 5	582 600	23.04
	GROUND SURFACE	613	24.02 23.71
STATION	ELEVATION (METERS)	619	22.74
(METERS) 0	21.48	620 623	23.80 24.11
44	21.48	637	24.26
60 <b>78</b>	21.70 22.10	654	24.51
96	22.42	674 689	24.32 24.14
105	22.01	693	23.53
114 158	22.28 21.85	701 725	24.13
169	21.88	725 732	24.02 24.02
197	21.95	741	24.54
200 202	18.14 18.90	744	25.21
206 207	19.23 19.11	CROSS	SECTION 11
209	20.21	STATION	GROUND SURFACE ELEVATION
213 220	19.81 20.09	(METERS)	(METERS)
224	18.32	0	25.60
235	21.52	18 21	23.07 24.78
241 258	22.65 22.22	27	25.27
276	22.01	30	24.44
288	21.00	61 67	25.33 22.83
294 297	22.13 22.65	72	23.74
328	22.43	76	23.23
343	21.55	81 84	24.41 25.09
350 355	20.33 19.29	100	24.11
356	20.12	112	24.60
359	22.28	120 151	25.05 25.24
383 418	22.55 22.34	164	24.29
448	22.19	236	25.12
474	21.97	250 267	24.38 24.57
501 532	21.73 21.88	274	22.22
535	21.76	286 297	21.31
540 542	20.76 19.84	300	22.22 23.84
543	20.76	303	25.27
548	23.64	317 338	25.18 24.84
CROS	S SECTION 6	362	25.21
ChOS	GROUND SURFACE	375	25.73
STATION	ELEVATION	378	25.97
(METERS)	(METERS)	BRIDG	E SECTION
0	22.97		GROUND SURFACE
30 45	22.07 21.97	STATION	ELEVATION
45 90	21.97	(METERS)	(METERS)

356	20.12	112	24.60
359	22.28	120	25.05
383	22.55	151	25.24
418	22.34	164	24.29
448	22.19	236	25.12
474	21.97	250	24.38
501	21.73	267	24.57
532	21.88	274	22.22
535	21.76	286	21.31
540	20.76	297	22.22
542	19.84	300 303	23.84
543	20.76	317	25.27 25.18
548	23.64	338	24.84
		362	25.21
CROSS	SECTION 6	375	25.73
	GROUND SURFACE	378	25.97
STATION	ELEVATION	0,0	20.07
(METERS)	(METERS)	BRIDGI	SECTION
0	22.97		
30	22.07		GROUND SURFACE
45	21.97	STATION	ELEVATION
90	22.37	(METERS)	(METERS)
107	22.55	0	25.73
139	22.77	0	25.39
		3	24.69
145	22.43	6	23.29
151	22.46	6	23.13
164	22.83	9	22.25
166	22.25	9 12	21.40
167	21.40		20.48
170	20.48	15	20.09
173	20.09	18 21	20.15 19.14
176	20.15	24	17.83
179	19.14	27	17.56
182	17.83	30	17.56
185	17.56	34	17.31
188	17.56	37	17.13
191	17.31	40	17.62
194	17.13	43	18.17
198	17.62	46	18.96
201	18.17	49	20.27
204	18.96	52	21.18
207	20.27	52	22.28
210	21.18	54	23.20
210		55	23.44
	22.28	58	24.66
224	22.52	61	25.24
230	22.22	61	25.73
265	21.81	INTERIOR—GEOLOGICA	L SURVEY, RESTON, VA.—1978—W78530

For sale by Branch of Distribution, U.S. Geological Survey 1200 South Eads Street, Arlington, VA 22202 and Branch of Distribution, U.S. Geological Survey, Box 25286, Federal Center, Denver, CO 80225