


Introduction.—The approximate areas flooded by Hurricane Frederic tides of September 12-13, 1979, along coastal areas of Alabama, Florida, and Mississippi are shown in a series of hydrologic atlases. The atlases (fig. 1) are listed below. The area covered by the atlases extends from about 8 miles west of Fort Walton Beach, Fla., westward along the Gulf Coast through Alabama to Moss Point, Miss., a distance of about 115 miles.

The Chickasaw map shows the areas flooded along the western side of the Mobile River from about 1 mile north of Satsuma, Ala., to Chickasaw, Ala. Extensive wind damage occurred in this area in addition to minor flood damage to some houses and industrial com-

Elevations shown are referred to National Geodetic Vertical Datum of 1929 (NGVD).

## HYDROLOGIC INVESTIGATIONS ATLAS NUMBER






FIGURE 1—Index map of the Mississippi, Alabama, and Florida gulf coast showing location of quadrangles for which flood boundaries of Hurricane Frederic are delineated

Hurricane Frederic was one of the most intense hurricanes of record to enter the United States mainland. A National Weather Service (NWS), National Oceanic and Atmospheric Administration (NOAA) research aircraft reported a flight-level wind of 138 knots (about 160 miles per hour) a short time prior to landfall. A wind velocity gage maintained by the NWS near Dauphin Island, Ala., recorded a maximum wind speed of about 126 knots (145 miles per hour). Lowest central pressure recorded, 943 millibars (about 27.8 inches of mercury), was that reported aboard an Air Force Reconnaissance Aircraft; unofficial central pressure reported at Grand Bay, Ala., was 931 millibars (about 27.5 inches of mercury). The maximum recorded precipitation along the coast during the passage of the hurricane was about 8.5 inches at Dauphin Island, Ala. A map of the storm track

furnished by NWS is shown below. (See fig. 2.) Flooding and water-related damages were most severe at Dauphin Island and Gulf Shores, Ala. However, significant flooding and damage occurred as far east as Pensacola Beach, Fla., and as far west as Moss Point, Miss. Maximum prevailing flood elevations were about 9.7 ft at Dauphin Island, Ala., about 10.3 ft at the U.S. Highway 98 Causeway across Mobile Bay, Ala., and about 14.3 ft at Gulf Shores, Ala.

American Red Cross casualty figures list 10 known deaths in Alabama, 1 in Florida, and 2 in Mississippi. The total number of storm-related injuries and illnesses for the three States is 4,711. Estimates indicate that the total damage caused the Hurricane Frederic probably will exceed \$2 billion. In comparison, the total damage for Hurricane Camille (1969) was \$1.3 billion.

Past tide records were furnished by the U.S. Army Corps of Engineers, Mobile District, and the Mississippi District of the U.S. Geological Survey. Floodmark elevations and other data for Hurricane Frederic were compiled jointly by the Alabama, Florida, and Mississippi Districts of the Geological Survey and the Corps of Engineers.

Acknowledgments.—We greatly appreciate the cooperation of the National Weather Service, National Oceanic and Atmospheric Administration; the U.S. Army Corps of Engineers; the U.S. Air Force; the U.S. Coast Guard; the Alabama Health Department, Division of Public Water Supplies; The American Red Cross; and others who




FIGURE 2—The track of Hurricane Frederic, September 2–14, 1979 (from track of Hurricane Frederic, August 29 to September 14, 1979, furnished by National Weather Service)




FIGURE 3—Known annual maximum tides at Mobile, Alabama, 1772–1979 (Gage at Alabama State Docks)

Multiply inch-pound units By 2.54 25.4

To obtain S.I. units centimeter (cm) millimeter (mm) meter (m) .0003048 kilometer (km) mile (mi) kilometer (km) knot (kt) meter per second (m/s) 1.609 mile per hour (mi/h) kilometer per hour (km/h) kilopascal (kPa) millibar (mb)


International system of units (S.I.).—Most units of measurement

used in this atlas are inch-pound units. The following factors may be

used to convert inch-pound units to Standard International (S.I.) units:

Tidal records.—Records of storm tides along the Gulf Coast have been documented since 1772 at Mobile, Ala., by the Corps of Engineers and others, and continuous tide records have been compiled by the Corps of Engineers since 1940. A tide gage is located at the Alabama State Docks, Mobile, Ala. Elevations of the annual maximum tides at this gage are shown in figure 3. Significant tide elevations at various points along the Gulf Coast for more than 20 hurricanes since 1893 have been recorded by the Corps of Engineers, the Geological Survey, and others. Data pertaining to some of the highest tides of record are shown in table 1. Additional data for Hurricane Camille (1969) tides are shown on some of the maps.


TABLE 1—Hurricane tide elevations at selected locations along the Gulf of Mexico coast, 1772-1979; in feet above National Geodetic Vertical Datum of 1929



Storm-tide frequency.—Frequency of high storm tides in Mobile

Bay was derived from a statistical evaluation of the tidal records of the gage at Mobile, Ala. The frequency, expressed as the relation of recurrence interval to elevation of high tide at the Mobile gage, is shown in figure 4. The recurrence interval is inversely related to the percent probability of an event being equaled or exceeded in any one year. The percent probability of high-tide elevations at the Mobile gage is also indicated. At the Mobile gage, Hurricane Frederic's maximum tide was estimated to have a recurrence interval of about 25 to 30 years; that is, it may be equaled or exceeded on the average of about 40 times in a thousand-year period. The maximum tide at Biloxi, Miss., during Hurricane Camille (1969) was estimated to have a recurrence interval of about 170 years. Because tidal waves dissipate as they move into the bays and

estuaries, the frequency data at the Mobile gage are applicable only at the gage site and at nearby points.






FIGURE 4—Frequency of high tides at Mobile gage (Mobile River at Alabama State Docks)

Variations in maximum tide elevations.—Water-surface elevations of maximum tides of Hurricane Frederic varied from place to place, especially along beach fronts. High-water marks for Hurricane Frederic are identified on atlases as "inside" or "outside." Marks found within a building or structure are labeled "inside;" those located outside of any enclosure are identified as "outside." Where two or more outside marks are shown at one location, the lower marks are considered to be the prevailing high tide; the higher marks are maximum wave height or runup. The maximum documented wave height above the prevailing tide for Hurricane Frederic is about 7 feet. Where the elevation of several high-water marks at a location varied

slightly, the average elevation of the marks is shown. Extent of flooding.—Approximate flood boundaries of Hurricane Frederic are delineated on U.S. Geological Survey topographic maps. Driftlines along streets, roads, dunes, and other landmarks were used

to define the boundaries. Depth of flooding.—The depth of flooding at any point can be estimated by subtracting the ground-surface elevation from the water-surface elevation determined by interpolating between maximum tide elevations shown on the map. Approximate ground elevations can be estimated from contours on the map, although more accurate elevations can be obtained by leveling to bench marks. The elevations of contour lines on some maps are in meters. Elevations of high-water marks shown on these maps are given both in meters and

Emergency water supplies.—Some water wells identified by the Alabama Health Department, Division of Public Water Supplies, as either approved or potential emergency water supplies, are shown on

Additional information.—Other information pertaining to floods along the Gulf Coast may be obtained at the district offices of the U.S. Geological Survey, Tuscaloosa, Alabama, Tallahassee, Florida, and Jackson, Mississippi. Descriptions of tidal characteristics, tidal records, and tidal data may be obtained from the following published reports: Harris, D. L., and Lindsay, C. V., 1957, An index of tide gages and tide gage records for the Atlantic and Gulf Coasts of the United States,

U.S. Department of Commerce, Weather Bureau National Hurricane Research Project, report 7. Wilson, K. V., and Hudson, J. W., 1969, Hurricane Camille tidal flood of August 1969 along the Gulf Coast, U.S. Geological Survey Hydrologic Investigations Atlas (name of quadrangle), Mississippi. HA-402 Pass Christian. HA\_395 Logtown.

HA-396 English Lookout, HA-403 Gulfport North-South. La.-Miss. HA-397 Kiln. HA-404 Biloxi. HA-398 Waveland-Grand HA-405 Ocean Springs-Deer

Island Pass. HA-406 Pascagoula. HA-399 Vidalia. (Scale 1:62,500.) HA-400 Bay St. Louis. HA-407 Kreole-Grand Bay

HA-401 Gulfport NW. U.S. Department of the Army, Corps of Engineers, Mobile District, 1965. Report on Hurricane survey of Mississippi Coast: 49 p. \_1965, Report on Hurricane survey of Northwest Florida, 49 p.

\_1966, Report on Hurricane survey of the Alabama Gulf Coast, 40 p. \_\_1967, Hurricane Betsy, 8-11 September 1965: 65 p.

\_\_\_\_\_1970, Hurricane Camille, 14-22 August 1969, 80 p \_\_1976, Hurricane Eloise, 16-23 September 1975, 89 p.

## HURRICANE FREDERIC TIDAL FLOODS OF SEPTEMBER 12-13, 1979, ALONG THE GULF COAST, CHICKASAW QUADRANGLE, ALABAMA