



DESCRIPTION OF SCENE
At the left in this view east from the lander, a field of drifts of very fine grained material dominates the scene. This material probably covered the area as a thick blanket and was subsequently stripped off by the wind; patches of the material were left behind in the form of drifts scattered among the blocks that litter the landscape. The ridge that forms the horizon above the drifts (line 80, sample 700) lies about 1.18 km from the lander. The block-strewn ridge that forms the horizon on the right is only about 80 m from the lander. The angular blocks that cover the surface range in size from a few tens of millimeters to over 1 m.

Parts of the lander are visible in the lower right. The large object at the center of the scene is the surface sampler in its stored position. Only the back of the instrument housing is visible in the mosaic of two pictures that include it. Most picture-taking sequences for the Viking cameras were planned to avoid parts of the lander, except for the surface sampler, and to image as much of the surface as possible.

At the lower left (line 650, sample 650) just above the lander is a trench dug by the surface sampler to obtain specimens of the martian soil for analysis by instruments on board the lander. The soil was analyzed for biologic activity and for organic and inorganic content. The trench, about 85 mm wide, was dug in a drift of the very fine grained material. During landing, one of the footpads of the spacecraft was buried in this drift.

At the lower right, (line 1550, sample 1750) exhaust from the retro rockets has swept away fine-grained material from beneath the lander during its landing maneuvers and has exposed a firm layer of "Martiancrete". The bright cylindrical object (line 1550, sample 2064) is a latch pin that secured the surface sampler until after landing. The latch pin was released by an extension command to the surface sampler and fell to the surface before the instrument began its sampling activities. The pin is 6 mm in diameter and 82 mm long.

THE VIKING MISSION
Two Viking spacecraft, each consisting of an orbiter and lander, were launched from Kennedy Space Center on August 20 and September 9, 1975. The Viking 1 spacecraft arrived at Mars on June 19, 1976, and was placed in a highly elliptic orbit around the planet at a periastron altitude of nearly 1500 km. The orbiter cameras were used in conjunction with other instrumental methods to find a suitable landing site for the lander. After about 20 days in orbit, the lander was separated from the orbiter, and on July 20, 1976, Viking Lander 1 touched down on the surface of Mars at lat. 22.483° N and long. 47.968° W. (Morris and Jones, 1981) on the west edge of a large basin called Chryse Planitia. It landed in a stable position at a 3° tilt downward in the direction 284.9° clockwise from north.

The side of the lander on which the two cameras are mounted faces southeast. When the cameras are pointed in a direction normal to the front of the lander, the viewing direction is 141.6° clockwise from north along the horizon. The first picture from the surface of Mars, of an area near the lander's footpad 3, was taken immediately after landing by camera 2. During the ensuing 43 days, the cameras responded to all commands and successfully carried out their assigned mission. On September 2, the activities of Lander 1 were reduced to accommodate the planned receipt of data from Viking Lander 2.

On September 3, 1976, Viking Lander 2 successfully landed on Utopia Planitia of Mars (lat. 68° 56' N, 225.736° W), more than 6500 km northeast of Lander 1. (Mayo and others, 1977; Davies and others, 1978). Lander 2 faces approximately north and tilts 8.2° downward in the direction of 274.4° clockwise from north. The viewing direction of its cameras when pointed in a direction normal to the front of the lander is 29.0° clockwise from north along the horizon. The cameras on Viking Lander 2 operated successfully for 61 days until the primary mission of both landers was completed on November 15, 1976, at solar conjunction.

During the primary mission, 454 pictures of the martian surface were processed from Viking Lander 1 data and 582 pictures from Viking Lander 2 data. The extended mission of Viking Lander 1 began December 15, after solar conjunction, and ended in June 1978. During this period, an additional 1636 pictures were obtained from Lander 1 data and 1311 pictures from Lander 2 data. A comprehensive description of the Viking primary mission and the results of eight scientific experiments on board the landers were published in the *Journal of Geophysical Research* (v. 82, no. 28, Sept. 30, 1977; see References).

GEOMETRY OF THE MOSAICS
The computer formatting of the Viking Lander mosaics was done at the Image Processing Laboratories of the Jet Propulsion Laboratory of the California Institute of Technology, Pasadena, Calif., under the general supervision of Elliott C. Levinthal of the Department of Genetics, Stanford University, who represented the Viking Lander Imaging Team. A detailed description of the multiple steps involved in the construction of the Viking Lander mosaics and an acknowledgment of the many people who assisted in the project were given by Levinthal (1980).

GEOMETRY OF THE MOSAICS
The cameras on the Viking Lander acquire data by sampling in equal increments of elevation and azimuth angle. In the accompanying mosaic, 8 mm subpixels at 1° horizontal or vertical angle, regardless of the place of measurement within the panorama. If the martian surface were flat, one pixel (0.04°) on the surface would be 1 mm wide at 40° camera elevation and 2 m wide at imaging 0° from, most straight lines in the scene appear curved in the reconstruction. This representation of the picture data differs from that of a conventional camera having "point perspective" picture geometry, in which rays are projected from object space through the perspective point in the camera lens, to an image plane in the camera.

The geometry of the lander pictures is complicated by additional factors. Because both landers are tilted with respect to the horizon, on the uncorrected pictures the horizon resembles a sine curve. Computer rectification of the pictures measured with respect to the local gravity vector, and horizontal angles can be measured from martian north. These angles are not related in any simple way to the azimuth and elevation angles given in "camera coordinates" for the uncorrected pictures.

There are other geometric distortions due to the camera: optic path distortion that affects a light ray after it passes the camera window; and camera-stem distortions, or "bolt-down" errors, that are caused by the way the cameras are mounted on the lander. The geometric transformation used in creating the mosaic took into account the optic path distortion but not the "bolt-down" errors. However, along the horizon, the error in azimuth angle is equal to the rotational "bolt-down" error for each camera to an accuracy of less than 1 pixel. The scale "azimuth angles from Mars north" has been adjusted to take into account this correction.

The residual azimuth angle errors are less than 1 pixel along the horizon and become larger with steeper elevation angles and larger lander tilts. For the worst case, Lander 2, camera 1, this error is a maximum of 5.7 ± 1 pixel at 40° elevation. The somewhat sinusoidal azimuth-dependent residual elevation error is a maximum of 3 ± 1 pixel for Lander 2, camera 1, and approximately 1 pixel for the other cameras.

VIKING LANDER MOSAICS
The Viking Lander camera acquired many high-resolution pictures of the Chryse Planitia and Utopia Planitia landing sites. Each picture is the product of computer processing of Earth of digital image data transmitted from Mars as a result of "camera events" carried out by one of the lander camera systems. Further computer processing of data from a selected number of these events yielded a total of 10 mosaics. Two pairs of mosaics from Lander 1 data from mosaic from each camera) consisted of one pair made from data taken in the morning (0700-0800 hours) and one pair made with data acquired in mid-afternoon (1400-1530 hours). Similarly, three pairs of mosaics for the Lander 2 site consisted of one pair between 0700 and 0800 hours, one pair at noon, and one pair between 1700 and 1800 hours.

Procedures used for processing the Viking Lander camera data were described by Levinthal and others (1977). The individual camera events used in each mosaic are identified in the outline of the accompanying camera view. Detailed descriptions and reproductions of these camera events were given by Tucker (1978). Copies of the Viking Lander pictures can be obtained from the National Space Science Data Center, Goddard Space Flight Center, Greenbelt, MD, 20771.

The Lander camera system (Huck and others, 1975a) had selectable focus settings for a depth of field from 1.2 m to infinity in the high-resolution (0.04° instantaneous field of view) mode. The survey (low-resolution) mode has an instantaneous field of view of 0.12°; this mode was used in the mosaics only where no high-resolution data were available.

Each complete mosaic extends 34.25° in azimuth, from approximately 5° above the horizon to 60° below. A complete mosaic incorporates approximately 15 million picture elements (pixels). In order to manage the processing of such large data bases, each mosaic was compiled from four individual azimuthal sectors.

Most of the data used in the mosaics were selected from the primary mission. In some cases, extended-mission data were included where primary-mission coverage was absent or where the surface was obscured by the sampler arm. Further selection was made on the basis of optimum focus.

The image data were photographically corrected (Huck and others, 1975b; Patterson and others, 1977; Wolfe and others, 1977) for differences caused by variations in exposure and for solar-lighting differences caused by minor time-of-day variations in the pictures of the scene. The geometry was then transformed to a local Mars horizon and corrected for geometric camera errors (Patterson and others, 1977; Wolfe, 1979). The corrected pixels composing a sector were then combined by the computer into a single image, and an optimum contrast correction was applied.

The mosaics are composites of the best pixels of all the Lander pictures used for each sector. In the computer mosaicking process, the image data derived from the camera systems parameters were assigned priorities on the basis of quality or detail. These data were examined by the computer in sequence according to the priorities, and the best pixels of each data set were used for the mosaic.

The computer formatting of the Viking Lander mosaics was done at the Image Processing Laboratories of the Jet Propulsion Laboratory of the California Institute of Technology, Pasadena, Calif., under the general supervision of Elliott C. Levinthal of the Department of Genetics, Stanford University, who represented the Viking Lander Imaging Team. A detailed description of the multiple steps involved in the construction of the Viking Lander mosaics and an acknowledgment of the many people who assisted in the project were given by Levinthal (1980).

REFERENCES
Davies, M. E., Katayama, F. Y., and Roth, J. A., 1978. Control net of Mars: February 1978. *Rand Corp. R2309-NASA*, 91 p.

Huck, F. O., McCall, H. F., Patterson, W. R., and Taylor, E. K., 1975a. The Viking Mars Lander camera. *Space Science Instruments*, v. 1, no. 2, p. 189-241.

Huck, F. O., Burcher, E. E., Taylor, J. J., and Wall, S. D., 1975b. Radiometric performance of the Viking Mars Lander camera. U. S. National Aeronautics and Space Administration Technical memorandum TMX-7852.

Levinthal, E. C., 1980. The mosaic of Mars as seen by the Viking Lander camera. NASA Contractor Report, (in press).

Levinthal, E. C., Green, William, Jones, K. L., and Tucker, Robert, 1977. Processing the Viking Lander camera data. *Journal of Geophysical Research*, v. 82, no. 28, p. 4412-4420.

Mayo, A. P., Blackshar, W. T., Tolson, R. H., Michael, V. H., Jr., Kelly, G. M., Brouillette, J. P., and Komarek, T. A., 1977. Lander locations, Mars physical phenomena, and solar system parameters: Determination from Viking Lander tracking data. *Journal of Geophysical Research*, v. 82, no. 28, p. 4271-4303.

Morris, J. C., and Jones, K. L., 1980. Viking 1 Lander on the surface of Mars: Revised location. *Science* (in press).

Patterson, W. R., III, Huck, F. O., Wall, S. D., and Wolfe, M. R., 1977. Calibration and performance of the Viking Lander camera. *Journal of Geophysical Research*, v. 82, no. 28, p. 3491-4400.

Tucker, R. B., 1978. Viking Lander imaging investigation: Picture catalog of primary mission experiment data record given by Levinthal (1980).

Wolfe, M. R., Atwood, D. L., and Merrill, M. F., 1977. Viking Lander camera radiometry calibration report. California Institute of Technology, Jet Propulsion Laboratory Publication 77-42, v. 1, 50 p.