





IPL PIC ID 77-10-11-201443
TAPE NO. D160 000
JET PROPULSION LABORATORY


Interior - Geological Survey, Reston, Va. - 1968 - G86039



OUTLINE OF CAMERA 2 VIEW SHOWING CAMERA EVENTS USED IN MOSAIC



VERTICAL VIEW SHOWING VIKING LANDER 1 ORIENTATION
Grid is in spacecraft coordinates



COMPLETE MOSAIC, MORNING SCENE, CAMERA 2
(Corrected for tilt)

DESCRIPTION OF SCENE

The view is north, directly over the top of the lander. The terrain behind the lander is a flat, level plain littered with angular blocks centimeters to meters in size, which are hoisted in places by drifts of very fine grained material. The surface has less relief than the terrain in front of the lander. Parts of the lander block the view of the foreground. The most of the high-gain antenna dominates the center of the scene (line 200, sample 3350). The two large bright objects on each side are covers of the Radioscience Thermoelectric Generators (RTGs) that power the lander. Three photometric calibration charts for the cameras are seen mounted on top of the lander (line 650, sample 2750; line 660, sample 2800; line 450, sample 3500). A circular magnifying mirror used to view particles on magnets mounted on the collector head of the surface sampler is at the right of one of the photometric calibration charts at the center of the lander (line 575, sample 3150). A grid pointed on top of the lander to aid in determining sizes of particles dumped onto it by the surface sampler is seen in the bottom center of the mosaic.

THE VIKING MISSION

Two Viking spacecraft, each consisting of an orbiter and lander, were launched from Kennedy Space Center on August 20 and September 9, 1975. The Viking 1 spacecraft arrived at Mars on June 19, 1976, and was placed in a highly elliptic orbit around the planet at a perapsis altitude of nearly 1500 km. The orbiter camera was used in conjunction with other instrumental methods to find a suitable landing site for the lander. After about 30 days in orbit, the lander was separated from the orbiter, and on July 20, 1976, Viking Lander 1 touched down on the surface of Mars at lat. 22.483° N and long. 47.968° W. (Morris and Jones, 1980) on the west edge of a large basin called Chryse Planitia. It landed in a stable position at a 3° tilt downward in the direction 284.9° clockwise from north. The side of the lander on which the two cameras are mounted faces southeast. When the cameras are pointed in a direction normal to the front of the lander, the viewing direction is 141.6° clockwise from north along the horizon. The first picture from the surface of Mars, of an area near the lander's footprint 3, was taken immediately after landing by camera 2. During the ensuing 43 days, the cameras responded to all commands and successfully carried out their assigned mission. On September 2, the activities of Lander 1 were reduced to accommodate the planned receipt of data from Viking Lander 2.

On September 3, 1976, Viking Lander 2 successfully landed on Utopia Planitia of Mars (47.966° N, 225.736° W), more than 6500 km northeast of Lander 1 (Mayo and others, 1977; Davies and others, 1978). Lander 2 faces approximately north and tilts 8.2° downward in the direction of 277.4° clockwise from north. The viewing direction of its cameras when pointed in a direction normal to the front of the lander is 29.0° clockwise from north along the horizon. The cameras on Viking Lander 2 operated successfully for 61 days until the primary mission of both landers was completed on November 15, 1976, at solar conjunction. During the primary mission, 454 pictures of the martian surface were processed from Viking Lander 1 data and 582 pictures from Viking Lander 2 data. The extended mission of Viking Lander 2 began December 15, after solar conjunction, and ended in June 1978. During this period, an additional 1638 pictures were obtained from Lander 1 data and 1311 pictures from Lander 2 data. A comprehensive description of the Viking primary mission and the results of eight scientific experiments on board the landers were published in the Journal of Geophysical Research, v. 82, no. 28, Sept. 30, 1977; see references.

*Latitudes are areographic (see de Vasconcelos and others, 1973).

VIKING LANDER MOSAICS

The Viking Lander camera acquired many high-resolution pictures of the Chryse Planitia and Utopia Planitia landing sites. Each picture is the product of computer processing on Earth of digital image data transmitted from Mars as a result of "camera events" carried out by one of the lander camera systems. Further computer processing of data from a selected number of these events yielded a total of 10 mosaics. Two pairs of mosaics from Lander 1 data (one mosaic from each camera) consisted of one pair made with data taken in the morning (0700-0800 hours) and one pair made with data acquired in mid-afternoon (1400-1530 hours). Similarly, three pairs of mosaics for the Lander 2 site consisted of one pair between 0700 and 0800 hours, one pair at noon, and one pair between 1700 and 1800 hours.

Procedures used for processing the Viking Lander camera data were described by Levalath and others (1977). The individual camera events used in each mosaic are identified in the outline of the accompanying camera views. Detailed descriptions and reproductions of these camera events were given by Tucker (1978). Copies of the Viking Lander pictures can be obtained from the National Space Science Data Center, Goddard Space Flight Center, Greenbelt, MD, 20771.

The Lander camera system (Huck and others, 1975a) has selectable focus settings for a depth of field from 1.2 m to infinity in the high-resolution (0.4° instantaneous field of view) mode. The survey (low-resolution) mode has an instantaneous field of view of 0.12°; this mode was used in the mosaics only where no high-resolution data were acquired. Each complete mosaic extends 342.5° in azimuth, from approximately 5° above the horizon to 60° below. A complete mosaic incorporates approximately 15 million picture elements (pixels). In order to manage the processing of such large data bases, each mosaic was composed of four individual azimuthal sectors.

Most of the data used in the mosaics were selected from the primary mission. In some cases, extended-mission data were included where primary-mission coverage was absent or where the surface was obscured by the sampler arm. Further selection was made on the basis of optimum focus.

The image data were photoelectrically corrected (Huck and others, 1975b; Patterson and others, 1977; Wolfe and others, 1977) for differences caused by variations in exposure and for subtracting differences caused by minor time-of-day variations in the pictures of the set. The geometry was then transformed to a local Mars horizon and corrected for geometric camera errors (Patterson and others, 1977; Wolfe, 1979). The corrected pixels composing a sector were then combined by the computer into a single image, and an optimum contrast correction was applied.

The mosaics are composites of the best pixels of all the Lander pictures used for each sector. In the computer mosaicking process, the image data derived from the camera events for each sector were assigned priorities on the basis of quality or detail. These data were examined by the computer in sequence according to the priorities, and the best pixels of each data set were used for the mosaic.

The computer formatting of the Viking Lander mosaics was done at the Image Processing Laboratories of the Jet Propulsion Laboratory of the California Institute of Technology, Pasadena, Calif., under the general supervision of Elliott C. Levalath of the Department of Geomatics, Stanford University, who represented the Viking Lander Imaging Team. A detailed description of the multiple steps involved in the construction of the Viking Lander mosaics and an acknowledgment of the many people who assisted in the project were given by Levalath (1980).

GEOMETRY OF THE MOSAICS

The cameras on the Viking Lander acquire data by sampling in equal increments of elevation and azimuth angle. In the accompanying mosaic, 8 mm subtends a 1° horizontal or vertical angle, regardless of the place of measurement within the panorama. If the martian surface were flat, one pixel (0.75 m) on the surface would be 1 mm wide at 60° camera elevation and 2 m wide at the horizon 3 km away. Characteristically for this type of imaging system, most straight lines in the scene appear curved in the reconstruction. This representation of the picture data differs from that of a conventional camera having "point perspective" picture geometry, in which rays are projected from object space, through the perspective point in the camera lens, to an image plane in the camera.

The geometry of the Lander pictures is complicated by additional factors. Because both landers are tilted with respect to the horizon, the uncorrected pictures the horizon resembles a sine curve. Computer rectification of the pictures results in a straight horizon along which vertical angles can be measured with respect to the local gravity vector, and horizontal angles can be measured from martian north. These angles are not related in any simple way to the azimuth and elevation angles given in "camera coordinates" for the uncorrected pictures.

There are other geometric distortions due to the camera: optic path distortion that affects a light ray after it passes the camera windows; and camera-system distortions, or "roll-down" errors, that are caused by the way the cameras are mounted on the lander. The geometric transformation used in creating the mosaics took into account the optic path distortion but not the "roll-down" errors. However, along the horizon, the error in azimuth angle is equal to the rotational "roll-down" error for each camera to an accuracy of less than 1 pixel. The scale "azimuth angles from Mars north" has been adjusted to take into account this correction.

The residual azimuth angle errors are less than 1 pixel along the horizon and become larger with steeper elevation angles and larger lander tilts. For the worst case, Lander 2, camera 1, this error is a maximum of 5.7 1 pixels at 60° elevation. The somewhat sinusoidal azimuth-dependent residual elevation errors is a maximum of 3.1 pixels for Lander 2, camera 1, and approximately 1 pixel for the other cameras.

REFERENCES

Davies, M. E., Katsiyama, F. Y., and Roth, J. A., 1978, Control net of Mars, February 1978, Rand Corp. R-1309, NASA, 91 p.

Huck, F. O., McCall, H. P., Patterson, W. R., and Taylor, G. R., 1975a, The Viking Mars Lander camera: Space Science Instrumentation, 1, no. 2, p. 189-241.

Huck, F. O., Barber, E. J., Taylor, E. J., and Wall, S. D., 1975b, Radiometric performance of the Viking Mars Lander cameras, U.S. National Aeronautics and Space Administration Technical Memorandum, TMX-72692.

Levalath, E. C., 1980, The mosaics of Mars as seen by the Viking Lander cameras, NASA Contractor Report, (in press).

Levalath, E. C., Green, William, Jones, K. L., and Tucker, Robert, 1977, Processing the Viking Lander camera data, Journal of Geophysical Research, v. 82, no. 28, p. 4411-4420.

Mayo, M. R., Blackhear, W. T., Tolson, R. H., Michael, W. H., Jr., Kelly, G. M., Brankle, J. P., and Komarek, T. A., 1977, Lander location, Mars physical spheroids, and solar system parameters: Determination from Viking Lander tracking data, Journal of Geophysical Research, v. 82, no. 28, p. 4397-4403.

Morris, U. C. and Jones, K. L., 1980, Viking 1 Lander on the surface of Mars, Revised location. (in press).

Patterson, W. R., III, Huck, F. O., Wall, S. D., and Wolfe, M. R., 1977, Calibration and performance of the Viking Lander cameras, Journal of Geophysical Research, v. 82, no. 28, p. 3991-4000.

Tucker, R. B., 1978, Viking Lander imaging investigation—picture catalog of primary mission experiment data recorded by the Viking Lander cameras, National Aeronautics and Space Administration Reference Publication 1007, 558 p.

de Vasconcelos, G. D., Davies, M. E., and Sturms, F. M., Jr., 1973, The Martian 9° areographic coordinate system, Journal of Geophysical Research, v. 78, no. 20, p. 4395-4404.

Wolfe, M. R., 1979, Viking Lander camera geometric calibration report: California Institute of Technology, Jet Propulsion Laboratory, (in press).

Wolfe, M. R., Atwood, D. L., and Merrill, M. E., 1977, Viking Lander camera radiometric calibration report: California Institute of Technology, Jet Propulsion Laboratory Publication 77-62, v. 1, 90 p.

VIKING LANDER 1 RECTIFIED PHOTOMOSAIC
MORNING SCENE - CAMERA 2 - SECTOR 4