



IPL PIC ID 77-10-10-213201  
JET PROPULSION LABORATORY

Interior-Geological Survey, Reston, Va.—1984—G83063




OUTLINE OF CAMERA 1 VIEW SHOWING CAMERA EVENTS USED IN MOSAIC



COMPLETE MOSAIC, EVENING SCENE, CAMERA 1  
(Corrected for tilt)

Rock No.	Height	Distance	Size
1	0.4m	2.4m	30mm
2	0.4m	2.4m	30mm
3	0.4m	2.4m	30mm
4	0.4m	2.4m	30mm
5	0.4m	2.4m	30mm
6	0.4m	2.4m	30mm
7	0.4m	2.4m	30mm
8	0.4m	2.4m	30mm
9	0.4m	2.4m	30mm
10	0.4m	2.4m	30mm
11	0.4m	2.4m	30mm
12	0.4m	2.4m	30mm
13	0.4m	2.4m	30mm
14	0.4m	2.4m	30mm
15	0.4m	2.4m	30mm
16	0.4m	2.4m	30mm
17	0.4m	2.4m	30mm
18	0.4m	2.4m	30mm
19	0.4m	2.4m	30mm
20	0.4m	2.4m	30mm



VERTICAL VIEW SHOWING VIKING LANDER 2 ORIENTATION  
Grid is in spacecraft coordinates

**DESCRIPTION OF SCENE**

North of the lander the scene is a flat, boulder-strewn landscape. The boulders are highly pitted or vesicular. The vesicles probably originated from gas bubbles in cooling lava. The interblock areas are composed of fine-grained material that is bound in a coherent crust that breaks into shaly fragments (line 1200, sample 2100). A shallow trough crosses the near field (line 320, sample 430, to line 450, sample 2200), trending approximately east-west. The trough is 8 m from the lander, about 1 m wide, and 10 cm deep. Small drifts (10 cm high) of fine-grained material occupy the floor of the trough (line 460, sample 1400). The trough is part of a polygonal network suggesting that the trough may have formed from cracks resulting from contraction owing to either cooling of a basaltic lava flow or thermal expansion and contraction of frozen ground.

The side of the lander on which the two cameras are mounted faces southeast. When the cameras are pointed in a direction normal to the front of the lander, the viewing direction is 141.6° clockwise from north along the horizon. The first picture from north along the horizon. The first picture from the surface of Mars, of an area near the lander's footpad 3, was taken immediately after landing by camera 2. During the ensuing 43 days, the cameras responded to all commands and successfully carried out their assigned mission. On September 2, the activities of Lander 1 were reduced to accommodate the planned receipt of data from Viking Lander 2.

On September 3, 1976, Viking Lander 2 successfully landed on Utopia Planitia of Mars (47.866° N., 225.736° W.), more than 6500 km northeast of Lander 1 (Mayo and others, 1977; Davies and others, 1978). Lander 2 faces approximately north and tilts 8.2° downward in the direction of 274.4° clockwise from north. The viewing direction of its cameras when pointed in a direction normal to the front of the lander is 20.0° clockwise from north along the horizon. The cameras on Viking Lander 2 operated successfully for 61 days until the primary mission of both landers was completed on November 15, 1976, at solar conjunction.

During the primary mission, 454 pictures of the martian surface were processed from Viking Lander 1 data and 582 pictures from Viking Lander 2 data. A comprehensive description of the Viking primary mission and the results of eight scientific experiments on board the landers were published in the Journal of Geophysical Research (v. 82, no. 28, Sept. 30, 1977; see References).

\*Latitude is aerographic (see de Vasconcelos and others, 1973).

**THE VIKING MISSION**

Two Viking spacecraft, each consisting of an orbiter and lander, were launched from Kennedy Space Center on August 20 and September 9, 1975. The Viking 1 spacecraft arrived at Mars on June 19, 1976, and was placed in a highly elliptic orbit around the planet at a periastron altitude of nearly 1500 km. The orbiter cameras were used in conjunction with other instrumental methods to find a suitable landing site for the lander. After about 30 days in orbit, the lander was separated from the orbiter, and on July 20, 1976, Viking Lander 1 touched down on the surface of Mars at 224.83° W. and 47.866° N. (Moore and Jones, 1980) on the west edge of a large basin called Chryse Planitia. It landed in a stable position at a 3° tilt downward in the direction 284.9° clockwise from north.

The side of the lander on which the two cameras are mounted faces southeast. When the cameras are pointed in a direction normal to the front of the lander, the viewing direction is 141.6° clockwise from north along the horizon. The first picture from the surface of Mars, of an area near the lander's footpad 3, was taken immediately after landing by camera 2. During the ensuing 43 days, the cameras responded to all commands and successfully carried out their assigned mission. On September 2, the activities of Lander 1 were reduced to accommodate the planned receipt of data from Viking Lander 2.

On September 3, 1976, Viking Lander 2 successfully landed on Utopia Planitia of Mars (47.866° N., 225.736° W.), more than 6500 km northeast of Lander 1 (Mayo and others, 1977; Davies and others, 1978). Lander 2 faces approximately north and tilts 8.2° downward in the direction of 274.4° clockwise from north. The viewing direction of its cameras when pointed in a direction normal to the front of the lander is 20.0° clockwise from north along the horizon. The cameras on Viking Lander 2 operated successfully for 61 days until the primary mission of both landers was completed on November 15, 1976, at solar conjunction.

During the primary mission, 454 pictures of the martian surface were processed from Viking Lander 1 data and 582 pictures from Viking Lander 2 data. A comprehensive description of the Viking primary mission and the results of eight scientific experiments on board the landers were published in the Journal of Geophysical Research (v. 82, no. 28, Sept. 30, 1977; see References).

\*Latitude is aerographic (see de Vasconcelos and others, 1973).

**VIKING LANDER MOSAICS**

The Viking Lander camera acquired many high-resolution pictures of the Chryse Planitia and Utopia Planitia landing sites. Each picture is the product of computer processing on Earth of data-image data transmitted from Mars as a result of "camera events" carried out by one of the lander camera systems. Further computer processing of data from a selected number of these events yielded a total of 10 mosaics. Two pairs of mosaics from Lander 1 data (one mosaic from each camera) consisted of one pair made from data taken in the morning (0700-0800 hours) and one pair made with data acquired in mid-afternoon (1400-1500 hours). Similarly, three pairs of mosaics for the Lander 2 site consisted of one pair between 1700 and 1800 hours, one pair of noon, and one pair between 1700 and 1800 hours.

Procedures used for processing the Viking Lander camera data were described by Levinthal and others (1977). The individual camera events used in each mosaic are identified in the outline of the accompanying camera view. Detailed descriptions and reproductions of these camera events were given by Tucker (1978). Copies of the Viking Lander pictures can be obtained from the National Space Science Data Center, Goddard Space Flight Center, Greenbelt, MD, 20771.

The Lander camera system (Huck and others, 1975a) has selectable focus settings for a depth of field from 1.2 m to infinity in the high-resolution (0.64x instantaneous field of view) mode. The survey (low-resolution) mode has an instantaneous field of view of 0.12°; this mode was used in the mosaics only where no high-resolution data were acquired.

Each complete mosaic extends 342.5° in azimuth, from approximately 5° above the horizon to 60° below. A complete mosaic incorporates approximately 15 million picture elements (pixels). In order to manage the processing of such large data bases, each mosaic was compiled from four individual azimuthal sectors.

Most of the data used in the mosaics were selected from the primary mission. In some cases, extended-mission data were included where primary-mission coverage was absent or where the surface was obscured by the sampler arm. Further selection was made on the basis of optimum contrast.

The image data were photometrically corrected (Huck and others, 1975b; Patterson and others, 1977; Wolfe and others, 1977) for differences caused by variations in exposure and for solar-lighting differences caused by minor time-of-day variations in the pictures of the set. The computer mosaicking process, the image data derived from the camera events for each sector were assigned priorities on the basis of quality of detail. These data were examined by the computer to sequence according to the priorities, and the best pixel of each scene was used to compose the mosaic.

The mosaics are composites of the best pixels of all the Lander pictures used for each sector. In the computer mosaicking process, the image data derived from the camera events for each sector were assigned priorities on the basis of quality of detail. These data were examined by the computer to sequence according to the priorities, and the best pixel of each scene was used to compose the mosaic.

The computer formatting of the Viking Lander mosaics was done at the Image Processing Laboratories of the Jet Propulsion Laboratory of the California Institute of Technology, Pasadena, Calif., under the general supervision of Elliott C. Levinthal of the Department of Genetics, Stanford University, who represented the Viking Lander imaging team. A detailed description of the multiple procedures in the construction of the Viking Lander mosaics and an acknowledgment of the many people who assisted in the project were given by Levinthal (1980).

**GEOMETRY OF THE MOSAICS**

The cameras on the Viking Lander acquire data by sampling in equal increments of elevation and azimuth angle. In the accompanying mosaic, 8 mm subtends a 1° horizontal or vertical angle, regardless of the place of measurement within the panorama. If the martian surface were flat, one pixel (0.04°) on the surface would be 1 mm wide at 60° camera elevation and 2 m wide at the horizon 3 km away. Characteristically for this type of imaging system, most straight lines in the scene appear curved in the reconstruction. This representation of the picture data differs from that of a com-

ventional camera having "point perspective" picture geometry, in which rays are projected from object space, through the perspective point in the camera lens, to an image plane in the camera.

The geometry of the Lander pictures is complicated by additional factors. Because both landers are tilted with respect to the horizon, the uncorrected pictures of the horizon resemble a sine curve. Computer rectification of the pictures results in a straight horizon along which vertical angles can be measured with respect to the local gravity vector, and horizontal angles can be measured from martian north. These angles are not related in any simple way to the azimuth and elevation angles given in "camera coordinates" for the unrectified pictures.

There are other geometric distortions due to the camera: optic path distortion that affects a light ray after it passes the camera windows; and camera-system distortions, or "bolt-down" errors, that are caused by the way the cameras are mounted on the lander. The geometric transformation used in creating the mosaics took into account the optic path distortion but not the "bolt-down" errors. However, along the horizon, the error in azimuth angle is equal to the rotational "bolt-down" error for each camera to an accuracy of less than 1 pixel. The scale "azimuth angles from Mars north" has been adjusted to take into account this correction.

The residual azimuth angle errors are less than 1 pixel along the horizon and become larger with steeper elevation angles and larger lander tilts. For the worst case, Lander 2, camera 1, this error is a maximum of 5.7 ± 1 pixels at 40° elevation. The somewhat sinusoidal azimuth-dependent residual elevation error is a maximum of 3 ± 1 pixels for Lander 2, camera 1, and approximately 1 pixel for the other cameras.

**REFERENCES**

Davies, M. E., Katayama, F. Y., and Roth, J. A., 1978, Control net of Mars: February 1978. Rand Corp. R-2309, NASA, 11 p.

Huck, F. O., McCall, H. F., Patterson, W. R., and Taylor, G. R., 1975a, The Viking Mars Lander camera. Space Science Instruments, v. 1, no. 2, p. 189-241.

Huck, F. O., Huchter, E. J., Taylor, E. J., and Wall, S. D., 1975b, Radiometric performance of the Viking Mars Lander cameras. U. S. National Aeronautics and Space Administration Technical Memorandum TM-72092.

Levinthal, E. C., and Jones, K. L., 1980, The mosaics of Mars as seen by the Viking Lander cameras. NASA Contractor Report, 1326.

Levinthal, E. C., Green, William, Jones, K. L., and Tucker, Robert, 1977, Processing the Viking Lander camera data. Journal of Geophysical Research, v. 82, no. 28, p. 4412-4429.

Mayo, A. P., Blackhour, W. T., Tolson, R. H., Michael, W. H., Jr., Kelly, G. M., Brunk, P., and Komarek, T. A., 1977, Lander locations, Mars physical characteristics, and solar system parameters: Determination from Viking Lander tracking data. Journal of Geophysical Research, v. 82, no. 28, p. 427-430.

Morris, E. C., and Jones, K. L., 1980, Viking Lander 1 on the surface of Mars: Revised location. Icarus, v. 44, no. 1, p. 217-222.

Patterson, W. R., III, Huck, F. O., Wall, S. D., and Wolfe, M. R., 1977, Calibration and performance of the Viking Lander cameras. Journal of Geophysical Research, v. 82, no. 28, p. 3491-4400.

Tucker, R. B., 1978, Viking Lander imaging investigation: picture catalog of primary mission experiment data record. National Aeronautics and Space Administration Reference Publication 1007, 558 p.

de Vasconcelos, G. D., Davies, M. E., and Strims, F. M., Jr., 1973, The Mariner 9 aerographic coordinate system. Journal of Geophysical Research, v. 78, no. 20, p. 4395-4400.

Wolfe, M. R., 1981, Viking Lander camera geometry calibration report. California Institute of Technology, Jet Propulsion Laboratory Publication 79-54, v. 1, 36 p.

Wolfe, M. R., Atwood, D. L., and Merrill, M. E., 1977, Viking Lander camera radiometry calibration report. California Institute of Technology, Jet Propulsion Laboratory Publication 77-62, v. 1, 90 p.

**VIKING LANDER 2 RECTIFIED PHOTOMOSAIC  
EVENING SCENE - CAMERA 1 - SECTOR 3**