Base by U.S. Geological Survey

3 1818 00186172 2

MF-981-A
cop. 1

ROAD-SALT STORAGE AND ROAD NETWORK IN CONNECTICUT

Includes favorable aquifers and salt use by town

By

James W. Bingham and James L. Ralston

1978

EXPLANATION

Favorable aquifers Known or inferred coarse-grained and layered (coarse-over-fine and fine-over-coarse) sediments of hydrologic significance to water supply. Yield of wells in these deposits varies greatly, depending on the saturated thickness of the deposits and the aquifer characteristics. Most wells yield enough water for domestic use (about 500 gallons per day or more); large amounts of water (500 to 2000 gallons per minute) for industrial use and municipal supply can be obtained from wells in some favorable areas.

Solid symbol indicates reported ground-water contamination

Interstate Highway

U.S. Highway

State Highway

Other divided highways with interchange

Other roads

Connecticut Department of Transportation salt pile

Connecticut Department of Transportation salt pile, former location.

Town salt pile

Distribution storage pile, private

Based on published and unpublished data assembled for the Connecticut Areawide Water Management Program. Accompanying figure by the U.S. Geological Survey in cooperation with the Connecticut Department of Environmental Protection, from files of the U.S. Geological Survey, Connecticut Department of Environmental Protection, Connecticut Department of Transportation, and Towns.

GEOLOGICAL SURVEY
U.S. DEPT. OF THE INTERIOR
LIBRARY
JAN 29 1979

Scale 1:125,000

1 inch equals approximately 2 miles

0 1 2 3 4 5 KILOMETERS

0 1 2 3 4 5 MILES

ROAD-SALT USE SURVEYED BY TOWN, WINTER OF 1976-77

Size of symbol is an index of salt use in tons per mile of road and not absolute value

Under 50 tons per mile

50 to 100 tons per mile

100 to 200 tons per mile

Over 200 tons per mile

CONNECTICUT

Shaded areas have sand and gravel aquifers with yields, in most cases, greater than 50 gallons per minute to wells.

Hatched areas have sand and gravel aquifers with yields, in most cases, less than 50 gallons per minute to wells.

CONNECTICUT

Shaded areas have sand and gravel aquifers with yields, in most cases, greater than 50 gallons per minute to wells.

Hatched areas have sand and gravel aquifers with yields, in most cases, less than 50 gallons per minute to wells.

LONG ISLAND SOUND

NEW YORK

RHODE ISLAND

MASSACHUSETTS

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

PREPARED IN COOPERATION WITH THE
STATE OF CONNECTICUT
DEPARTMENT OF ENVIRONMENTAL PROTECTION

MISCELLANEOUS FIELD STUDIES MAP MF-981-A