

EXPLANATION

— 80 —
OVERBURDEN ISOPACHS - Showing thickness of overburden, in feet, from surface to top of coal bed. Dashed where vertical accuracy possibly not within 40 feet. Isopach interval 40 feet (12 m) over strip-pable coal and 80 feet (24 m) beyond the stripping-limit line.

— SL —
STRIPPING-LIMIT LINE - Boundary for surface mining (in this quadrangle, the 100-foot-overburden isopach). Arrow points toward strip-pable area.

— 10 —
MINING-RATIO CONTOUR - Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in areas underlain by coal of Reserve Base thickness within the stripping-limit. To convert mining ratio to cubic meters of overburden per metric ton of recoverable coal, multiply mining ratio by 0.8428.

○ 140
DRILL HOLE - Showing thickness of overburden, in feet, from surface to top of coal bed.

Fe - Ferron coal zone


COAL BED SYMBOL AND NAME - Coal bed identified by bracketed numbers is not formally named, but is numbered for identification purposes in this quadrangle only.

— Fe —
TRACE OF COAL ZONE OUTCROP - Showing symbol of name of coal zone as listed above. Arrow points toward coal-bearing area. Dashed where inferred.

..... c
INFERRED LIMIT OF BURNED AND CLINKERED COAL - Arrow points toward area of baked and fused rock.

To convert feet to meters, multiply feet by 0.3048.

NOTE: Overburden isopachs and mining ratio contours are not drawn beyond those shown because of insufficient data.



This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

**COAL RESOURCE OCCURRENCE MAP OF THE NORTHWEST QUARTER OF THE
FACTORY BUTTE 15-MINUTE QUADRANGLE, WAYNE COUNTY, UTAH
BY
DAMES AND MOORE
1979**

PLATE 6
OVERBURDEN ISOPACH AND
MINING RATIO MAP OF THE
FERRON [I] COAL BED