

Figure 4.-- Microlog of test well B-5

				MICROLOG <small>(WITH CALIPER)</small>			
COUNTY <u>SOCORRO</u> FIELD or LOCATION <u>BOSQUE DEL APACHE</u> WELL TEST WELL B-5 COMPANY U. S. ARMY				COMPANY <u>U. S. ARMY</u> <u>WHITE SANDS MISSILE RANGE</u> WELL <u>TEST WELL B-5</u> FIELD <u>BOSQUE DEL APACHE GRANT</u> COUNTY <u>SOCORRO</u> STATE <u>NEW MEXICO</u>			
Permanent Datum: <u>G.L.</u> , Elev. <u>4523</u> Log Measured From <u>G.L., 0</u> Ft. Above Perm. Datum Drilling Measured From <u>G.L.</u>				Other Services: <u>DIL</u> Elev.: K.B. <u>D.F.</u> <u>G.L. 4523</u>			
Date <u>5-10-67</u> Run No. <u>ONE</u> S.O. (LAYNE TEXAS) <u>2310-67</u> Depth—Driller <u>512</u> Depth—Logger <u>510</u> Btm. Log Interval <u>507</u> Top Log Interval <u>10</u> Casing—Driller @ @ @ @ Casing—Logger Bit Size <u>12.5 TO 455, 6 5/8 TO 512</u> Type Fluid in Hole <u>WATER</u>							
Dens. Visc. _____ ml pH Fluid Loss _____ ml Source of Sample <u>CIRCULATED</u> Rm @ Meas. Temp. <u>5.59@ 83 °F</u> @ °F @ °F @ °F Rmf @ Meas. Temp. <u>5.40@ 84 °F</u> @ °F @ °F @ °F Rmc @ Meas. Temp. @ °F @ °F @ °F @ °F Source: Rmf Rmc Rm @ BHT <u>5.56@ 84 °F</u> @ °F @ °F @ °F Time Since Circ. <u>2 HOURS</u> Max. Rec. Temp. <u>84 °F</u> °F °F °F °F Equip. Location <u>3720 HOBBS</u> Recorded By <u>RATLIFF</u> Witnessed By <u>COOPER-MATUS</u>							
FOLD HERE							
REMARKS				Changes in Mud Type or Additional Samples Date Sample No. Depth—Driller Type Fluid in Hole Dens. Visc. ph Fluid Loss Source of Sample Rm @ Meas. Temp. Rmf @ Meas. Temp. Rmc @ Meas. Temp. Source: Rmf Rmc Rm @ BHT Rmf @ BHT Rmc @ BHT			
				Scale Changes Scale Up Hole Scale Down Hole Equipment Data Tool Position Tool Type Run No. Mud Log: Rm: <u>5.65</u> Depth: <u>470</u>			
Equip. Used: PANEL No. <u>MPP-B-54</u>				SONDE No. <u>MPS-C-28</u>			

