


SCHLUMBERGER
PROXIMITY LOG-MICROLOG
 (WITH CALIPER)

COUNTY DONA ANA FIELD or LOCATION WILDCAT WELL T-17 COMPANY JERRY BURGETT	COMPANY JERRY BURGETT WELL T-17 FIELD WILDCAT COUNTY DONA ANA STATE NEW MEXICO LOCATION NE 1/4, SE 1/4, NW 1/4 Other Services: DIL Sec. 27 Twp. 23-S Rge. 5-E Permanent Datum: G.L., Elev. 4020 Log Measured From K.B., 10 Ft. Above Perm. Datum Drilling Measured From K.B. Elev.: K.B. 4030 D.F. G.L. 4020
Date 4-24-69 Run No. ONE Depth—Driller 2515 Depth—Logger 2509 Btm. Log Interval 2507 Top Log Interval 0 Casing—Driller @ @ @ @ Casing—Logger @ @ @ @ Bit Size 6 3/4 Type Fluid in Hole ALCOHOL, MINERAL OIL, QUEABASCO, SODA ASH Dens. Visc. 9.0 34 pH Fluid Loss 9.5 10 ml ml ml ml Source of Sample PIT R _m @ Meas. Temp. 4.46 @ 88 °F @ °F @ °F R _{mf} @ Meas. Temp. 4.23 @ 89 °F @ °F @ °F R _{mc} @ Meas. Temp. 6.5 @ 85 °F @ °F @ °F Source: R _{mf} R _{mc} M C R _m @ BHT 4.8 @ 85 °F @ °F @ °F Time Since Circ. 6 HOURS Max. Rec. Temp. 85 °F °F °F Equip. Location 3720 HOBBS Recorded By FREEMAN Witnessed By BURGETT	

The well name, location and borehole reference data were furnished by the customer.

FOLD HERE

REMARKS

Changes in Mud Type or Additional Samples		Scale Changes		Equipment Data					
		Type Log	Depth	Scale Up Hole	Scale Down Hole	Pad Type	Tool Type	Tool Pos.	Other
Date	Sample No.								
Depth—Driller	Type Fluid in Hole								
Dens.	Visc.								
ph	Fluid Loss								
Source of Sample									
R _m @ Meas. Temp.									
R _{mf} @ Meas. Temp.									
R _{mc} @ Meas. Temp.									
Source: R _{mf} R _{mc}									
R _m @ BHT									
R _{mf} @ BHT									
R _{mc} @ BHT									

Equip. Used: CART. No.:

PANEL No.:

SONDE No.:

Figure 8a.--Proximity log-microlog of test well T-17.