

data locating
 Table 4.--Model test ~~values of the location of~~ the water-table divide
 [Feet south of the north shoreline of the model]

SIMULATED VERTICAL HYDRAULIC CONDUCTIVITY OF GARDINERS CLAY (feet per day)	SIMULATED AVERAGE RECHARGE (million gallons per day per square mile)	Model A ¹				Model B ¹				Model C ¹				Model D ¹			
		TYPE 1 TESTS	TYPE 2 TESTS	TYPE 3 TESTS	TYPE 4 TESTS	TYPE 1 TESTS	TYPE 2 TESTS	TYPE 3 TESTS	TYPE 4 TESTS	TYPE 1 TESTS	TYPE 2 TESTS	TYPE 3 TESTS	TYPE 4 TESTS	TYPE 1 TESTS	TYPE 2 TESTS	TYPE 3 TESTS	TYPE 4 TESTS
1.34 x 10 ⁻¹	1.25	37,000	--	34,000	--	--	--	--	--	--	--	--	--	--	--	--	--
	1.00	38,000	37,000	34,000	35,000	--	--	--	--	--	--	--	--	--	38,000	28,000	28,000
	.75	37,000	--	35,000	--	--	--	--	--	--	--	--	--	--	--	--	--
	.50	39,000	--	36,000	--	--	--	--	--	--	--	--	--	--	--	--	--
	.25	39,000	--	39,000	--	--	--	--	--	--	--	--	--	--	--	--	--
	.10	42,000	--	42,000	--	--	--	--	--	--	--	--	--	--	--	--	--
6.70 x 10 ⁻³	1.25	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	1.00	40,000	39,000	35,000	35,000	38,000	38,000	32,000	33,000	38,000	39,000	30,000	31,000	--	39,000	28,000	28,000
	.75	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	.50	--	--	--	--	38,000	--	34,000	--	39,000	--	34,000	--	--	--	--	--
	.25	--	--	--	--	--	--	36,000	--	--	--	--	--	--	--	--	--
	.10	--	--	--	--	40,000	--	40,000	--	40,000	--	--	--	--	--	--	--
6.70 x 10 ⁻⁴	1.25	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	1.00	--	42,000	34,000	34,000	--	40,000	32,000	33,000	--	40,000	30,000	30,000	--	39,000	28,000	29,000
	.75	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	.50	--	--	--	--	40,000	--	35,000	--	41,000	--	34,000	--	--	--	--	--
	.25	--	--	--	--	--	--	--	--	--	--	36,000	--	--	--	--	--
	.10	43,000	--	--	--	--	--	--	--	41,000	--	39,000	--	39,000	--	--	--
6.70 x 10 ⁻⁵	1.25	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	1.00	--	44,000	36,000	36,000	--	--	--	--	--	--	--	--	--	42,000	--	28,000
	.75	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	.50	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	.25	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	.10	--	--	--	--	--	--	--	--	--	--	--	--	--	--	36,000	--

- 1/ Values of hydraulic conductivity are listed in table 2.
 2/ Type-1 tests--no simulation of streams, and subsea flow limited by the interface;
 3/ Type-2 tests--no simulation of streams, and subsea flow beyond the interface;
 4/ Type-3 tests--simulation of streams, and subsea flow limited by the interface;
 5/ Type-4 tests--simulation of streams, and subsea flow beyond the interface;