

WATER QUALITY AND BATHYMETRY OF SAND LAKE, ANCHORAGE, ALASKA

By Donald E. Donaldson

Sand lake is the deepest lake in the lowlands of Anchorage. It is underlain by deltaic sands and gravels (Scholl and Dobrovolsky, 1972). Sand Lake has no observable surface inlet or outlet. Short-term water-level changes are controlled primarily by precipitation, surface runoff from the surrounding residential area, and evaporation. Long-term changes reflect the regional ground-water level, which in turn may be affected by urban-development practices within the lake basin. However, at this time not enough is known of the hydrology to define precisely the origin of the lake water or the amount and direction of subsurface drainage (Zenone, 1976).

During the past 10 years, urban growth has accelerated in Anchorage. The Sand Lake area exemplifies this growth trend; its population has more than tripled since 1963. In 1973, 36 private dwellings line the shore and approximately 200 homes were within one-quarter mile of the lake. During 1974 and 1975, housing density increased further; Sand Lake has become an urban lake.

As urban development and human activities increase, water resources of an area may be adversely affected unless sound water-resource management practices are instituted (Hasler, 1969; Britton, Averett, and Ferreira, 1975). One form of lake degradation is eutrophication, the natural or artificial enrichment of lake waters by nutrients required by plants; plant growth consequently proliferates, tending to hasten the extinction of a lake (Beeton, 1970). Natural eutrophication is a long-term process, measured in geologic time. However, cultural eutrophication may be much faster and is a major problem in water-resource management (Fruh and others, 1966).

Nutrition of plants in a lake depends on the amounts of certain elements present and their interaction. Phosphorus, nitrogen, iron, and silica are generally accepted as important nutrients promoting plant growth (Britton, Averett, and Ferreira, 1975; Lee, 1970). Bartsch (1972) has reported that increases of phosphorus frequently lead to accelerated eutrophication. One major source of phosphorus and nitrogen is urban runoff (Lee, 1970; Hasler, 1969).

PURPOSE AND SCOPE

A study of Sand Lake was undertaken by the U.S. Geological Survey and the Greater Anchorage Area Borough (now part of the Municipality of Anchorage) to define the water quality and provide a starting point for urban water-resource management.

This report summarizes water-quality and bathymetric information collected by the Geological Survey between 1967 and 1975. This information is intended for use by environmental planning departments, developers, and others interested in or responsible for the management of urban water resources.

DATA COLLECTION AND ANALYSIS

Between 1967 and 1975 miscellaneous water-quality samples were collected from Sand Lake. The 1960 samples are grab samples collected close to the south shore of the lake near site 2. In 1972 three sample sites were chosen; from these sites, samples were collected at selected depths in March, June, and August. The 1974 sample was taken at a point near the middle of the lake (near site 2) and 3 ft (1 m) below the ice. The 1975 samples were integrated with depth (from top to bottom) and came from the east end of the lake (near site 1). In 1974 and 1975 additional water-quality data were acquired, including samples of snow-melt water collected from street gutters during spring breakup periods in the Brentwood subdivision.

The chemical analytical methods and techniques used in this study are described in Raimwater and Thatcher (1960), Brown, Skougstad, and Fishman (1970), and Slack, Averett, Greeson, and Lipscomb (1973).


SELECTED REFERENCES

- Bartsch, A. F., 1972, Role of phosphorus in eutrophication: U.S. Environmental Protection Agency, Natl. Environmental Research Center, Ecological Research Series EPA-600/3-72-001, 45 p.
- Beeton, A. M., 1970, Statement on pollution of the Great Lakes: Wisconsin Univ., Milwaukee, Center for Great Lakes Studies, Spec. Rept. 11, 35 p.
- Britton, L. J., Averett, R. C., and Ferreira, R. F., 1975, An introduction to the processes, problems, and management of urban lakes: U.S. Geol. Survey Circ. 601-K, 22 p.
- Brown, Eugene, Skougstad, M. W., and Fishman, M. J., 1970, Methods for collection and analysis of water samples for dissolved minerals and gases: U.S. Geol. Survey Techniques of Water-Resources Inv., book 5, chap. A1, 160 p.
- Donaldson, D. E., Still, P. S., and Zenone, Chester, 1975, Water-quality data 1960-1973, Anchorage and vicinity, Alaska: U.S. Geol. Survey open-file rept., 59 p.
- Doudoroff, P., and Katz, M., 1953, Critical review of literature on the toxicity of industrial wastes and their components in fish-pt. 2, The metals, as salts: Sewage Indus. Wastes, v. 25, p. 802-839.
- Environmental Protection Agency, Environmental Studies Board, 1972, Water quality criteria 1972-a report of the Committee on Water Quality Criteria: Washington, U.S. Govt. Printing Office, 549 p., [1973].
- Fruh, E. G., Stewart, K. M., Lee, G. F., and Rolich, G. A., 1966, Measurements of eutrophication and trends: Water Pollution Control Jour., v. 38, no. 8, p. 1237-1250.
- Hasler, A. D., 1969, Cultural eutrophication is reversible: Bioscience, v. 19, no. 5, p. 425-431.
- Kluesener, J. W., and Lee, G. F., 1974, Nutrient loading from a separate storm sewer in Madison, Wisconsin: Water Pollution Control Federation Jour., v. 46, no. 5, p. 920-935.
- Lee, G. F., 1970, Eutrophication: Wisconsin Univ., Water Resources Center Occasional Paper No. 2, 39 p.
- Pickering, Q. H., and Gast, M. H., 1972, Acute and chronic toxicity of cadmium to the fathead minnow (*Pimephales promelas*): Fisheries Research Board Canada Jour., Ottawa, Ontario, Canada.
- Putnam, H. D., Brezonik, P. L., and Shannon, E. E., 1972, Eutrophication factors in north central Florida lakes: U.S. Environmental Protection Agency, Water Pollution Control Research Series 16010 D08, 141 p.
- Raimwater, F. H., and Thatcher, L. L., 1960, Methods for collection and analysis of water samples: U.S. Geol. Survey Water-Supply Paper 1454, 301 p.
- Schindler, D. W., 1974, Eutrophication and recovery in experimental lakes—implications for lake management: Science, v. 184, p. 897-899.
- Scholl, H. R., and Dobrovolsky, Ernest, 1972, Generalized geologic map of Anchorage and vicinity, Alaska: U.S. Geol. Survey Misc. Geol. Map 1-787-A.
- Schroeder, H. A., 1965, The biological trace elements or peripatetics through the periodic table: Jour. Chronic Diseases, v. 18, p. 217-228.
- Slack, K. V., Averett, R. C., Greeson, P. E., and Lipscomb, R. G., 1973, Methods for collection and analysis of aquatic biological and microbiological samples: U.S. Geol. Survey Techniques of Water-Resources Inv., book 5, chap. A4, 165 p.
- U.S. Geological Survey, 1973, Water resources data for Alaska, 1972-pt. 2, Water quality records: U.S. Geol. Survey annual State data-compilation rept., p. 306-308.
- Zenone, Chester, 1976, Geohydrology of the lowlands lakes area, Anchorage, Alaska: U.S. Geol. Survey Water-Resources Inv. 76-22, (2 sheets).
- Zenone, Chester, and Donaldson, D. E., 1974, Water-quality and geohydrologic data at two sanitary landfill sites near Anchorage, Alaska: U.S. Geol. Survey open-file map rept.


CONVERSION FACTORS

For those readers who may prefer to use metric units rather than English units, the conversion factors for the terms used in this report are listed below.


Multiply English units	By	To obtain metric units
feet (ft)	0.3048	meters (m)
miles (mi)	1.609	kilometers (km)




Vertical aerial photograph showing the extent of urbanization around Sand Lake in June 1975. PHOTO BY NORTH PACIFIC AERIAL SURVEYS, INC.



Sand Lake and vicinity, Anchorage, Alaska.



Bathymetry of Sand Lake.



Profiles of Selected Water-Quality Parameters, 1972

Seasonal profiles show that Sand Lake is dimictic, that is, the water turns over twice each year. The data indicate, further, that the lake is oligotrophic, that is, having low concentrations of nutrients (nitrogen and phosphorus) and dissolved solids. With the exception of the deepest sample from site 2 (middle) in August, the dissolved-oxygen content was at least 4 mg/l at sampling times. These profiles and the data in the table represent baseline information that may be used to monitor possible water-quality changes.

Selected water-quality data, Sand Lake and Brentwood subdivision runoff water, 1967 to 1975

Parameters	Units	Sand Lake										Brentwood subdivision runoff		
		1960					1972*					1974		
		6/12	9/3	3/27	6/27	8/23	3/27	2/5	5/30	10/7	3/26	4/6	1975	4/7
Specific conductance	micromhos	47	48	62†	51†	52†	60	67	58	58	180	750	360	
Temperature	°C	16.5	22.0	+	+	+	2.0	0.5	10.0	9.5	4.5	4.0	5.0	
Dissolved solids	mg/l	23	24	37	31	31	29	40	30	30	93	-	-	
Total hardness (as CaCO ₃)	mg/l	12	13	-	-	-	15	23	20	19	22	-	-	
pH	units	6.6	6.6	+	+	+	6.8	7.7	6.5	7.0	6.4	6.4	6.5	
Color	Pt-Co units	0	10	-	-	-	5	10	4	5	100	-	-	
Dissolved silica (SiO ₂)	mg/l	0.1	0.1	0.3	0.3	0.4	0.1	0.7	0.2	0.1	2.6	-	-	
Dissolved calcium (Ca)	mg/l	2.8	3.2	3.7	4.1	3.0	3.7	5.7	4.7	4.2	6.8	26	20	
Dissolved magnesium (Mg)	mg/l	1.4	1.2	1.6	1.6	1.6	1.5	2.1	1.9	2.0	1.3	-	-	
Dissolved sodium (Na)	mg/l	1.8	2.0	2.6	2.0	2.6	3.1	3.8	3.2	3.2	19	74	34	
Dissolved potassium (K)	mg/l	1.3	1.7	1.6	1.3	1.6	2.2	2.1	1.7	1.7	7.8	-	-	
Bicarbonate (HCO ₃)	mg/l	8.0	6.0	12	10	11	10	22	11	15	30	10	17	
Carbonate (CO ₃)	mg/l	0	0	0	0	0	0	0	0	0	0	0	0	
Dissolved sulfate (SO ₄)	mg/l	9.0	9.2	9.6	7.7	8.4	8.6	8.7	7.2	6.5	4.5	-	-	
Dissolved chloride (Cl)	mg/l	2.8	2.9	2.9	3.0	3.0	4.1	5.3	5.2	4.4	33	40	74	
Dissolved nitrate (as N)	mg/l	0.00	0.08	0.12†	0.03†	0.00†	0.14**	0.04**	0.01**	0.04**	0.45	-	-	
Dissolved nitrite (as N)	mg/l	-	-	0.00	0.00	-	-	-	-	-	-	-	-	
Dissolved orthophosphorus (as P)	mg/l	-	-	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.24	-	-	
Total phosphorus (as P)	mg/l	-	-	0.01†	0.00†	0.01†	-	-	-	0.01	0.74	0.37	0.31	
Total organic carbon	mg/l	-	-	-	-	14	-	6.0	-	27	-	-	-	
Chlorophyll a, b	µg/l	-	-	-	-	-	-	0	-	-	-	-	-	
Algal growth potential	mg/l	-	-	-	-	-	-	-	1.2	-	-	-	-	
Total coliform ¹	Colony forming units per 100 ml	-	-	7	25	-	-	-	-	-	-	-	-	
Aluminum (Al)	µg/l	-	-	-	-	-	-	100	-	-	-	-	-	
Arsenic (As)	µg/l	-	-	-	-	-	-	20	-	20	-	-	-	
Boron (B)	µg/l	-	-	d21, t13	t11	d10	-	-	t60	-	-	-	-	
Cadmium (Cd)	µg/l	-	-	d2	d3	d2	-	t10	-	t1	-	t0.1	t2	
Chromium (Cr)	µg/l	-	-	d3	d3	d4	-	t0	-	-	-	t30	t50	
Copper (Cu)	µg/l	-	-	d12	d20	d32	-	t30	-	-	-	t85	t110	
Iron (Fe)	µg/l	t40	-	d60	d49	d15	d80	t60, d10	-	t110, d60	d700	t20,000	t33,000	
Lead (Pb)	µg/l	-	-	d3	d4	d3	t<100	t<100	-	t5	t600	t900	t<1000	
Manganese (Mn)	µg/l	-	-	d28	d25	d17	d0	t10, d10	-	d20	d90	-	-	
Selenium (Se)	µg/l	-	-	-	-	-	-	t0.0	-	-	-	-	-	
Silver (Ag)	µg/l	-	-	-	-	-	-	t<10	-	-	-	-	-	
Zinc (Zn)	µg/l	-	-	-	-	-	-	t10	-	-	-	-	-	


¹ See profiles for graphic presentation of selected data.
* Mean concentrations calculated from 18 samples in March, 18 in June, and 15 in August.
** Nitrate values for 1974 and 1975 reflect nitrate plus nitrite as N.

¹ Analyses by Alaska Department of Health and Social Services.
d Dissolved.
t Total.

ERRATA SHEET for USGS open-file report 76-254

"Water quality and bathymetry of Sand Lake, Anchorage, Alaska", by D.E. Donaldson

- In figure titled "Bathymetry of Sand Lake", the position of sampling site 2 is incorrect. Correct location is 400 feet southwest of the plotted position, within the closed 30-foot contour line.
- In the table "Selected water quality data, etc"
 - In the row containing sample dates for Sand Lake, extend upward the vertical line at the right of 3/27 to separate 1974 from 1975
 - The Selenium concentration for Sand Lake sample date 2/5/1975 should read: t0
 - The Cadmium concentration for Brentwood Subdivision sample date 4/6/1975 should read: t1



Concentration of Selected Chemical Constituents in Snowmelt Runoff from Brentwood Subdivision, 1975

Snowmelt water entering Brentwood Canal from the adjacent Brentwood subdivision has a dissolved-solids concentration 10 times as great as that in the main body of Sand Lake. The urban runoff also contains lead concentrations 100 times greater and iron 1,000 times greater than those of Sand Lake water. Lead concentrations exceed known values in any other surface or ground water in the Anchorage area, including water collected beneath landfills (Donaldson, Still, and Zenone, 1975; Zenone and Donaldson, 1974). Concentrations of several other metals may pose a threat to various aquatic life forms (Schroeder, 1965; Doudoroff and Katz, 1953; Pickering and Gast, 1972).

These data were collected during the initial snowmelt runoff flow in the street gutters of the Brentwood subdivision. The volume of snowmelt and rainfall runoff entering Brentwood Canal has not been measured, but it could vary greatly depending on amount, distribution, and intensity of precipitation.