

**OPEN-FILE REPORT**  
This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

**OPEN FILE REPORT 78-038**  
**PLATE 6 OF 54**

**EXPLANATION**

**OVERBURDEN ISOPACHS**--Showing thickness of overburden, in feet, from the surface to the top of the coal bed. Isopach interval 200 feet (61 m).

**STRIPPING-LIMIT LINE**--Boundary for surface mining of the coal bed (in this quadrangle, the 200-foot-overburden isopach). Arrows point toward the area suitable for surface mining. Recovery factor of 85 percent within that area in this quadrangle.

**MINING RATIO CONTOUR**--Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in areas within the stripping-limit.

**BOUNDARY OF RESERVE BASE COAL**--Drawn along the outcrop of coal bed or the contact between burned and unburned coal. Arrows point toward area of Reserve Base coal.



**WELL HOLE**--Upper number is thickness of overburden, in feet, from surface to top of the coal bed. Lower number is the mining ratio, shown where thickness of overburden is less than 200 feet (61 m).

To convert cubic yards of overburden per short ton of recoverable coal to cubic meters of overburden per metric ton of recoverable coal, multiply by 0.84.

To convert feet to meters, multiply feet by 0.3.

Base from U.S. Geological Survey, 1972

Compiled in 1977



**COAL RESOURCE OCCURRENCE AND COAL DEVELOPMENT POTENTIAL MAPS OF THE  
STROUD CREEK QUADRANGLE, ROSEBUD AND BIG HORN COUNTIES, MONTANA**

BY  
**W. J. MAPEL, B. K. MARTIN, AND B. A. BUTLER**  
1978

**PLATE 6**  
**ISOPACH OF OVERBURDEN  
AND MINING-RATIO MAP  
OF THE ANDERSON  
COAL BED**