

OPEN FILE REPORT
This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

OPEN FILE REPORT 78-041
PLATE 6 OF 34

EXPLANATION

200
OVERBURDEN ISOPACHS--Showing thickness of overburden, in feet, from the surface to the top of the coal bed. Isopach interval 200 feet (61 m).


SL
STRIPPING LIMIT LINE--Boundary for surface mining of the coal bed (in this quadrangle, the 200-foot-overburden isopach). Arrows point toward the area suitable for surface mining.

10
MINING RATIO CONTOUR--Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in areas within the stripping limit.

B
BOUNDARY OF RESERVE BASE COAL--Drawn along the outcrop of coal bed or the contact between burned and unburned coal where the coal bed is 5 feet (1.5 m) or more thick, and the 5-foot (1.5-m) coal isopach. Arrows point toward area of Reserve Base coal.

To convert cubic yards of overburden per short ton of recoverable coal to cubic meters of overburden per metric ton of recoverable coal, multiply by 0.84.

To convert feet to meters, multiply feet by 0.3.



COAL RESOURCE OCCURRENCE AND COAL DEVELOPMENT POTENTIAL MAPS OF THE SOUTHERN PART OF THE CLUBFOOT CREEK QUADRANGLE, ROSEBUD COUNTY, MONTANA

BY
W. J. MAPEL AND B. K. MARTIN
1978

PLATE 6
ISOPACH OF OVERBURDEN
AND MINING RATIO MAP
OF THE CANYON AND NANCE
COAL BEDS