

NI 17-4
SERIES V501[illegible]

ROAD DATA 1954 - PARTIALLY REVISED 1964
 Figures in feet denote approximate distances in miles between towns

UNPAVED PLACES

Over 500,000
 250,000 to 500,000
 25,000 to 250,000
 5,000 to 25,000
 Less than 5,000
 (ALL RIGGS)

ROADS

Hard surface, heavy duty
 More than two lanes wide
 Two lanes wide, Federal route marker
 Hard surface, medium duty
 More than two lanes wide
 Two lanes wide, State, interstate route markers
 Improved light duty
 Unimproved dirt
 Trail

LANDMARKS: School, Church, Other, etc.

Horizontal contour point

Slope elevation in feet

Marsh or swamp

Intermittent or dry stream

Power line

Woods brushwood

Approximate road alignment

Woods-brushwood _____ Power line _____

FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092

GRID ZONE DESIGNATION 17S 100,000 M SQUARE IDENTIFICATION IGNORE THE SMALLER figures of any grid number. These are for finding the full coordinates. Use ONLY THE LARGEST figures of the grid number. example 3770000	TO HAVE A STANDARD REFERENCE ON THIS SHEET TO MEASURE 1000 METRES SAMPLE POINT TOWNVILLE Read letters identifying 100,000 metre squares in which the point lies Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or in the east flank Estimate between grid lines to find smaller figure HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the top or bottom margin, or as the line itself Estimate between grid lines to find smaller figure	17 7 5 6
SAMPLE REFERENCE If reporting between 500 ft in any direction, point grid Zone Description as: example 17S125020	17S 125020	17S125020

GREENVILLE, S. C.; GA.; N. C.
1954