

EXPLANATION

— 200 —
OVERBURDEN ISOPACHS - Showing thickness of overburden, in feet, from surface to top of coal bed. Dashed where vertical accuracy possibly not within 40 feet. Isopach interval 200 feet (61.0 m).

○ 315

DRILL HOLE - Showing thickness of overburden, in feet, from surface to top of coal bed.

— 15 —
MINING-RATIO CONTOUR - Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in areas underlain by coal of Reserve Base thickness within the stripping limit (in this quadrangle the 200-foot-overburden isopach).

F2 - F2 (Red Rim) of Lower Fort Union Coal Zone

COAL BED SYMBOL AND NAME

— F2 —



TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Dashed where inferred; short dashed where inferred by present authors.

To convert feet to meters, multiply feet by 0.3048.

To convert mining ratio to cubic meters of overburden per metric ton of recoverable coal, multiply mining ratio by 0.8428.

NOTE: Overburden isopachs are not drawn beyond those shown because of insufficient data.

SCALE 1:24 000



COAL RESOURCE OCCURRENCE MAP OF THE NORTHWEST QUARTER OF THE BRIDGER
PASS 15-MINUTE QUADRANGLE, CARBON COUNTY, WYOMING
BY
DAMES & MOORE
1978

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.