



**EXPLANATION**

— 10 —  
— 9 —

ISOPACHS - Showing thickness of coal, in feet. Long dashed where inferred; short dashed where projected beyond coal-bearing area. Isopach interval 5 feet for the Creston No. 3 coal bed and 1 foot for the Horse Butte coal bed.

○ 17.0

DRILL HOLE - Showing thickness of coal, in feet.

▲ 7.4

POINT OF MEASUREMENT - Showing thickness of coal, in feet. Includes all points of measurement other than drill holes.

Cr-3 - Creston No. 3

**COAL BED SYMBOL AND NAME**

--- Cr-3 ---

TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Arrow points toward coal-bearing area. Dashed where inferred; short dashed where inferred by present authors.

INFERRED LIMIT OF BURNED AND CLINKERED COAL - Arrow points toward area of baked and fused rock.

TRACE OF FAULT - Bar and ball on down-thrown side. Dashed where inferred or approximately located.

To convert feet to meters, multiply feet by 0.3048.

Base from U.S. Geological Survey, 1967

Scale 1:24,000

UTM GRID AND 1967 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

WYOMING QUADRANGLE LOCATION

Compiled in 1977/1978

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

**COAL RESOURCE OCCURRENCE MAP OF THE CRESTON QUADRANGLE,  
SWEETWATER AND CARBON COUNTIES, WYOMING**

BY  
**DAMES & MOORE**  
1978