

EXPLANATION

55  
50  
ISOPACHS OF COAL BED—Showing thickness in feet, interval 5 feet. Dashed where coal is burned or eroded.



37  
DRILL HOLE—Showing coal thickness in feet.

8.9+  
TRACE OF COAL BED OUTCROP—Showing coal thickness in feet, measured at triangle. Arrow points toward the coal-bearing area. "V" symbol indicates burned rock with dotted line showing limit of burning. Dashed where inferred.

0  
FAULT—D indicates downthrown side. Dashed where inferred, dotted where covered.


4  
MINING RATIO CONTOUR—Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in area suitable for surface mining within the stripping limit.

To convert feet to meters, multiply feet by 0.3048.



MAP SHOWING LOCATION OF THE PITCH DRAW QUADRANGLE AND THE POWDER RIVER BASIN KNOWN RECOVERABLE COAL RESOURCE AREA (STIPPLED), WYOMING

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.



**COAL RESOURCE OCCURRENCE MAP OF THE PITCH DRAW QUADRANGLE, CAMPBELL COUNTY, WYOMING**

BY  
**IntraSearch**  
1979