



EXPLANATION

— 30 W-P —
— 25 P —
ISOPACHS OF COAL BED—Showing thickness in feet, interval 5 feet.

— D —
FAULT—D indicates downthrown side. Dashed where inferred, dotted where covered.

● 32
DRILL HOLE—Showing coal thickness in feet.

— SL —
STRIPPING LIMIT LINE— 500 foot overburden isopach boundary for surface mining of coal. Arrow indicates area suitable for surface mining.

— 15 —
MINING RATIO CONTOUR—Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in area suitable for surface mining within the stripping limit.

To convert feet to meters, multiply feet by 0.3048.



MAP SHOWING LOCATION OF THE PITCH DRAW QUADRANGLE AND THE POWDER RIVER BASIN KNOWN RECOVERABLE COAL RESOURCE AREA (STIPPLED), WYOMING

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

Base from U.S. Geological Survey, 1971

SCALE 1:24,000

1 MILE
0 1000 2000 3000 4000 5000 6000 7000 FEET
1 2 3 4 5 6 7 8 9 10 KILOMETER

UTM GRID AND 1971 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

WYOMING
QUADRANGLE LOCATION

COAL RESOURCE OCCURRENCE MAP OF THE PITCH DRAW QUADRANGLE, CAMPBELL COUNTY, WYOMING

BY
IntraSearch
1979