


EXPLANATION

- 1250
- OVERBURDEN ISOPACH—Showing thickness of overburden, in feet, from the surface to the top of the coal bed. Isopach interval 250 feet.
- 25
- INTERBURDEN ISOPACH—Showing thickness of interburden, in feet, between the splits of the coal bed. Isopach interval 25 feet.
- 1498 1643
100
- DRILL HOLE—Showing thickness of overburden, in feet, from the surface to top of coal bed. Lower number indicates interburden thickness, in feet, between upper and lower splits of coal bed.

To convert feet to meters, multiply feet by 0.3048.





MAP SHOWING LOCATION OF THE CROTON QUADRANGLE AND THE POWDER RIVER BASIN KNOWN RECOVERABLE COAL RESOURCE AREA (STIPPLED), WYOMING

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

Base from U.S. Geological Survey, 1972

(ECHETA)
4872 IV NW
SCALE 1:24,000

Compiled in 1979



COAL RESOURCE OCCURRENCE MAP OF THE CROTON QUADRANGLE, CAMPBELL COUNTY, WYOMING

BY
IntraSearch
1979

PLATE 51
ISOPACH MAP OF OVERBURDEN AND INTERBURDEN OF PAWNEE COAL BED