UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

TRUMAN DRAW QUADRANGLE
WYOMING—CAMPBELL CO.
7.5 MINUTE SERIES (TOPOGRAPHIC)

OPEN FILE REPORT 79-029
PLATE 75 OF 75

4873 II NW (LAREY DRAW)

4873 II NW (RECLUSE)

105°52'30" 50' R. 75 W. (SPOTTED HORSE) R. 74 W. 47'30" 105°45'
44°37'30"

T. 54 N.

T. 53 N.

35'

32'30"

T. 53 N.
T. 52 N.

44°30'

1 400 000 FEET

(CROTON)

(WILDCAT)

(ECHETA) 4872 IV NW

(TWENTYMILE BUTTE) 4872 IV NE

(ORIVA NW) 4872 I NW

Base from U.S. Geological Survey, 1971

SCALE 1:24 000

Compiled in 1979

UTM GRID AND 1971 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

GN MN 0°34' 10 MILS 14½° 258 MILS

1 MILE
1000 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 KILOMETER

WYOMING
QUADRANGLE LOCATION

EXPLANATION

NON-FEDERAL COAL LAND-Coal development potential is not rated.

AREA OF HIGH COAL DEVELOPMENT POTENTIAL FOR IN-SITU GASIFICATION-Total coal bed thickness from 1000 to 3000 feet (305 to 914 m) beneath the surface is greater than 200 feet (61 m).

AREA OF MODERATE COAL DEVELOPMENT POTENTIAL FOR IN-SITU GASIFICATION-Total coal bed thickness from 1000 to 3000 feet (305 to 914 m) beneath the surface is from 100 to 200 feet (30 to 61 m).

AREA OF LOW COAL DEVELOPMENT POTENTIAL FOR IN-SITU GASIFICATION-Total coal bed thickness from 1000 to 3000 feet (305 to 914 m) beneath the surface is less than 100 feet (30 m), or coal beds greater than 5 feet (1.5 m) thick are buried 500 to 1000 feet (152 to 305 m).

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

COAL DEVELOPMENT POTENTIAL MAP OF THE TRUMAN DRAW QUADRANGLE, CAMPBELL COUNTY, WYOMING

BY

IntraSearch

1979

PLATE 75
COAL DEVELOPMENT POTENTIAL
FOR IN-SITU GASIFICATION