


EXPLANATION

- 500 —
OVERBURDEN ISOPACH—Showing thickness of overburden, in feet, from the surface to the top of the coal bed. Isopach interval 100 feet below the 500 foot isopach; 250 feet above the 500 foot isopach.
- 125 —
INTERBURDEN ISOPACH—Showing thickness of interburden, in feet, between the splits of the coal bed. Isopach interval 25 feet.
- 207 ● 508 ● 146
○ 7 ○ 5
DRILL HOLE—Showing thickness of overburden, in feet, from the surface to top of coal bed. Lower number indicates interburden thickness, in feet, between upper and lower splits of coal bed.
- D —
FAULT—D indicates downthrown side. Dashed where inferred.
- To convert feet to meters multiply feet by 0.3048.



MAP SHOWING LOCATION OF THE WILDCAT QUADRANGLE AND THE POWDER RIVER BASIN KNOWN RECOVERABLE COAL RESOURCE AREA (STIPPLED), WYOMING

COAL RESOURCE OCCURRENCE MAP OF THE WILDCAT QUADRANGLE, CAMPBELL COUNTY, WYOMING

BY
IntraSearch
1979

PLATE 26
ISOPACH MAP OF OVERBURDEN AND INTERBURDEN OF LOWER SMITH-SWARTZ COAL ZONE

This report has not been edited for conformity with U. S. Geological Survey editorial standards or stratigraphic nomenclature.

4873 II NE (SPOTTED HORSE)
 4873 II SE (TRUMAN DRAW)
 4873 II SW (TENTH WILE BUTTE)
 4873 II NW (RECLUSE)
 4873 II NW (FORVA NW)
 4873 II NW (CAMPBELL)
 4873 II SE (CAMPBELL)

Compiled in 1979

Base from U.S. Geological Survey, 1971

