

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

TEXT TO ACCOMPANY:
COAL RESOURCE OCCURRENCE
AND
COAL DEVELOPMENT POTENTIAL
MAPS
OF THE
ROUGH CREEK QUADRANGLE,
CAMPBELL COUNTY, WYOMING

BY
INTRASEARCH INC.
DENVER, COLORADO

OPEN FILE REPORT 79-063
1979

This report is preliminary, and has not been
edited or reviewed for conformity with
United States Geological Survey standards or
stratigraphic nomenclature.

TABLE OF CONTENTS

	<u>PAGE</u>
I. INTRODUCTION	1
II. GEOLOGY	3
III. DATA SOURCES	8
IV. COAL BED OCCURRENCE	10
V. GEOLOGICAL AND ENGINEERING MAPPING PARAMETERS	12
VI. COAL DEVELOPMENT POTENTIAL	15
Table 1.--Strippable Coal Reserve Base and Hypothetical Resource Data (in short tons) for Federal Coal Lands in the Rough Creek Quadrangle, Campbell County, Wyoming.	18
SELECTED REFERENCES	19

TABLE OF CONTENTS (continued)

<u>MAPS</u>	<u>PLATES</u>
1. Coal Data Map	1
2. Boundary and Coal Data Map	2
3. Coal Data Sheet	3
4. Isopach and Mining Ratio Map of Middle-Lower Wyodak Coal Zone	4
5. Structure Contour Map of Middle-Lower Wyodak Coal Zone	5
6. Isopach Map of Overburden and Interburden of Middle-Lower Wyodak Coal Zone	6
7. Areal Distribution of Identified Resources of Middle-Lower Wyodak Coal Zone	7
8. Identified and Hypothetical Resources of Middle-Lower Wyodak Coal Zone	8
9. Coal Development Potential for Surface Mining Methods	9

CONVERSION TABLE

<u>TO CONVERT</u>	<u>MULTIPLY BY</u>	<u>TO OBTAIN</u>
inches	2.54	centimeters (cm)
feet	0.3048	meters (m)
miles	1.609	kilometers (km)
acres	0.40469	hectares (ha)
tons (short)	0.9072	metric tons (t)
cubic yards/ton	0.8428	cubic meters per metric ton
acre feet	0.12335	hectare-meters
Btu/lb	2.326	kilojoules/kilogram (kJ/kg)
Btu/lb	0.55556	kilocalories/kilogram (kcal/kg)
Fahrenheit	5/9 (F-32)	Celsius

I. Introduction

This report and accompanying maps set forth the Coal Resource Occurrence (CRO) and Coal Development Potential (CDP) of coal beds within the Rough Creek Quadrangle, Campbell County, Wyoming. This CRO and CDP map series includes 9 plates (U. S. Geological Survey Open-File Report 79-063. The project is compiled by IntraSearch Inc., 1600 Ogden Street, Denver, Colorado, under KRCRA Northeastern Powder River Basin, Wyoming Contract Number 14-08-0001-17180. This contract is a part of a program to provide an inventory of unleased federal coal in Known Recoverable Coal Resource Areas (KRCRA) in the western United States.

The Rough Creek Quadrangle is located in Campbell County, in northeastern Wyoming. It encompasses parts of Townships 45 and 46 North, Ranges 69 and 70 West, and covers the area: 43° 52' 30" to 44° 00' north latitude; 105° 07' 30" to 105° 15' west longitude.

A maintained gravel road parallels Dry Creek and provides access to the northwest corner of the Rough Creek Quadrangle. An unimproved road extends north-south through the center of the study area. Numerous minor roads and trails that branch from this unimproved road constitute an avenue of access to much of the quadrangle. Wyoming State Highway 59, connecting Douglas and Gillette, Wyoming, is located approximately 10 miles (16 km) west of the Rough Creek Quadrangle. The closest railroad is the Burlington Northern trackage, approximately 5 miles (8 km) to the west near the proposed Coal Creek mine.

Dry Creek, Rough Creek, and Yellow Hammer Creek in the northwest quadrant, and the East Fork of Coal Creek in the southwest corner flow north-westward into the Belle Fourche River. Several minor creeks in the southeast

portion of the study area flow southeastward into the Cheyenne River. Minimum elevations of 4640 feet (1414 m) above sea level are located in the valley floor of Dry Creek. A maximum elevation of 5111 feet (1558 m) above sea level occurs in the southeast portion of the Rough Creek Quadrangle. The somber grays, yellows, and browns of outcropping shales and siltstones contrast strikingly with the brilliant reds, oranges, and purples of "clinker", and deep greens of the juniper and pine tree growth.

The thirteen to fourteen inches (33 to 36 cm) of annual precipitation that falls in this semi-arid region accrues principally in the springtime. Summer and fall precipitation usually originates from thunderstorms, and infrequent snowfalls of six inches (15 cm) or less generally characterize winter precipitation. Although temperatures ranging from less than -25°F (-32°C) to more than 100°F (38°C) have been recorded near Gillette, Wyoming, average wintertime minimums and summertime maximums approach +5° to +15°F (-15° and -9°C) and 75° to 90°F (24° to 32°C), respectively.

Surface ownership is divided among fee, state, and federal categories with the state and federal surface generally leased to ranchers for grazing purposes. Details of surface ownership are available at the Campbell County Courthouse in Gillette, Wyoming. Details of mineral ownership on federal lands area available from the U. S. Bureau of Land Management in Cheyenne, Wyoming. Federal coal ownership is shown on Plate 2 of the Coal Resource Occurrence maps. The non-federal coal ownership comprises both fee and state coal resources.

The Coal Resource Occurrence and Coal Development Potential program pertains to unleased federal coal and focuses upon: 1) the delineation of lignite, subbituminous, bituminous and anthracite coal at the surface and in the subsurface on federal land; 2) the identification of total tons in place as well as recoverable tons; 3) categorization of these tonnages into measured, indicated, and inferred reserves and resources, and hypothetical resources; and 4) recommendations regarding the potential for surface mining, underground mining, and in-situ gasification of the coal beds. This report evaluates the coal resources of all unleased federal coal beds in the quadrangle which are 5 feet (1.5 m) or greater in thickness and occur at depths down to 3000 feet (914 m). No resources or reserves are computed for leased federal coal, state coal, fee coal, or lands encompassed by coal prospecting permits and preference right lease applications.

Surface and subsurface geological and engineering extrapolations drawn from the current data base suggest the occurrence of approximately 481 million tons (436 million metric tons) of total unleased federal coal resources in the Rough Creek Quadrangle.

The suite of maps that accompany this report set forth and portray the coal resource and reserve occurrence in considerable detail. For the most part, this report supplements the cartographically displayed information with minimum verbal duplication of the CRO-CDP map data.

II. Geology

Regional. The thick, economic coal deposits of the Powder River Basin in northeastern Wyoming occur mostly in the Tongue River Member of the Fort Union Formation, and in the lower part of the Wasatch Formation. Approximately 3000 feet (914 m) of the Fort Union Formation, that includes the

Tongue River, Lebo, and Tullock Members of Paleocene age, are unconformably overlain by approximately 700 feet (213 m) of the Wasatch Formation of Eocene age. These Tertiary formations lie in a structural basin flanked on the east by the Black Hills uplift, on the south by the Hartville and Casper Mountain uplifts, and on the west by the Casper Arch and the Big Horn Mountain uplift. The structural configuration of the Powder River Basin originated in Late Cretaceous time, with episodic uplift thereafter. The Cretaceous Cordillera was the dominant positive land form throughout the Rocky Mountain area at the close of Mesozoic time.

Outcrops of the Wasatch Formation and the Tongue River Member of the Fort Union Formation cover most of the areas of major coal resource occurrence in the Powder River Basin. The Lebo Member of the Fort Union Formation is mapped at the surface northeast of Recluse, Wyoming, east of the principal coal outcrops and associated clinkers (McKay, 1974), and presumably projects into the subsurface beneath much of the basin. One of the principal characteristics for separating the Lebo and Tullock Members (collectively referred to as the Ludlow Member east of Miles City, Montana) from the overlying Tongue River Member is the color differential between the lighter-colored upper portion and the somewhat darker lower portion (Brown, 1958). Although geologists working with subsurface data, principally geophysical logs, in the basin are trying to develop criteria for subsurface recognition of the Lebo-Tullock and Tongue River-Lebo contacts, no definitive guidelines are known to have been published. Hence, for subsurface mapping purposes, the Fort Union Formation is not divided into its member subdivisions for this study.

During the Paleocene epoch, the Powder River Basin tropic to subtropic depositional environment included broad, inland flood basins with extensive swamps, marshes, freshwater lakes, and a sluggish but active northeastward discharging drainage system, superimposed on a near base level, emerging sea floor. Much of the vast areas where organic debris collected was within a reducing depositional environment. Localized uplifts began to disturb the near sea level terrain of northeastern Wyoming, following retreat of the Cretaceous seas. However, the extremely fine-grained characteristics of the Tongue River Member clastics suggest that areas of recurring uplift peripheral to the Powder River Basin were subdued during major coal deposit formation.

The uplift of areas surrounding the Powder River Basin created a structural basin of asymmetric characteristic, with the steep west flank located on the eastern edge of the Big Horn Mountains. The axis of the Powder River Basin is difficult to specifically define, but is thought to be located in the western part of the Basin, and to display a north-south configuration some 15 to 20 miles (24 to 32 km) east of Sheridan, Wyoming. Thus, the sedimentary section described in this report lies on the east flank of the Powder River Basin, with gentle dips of two degrees or less disrupted by surface structure thought to relate to tectonic adjustment and differential compaction.

Some coal beds in the Powder River Basin exceed 200 feet (61 m) in thickness. Deposition of these thick, in-situ coal beds requires a discrete balance between subsidence of the earth's crust and in-filling by tremendous volumes of organic debris. These conditions in concert with a favorable ground water table, non-oxidizing clear water, and a climate amenable to the luxuriant growth of vegetation produce a stabilized swamp critical to the deposition of coal beds.

Deposition of the unusually thick coal beds of the Powder River Basin may be partially attributable to short distance water transportation of organic detritus into areas of crustal subsidence. Variations in coal bed thickness throughout the basin relate to changes in the depositional environment. Drill hole data that indicate either the complete absence or extreme attenuation of a thick coal bed probably relate to location of the drillholes within the ancient stream channel system servicing this low land area in Early Cenozoic time. Where thick coal beds thin rapidly from the depocenter of a favorable depositional environment, it is not unusual to encounter synclinal structure over the maximum coal thickness due to the differential compaction between organic debris in the coal depocenter and fine-grained clastics in the adjacent areas.

The Wasatch Formation of Eocene age crops out over most of the central part of the Powder River Basin and exhibits a disconformable contact with the underlying Fort Union Formation. The contact has been placed at various horizons by different workers; however, for the purpose of this report, in northwestern Campbell County, Wyoming, the contact is positioned near the top of the Roland coal bed as mapped by Olive (1957) and is considered to disconformably descend in the stratigraphic column to the top of the Wyodak-Anderson coal bed (Roland coal bed of Taff, 1909) along the eastern boundary of the coal measures. No attempt is made to differentiate the Wasatch and Fort Union Formations on geophysical logs or in the subsurface mapping program that is a part of this CRO-CDP project.

Although Wasatch and Fort Union lithologies are too similar to allow differentiation in some areas, most of the thicker coal beds occur in the Fort Union section on the east flank of the Powder River Basin. Furthermore, orogenic movements peripheral to the basin apparently increased in

magnitude during Wasatch time causing the deposition of friable, coarse-grained to gritty arkosic sandstones, fine-to very fine-grained sandstones, siltstones, mudstones, claystones, brown-to-black carbonaceous shales and coal beds. These sediments are noticeably to imperceptibly coarser than the underlying Fort Union clastics.

The Rough Creek Quadrangle is located in an area where surface rocks are classified into the Tongue River Member of the Fort Union Formation and the Wasatch Formation. Although the Tongue River Member is reportedly 1200 to 1300 feet (366 to 396 m) thick (Olive, 1957), only 450 to 500 feet (137 to 152 m) are exposed in this area. Approximately 26 to 120 feet (8 to 37 m) of the Wasatch Formation are present in this quadrangle. Olive (1957) correlated coal beds in the Spotted Horse coal field with coal beds in the Sheridan coal field (Baker, 1929) and Gillette coal field (Dobbin and Barnett, 1927), Wyoming, and with coal beds in the Ashland coal field (Bass, 1932) in southeastern Montana. This report utilizes, where possible, the coal bed nomenclature used in previous reports. Baker (1929) assigned names to the Anderson and Canyon coal beds, and the Cook coal bed was named by Bass (1932).

IntraSearch's correlation of thick coal beds from the Spotted Horse coal field to Gillette points out that the Wyodak coal bed, named the D coal bed by Dobbin and Barnett (1927), is equivalent to the Anderson, Canyon and all or part of the Cook coal beds to the north and west of Gillette, Wyoming. Correlation of this suite of coal beds with the Wyodak coal bed south and southwest of Gillette suggest that the Anderson and Canyon coal beds equate with the upper ten to twenty-five percent of the thick Wyodak coal bed, and the Cook and Wall or Upper Wall coal beds are equivalent to the major part of the Wyodak coal bed. Due to problematic correlations outside of the Gillette area, the name Wyodak has been infor-

mally used by many previous authors to represent the coal beds in the area surrounding the Wyodak coal mine. The Wildcat and Moyer coal beds were informally named by IntraSearch (1978b and 1979).

Local. The Rough Creek Quadrangle lies on the eastern flank of the Powder River Basin, where the strata dip gently westward. The Wasatch Formation caps the higher elevations over approximately thirty percent of the quadrangle, and is comprised of friable, coarse-grained to gritty arkosic sandstones, fine-to very fine-grained sandstones, siltstones, mudstones, claystones, brown-to-black carbonaceous shales, and coal beds. The Tongue River Member of the Fort Union Formation crops out over the remaining area. The Fort Union Formation is composed of very fine-grained sandstones, siltstones, claystones, shales, carbonaceous shales, and numerous coal beds.

III. Data Sources

Areal geology of the coal outcrops and associated clinker is derived from the Preliminary Coal Resource Occurrence Map of the Rough Creek Quadrangle by Buck (1977) . Except for minor outcrops in the extreme southwestern quadrant, the W_1 and W_2 outcrops of Buck (1977) are referred to by IntraSearch in this report as the Middle and Lower Wyodak coal bed outcrops, respectively. Outcrop configurations of Buck are adjusted to a minor degree so that they relate to the current topographic map of this area.

The major source of subsurface control, particularly on deep coal beds, is the geophysical logs from oil and gas test bores and producing wells. Some geophysical logs are not applicable to this study, for the logs relate only to the deep potentially productive oil and gas zones.

More than eighty percent of the logs include resistivity, conductivity, and self-potential curves. Occasionally the logs include gamma, density, and sonic curves. These logs are available from several commercial sources.

All geophysical logs available in the quadrangle are scanned to select those with data applicable to Coal Resource Occurrence mapping. Paper copies of the logs are obtained, interpreted, and coal intervals annotated. Maximum accuracy of coal bed identification is accomplished where gamma, density, and resistivity curves are available. Coal bed tops and bottoms are picked on the logs at the midpoint between the minimum and maximum curve deflections. The correlation of coal beds within and between quadrangles is achieved utilizing a fence diagram to associate local correlations with regional coal occurrences.

In some parts of the Powder River Basin, additional subsurface control is available from U. S. Geological Survey open-file reports that include geophysical and lithologic logs of shallow holes drilled specifically for coal exploration. A sparse scattering of subsurface data points are shown on unpublished CRO-CDP maps compiled by the U. S. Geological Survey, and where these data are utilized, the rock-coal intervals are shown on the Coal Data Map (Plate 1). Inasmuch as these drillholes have no identifier headings, they are not set forth on the Coal Data Sheet (Plate 3). The geophysical logs of these drill holes were not available to IntraSearch to ascertain the accuracy of horizontal location, topographic elevation, and down-hole data interpretation.

The reliability of correlations, set forth by IntraSearch in this report, vary depending on: the density and quality of lithologic and geophysical logs; the detail, thoroughness, and accuracy of published and unpublished surface geological maps, and interpretative proficiency. There is no intent on the part of IntraSearch to refute nomenclature established in

the literature or used locally by workers in the area. IntraSearch nomenclature focuses upon the suggestion of regional coal bed names applicable throughout the eastern Powder River Basin. It is expected and entirely reasonable that some differences of opinion regarding correlations as suggested by IntraSearch exist. Additional drilling for coal, oil, gas, water, and uranium, coupled with expanded mapping of coal bed outcrops and associated clinkers will broaden the data base for coal bed correlations and allow continued improvement in the understanding of coal bed occurrences in the eastern Powder River Basin.

The topographic map of the Rough Creek Quadrangle is published by the U. S. Geological Survey, compilation date, 1971. Land ownership data are compiled from land plats available from the U. S. Bureau of Land Management in Cheyenne, Wyoming. This information is current to October 13, 1977.

IV. Coal Bed Occurrence

Fort Union coal beds that are present in all or part of the Rough Creek Quadrangle include, in descending stratigraphic order, the Upper Wyodak, Middle Wyodak, Lower Wyodak, Wildcat, and Moyer coal beds. A complete suite of maps (structure, isopach, mining ratio, overburden/interburden, identified resources, and areal distribution of identified resources) is prepared for the Middle and Lower Wyodak coal zone. Areal extent of the Upper Wyodak coal bed is restricted to a small area approximately one square mile in size, therefore, no maps are prepared for this coal bed. The Wildcat and Moyer coal beds are not mapped due to insufficient thickness, lack of areal extent, and insufficient data.

No physical and chemical analyses are known to have been published regarding the coal beds in the Rough Creek Quadrangle. However, an "as received" basis proximate analyses for the Wyodak coal bed exists in the Neil Butte Quadrangle to the west and is as follows:

COAL BED NAME		ASH	FIXED CARBON	MOISTURE	VOLATILES	SULPHUR	BTU/LB
Hole							
Wyodak (U)	755	4.438	35.522	27.405	32.719	0.207	8568

(U) - U. S. Geological Survey and Montana Bureau of Mines and Geology - 1976.

The Coal Data Sheet, Plate 3, shows the downhole identification of coal beds within the quadrangle as interpreted from U. S. Geological Survey and Montana Bureau of Mines and Geology drill holes, and from oil and gas test bores and producing sites. A datum coal bed is utilized to position columnar sections on Plate 3. This portrayal is schematic by design; hence no structural or coal thickness implications are suggested by the dashed correlation lines projected through no record (NR) areas. Inasmuch as the Wyodak zone underlies most of the quadrangle, it is designated as datum for the correlation diagram. Subsurface data are sparse for the correlation of coal beds in the Rough Creek Quadrangle. The Wildcat coal bed is identified in only three drill holes and averages 4 feet (1.2 m) thick. Only two geophysical logs contain information on the Moyer coal bed, and these indicate an average thickness of 6 feet (1.8 m). Neither the Wildcat nor Moyer coal beds are mapped in this quadrangle.

The Wyodak coal bed is eroded from approximately fifty percent of the quadrangle with some burning apparent along the coal bed outcrop. A coal bed split line extends across the northwest corner of the study area: hence, in the southern and eastern portions of the Rough Creek Quadrangle, the Wyodak coal bed divides into the Middle and Lower Wyodak coal beds (Plate 5). Exten-

sive burning of the Lower Wyodak coal bed is apparent in the northwest corner of the study area. The undivided Wyodak coal bed ranges from 15 to 30 feet (5 to 9 m) thick, attaining the maximum thickness of 30 feet (9 m) in the extreme northwest corner of the quadrangle. South of the line that divides the Middle and Lower Wyodak coal beds, the Upper and Middle Wyodak coal beds converge, necessitating use of the upper Wyodak outcrop configuration for both the Upper and Middle Wyodak burn-erosion line. Both the Middle and Lower Wyodak coal beds south of the split line contain non-coal intervals less than 24 feet (7 m) thick. From 25 to 50 feet (8 to 15 m) of clastic sediment separate the Middle and Lower Wyodak coal beds. The Middle Wyodak coal bed averages 38 feet (12 m) thick, and varies from 35 to 40 feet (11 to 12 m) in thickness. The Lower Wyodak coal bed ranges from 10 to 20 feet (3 to 6 m) thick, and averages 14 feet (4 m). Structural contours on top of the Middle and Lower Wyodak coal beds indicate a westward dip of one to two degrees (Plate 5). The Wyodak coal bed lies less than 200 feet (61 m) beneath the surface throughout the Rough Creek Quadrangle.

V. Geological and Engineering Mapping Parameters

The correct horizontal location and elevation of drill holes utilized in subsurface mapping are critical to map accuracy. IntraSearch plots the horizontal location of the drill hole as described on the geophysical log heading. Occasionally this location is superimposed or near to a drillsite shown on the topographic map, and the topographic map horizontal location is utilized. If the ground elevation on the geophysical log does not agree with the topographic elevation of the drillsite, the geophysical log ground elevation is adjusted to conformance. If there is

no indication of a drillsite on the topographic map, the "quarter, quarter, quarter" heading location is shifted within a small area until the ground elevation on the heading agrees with the topographic map elevation. If no elevation agreement can be reached, the well heading or data sheet is rechecked for footage measurements and ground elevation correctness. Inquiries to the companies who provided the oil and gas geophysical logs frequently reveal that corrections have been made in the original survey. If all horizontal location data sources have been checked and the information accepted as the best available data, the drillsite elevation on the geophysical log is modified to agree with the topographic map elevation. IntraSearch considers this agreement mandatory for the proper construction of most subsurface maps, but in particular, the overburden isopach, the ratio, and Coal Development Potential maps.

Subsurface mapping is based on geologic data within and adjacent to the Rough Creek Quadrangle area. Data from geophysical logs are used to correlate coal beds and control contour lines for the coal thickness, structure, and overburden maps. Isopach lines are also drawn to honor selected measured sections where there is sparse subsurface control. Where isopach contours do not honor surface measured sections, the surface thicknesses are thought to be attenuated by oxidation and/or erosion, hence not reflective of total coal thickness. Isopach lines extend to the coal bed outcrops, the projections of coal bed outcrops, and the contact between porcellanite (clinker) and unoxidized coal in place. Attenuation of total coal bed thickness is known to take place near these lines of definition; however, the overestimation of coal bed tonnages that results from this projection of total coal thickness is insignificant to the Coal Development Potential maps. Structure contour maps are constructed on the tops of the main coal beds.

Where subsurface data is scarce, supplemental structural control points are selected from the topographic map along coal outcrops.

In preparing overburden isopach maps, no attempt is made to identify coal beds that occur in the overburden to a particular coal bed under study. Mining ratio maps for this quadrangle are constructed utilizing a ninety-five percent recovery factor. Contours of these maps identify the ratio of cubic yards of overburden to tons of recoverable coal. Where ratio control points are sparse, interpolated points are computed using coal structure, coal isopach, and topographic control. On the Areal Distribution of Identified Resources Map (ADIR), coal bed reserves are not calculated where the coal is less than 5 feet (1.5 m) thick, where the coal occurs at a depth greater than 500 feet (152 m), where non-federal coal exists, or where federal coal leases, preference right lease applications, and coal prospecting permits exist.

Coal tonnage calculations involve the planimetering of areas of measured, indicated, inferred reserves and resources, and hypothetical resources to determine their areal extent in acres. An Insufficient Data Line is drawn to delineate areas where surface and subsurface data are too sparse for CRO map construction. Various categories of resources are calculated in the unmapped areas by utilizing coal bed thicknesses mapped in the geologically controlled area adjacent to the insufficient data line. Acres are multiplied by the average coal bed thickness and 1770 (the number of tons of subbituminous C per acre-foot, 13,018 metric tons per hectare-meter), to determine total tons in place. Recoverable tonnage is calculated at 95 percent of the total tons in place. Where tonnages are computed for the CRO-CDP map series, resources and reserves are expressed in millions of tons. Frequently the planimetering of coal resources on a sectionized basis involves

complexly curvilinear lines (coal bed outcrop and 500-foot stripping limit designations) in relationship with linear section boundaries and circular resource category boundaries. Where these relationships occur, generalizations of complex curvilinear lines are discretely utilized, and resources and/or reserves are calculated within an estimated two to three percent plus or minus accuracy.

VI. Coal Development Potential

Strippable Coal Development Potential. Areas where coal beds are 5 feet (1.5 m) or more in thickness and are overlain by 500 feet (152 m) or less of overburden are considered to have potential for surface mining and are assigned a high, moderate, or low development potential based on the mining ratio (cubic yards of overburden per ton of recoverable coal). The formula used to calculate mining ratios is as follows:

$$MR = \frac{t_o (0.911) *}{t_c (rf)}$$

where MR=mining ratio
t_o=thickness of overburden
t_c=thickness of coal
rf=recovery factor
0.911=conversion factor (cu.yds./ton)

*Use (0.922) for lignite

A surface mining potential map (Plate 9) is prepared utilizing the following mining ratio criteria for coal beds 5 to 40 feet (1.5 to 12 m) thick:

1. Low development potential = 15:1 and greater ratio.
2. Moderate development potential = 10:1 to 15:1 ratio.
3. High development potential = 0 to 10:1 ratio.

The following mining ratio criteria is utilized for coal beds greater than 40 feet (12 m) thick:

1. Low development potential = 7:1 and greater ratio.
2. Moderate development potential = 5:1 to 7:1 ratio.
3. High development potential = 0 to 5:1 ratio.

The Upper Wyodak, Middle Wyodak, and Lower Wyodak coal beds lie less than 200 feet (61 m) beneath the surface throughout the Rough Creek Quadrangle. The combined Middle and Lower Wyodak coal beds have a mining ratio of less than 10:1 throughout forty percent of the study area, therefore this area has a high development potential for surface mining. Areas of no coal are present in approximately fifty percent of the quadrangle where the Wyodak coal beds are burned or eroded in the eastern and northeastern portions of the study area (Plate 9). Moderate potential areas occur in the western portion of the quadrangle due to Wyodak coal bed thinning and increasing overburden thicknesses. Table 1 sets forth the estimated strip-pable reserve base tonnages per coal bed for the quadrangle.

Underground Mining Coal Development Potential. Subsurface coal mining potential throughout the Rough Creek Quadrangle is considered low. Inasmuch as recovery factors have not been established for the underground development of coal beds in this quadrangle, reserves are not calculated for coal beds buried more than 500 feet (152 m) beneath the surface. Because of the thinness and limited areal extent of the Wildcat and Moyer coal beds, they are not mapped and no reserve base is calculated for the underground mining potential.

In-Situ Gasification Coal Development Potential. The evaluation of subsurface coal deposits for in-situ gasification potential relates to the occurrence of coal beds more than 5 feet (1.5 m) thick buried from 500 to 3000 feet (152 to 914 m) beneath the surface. This categorization is as follows:

1. Low development potential relates to: 1) a total coal section less than 100 feet (30 m) thick that lies 500 feet (152 m) to 3000 feet (914 m) beneath the surface, or 2) coal beds 5 feet (1.5 m) or more in thickness that lie 500 feet (152 m) to 1000 feet (305 m) beneath the surface.
2. Moderate development potential is assigned to a total coal section from 100 to 200 feet (30 to 61 m) thick, and buried from 1000 to 3000 feet (305 to 914 m) beneath the surface.
3. High development potential involves 200 feet (61 m) or more of total coal thickness buried from 1000 to 3000 feet (305 to 914 m).

The coal development potential for in-situ gasification on the Rough Creek Quadrangle is low, hence no CDP map is generated for this map series.

Table 1.--Strippable Coal Reserve Base and Hypothetical Resource Data (in short tons) for Federal Coal Lands in the Rough Creek Quadrangle, Campbell County, Wyoming.

Development potentials are based on mining ratios (cubic yards of overburden/ton of recoverable coal).

Coal Bed	High Development Potential (0-10:1 Mining Ratio)	Moderate Development Potential (10:1-15:1 Mining Ratio)	Low Development Potential (>15:1 Mining Ratio)	Total
<u>Reserve Base</u>				
Middle-Lower Wyodak	413,730,000	33,420,000	8,330,000	455,480,000
Total	413,730,000	33,420,000	8,330,000	455,480,000
<u>Hypothetical Resource</u>				
Middle-Lower Wyodak	_____	_____	1,720,000	1,720,000
Total	_____	_____	1,720,000	1,720,000
GRAND TOTAL	413,730,000	33,420,000	10,050,000	457,200,000

SELECTED REFERENCES

- Baker, A. A., 1929, The northward extension of the Sheridan coal field, Big Horn and Rosebud Counties, Montana: U. S. Geol. Survey Bull. 806-B, p. 15-67.
- Bass, N. W., 1932, The Ashland coal field, Rosebud, Powder River, and Custer Counties, Montana: U. S. Geol. Survey Bull. 831-B, p. 19-105.
- Brown, R. W., 1958, Fort Union Formation in the Powder River Basin, Wyoming: Wyo. Geol. Soc. Guidebook, Thirteenth Annual Field Conf., p. 111-113.
- Buck, S. P., 1977, Preliminary coal resource occurrence map of the Rough Creek Quadrangle, Campbell County, Wyoming: U. S. Geol. Survey unpublished report, scale 1:24,000.
- Dobbin, C. E., and Barnett, V. H., 1927, The Gillette coal field, north-eastern Wyoming, with a chapter on the Minturn district and north-western part of the Gillette field by W. T. Thom, Jr.: U. S. Geol. Survey Bull. 796-A, p. 1-50.
- Glass, G. B., 1975, Review of Wyoming coal fields, 1975: Wyoming Geol. Survey Public Information circ. 4, p. 10.
- IntraSearch Inc., 1978a, Coal resource occurrence and coal development potential of the Cabin Creek Northeast Quadrangle, Sheridan and Campbell Counties, Wyoming and Powder River County, Montana: U. S. Geol. Survey Open-File Report 78-064, 21 p.
- _____, 1978b, Coal resource occurrence and coal development potential of the Rocky Butte Quadrangle, Campbell County, Wyoming: U. S. Geol. Survey Open-File Report 78-830, 22 p.
- _____, 1979, Coal resource occurrence and coal development potential of the Larey Draw Quadrangle, Campbell County, Wyoming: U. S. Geol. Survey Open-File Report 79-023, 29 p.

- Jacob, A. F., 1973, Depositional environments of Paleocene Tongue River Formation: Am. Assoc. of Petroleum Geologists Bull., vol. 56, no. 6, p. 1038-1052.
- McKay, E. J., 1974, Preliminary geologic map of the Bertha 2 NW (Rocky Butte) Quadrangle, Campbell County, Wyoming: U. S. Geol. Survey Open-File Report 74-173, scale 1:24,000.
- Olive, W. W., 1957, The Spotted Horse coal field, Sheridan and Campbell Counties, Wyoming: U. S. Geol. Survey Bull. 1050, 83 p.
- Schell, E. M., and Mowat, G. D., 1972, Reconnaissance map showing some coal and clinker beds in the Fort Union and Wasatch Formations in the eastern Powder River Basin, Campbell and Converse Counties, Wyoming: U. S. Geol. Survey Open-File Report scale 1:63,360.
- Taff, J. A., 1909, The Sheridan coal field, Wyoming: U. S. Geol. Survey Bull. 341-B, p. 123-150.
- U. S. Bureau of Mines and U. S. Geological Survey, 1976, Coal resource classification system of the U. S. Bureau of Mines and U. S. Geological Survey: U. S. Geol. Survey Bull. 1450-B, 7p.
- U. S. Geological Survey and Montana Bureau of Mines and Geology, 1973, Preliminary report of coal drill-hole data and chemical analyses of coal beds in Sheridan and Campbell Counties, Wyoming, and Big Horn County, Montana: U. S. Geol. Survey Open-File Report 73-351, 51 p.
- U. S. Geological Survey and Montana Bureau of Mines and Geology, 1974, Preliminary report of coal drill-hole data and chemical analyses of coal beds in Campbell County, Wyoming: U. S. Geol. Survey Open-File Report 74-97, 241 p.
- U. S. Geological Survey and Montana Bureau of Mines and Geology, 1976, Preliminary report of coal drill-hole data and chemical analyses of coal beds in Campbell and Sheridan Counties, Wyoming; Custer,

- Prairie, and Garfield Counties, Montana: and Mercer County, North Dakota: U. S. Geol. Survey Open-File Report 76-319, 377 p.
- U. S. Geological Survey and Montana Bureau of Mines and Geology, 1976, Preliminary report of coal drill-hole data and chemical analyses of coal beds in Campbell, Converse, and Sheridan Counties of Wyoming; and Big Horn, Richland, and Dawson Counties, Montana: U. S. Geol. Survey Open-File Report 76-450, 382 p.
- U. S. Geological Survey and Montana Bureau of Mines and Geology, 1977, Preliminary report on 1976 drilling of coal in Campbell and Sheridan Counties, Wyoming; and Big Horn, Dawson, McCone, Richland, Roosevelt, Rosebud, Sheridan, and Wibaux Counties, Montana: U. S. Geol. Survey Open-File Report 77-283, 403 p.
- U. S. Geological Survey and Montana Bureau of Mines and Geology, 1978, Preliminary report of 1977 coal drilling in eastern Montana and north-eastern Wyoming; Geophysical logs for Campbell and Converse Counties, Wyoming: U. S. Geol. Survey Open-File Report 77-721 E, 202 p.
- Warren, W. C., 1959, Reconnaissance geology of the Birney-Broadus coal field, Rosebud and Powder River Counties, Montana: U. S. Geol. Survey Bull. 1072-J, p. 561-585.
- Weimer, R. J., 1977, Stratigraphy and tectonics of western coals, in Geology of Rocky Mountain Coal, A Symposium, 1976: Colorado Geol. Survey Resource Series 1, p. 9-27.