

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

TEXT TO ACCOMPANY:  
COAL RESOURCE OCCURRENCE  
AND  
COAL DEVELOPMENT POTENTIAL  
MAPS  
OF THE  
NORTH BUTTE QUADRANGLE,  
CAMPBELL COUNTY, WYOMING

BY  
INTRASEARCH INC.  
DENVER, COLORADO

OPEN FILE REPORT 79-064

1979

This report is preliminary, and has not been edited or reviewed for conformity with United States Geological Survey standards or stratigraphic nomenclature.

## TABLE OF CONTENTS

	<u>PAGE</u>
I. INTRODUCTION	1
II. GEOLOGY	3
III. DATA SOURCES	8
IV. COAL BED OCCURRENCE	9
V. GEOLOGICAL AND ENGINEERING MAPPING PARAMETERS	12
VI. COAL DEVELOPMENT POTENTIAL	14
Table 1.--Coal Resource Base and Hypothetical Resources Data (in short tons) for Underground Mining Methods for Federal Coal Lands in the North Butte Quadrangle, Campbell County, Wyoming.	17
Table 2.--Coal Resource Base and Hypothetical Resources Data (in short tons) for In-Situ Gasification for Federal Coal Lands in the North Butte Quadrangle, Campbell County, Wyoming.	18
SELECTED REFERENCES	19

TABLE OF CONTENTS (continued)

	<u>MAPS</u>	<u>PLATES</u>
1.	Coal Data Map	1
2.	Boundary and Coal Data Map	2
3.	Coal Data Sheet	3
4.	Isopach Map of Smith Coal Bed	4
5.	Structure Contour Map of Smith Coal Bed	5
6.	Isopach Map of Overburden of Smith Coal Bed	6
7.	Areal Distribution of Identified Resources of Smith Coal Bed	7
8.	Identified and Hypothetical Resources of Smith Coal Bed	8
9.	Isopach Map of Wyodak Coal Zone	9
10.	Structure Contour Map of Wyodak Coal Zone	10
11.	Isopach Map of Overburden of Wyodak Coal Zone	11
12.	Areal Distribution of Identified Resources of Wyodak Coal Zone	12
13.	Identified Resources of Wyodak Coal Zone	13
14.	Isopach Map of Pawnee Coal Bed	14
15.	Structure Contour Map of Pawnee Coal Bed	15
16.	Isopach Map of Overburden of Pawnee Coal Bed	16
17.	Areal Distribution of Identified Resources of Pawnee Coal Bed	17
18.	Identified Resources of Pawnee Coal Bed	18
19.	Isopach Map of Wildcat-Moyer Coal Zone	19
20.	Structure Contour Map of Wildcat-Moyer Coal Zone	20
21.	Isopach Map of Overburden of Wildcat-Moyer Coal Zone	21
22.	Areal Distribution of Identified Resources of Wildcat-Moyer Coal Zone	22
23.	Identified and Hypothetical Resources of Wildcat-Moyer Coal Zone	23

CONVERSION TABLE

<u>TO CONVERT</u>	<u>MULTIPLY BY</u>	<u>TO OBTAIN</u>
inches	2.54	centimeters (cm)
feet	0.3048	meters (m)
miles	1.609	kilometers (km)
acres	0.40469	hectares (ha)
tons (short)	0.9072	metric tons (t)
cubic yards/ton	0.8428	cubic meters per metric tons
acre feet	0.12335	hectare-meters
Btu/lb	2.326	kilojoules/kilogram (kJ/kg)
Btu/lb	0.55556	kilocalories/kilogram (kcal/kg)
Fahrenheit	$5/9 (F-32)$	Celsius

I. Introduction

This report and accompanying maps set forth the Coal Resource Occurrence (CRO) and Coal Development Potential (CDP) of coal beds within the North Butte Quadrangle, Campbell County, Wyoming. This CRO and CDP map series (U. S. Geological Survey Open-File Report 79-064) includes 23 plates. The project is compiled by IntraSearch Inc., 1600 Ogden Street, Denver, Colorado, under KRCRA Eastern Powder River Basin, Wyoming Contract Number 14-08-0001-17180. This contract is a part of a program to provide an inventory of unleased federal coal in Known Recoverable Coal <sup>Resource</sup> Areas (KRCRAs) in the western United States.

The North Butte Quadrangle is located in Campbell County, in northeastern Wyoming. It encompasses parts of Townships 44 and 45 North, Ranges 75 and 76 West, and covers the area: 43°45' to 43° 52'30" north latitude; 105° 52' 30" to 106° 00' west longitude.

Main access to the North Butte Quadrangle is provided by maintained gravel roads which angle across the northwestern and southeastern quadrants. Minor roads and trails branching from these roads provide access to the more remote regions of the quadrangle. The closest railroad is the proposed Burlington Northern trackage, 25 miles (40 km) to the east.

Drainage patterns generate from the high, rugged terrain of the North Butte in the Pumpkin Buttes region in the southwestern portion of the quadrangle. Elevations attain heights of 6052 feet (1845 m) above sea level, 1300 to 1350 feet (396 to 411 m) above the valley floors. Significant westward drainage is provided by Willow Creek and the North Prong of Willow Creek which flow into the Powder River. Northeastward flowing Bons Draw and Collins Draw drain into the Belle Fourche River.

The 13 to 14 inches (33 to 36 cm) of annual precipitation that falls in this semi-arid region accrues principally in the springtime. Summer and fall precipitation usually originates from thunderstorms, and infrequent snowfalls of six inches (15 cm) or less generally characterize winter precipitation. Although temperatures ranging from less than -25°F (-32°C) to more than 100°F (38°C) have been recorded near Gillette, Wyoming, average wintertime minimums and summertime maximums approach +5° to +15°F (-15° and -9°C) and 75° to 90°F (24° to 32°C), respectively.

Surface ownership is divided among fee, state, and federal categories. State and federal lands are generally leased to ranchers for grazing purposes. Details of surface ownership are available at the Campbell County Courthouse in Gillette, Wyoming. Details of mineral ownership on federal lands are available from the U. S. Bureau of Land Management in Cheyenne, Wyoming. Federal coal ownership is shown on Plate 2 of the Coal Resource Occurrence maps. The non-federal coal belongs to both fee and state owners.

The Coal Resource Occurrence and Coal Development Potential program is restricted to unleased federal coal and focuses upon: 1) the delineation of lignite, subbituminous coal, bituminous coal, and anthracite at the surface and in the subsurface on federal land; 2) subdivision of deposits into measured, indicated, and inferred reserve resource categories, and hypothetical resources; 3) the measurement of coal resources in place as well as recoverable reserves; and 4) the determination of the potential for surface or underground mining, and in-situ gasification of the coal beds. This report contains an evaluation of the coal resources of all unleased federal coal beds in the quadrangle, which are 5 feet (1.5 m) or greater in thickness and occur at depths down to 3000 feet (914 m). No resources or reserves are computed for

leased federal coal, state coal, fee coal, or lands encompassed by coal prospecting permits and preference right lease applications.

Surface and subsurface geological and engineering extrapolations drawn from the current data base suggest the occurrence of approximately 8.4 billion tons (7.6 billion metric tons) of unleased federal coal resources in the North Butte Quadrangle.

The suite of maps that accompany this report portray the coal resource and reserve occurrence in detail. For the most part, this report supplements the cartographic information, with minimum duplication of the map data.

## II. Geology

Regional. The thick, economic coal deposits of the Powder River Basin in northeastern Wyoming occur mostly in the Tongue River Member of the Fort Union Formation, and in the lower part of the Wasatch Formation. Approximately 3000 feet (914 m) of the Fort Union Formation, that includes the Tongue River, Lebo, and Tullock Members of Paleocene age, are unconformably overlain by approximately 700 feet (213 m) of the Wasatch Formation of Eocene age. These Tertiary formations lie in a structural basin flanked on the east by the Black Hills uplift, on the south by the Hartville and Casper Mountain uplifts, and on the west by the Casper Arch and the Big Horn Mountain uplift. The structural configuration of the Powder River Basin originated in Late Cretaceous time, with episodic uplift thereafter. The Cretaceous Cordillera was the dominant positive land form throughout the Rocky Mountain area at the close of Mesozoic time.

Outcrops of the Wasatch Formation and the Tongue River Member of the Fort Union Formation cover most of the areas of major coal resource occurrence in the Powder River Basin. The Tongue River Member is

composed of very fine-grained sandstones, siltstones, claystones, shales, carbonaceous shales, and numerous coal beds. The Lebo Shale Member of the Fort Union Formation consists of light-to dark-gray very fine-grained to conglomeratic sandstone with interbedded siltstone, claystone, carbonaceous shale and thin coal beds. Thin bedded calcareous ironstone concretions interbedded with massive white sandstone and slightly bentonitic shale occur throughout the unit.

The Lebo Member is mapped at the surface northeast of Recluse, Wyoming, east of the principal coal outcrops and associated clinkers (McKay, 1974), and presumably projects into the subsurface beneath much of the basin. One of the principal characteristics for separating the Lebo and Tullock Members (collectively referred to as the Ludlow Member east of Miles City, Montana) from the overlying Tongue River Member is the color differential between the lighter-colored upper portion and the somewhat darker lower portion (Brown, 1958). Although geologists working with subsurface data, principally geophysical logs, in the basin are trying to develop criteria for subsurface recognition of the Lebo-Tullock and Tongue River-Lebo contacts, no definitive guidelines are known to have been published. Hence, for subsurface mapping purposes, the Fort Union Formation is not divided into its members for this study.

During the Paleocene epoch, the Powder River Basin tropic to subtropic depositional environment included broad, inland flood basins with extensive swamps, marshes, freshwater lakes, and a sluggish but active northeastward discharging drainage system, superimposed on an emerging sea floor, near base level. Much of the vast area where organic debris collected was within a reducing depositional environment. Localized uplifts began to disturb the near sea level terrain of northeastern Wyoming following retreat of the Cretaceous seas. However, the

extremely fine-grained characteristics of the Tongue River Member clastics suggest that areas of recurring uplift peripheral to the Powder River Basin were subdued during major coal deposit formation.

The uplift of areas surrounding the Powder River Basin created a structural basin of asymmetric characteristic, with the steep west flank located on the eastern edge of the Big Horn Mountains. The axis of the Powder River Basin is difficult to specifically define, but is thought to be located in the western part of the Basin, and to display a north-south configuration some 15 to 20 miles (24 to 32 km) east of Sheridan, Wyoming. Thus, the sedimentary section described in this report lies on the east flank of the Powder River Basin, with gentle dips of two degrees or less disrupted by surface structure thought to relate to tectonic adjustment and differential compaction.

Some coal beds in the Powder River Basin exceed 200 feet (61 m) in thickness. Deposition of these thick, in-situ coal beds requires a discrete balance between subsidence of the earth's crust and in-filling by tremendous volumes of organic debris. These conditions in concert with a favorable ground water table, non-oxidizing clear water, and a climate amenable to the luxuriant growth of vegetation produce a stabilized swamp critical to the deposition of coal beds.

Deposition of the unusually thick coal beds of the Powder River Basin may be partially attributable to short-distance water transportation of organic detritus into areas of crustal subsidence. Variations in coal bed thickness throughout the basin relate to changes in the depositional environment. Drill hole data that indicate either the complete absence or extreme attenuation of a thick coal bed probably relate to location of the drill holes within the ancient stream channel system draining this low land area in Early Cenozoic time. Where thick

coal beds thin rapidly from the depocenter of a favorable depositional environment, it is not unusual to encounter a synclinal structure over the maximum coal thickness due to the differential compaction between organic debris in the coal depocenter and fine-grained clastics in the adjacent areas.

The Wasatch Formation of Eocene age crops out over most of the central part of the Powder River Basin and exhibits a disconformable contact with the underlying Fort Union Formation. The contact has been placed at various horizons by different workers; however, for the purpose of this report, the contact is positioned near the top of the Roland coal bed as mapped by Olive (1957) in northwestern Campbell County, Wyoming, and is considered to disconformably descend in the stratigraphic column to the top of the Wyodak-Anderson coal bed (Roland coal bed of Taff, 1909) along the eastern boundary of the coal measures. No attempt is made to differentiate the Wasatch and Fort Union Formations on geophysical logs or in the subsurface mapping program that is a part of this CRO-CDP project.

Although Wasatch and Fort Union lithologies are too similar to allow differentiation in some areas, most of the thicker coal beds occur in the Fort Union section on the east flank of the Powder River Basin. Furthermore, orogenic movements peripheral to the basin apparently increased in magnitude during Wasatch time causing the deposition of friable, coarse-grained to gritty, arkosic sandstones, fine- to very fine-grained sandstones, siltstones, mudstones, claystones, brown-to-black carbonaceous shales and coal beds. These sediments are noticeably to imperceptibly coarser than the underlying Fort Union clastics.

The North Butte Quadrangle is located in an area where surface rocks are classified into the White River Formation and the Wasatch Formation. The White River Formation is present only in the isolated area of the North Butte in the Pumpkin Buttes region. The Wasatch Formation is exposed throughout the remaining area of the quadrangle. Olive (1957) correlated coal beds in the Spotted Horse coal field with coal beds in the Sheridan coal field (Baker, 1929) and Gillette coal field (Dobbin and Barnett, 1927), Wyoming, and with coal beds in the Ashland coal field (Bass, 1932) in southeastern Montana.

This report utilizes, where possible, the coal bed nomenclature used in previous reports. The Smith coal bed was named by Taff (1909). IntraSearch's correlation of thick coal beds from the Spotted Horse coal field to Gillette points out that the Wyodak coal bed, named the "D" coal bed by Dobbin and Barnett (1927), is equivalent to the Anderson, Canyon, and all or part of the Cook coal beds to the north and west of Gillette, Wyoming. Correlation of this suite of coal beds with the Wyodak coal bed south and southwest of Gillette suggests that the Anderson and Canyon coal beds equate with the upper ten to twenty-five percent of the thick Wyodak coal bed, and the Cook and Wall or Upper Wall coal beds are equivalent to the major part of the Wyodak coal bed. Due to problematic correlations outside of the Gillette area, the name Wyodak has been informally used by many previous authors to represent the coal beds in the area surrounding the Wyodak coal mine. The Pawnee coal bed was named by Warren (1959). The Wildcat and Moyer coal beds were informally named by IntraSearch (1978 and 1979).

The North Butte Quadrangle lies near the center of the Powder River Basin. The White River Formation caps North Butte. The White River Formation is composed of arkosic sandstones, siltstones, and claystones. The Wasatch Formation, which crops out over the remainder of

the quadrangle, is composed of friable, coarse-grained to gritty, arkosic sandstones, fine- to very fine-grained sandstones, siltstones, mudstones, claystones, brown-to-black carbonaceous shales, and coal beds.

### III. Data Sources

Publications regarding the areal geology of coal outcrops and associated clinker at a scale appropriate for the CRO-CDP mapping program are unknown at the time of this publication. Examination of the map of the Gillette coal field (Dobbin and Barnett, 1927) indicates that it is possible that no coal bed outcrops are present in the North Butte Quadrangle.

The major sources of subsurface control, particularly on deep coal beds, is the geophysical logs from oil and gas test bores and producing wells. Some geophysical logs are not applicable to this study, for the logs relate only to the deep potentially productive oil and gas zones. More than eighty percent of the logs include resistivity, conductivity, and self-potential curves. Occasionally the logs include gamma, density, and sonic curves. These logs are available from several commercial sources.

All geophysical logs available in the quadrangle are scanned to select those with data applicable to Coal Resource Occurrence mapping. Paper copies of the logs are obtained, interpreted, and coal intervals annotated. Maximum accuracy of coal bed identification is accomplished where gamma, density, and resistivity curves are available. Coal bed tops and bottoms are picked on the logs at the midpoint between the minimum and maximum curve deflections. The correlation of coal beds within and between quadrangles is achieved utilizing a fence diagram to associate local correlations with regional coal occurrences.

The reliability of correlations, set forth by IntraSearch in this report, vary depending on: the density and quality of lithologic and geophysical logs; the detail, thoroughness, and accuracy of published and unpublished surface geological maps, and interpretative proficiency. There is no intent on the part of IntraSearch to refute nomenclature established in the literature or used locally by workers in the area. IntraSearch's nomenclature focuses upon the suggestion of regional coal bed names applicable throughout the eastern Powder River Basin. It is expected and entirely reasonable that some differences of opinion regarding correlations, as suggest by IntraSearch, exist. Additional drilling for coal, oil, gas, water, and uranium, coupled with expanded mapping of coal bed outcrops and associated clinkers will broaden the data base for coal bed correlations and allow continued improvement in the understanding of coal bed occurrences in the eastern Powder River Basin.

The topographic map of the North Butte Quadrangle is published by the U. S. Geological Survey, compilation date, 1953. Land network and mineral ownership data are compiled from land plats available from the U. S. Bureau of Land Management in Cheyenne, Wyoming. This information is current to October 13, 1977.

#### IV. Coal Bed Occurrence

Wasatch and Fort Union coal beds that are present in all or part of the North Butte quadrangle include, in descending stratigraphic order, the Smith, an unnamed local, the Wyodak, another unnamed local, the Pawnee, the Upper Wildcat, the Lower Wildcat, and the Moyer coal beds. A complete suite of maps (structure, isopach, overburden, identified and where applicable, hypothetical resources, and areal distribution of identified resources) is prepared for the Smith and Pawnee coal beds

and the Wyodak and Wildcat-Moyer coal zones. Insufficient thickness and areal extent preclude detailed mapping of the local coal beds.

No physical and chemical analyses are known to have been published regarding the coal beds in the North Butte Quadrangle. However, the general "as received" basis proximate analyses for central and southern Campbell County, and northern Converse County coal beds are as follows:

COAL BED NAME		ASH %	FIXED CARBON %	MOISTURE %	VOLATILES %	SULFUR %	BTU/LB
Smith	(U) Hole 7312C	6.167	33.340	29.610	30.883	1.068	8215
Wyodak	(U) Hole 757	6.024	32.831	26.907	34.237	0.336	8366
Pawnee	(U) Hole 7424C	7.880	31.029	31.910	29.183	0.386	7344
Wildcat	(*) 11447	4.3	29.4	27.8	29.4	0.27	8410

(\*) - Winchester, 1912

(U) - U. S. Geological Survey & Montana Bureau of Mines & Geology - 1974 & 1976.

The Coal Data Sheet, Plate 3, shows the downhole identification of coal beds within the quadrangle as interpreted from geophysical logs of oil and gas test bores and producing sites. A datum coal bed is utilized to position columnar sections on Plate 3. This portrayal is schematic by design; hence, no structural or coal thickness implications are suggested by the dashed correlation lines projected through no record (NR) intervals. Inasmuch as the Wyodak coal zone underlies the entire quadrangle, it is designated as datum for the correlation diagram.

The Wyodak coal zone shows the thickest occurrence throughout the quadrangle, and the Smith and Pawnee coal beds show the thinnest occurrence. All of the coal beds in the North Butte Quadrangle occur at depths greater than 500 feet (152 m) beneath the surface.

Pinched out in portions of the northwestern and southeastern quadrants, the Smith coal bed attains a maximum thickness of approxi-

mately 7 feet (2 m) in the northeastern quadrant. The Smith coal bed dips one to two degrees to the west, and lies from less than 750 feet (229 m) to greater than 1750 feet (533 m) beneath the surface.

The Wyodak coal zone lies approximately 474 to 594 feet (144 to 181 m) beneath the overlying Smith coal bed. The Wyodak coal zone is composed of two to five coal beds. The total interburden contained within the Wyodak coal zone varies from 8 to 206 feet (2.4 to 63 m) in thickness. The combined thickness of coal beds in the Wyodak coal zone attains a maximum value of more than 170 feet (52 m) in the southwestern corner, and a minimum thickness of less than 90 feet (27 m) in the northeastern quadrant. The structure contour map, drawn on top of the Upper Wyodak coal bed, indicates a westward dip with an east to west trending anticline and syncline present in the northern half of the quadrangle. The Wyodak coal zone lies from less than 1250 feet (381 m) to greater than 2250 feet (686 m) beneath the surface.

A non-coal interval of 309 to 462 feet (94 to 141 m) separates the Wyodak coal zone from the Pawnee coal bed. The Pawnee coal bed ranges in thickness from 0 to 7 feet (0 to 2.1 m) with maximum thickness occurring in the northwestern quarter of the quadrangle. It is absent from approximately fifty percent of the quadrangle throughout portions of the southern and eastern regions. The structure contours drawn on top of the Pawnee coal bed indicate a westward dip of less than two degrees. It lies from less than 2000 feet (610 m) to greater than 3000 feet (914 m) below the surface.

The Wildcat-Moyer coal zone is located approximately 286 to 350 feet (87 to 107 m) below the Pawnee coal bed. The composite thickness for coal beds in the Wildcat-Moyer coal zone varies from less than 5 feet (1.5 m) along the northern quadrangle boundary to more than 25 feet (8 m) in the east-central portion of the quadrangle. The non-coal interburden

between the coal beds in the Wildcat-Moyer coal zone ranges from 26 to 127 feet (8 to 39 m) in thickness. The Wildcat-Moyer coal zone dips one to two degrees to the west and lies from less than 2250 feet (686 m) to greater than 3000 feet (914 m) beneath the surface.

V. Geological and Engineering Mapping Parameters

The correct horizontal location and elevation of drill holes utilized in subsurface mapping are critical to map accuracy. Intra-Search Inc., plots the horizontal location of the drill hole as described on the geophysical log heading. Occasionally this location is superimposed or near to a drillsite shown on the topographic map, and the topographic map horizontal location is utilized. If the ground elevation on the geophysical log does not agree with the topographic elevation of the drillsite, the geophysical log ground elevation is adjusted to conformance. If there is no indication of a drillsite on the topographic map, the "quarter, quarter, quarter" heading location is shifted within a small area until the ground elevation on the heading agrees with the topographic map elevation. If no elevation agreement can be reached, the well heading or data sheet is rechecked for footage measurements and ground elevation accuracy. Inquiries to the companies who provided the oil and gas geophysical logs frequently reveal that corrections have been made in the original survey. If all horizontal location data sources have been checked and the information accepted as the best available data, the drillsite elevation on the geophysical log is modified to agree with the topographic map elevation. IntraSearch Inc., considers this agreement mandatory for the proper construction of most subsurface maps, but in particular, the overburden isopach, the mining ratio, and Coal Development Potential maps.

Subsurface mapping is based on geologic data within and adjacent to the North Butte Quadrangle area. Data from geophysical logs are used to correlate coal beds and control contour lines for the coal thickness, structure, and overburden maps. Isopach lines are also drawn to honor selected surface measured sections where there is sparse subsurface control. Where isopach contours do not honor surface measured sections, the surface thicknesses are thought to be attenuated by oxidation and/or erosion, hence not reflective of total coal thickness. Isopach lines extend to the coal bed outcrops, the projections of coal bed outcrops, and the contact between porcellanite (clinker) and unoxidized coal in place. Attenuation of total coal bed thickness is known to take place near these lines of definition; however, the overestimation of coal bed tonnages that results from this projection of total coal thickness is insignificant to the Coal Development Potential maps. Structure contour maps are constructed on the tops of the main coal beds. Where subsurface data are scarce, supplemental structural control points are selected from the topographic map along coal outcrops.

In preparing overburden isopach maps, no attempt is made to identify coal beds that occur in the overburden to a particular coal bed under study. Mining ratio maps for this quadrangle are constructed utilizing a ninety-five percent recovery factor. Contours of these maps identify the ratio of cubic yards of overburden to tons of recoverable coal. Where ratio control points are sparse, interpolated points are computed at the intersections of coal bed and overburden isopach contours using coal structure, coal isopach, and topographic control. On the Areal Distribution of Identified Resources Map (ADIR), coal bed reserves are not calculated where the coal is less than 5 feet (1.5 m) thick, where the coal occurs at a depth greater than 500 feet (152 m),

where non-federal coal exists, or where federal coal leases, preference-right lease applications, and coal prospecting permits exist.

Coal tonnage calculations involve the planimetry of areas of measured, indicated, inferred reserves and resources, and hypothetical resources to determine their areal extent in acres. An Insufficient Data Line is drawn to delineate areas where surface and subsurface data are too sparse for CRO map construction. Various categories of resources are calculated in the unmapped areas by utilizing coal bed thicknesses mapped in the geologically controlled area adjacent to the insufficient data line. Acres are multiplied by the average coal bed thickness and 1750, or 1770 (the number of tons of lignite A or sub-bituminous C coal per acre-foot, respectively; 12,874 or 13,018 metric tons per hectare-meter, respectively), to determine total tons in place. Recoverable tonnage is calculated at ninety-five percent of the total tons in place. Where tonnages are computed for the CRO-CDP map series, resources and reserves are expressed in millions of tons. Frequently the planimetry of coal resources on a sectionized basis involves complexly curvilinear lines (coal bed outcrop and 500-foot stripping limit designations) in relationship with linear section boundaries and circular resource category boundaries. Where these relationships occur, generalizations of complexly curvilinear lines are discretely utilized, and resources and/or reserves are calculated within an estimated two to three percent plus or minus accuracy.

VI. Coal Development Potential

Strippable Coal Development Potential. Areas where coal beds are 5 feet (1.5 m) or more in thickness and are overlain by 500 feet (152 m) or less of overburden are considered to have potential for surface mining and are assigned a high, moderate, or low development

potential based on the mining ratio (cubic yards of overburden per ton of recoverable coal). The formula used to calculate mining ratios is as follows:

$$MR = \frac{to (0.911)*}{tc (rf)}$$

where MR = mining ratio  
to = thickness of overburden  
tc = thickness of coal  
rf = recovery factor  
0.911\* = conversion factor (cu. yds./ton)

\*A conversion factor of 0.922 is used for lignite.

The depth of 500 feet (152 m) was established by the U. S. Geological Survey for CRO-CDP mapping purposes as the maximum limit economically feasible for surface mining. Because all of the coal beds in the North Butte Quadrangle occur at depths greater than 500 feet (152 m) beneath the surface, the quadrangle is considered to have no development potential for surface mining methods, and no surface mining potential map is prepared.

Underground Mining Coal Development Potential. Subsurface coal mining potential throughout the North butte Quadrangle is considered low. Inasmuch as recovery factors have not been established for the underground development of coal beds in this quadrangle, reserves are not calculated for coal beds that occur more than 500 feet (152 m) beneath the surface. Table 2 sets forth the estimated coal resources in tons per coal bed.

In-Situ Gasification Coal Development Potential. The evaluation of subsurface coal deposits for in-situ gasification potential relates to the occurrence of coal beds more than 5 feet (1.5 m) thick buried from 500 to 3000 feet (152 to 914 m) beneath the surface. This categorization is as follows:

1. Low development potential relates to: 1) a total coal section less than 100 feet (30 m) thick that lies 500 feet (152 m) to 3000 feet (914 m) beneath the surface, or 2) a

single coal bed or coal zone 5 feet (1.5 m) or more in thickness which lies 500 feet (152 m) to 1000 feet (305 m) beneath the surface.

2. Moderate development potential is assigned to a total coal section from 100 to 200 feet (30 to 61 m) thick, and buried from 1000 to 3000 feet (305 to 914 m) beneath the surface.

3. High development potential involves 200 feet (61 m) or more of total coal thickness buried from 1000 to 3000 feet (305 to 914 m).

The coal development potential for in-situ gasification of unleased federal coal within the North Butte Quadrangle is moderate for the entire quadrangle. Hence no CDP map is generated for this map series. The coal resource tonnage for in-situ gasification with moderate and low development potential totals approximately 8.4 billion tons (7.6 billion metric tons) (Table 2). None of the coal beds in the North Butte Quadrangle qualify for a high development potential rating.

Table 1.--Coal Resource Base and Hypothetical Resource Data (in short tons)  
for Underground Mining Methods for Federal Coal Lands in the  
North Butte Quadrangle, Campbell County, Wyoming.

Coal Bed Name	High Development Potential	Moderate Development Potential	Low Development Potential	Total
<u>RESOURCE BASE TONNAGE:</u>				
Smith	-----	-----	136,420,000	136,420,000
Wyodak	-----	-----	7,419,070,000	7,419,070,000
Pawnee	-----	-----	51,970,000	51,970,000
Wildcat-Moyer	-----	-----	834,080,000	834,080,000
TOTAL	-----	-----	8,441,540,000	8,441,540,000
<u>HYPOTHETICAL RESOURCE TONNAGE</u>				
Smith	-----	-----	620,000	620,000
Wildcat-Moyer	-----	-----	5,420,000	5,420,000
TOTAL	-----	-----	6,040,000	6,040,000
GRAND TOTAL	-----	-----	8,447,580,000	8,447,580,000

Table 2.--Coal Resource Base and Hypothetical Resource Data (in short tons)  
for In-Situ Gasification for Federal Coal Lands in the North Butte  
Quadrangle, Campbell County, Wyoming.

Coal Bed Name	High Development Potential	Moderate Development Potential	Low Development Potential	Total
<u>RESOURCE BASE TONNAGE</u>				
	-----	8,335,890,000	85,650,000	8,441,540,000
TOTAL	-----	8,335,890,000	85,650,000	8,441,540,000
<u>HYPOTHETICAL RESOURCE TONNAGE</u>				
	-----	-----	6,040,000	6,040,000
GRAND TOTAL	-----	8,335,890,000	91,690,000	8,447,580,000

SELECTED REFERENCES

- Brown, R. W., 1958, Fort Union Formation in the Powder River Basin, Wyoming: Wyo. Geol. Assoc. Guidebook, Thirteenth Annual Field Conf., p. 111-113.
- Dobbin, C. E., and Barnett, V. H., 1927, The Gillette coal field, north-eastern Wyoming, with a chapter on the Minturn district and north western part of the Gillette field by W. T. Thom, Jr.: U. S. Geol. Survey Bull. 796-A, p. 1-50
- Glass, G. B., 1975, Review of Wyoming coal field, 1975; Wyoming Geol. Survey Public Information circ. 4, p. 10.
- IntraSearch, Inc., 1978, Coal resource occurrence and coal development potential of the Rocky Butte Quadrangle, Campbell County, Wyoming: U. S. Geol. Survey Open-File Report 78-830, 22 p.
- \_\_\_\_\_, 1979, Coal resource occurrence and coal development potential of the Larey Draw Quadrangle, Campbell County, Wyoming: U. S. Geol. Survey Open-File Report 79-023, 29 p.
- Jacob, A. F., 1973, Depositional environments of Paleocene Tongue River Formation: Am. Assoc. of Petroleum Geologists Bull, vol. 56, no. 6, p. 1038-1052.
- McKay, E. J., 1974, Preliminary geologic map of the Bertha 2 NW (Rocky Butte) Quadrangle, Campbell County, Wyoming: U. S. Geol. Survey Open-File Report 74-173, scale 1:24,000.
- Olive, W. W., 1957, The Spotted Horse coal field, Sheridan and Campbell Counties, Wyoming: U. S. Geol. Survey Bull. 1050, 83 p.
- Schell, E. M., and Mowat, G. D., 1972, Reconnaissance map showing some coal and clinker beds in the Fort Union and Wasatch Formations in the eastern Powder River Basin, Campbell and Converse Counties, Wyoming: U. S. Geol. Survey Open-File Report, scale 1:63,360.
- Taff, J. A., 1909, The Sheridan coal field, Wyoming: U. S. Geol. Survey Bull. 341-B, p. 123-150.

- U. S. Geological Survey and Montana Bureau of Mines and Geology, 1974,  
Preliminary report of coal drill-hole data and chemical analyses  
of coal beds in Campbell County, Wyoming: U. S. Geol. Survey Open-File  
Report 74-97 241 p.
- \_\_\_\_\_, 1976, Preliminary report of coal drill-hole data and chemical analyses  
of coal beds in Campbell and Sheridan Counties, Wyoming; Custer,  
Prairie, and Garfield Counties, Montana: and Mercer County, North  
Dakota: U. S. Geol. Survey Open-File Report 76-319, 377 p.
- Warren, W. C., 1959, Reconnaissance geology of the Birney-Broadus coal field,  
Rosebud and Powder River Counties, Montana: U. S. Geol. Survey Bull.  
1072-J, p. 561-585.
- Weimer, R. J., 1977, Stratigraphy and tectonics of western coals, in Geology  
of Rocky Mountain Coal, A Symposium, 1976: Colorado Geol. Survey Resource  
Series 1, p. 9-27.
- Winchester, D. E., 1912, The Lost Spring coal field, Converse County, Wyoming:  
U. S. Geol. Survey Bull. 471-F, p. 472-515.