

EXPLANATION

— 300 —
OVERBURDEN ISOPACH—Showing thickness of overburden, in feet, from the surface to the top of the coal bed. Isopach interval 100 feet.

○ 190/38 ● 226/4 ○ 169
DRILL HOLE—Showing thickness of overburden, in feet, from the surface to top of coal bed. Lower number indicates interburden thickness, in feet, between upper and lower splits of coal bed.

— — — — —
TRACE OF COAL BED—Dashed line indicates limit of unweathered coal. "V" symbol indicates burned rock with dotted line showing limit of burning. P.E. indicates partially eroded coal. Arrow points toward coal-bearing area.




To convert feet to meters multiply feet by 0.3048.



MAP SHOWING LOCATION OF THE RENO RESERVOIR QUADRANGLE AND THE POWDER RIVER BASIN KNOWN RECOVERABLE COAL RESOURCE AREA (STIPPLED), WYOMING

Base from U.S. Geological Survey, 1971

Compiled in 1979



**COAL RESOURCE OCCURRENCE MAP OF THE RENO RESERVOIR
QUADRANGLE, CAMPBELL COUNTY, WYOMING**

BY
IntraSearch
1979

PLATE 6
ISOPACH MAP OF OVERBURDEN
AND INTERBURDEN OF
WYODAK COAL ZONE

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.