

OPEN-FILE REPORT
This report has not been edited for conformity with U.S. Geological Survey editorial standards or Stratigraphic nomenclature

OPEN FILE REPORT 79-104
PLATE 25 OF 53

EXPLANATION

OVERBURDEN ISOPACHS--Showing thickness of overburden, in feet, from the surface to the top of the coal bed. Isopach interval 200 feet (61 m).

MINING RATIO CONTOUR--Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in areas within the stripping limit.

STRIPPING LIMIT LINE--Boundary for surface mining of the coal bed (in this quadrangle, the 200-foot overburden isopach). Arrows point toward the area suitable for surface mining.

BOUNDARY OF RESERVE BASE COAL--Drawn along the outcrop of coal bed or the contact between burned and unburned coal where the coal bed is 5 feet (1.5 m) or more thick, and the 5-foot coal isopach. Arrows point toward area of Reserve Base coal.


DRILL HOLE--Showing thickness of overburden, in feet, from the surface to the top of the coal bed.

To convert cubic yards of overburden per short ton of recoverable coal to cubic meters of overburden per metric ton of recoverable coal, multiply by 0.84.

To convert feet to meters, multiply feet by 0.3.

Base from U.S. Geological Survey, 1966

Compiled in 1977



**COAL RESOURCE OCCURRENCE AND COAL DEVELOPMENT POTENTIAL MAPS
OF THE FORT HOWES QUADRANGLE, ROSEBUD AND POWDER RIVER COUNTIES, MONTANA**

BY
E. J. MCKAY AND L. N. ROBINSON
1979

PLATE 25
**ISOPACH OVERBURDEN AND
MINING RATIO MAP OF THE
BREWSTER-ARNOLD COAL BED**