



EXPLANATION

— 200 —  
OVERBURDEN ISOPACHS - Showing thickness of overburden, in feet, from surface to top of coal bed. Dashed where vertical accuracy possibly not within 40 feet. Isopach interval is 100 feet (31 m) over strip-pable coal and 200 feet (61 m) beyond the stripping-limit line.

○ 250  
DRILL HOLE - Showing thickness of overburden, in feet, from surface to top of coal bed.

—●—  
TRACE OF FAULT - Bar and ball on down-thrown side when direction of movement is known. Dashed where inferred or approxi-mately located.

To convert feet to meters, multiply feet by 0.3048.

NOTE: Overburden isopachs are not drawn beyond those shown because of insufficient data.

Base from U.S. Geological Survey, 1958

SCALE 1:24,000

Compiled in 1977/1978



APPROXIMATE MEAN DECLINATION, 1958



COAL RESOURCE OCCURRENCE MAP OF THE SOUTHWEST QUARTER OF THE SUPERIOR  
15-MINUTE QUADRANGLE, SWEETWATER COUNTY, WYOMING

BY  
DAMES & MOORE  
1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

PLATE 5  
OVERBURDEN ISOPACH MAP  
OF THE ROCK SPRINGS NO. 15  
COAL BED