



- EXPLANATION
- 5 —
 - 6 —
- ISOPACHS - Showing thickness of coal, in feet. Isopach interval 1 foot.
- 7000 —
 - 7080 —
- STRUCTURE CONTOURS - Drawn on top of coal bed. Solid where vertical accuracy within 40 feet; long dashed where vertical accuracy possibly not within 40 feet; short dashed where projected above ground surface. Contour interval is 80 feet (24 m). Datum is mean sea level.
- 6920
 - 5.7
- DRILL HOLE - Showing altitude of top of coal bed, and thickness of coal, in feet.
- ▲ 7100
 - 3.6
- POINT OF MEASUREMENT - Showing altitude of top of coal bed, and thickness of coal, in feet. Includes all points of measurement other than drill holes.
- La - Lance, undifferentiated
 - Al - Almond, undifferentiated
- COAL BED SYMBOLS AND NAMES - Coal beds identified by bracketed numbers are not formally named, but are numbered for identification purposes in this quadrangle only.
- La[3] —
- TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Short dashed where inferred by present authors.
-
- TRACE OF FAULT - Bar and ball on down-thrown side when direction of movement is known. Dashed where inferred or approximately located.
- To convert feet to meters, multiply feet by 0.3048.

**COAL RESOURCE OCCURRENCE MAP OF THE SOUTHEAST QUARTER OF THE SUPERIOR
15-MINUTE QUADRANGLE, SWEETWATER COUNTY, WYOMING**
BY
DAMES & MOORE
1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.