



- EXPLANATION**
- ISOPACHS - Showing thickness of coal, in feet. Long dashed where inferred. Isopach interval 1 foot.
  - DRILL HOLE - Showing thickness of coal, in feet.
  - POINT OF MEASUREMENT - Showing thickness of coal, in feet. Includes all points of measurement other than drill holes.
  - COAL BED SYMBOLS AND NAMES - Coal beds identified by bracketed numbers are not formally named, but are numbered for identification purposes in this quadrangle only.
  - TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Arrow points toward coal-bearing area. Dashed where inferred; short dashed where inferred by present authors.
  - INFERRED LIMIT OF BURNED AND CLINKERED COAL - Arrow points toward area of baked and fused rock.
  - TRACE OF FAULT - Bar and ball on downthrown side when direction of movement is known. Dashed where inferred or approximately located.
- To convert feet to meters, multiply feet by 0.3048.

Base from U.S. Geological Survey, 1968

Scale 1:24,000

UTM GRID AND 1968 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

WYOMING QUADRANGLE LOCATION

Compiled in 1977/1978

**COAL RESOURCE OCCURRENCE MAP OF THE POINT OF ROCKS QUADRANGLE, SWEETWATER COUNTY, WYOMING**  
**BY DAMES & MOORE 1979**

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.