




EXPLANATION

- 5
6
- ISOPACHS - Showing thickness of coal, in feet. Isopach interval 1 foot.
- 7000
6900
- STRUCTURE CONTOURS - Drawn on top of coal bed. Solid where vertical accuracy within 40 feet; long dashed where vertical accuracy possibly not within 40 feet; short dashed where projected above ground surface. Contour interval is 100 feet (31 m). Datum is mean sea level.
- ▲ 7110
8.6
- POINT OF MEASUREMENT - Showing altitude of top of coal bed, and thickness of coal, in feet. Includes all points of measurement other than drill holes.
- Lb - Lebar
- COAL BED SYMBOL AND NAME
- Lb
- TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Arrow points toward coal-bearing area. Dashed where inferred.
- TRACE OF FAULT - Bar and ball on down-thrown side when direction of movement is known. Dashed where inferred or approximately located.
- INFERRED LIMIT OF BURNED AND CLINKERED COAL - Arrow points toward area of baked and fused rock.
- To convert feet to meters, multiply feet by 0.3048.

Base from U.S. Geological Survey, 1968

Compiled in 1977/1978



COAL RESOURCE OCCURRENCE MAP OF THE POINT OF ROCKS SE
QUADRANGLE, SWEETWATER COUNTY, WYOMING

BY
DAMES & MOORE
1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.