



EXPLANATION

NON-FEDERAL COAL LAND--Land for which the Federal Government does not own the coal rights.

COAL ISOPACH--Showing thickness of coal, in feet. Arrow points towards area where coal bed is 1 foot or more thick.

TRACE OF COAL BED OUTCROP--Showing symbol of name of coal bed (as shown on Plate 1). Arrow points toward coalbearing area.

STRIPPING-LIMIT LINE--Boundary for surface mining (in this quadrangle, the 150-foot overburden isopach). Arrow points toward the area suitable for surface mining where the recovery factor is 80% and away from the area suitable for subsurface mining (down dip to the 3,000-foot-overburden isopach) where the recovery factor is 50%.

15° DIP LINE--Boundary between areas where dip of coal bed is greater than 15° and where dip is less than 15°. Reserve Base tonnages are calculated beyond limit; Reserve tonnages are not. Arrow points toward area where coal bed dip is greater than 15°. This area is considered suitable for in-situ gasification only.

Surface	Subsurface	In-situ
RB R(80%)	RB R(50%)	RB(IS)
—	0.78 0.39	— (Measured)
0.01 0.01	3.03 1.51	— (Indicated)
—	0.61 0.36	0.45 (Inferred)
Hyp	Hyp 0.00	— (Hypothetical)

IDENTIFIED AND HYPOTHETICAL COAL RESOURCES--Showing totals for Reserve Base (RB) Reserves (R), and Hypothetical (Hyp) resources in millions of short tons, for each section or part of section of non-leased Federal coal land, both within and beyond the stripping-limit line. Reserve (R) tonnage is calculated by multiplying the Reserve Base (RB) tonnage by the appropriate recovery factor. Reserve tonnages are not calculated from in-situ Reserve Base tonnages. Dash indicates no resource in that category. 0.00 indicates that there are resources less than 10,000 short tons, in that category.

BOUNDARY LINES--Enclosing areas of measured (M), indicated (I), inferred (Inf) parts of identified coal resources. Dashed where projected from adjacent quadrangles. Hypothetical (Hyp) coal resources are located beyond the inferred part of identified coal resources (more than 3 miles from a measurement point).

To convert short tons to metric tons, multiply short tons by 0.9072.

To convert feet to meters, multiply feet by 0.3048.

To convert miles to kilometers, multiply miles by 1.6093.

Measured resources (M) are shown within a 3/4 mile radius of a point of measurement. Indicated resources (I) are shown within a 3-mile radius. Inferred resources (Inf) are shown within a 3-mile radius. Hypothetical resources (Hyp) are shown within a 3-mile radius.

NOTE: The explanation has been compiled to depict all possible combinations of data and does not intentionally represent any particular data point.

Base from U.S. Geological Survey, 1940
This map intended for land-use planning purposes only.

This report was prepared under contract to the U.S. Geological Survey, and has not been edited for conformity with Geological Survey editorial standards or stratigraphic nomenclature. Opinions expressed herein do not necessarily represent those of the Geological Survey.

UTM GRID AND 1978 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

SCALE 1:24,000

1 MILE
0 1000 2000 3000 4000 5000 6000 7000 FEET
1 KILOMETER

OKLAHOMA
QUADRANGLE LOCATION

Compiled 1980/1981