

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

TEXT TO ACCOMPANY:

COAL RESOURCE OCCURRENCE

AND

COAL DEVELOPMENT POTENTIAL

MAPS

OF THE

NORTHWEST QUARTER OF BETTY RESERVOIR 15' QUADRANGLE,

CONVERSE AND CAMPBELL COUNTIES, WYOMING

BY

INTRASEARCH INC.

DENVER, COLORADO

OPEN FILE REPORT 79-318

1979

This report is preliminary, and has not been edited or reviewed for conformity with United States Geological Survey standards or stratigraphic nomenclature.

TABLE OF CONTENTS

	<u>PAGE</u>
I. INTRODUCTION	2
II. GEOLOGY	3
III. DATA SOURCES	8
IV. COAL BED OCCURRENCE	10
V. GEOLOGICAL AND ENGINEERING MAPPING PARAMETERS	13
VI. COAL DEVELOPMENT POTENTIAL	15
Table 1.--Strippable Coal Reserve base Data (in short tons) for Federal Coal Lands in the Northwest Quarter of Betty Reservoir 15' Quad- rangle, Converse and Campbell Counties, Wyoming.	19
Table 2.--Coal Resource Base and Hypothetical Resource Data (in short tons) for Underground Mining Methods for Federal Coal Lands in the Northwest Quarter of Betty Reservoir 15' Quad- rangle, Converse and Campbell Counties, Wyoming.	20
Table 3.--Coal Resource Base and Hypothetical Resource Data (in short tons) for In-Situ Gasi- fication for Federal Coal Lands in the Northwest Quarter of Betty Reservoir 15' Quadrangle, Con- verse and Campbell County, Wyoming.	21
SELECTED REFERENCES	22

TABLE OF CONTENTS (continued)

<u>MAPS</u>	<u>PLATES</u>
1. Coal Data Map	1
2. Boundary and Coal Data Map	2
3. Coal Data Sheet	3
4. Isopach and Mining Ratio Map of Middle Wyodak Coal Bed	4
5. Structure Contour Map of Middle Wyodak Coal Bed	5
6. Isopach Map of Overburden of Middle Wyodak Coal Bed	6
7. Areal Distribution of Identified Resources of Middle Wyodak Coal Bed	7
8. Identified Resources of Middle Wyodak Coal Bed	8
9. Isopach and Mining Ratio Map of Lower Wyodak Coal Zone	9
10. Structure Contour Map of Lower Wyodak Coal Zone	10
11. Isopach Map of Overburden and Interburden of Lower Wyodak Coal Zone	11
12. Areal Distribution of Identified Resources of Lower Wyodak Coal Zone	12
13. Identified Resources of Lower Wyodak Coal Zone	13
14. Isopach Map of Wildcat-Moyer Coal Zone	14
15. Structure Contour Map of Wildcat-Moyer Coal Zone	15
16. Isopach Map of Overburden of Wildcat-Moyer Coal Zone	16
17. Areal Distribution of Identified Resources of Wildcat-Moyer Coal Zone	17
18. Identified and Hypothetical Resources of Wildcat-Moyer Coal Zone	18
19. Coal Development Potential for Surface Mining Methods	19

CONVERSION TABLE

<u>TO CONVERT</u>	<u>MULTIPLY BY</u>	<u>TO OBTAIN</u>
inches	2.54	centimeters (cm)
feet	0.3048	meters (m)
miles	1.609	kilometers (km)
acres	0.40469	hectares (ha)
tons (short)	0.9072	metric tons (t)
cubic yards/ton	0.8428	cubic meters per metric tons
acre feet	0.12335	hectare-meters
Btu/lb	2.326	kilojoules/kilogram (kJ/kg)
Btu/lb	0.55556	kilocalories/kilogram (kcal/kg)
Fahrenheit	5/9 (F-32)	Celsius

I. Introduction

This report and accompanying maps set forth the Coal Resource Occurrence (CRO) and Coal Development Potential (CDP) of coal beds within the Northwest Quarter of Betty Reservoir 15' Quadrangle, Converse and Campbell Counties, Wyoming. This CRO and CDP map series (U. S. Geological Survey Open-File Report 79-318) includes 19 plates. The project is compiled by IntraSearch Inc., 1600 Ogden Street, Denver, Colorado, under KRCRA Northeastern Powder River Basin, Wyoming Contract Number 14-08-0001-17180. This contract is a part of a program to provide an inventory of unleased federal coal in Known Recoverable Coal ^{Resource} Areas (KRCRAs) in the western United States.

The Northwest Quarter of Betty Reservoir 15' Quadrangle is located in Converse and Campbell Counties, in northeastern Wyoming. It encompasses all or parts of Townships 39, 40, and 41 North, Ranges 71 and 72 West, and covers the area: 43°22'30" to 43°30' north latitude; 105°22'30" to 105°30' west longitude.

The main avenue of access to the Northwest Quarter of Betty Reservoir 15' Quadrangle is Wyoming State Highway 59 which extends south-eastward from the northern to the southern boundaries of the study area. The numerous maintained gravel and unimproved dirt roads which intersect Wyoming State Highway 59 provide additional access to the region. The closest railroad is the proposed Burlington Northern trackage approximately 3 miles (5 km) to the east. Trackage of this railroad has been completed approximately 8 miles (13 km) northwest of the study area.

The surface drainage pattern of the Northwest Quarter of Betty Reservoir 15' Quadrangle is characterized by numerous ephemeral streams in deeply cut gullies. The most prominent of these streams is Antelope Creek, which flows intermittently northeastward through the northern half

of the area. The terrain attains a maximum elevation of approximately 5080 feet (1548 m) above sea level in the southeastern corner of the quadrangle. The minimum topographic elevation, approximately 4570 feet (1393 m) above sea level, occurs where Antelope Creek crosses the eastern boundary of the study area.

The thirteen to fourteen inches (33 to 36 cm) of annual precipitation that falls in this semi-arid region accrues principally in the springtime. Summer and fall precipitation usually originates from thunderstorms, and infrequent snowfalls of six inches (15 cm) or less generally characterize winter precipitation. Although temperatures ranging from less than -25°F (-32°C) to more than 100°F (38°C) have been recorded near Douglas, Wyoming, average wintertime minimums and summertime maximums approach +5° to +15°F (-15° and -9°C) and 75° to 90°F (24° to 32°C), respectively.

Surface ownership is divided among fee, state, and federal categories. State and federal lands are generally leased to ranchers for grazing purposes. Details of surface ownership are available at the Converse and Campbell County Courthouses in Douglas and Gillette, Wyoming, respectively. Details of mineral ownership on federal lands are available from the U. S. Bureau of Land Management in Cheyenne, Wyoming. Federal coal ownership is shown on Plate 2 of the Coal Resource Occurrence maps. The non-federal coal belongs to both fee and state owners.

The Coal Resource Occurrence and Coal Development Potential program is restricted to unleased federal coal and focuses upon: 1) the delineation of lignite, subbituminous coal, bituminous coal, and anthracite at the surface and in the subsurface on federal land; 2) subdivision of deposits into measured, indicated, and inferred reserve resource

categories, and hypothetical resources; 3) the measurement of coal resources in place as well as recoverable reserves; and 4) the determination of the potential for surface or underground mining, and in-situ gasification of the coal beds. This report contains an evaluation of the coal resources of all unleased federal coal beds in the quadrangle, which are 5 feet (1.5 m) or greater in thickness and occur at depths down to 3000 feet (914 m). No resources or reserves are computed for leased federal coal, state coal, fee coal, or lands encompassed by coal prospecting permits and preference right lease applications.

Surface and subsurface geological and engineering extrapolations drawn from the current data base suggest the occurrence of approximately 4.2 billion tons (3.8 billion metric tons) of unleased federal coal resources in the Northwest Quarter of Betty Reservoir 15' Quadrangle.

The suite of maps that accompany this report portray the coal resource and reserve occurrence in detail. For the most part, this report supplements the cartographic information, with minimum duplication of the map data.

II. Geology

Regional. The thick, economic coal deposits of the Powder River Basin in northeastern Wyoming occur mostly in the Tongue River Member of the Fort Union Formation, and in the lower part of the Wasatch Formation. Approximately 3000 feet (914 m) of the Fort Union Formation, that includes the Tongue River, Lebo, and Tullock Members of Paleocene age, are unconformably overlain by approximately 700 feet (213 m) of the Wasatch Formation of Eocene age. These Tertiary formations lie in a structural basin flanked on the east by the Black Hills uplift, on the south by the Hartville and Casper Mountain uplifts, and on the west by

the Casper Arch and the Big Horn Mountain uplift. The structural configuration of the Powder River Basin originated in Late Cretaceous time, with episodic uplift thereafter. The Cretaceous Cordillera was the dominant positive land form throughout the Rocky Mountain area at the close of Mesozoic time.

Outcrops of the Wasatch Formation and the Tongue River Member of the Fort Union Formation cover most of the areas of major coal resource occurrence in the Powder River Basin. The Tongue River Member is composed of very fine-grained sandstones, siltstones, claystones, shales, carbonaceous shales, and numerous coal beds. The Lebo Shale Member of the Fort Union Formation consists of light-to dark-gray very fine-grained to conglomeratic sandstone with interbedded siltstone, claystone, carbonaceous shale and thin coal beds. Thin bedded calcareous ironstone concretions interbedded with massive white sandstone and slightly bentonitic shale occur throughout the unit.

The Lebo Member is mapped at the surface northeast of Recluse, Wyoming, east of the principal coal outcrops and associated clinkers (McKay, 1974), and presumably projects into the subsurface beneath much of the basin. One of the principal characteristics for separating the Lebo and Tullock Members (collectively referred to as the Ludlow Member east of Miles City, Montana) from the overlying Tongue River Member is the color differential between the lighter-colored upper portion and the somewhat darker lower portion (Brown, 1958). Although geologists working with subsurface data, principally geophysical logs, in the basin are trying to develop criteria for subsurface recognition of the Lebo-Tullock and Tongue River-Lebo contacts, no definitive guidelines are known to have been published. Hence, for subsurface mapping purposes, the Fort Union Formation is not divided into its members for this study.

During the Paleocene epoch, the Powder River Basin tropic to subtropic depositional environment included broad, inland flood basins with extensive swamps, marshes, freshwater lakes, and a sluggish but active northeastward discharging drainage system, superimposed on an emerging sea floor, near base level. Much of the vast area where organic debris collected was within a reducing depositional environment. Localized uplifts began to disturb the near sea level terrain of northeastern Wyoming following retreat of the Cretaceous seas. However, the extremely fine-grained characteristics of the Tongue River Member clastics suggest that areas of recurring uplift peripheral to the Powder River Basin were subdued during major coal deposit formation.

The uplift of areas surrounding the Powder River Basin created a structural basin of asymmetric characteristic, with the steep west flank located on the eastern edge of the Big Horn Mountains. The axis of the Powder River Basin is difficult to specifically define, but is thought to be located in the western part of the Basin, and to display a north-south configuration some 15 to 20 miles (24 to 32 km) east of Sheridan, Wyoming. Thus, the sedimentary section described in this report lies on the east flank of the Powder River Basin, with gentle dips of two degrees or less disrupted by surface structure thought to relate to tectonic adjustment and differential compaction.

Some coal beds in the Powder River Basin exceed 200 feet (61 m) in thickness. Deposition of these thick, in-situ coal beds requires a discrete balance between subsidence of the earth's crust and in-filling by tremendous volumes of organic debris. These conditions in concert with a favorable ground water table, non-oxidizing clear water, and a climate amenable to the luxuriant growth of vegetation produce a stabilized swamp critical to the deposition of coal beds.

Deposition of the unusually thick coal beds of the Powder River Basin may be partially attributable to short-distance water transportation of organic detritus into areas of crustal subsidence. Variations in coal bed thickness throughout the basin relate to changes in the depositional environment. Drill hole data that indicate either the complete absence or extreme attenuation of a thick coal bed probably relate to location of the drill holes within the ancient stream channel system draining this low land area in Early Cenozoic time. Where thick coal beds thin rapidly from the depocenter of a favorable depositional environment, it is not unusual to encounter a synclinal structure over the maximum coal thickness due to the differential compaction between organic debris in the coal depocenter and fine-grained clastics in the adjacent areas.

The Wasatch Formation of Eocene age crops out over most of the central part of the Powder River Basin and exhibits a disconformable contact with the underlying Fort Union Formation. The contact has been placed at various horizons by different workers; however, for the purpose of this report, the contact is positioned near the top of the Roland coal bed as mapped by Olive (1957) in northwestern Campbell County, Wyoming, and is considered to disconformably descend in the stratigraphic column to the top of the Wyodak-Anderson coal bed (Roland coal bed of Taff, 1909) along the eastern boundary of the coal measures. No attempt is made to differentiate the Wasatch and Fort Union Formations on geophysical logs or in the subsurface mapping program that is a part of this CRO-CDP project.

Although Wasatch and Fort Union lithologies are too similar to allow differentiation in some areas, most of the thicker coal beds occur in the Fort Union section on the east flank of the Powder River Basin.

Furthermore, orogenic movements peripheral to the basin apparently increased in magnitude during Wasatch time causing the deposition of friable, coarse-grained to gritty, arkosic sandstones, fine- to very fine-grained sandstones, siltstones, mudstones, claystones, brown-to-black carbonaceous shales and coal beds. These sediments are noticeably to imperceptibly coarser than the underlying Fort Union clastics.

The Northwest Quarter of Betty Reservoir 15' Quadrangle is located in an area where surface rocks are classified into the Fort Union and Wasatch Formations. Approximately 200 feet (61 m) of Tertiary-age sediments are exposed in this area. Olive (1957) correlated coal beds in the Spotted Horse coal field with coal beds in the Sheridan coal field (Baker, 1929) and Gillette coal field (Dobbin and Barnett, 1927), Wyoming, and with coal beds in the Ashland coal field (Bass, 1932) in southeastern Montana. This report utilizes, where possible, the coal bed nomenclature used in previous reports.

IntraSearch's correlation of thick coal beds from the Spotted Horse coal field to Gillette points out that the Wyodak coal bed, named the "D" coal bed by Dobbin and Barnett (1927), is equivalent to the Anderson, Canyon and all or part of the Cook coal beds to the north and west of Gillette, Wyoming. Correlation of this suite of coal beds with the Wyodak coal bed south and southwest of Gillette suggests that the Anderson and Canyon coal beds equate with the upper ten to twenty-five percent of the thick Wyodak coal bed, and the Cook and Wall or Upper Wall coal beds are equivalent to the major part of the Wyodak coal bed. Due to problematic correlations outside of the Gillette area, the name Wyodak has been informally used by many previous authors to represent the coal beds in the area surrounding the Wyodak coal mine. The Wildcat and Moyer coal beds were informally named by IntraSearch (1978 and 1979).

Local. The Northwest Quarter of Betty Reservoir 15' Quadrangle lies near the eastern flank of the Powder River Basin, where the strata dip gently westward. The Wasatch Formation, comprised of friable, coarse-grained to very fine-grained, arkosic, sandstones, fine- to very fine-grained sandstones, siltstones, mudstones, claystones, brown-to-black carbonaceous shales, and coal beds overlies approximately ninety percent of the quadrangle. The Fort Union Formation crops out over the remaining area. The Fort Union Formation is composed of very fine-grained sandstones, siltstones, claystones, shales, carbonaceous shales, and numerous coal beds.

III. Data Sources

Areal geology of the coal outcrops and associated clinker is derived from Lingley (1976), and Denson and others (1978). Expansion of the Betty Reservoir 15' Quadrangle (scale 1:62,500) into 7 1/2' quadrangle maps (scale 1:24,000) was performed by the U. S. Geological Survey for Coal Resource Occurrence - Coal Development Potential mapping purposes.

The major source of subsurface control, particularly on deep coal beds, is the geophysical logs from oil and gas test bores, and producing wells. Some geophysical logs are not applicable to this study, for the logs relate only to the deep potentially productive oil and gas zones. More than eighty percent of the logs include resistivity, conductivity, and self-potential curves. Occasionally the logs include gamma, density, and sonic curves. These logs are available from several commercial sources.

All geophysical logs available in the quadrangle are scanned to select those with data applicable to Coal Resource Occurrence map-

ping. Paper copies of the logs are obtained, interpreted, and coal intervals annotated. Maximum accuracy of coal bed identification is accomplished where gamma, density, and resistivity curves are available. Coal bed tops and bottoms are picked on the logs at the midpoint between the minimum and maximum curve deflections. The correlation of coal beds within and between quadrangles is achieved utilizing a fence diagram to associate local correlations with regional coal occurrences.

In some parts of the Powder River Basin, additional subsurface control is available from U. S. Geological Survey open-file reports that include geophysical and lithologic logs of shallow holes drilled specifically for coal exploration. A sparse scattering of subsurface data points are shown on unpublished CRO-CDP maps compiled by the U. S. Geological Survey, and where these data are utilized, the rock-coal intervals are shown on the Coal Data Map (Plate 1). Inasmuch as these drill holes have no identifier headings, they are not set forth on the Coal Data Sheet (Plate 3). The geophysical logs of these drill holes were not available to IntraSearch to ascertain the accuracy of horizontal location, topographic elevation, and downhole data interpretation.

The reliability of correlations, set forth by IntraSearch in this report, vary depending on: the density and quality of lithologic and geophysical logs; the detail, thoroughness, and accuracy of published and unpublished surface geological maps, and interpretative proficiency. There is no intent on the part of IntraSearch to refute nomenclature established in the literature or used locally by workers in the area. IntraSearch's nomenclature focuses upon the suggestion of regional coal bed names applicable throughout the eastern Powder River Basin. It is expected and entirely reasonable that some differences of opinion

regarding correlations, as suggested by IntraSearch, exist. Additional drilling for coal, oil, gas, water, and uranium, coupled with expanded mapping of coal bed outcrops and associated clinkers will broaden the data base for coal bed correlations and allow continued improvement in the understanding of coal bed occurrences in the eastern Powder River Basin.

15'

The topographic map of the Betty Reservoir 15' Quadrangle is published by the U. S. Geological Survey, compilation date, 1959. Land network and mineral ownership data are compiled from land plats available from the U. S. Bureau of Land Management in Cheyenne, Wyoming. This information is current to October 13, 1977.

IV. Coal Bed Occurrence

Fort Union Formation coal beds that are present in all or part of the Northwest Quarter of Betty Reservoir 15' Quadrangle include, in descending stratigraphic order, the Middle Wyodak coal bed, the Lower Wyodak coal zone, the Pawnee coal bed, the Upper, Middle and Lower Wildcat coal beds, and the Moyer coal bed. Several local coal beds of limited lateral extent also occur within the quadrangle. A complete suite of maps (structure, isopach, mining ratio, overburden isopach, identified resources, and areal distribution of identified resources) is prepared for each of these coal beds except the local and Pawnee coal beds, where insufficient areal extent precludes detailed mapping. In addition, an interburden isopach map, presented with the overburden isopach map, is prepared for the Lower Wyodak coal bed.

Published physical and chemical analyses include the following results for a cored hole penetrating the Middle Wyodak coal bed in the Northwest Quarter of Betty Reservoir 15' Quadrangle:

COAL BED			FIXED					
NAME			ASH %	CARBON %	MOISTURE %	VOLATILES %	SULFUR %	BTU/LB
Middle	Hole							
Wyodak	(U)	7546	9.227	34.495	23.469	32.810	0.382	8315

(U) - U. S. Geological Survey & Montana Bureau of Mines & Geology -1976.

The Coal Data Sheet, Plate 3, shows the downhole identification of coal beds within the quadrangle as interpreted from geophysical logs of oil and gas test bores and producing sites, and coal exploration holes drilled by governmental agencies. Inasmuch as the Middle Wyodak coal bed underlies more than ninety-five percent of the quadrangle, it is designated as datum for the correlation diagram. This portrayal is schematic by design; hence, no structural or coal thickness implications are suggested by the dashed correlation lines projected through no record (NR) intervals.

The Middle Wyodak coal bed is the stratigraphically highest mappable horizon within the quadrangle. The thickness ranges from less than 5 feet (1.5 m) in the southwestern corner to greater than 35 feet (11 m) near the northern boundary of the quadrangle. Some burning has occurred along the outcrops, which are located in the southwestern quadrant and adjacent to Antelope Creek. Structure contours drawn on top of the Middle Wyodak coal bed indicate a gentle dip of one to two degrees to the northwest. The Middle Wyodak coal bed lies at depths up to 364 feet (111 m) beneath the surface.

Located 88 to 135 feet (27 to 41 m) below the Middle Wyodak coal bed, the Lower Wyodak coal zone is composed of two or more relatively thin coal beds which have been combined for mapping purposes. Pinched out in the southern and west-central portions of the quadrangle, the Lower Wyodak coal zone attains a maximum thickness of over 30 feet (9 m) in the northeastern corner of the quadrangle. The maximum total

thickness of non-coal interburden is more than 100 feet (30 m), and occurs in the northwestern quadrant. The Lower Wyodak coal zone dips northwestward one to two degrees, and is overlain by less than 500 feet (152 m) of overburden throughout approximately ninety-five percent of the area where it is present.

Where the Lower Wyodak coal bed is absent, the interburden between the Upper Wyodak and the Upper Wildcat coal beds varies from 916 to 1107 feet (279 to 337 m). The individual Upper, Middle, and Lower Wildcat coal beds and the Moyer coal bed have been combined for mapping purposes. Total thickness of the Wildcat-Moyer coal zone attains a maximum value slightly greater than 65 feet (20 m) in the southwestern corner of the quadrangle. A minimum thickness of less than 35 feet (11 m) occurs in the southeastern quadrant. The Upper Wildcat coal bed is separated from the Middle Wildcat coal bed by a non-coal interval varying from 6 to 130 feet (1.8 to 40 m). From 77 to 114 feet (23 to 35 m) of clastic debris divide the Middle Wildcat coal bed and the Lower Wildcat coal bed. The Moyer coal bed occurs between 100 and 162 feet (30 and 49 m) below the base of the Lower Wildcat coal bed. Total non-coal interburden within the Wildcat-Moyer coal zone attains a maximum thickness of 373 feet (114 m) in section 21, Township 40 North, Range 71 West. The structure contour map of the Wildcat-Moyer coal zone is drawn on top of the Upper Wildcat coal bed where it is present, and on top of the Middle Wildcat coal bed in the southeastern corner where the Upper Wildcat coal bed is absent. The structural configuration of the Wildcat-Moyer coal zone indicates a gentle westward dip of one to two degrees. The Wildcat-Moyer coal zone lies at depths greater than 500 feet (152 m) beneath the surface throughout the entire quadrangle.

V. Geological and Engineering Mapping Parameters

The correct horizontal location and elevation of drill holes utilized in subsurface mapping are critical to map accuracy. IntraSearch Inc., plots the horizontal location of the drill hole as described on the geophysical log heading. Occasionally this location is superimposed or near to a drillsite shown on the topographic map, and the topographic map horizontal location is utilized. If the ground elevation on the geophysical log does not agree with the topographic elevation of the drillsite, the geophysical log ground elevation is adjusted to conformance. If there is no indication of a drillsite on the topographic map, the "quarter, quarter, quarter" heading location is shifted within a small area until the ground elevation on the heading agrees with the topographic map elevation. If no elevation agreement can be reached, the well heading or data sheet is rechecked for footage measurements and ground elevation accuracy. Inquiries to the companies who provided the oil and gas geophysical logs frequently reveal that corrections have been made in the original survey. If all horizontal location data sources have been checked and the information accepted as the best available data, the drillsite elevation on the geophysical log is modified to agree with the topographic map elevation. IntraSearch Inc., considers this agreement mandatory for the proper construction of most subsurface maps, but in particular, the overburden isopach, the mining ratio, and Coal Development Potential maps.

Subsurface mapping is based on geologic data within and adjacent to the Northwest Quarter of Betty Reservoir 15' Quadrangle area. Data from geophysical logs are used to correlate coal beds and control contour lines for the coal thickness, structure, and overburden maps.

Isopach lines are also drawn to honor selected surface measured sections where there is sparse subsurface control. Where isopach contours do not honor surface measured sections, the surface thicknesses are thought to be attenuated by oxidation and/or erosion, hence not reflective of total coal thickness. Isopach lines extend to the coal bed outcrops, the projections of coal bed outcrops, and the contact between porcellanite (clinker) and unoxidized coal in place. Attenuation of total coal bed thickness is known to take place near these lines of definition; however, the overestimation of coal bed tonnages that results from this projection of total coal thickness is insignificant to the Coal Development Potential maps. Structure contour maps are constructed on the tops of the main coal beds. Where subsurface data are scarce, supplemental structural control points are selected from the topographic map along coal outcrops.

In preparing overburden isopach maps, no attempt is made to identify coal beds that occur in the overburden to a particular coal bed under study. Mining ratio maps for this quadrangle are constructed utilizing a ninety-five percent recovery factor. Contours of these maps identify the ratio of cubic yards of overburden to tons of recoverable coal. Where ratio control points are sparse, interpolated points are computed at the intersections of coal bed and overburden isopach contours using coal structure, coal isopach, and topographic control. On the Areal Distribution of Identified Resources Map (ADIR), coal bed reserves are not calculated where the coal is less than 5 feet (1.5 m) thick, where the coal occurs at a depth greater than 500 feet (152 m), where non-federal coal exists, or where federal coal leases, preference-right lease applications, and coal prospecting permits exist.

Coal tonnage calculations involve the planimetering of areas of measured, indicated, inferred reserves and resources, and hypothetical resources to determine their areal extent in acres. An Insufficient Data Line is drawn to delineate areas where surface and subsurface data are too sparse for CRO map construction. Various categories of resources are calculated in the unmapped areas by utilizing coal bed thicknesses mapped in the geologically controlled area adjacent to the insufficient data line. Acres are multiplied by the average coal bed thickness and 1750, or 1770 (the number of tons of lignite A or subbituminous C coal per acre-foot, respectively; 12,874 or 13,018 metric tons per hectare-meter, respectively), to determine total tons in place. Recoverable tonnage is calculated at ninety-five percent of the total tons in place. Where tonnages are computed for the CRO-CDP map series, resources and reserves are expressed in millions of tons. Frequently the planimetering of coal resources on a sectionized basis involves complexly curvilinear lines (coal bed outcrop and 500-foot stripping limit designations) in relationship with linear section boundaries and circular resource category boundaries. Where these relationships occur, generalizations of complexly curvilinear lines are discretely utilized, and resources and/or reserves are calculated within an estimated two to three percent plus or minus accuracy.

VI. Coal Development Potential

Strippable Coal Development Potential. Areas where coal beds are 5 feet (1.5 m) or more in thickness and are overlain by 500 feet (152 m) or less of overburden are considered to have potential for surface mining and are assigned a high, moderate, or low development potential based on the mining ratio (cubic yards of overburden per ton of recoverable coal). The formula used to calculate mining ratios is as follows:

$$MR = \frac{to (0.911)*}{tc (rf)}$$

where MR = mining ratio
to = thickness of overburden
tc = thickness of coal
rf = recovery factor
0.911* = conversion factor (cu. yds./ton)

*A conversion factor of 0.922 is used for lignite.

A surface mining potential map (Plate 19) is prepared utilizing the following mining ratio criteria for coal beds 5 to 40 feet (1.5 to 12 m) thick:

1. Low development potential = 15:1 and greater ratio.
2. Moderate development potential = 10:1 to 15:1 ratio.
3. High development potential = 0 to 10:1 ratio.

The following mining ratio criteria is utilized for coal beds greater than 40 feet (12 m) thick:

1. Low development potential = 7:1 and greater ratio.
2. Moderate development potential = 5:1 to 7:1 ratio.
3. High development potential = 0 to 5:1 ratio.

The surface mining potential is high for approximately eighty percent of the Northwest Quarter of Betty Reservoir 15' Quadrangle due to occurrence of the thick Middle and Lower Wyodak coal beds at depths less than 500 feet (152 m) beneath the surface throughout much of the area (Plate 19). The areas of moderate potential, located in the northwest, southeast, west-central and central portions of the quadrangle, relate to either increased overburden beneath higher terrain or erosion of the Middle Wyodak coal bed. The moderate potential area covers approximately fifteen percent of the quadrangle. Low development potential for surface mining, exists in about three percent of the quadrangle, in the central, west-central and southeastern parts of the area, develops from high overburden to coal ratios in areas of high

relief or the absence of the Middle Wyodak coal bed due to erosion.

In the southwest quadrant, a small area, approximately two percent of the quadrangle, is mapped as no coal development potential for surface mining. In this area the Middle Wyodak coal bed thins to less than five feet (1.5 m) thick. Table 1 sets forth the estimated strippable reserve base tonnages per coal bed for the quadrangle.

Underground Mining Coal Development Potential. Subsurface coal mining potential throughout the Northwest Quarter of Betty Reservoir 15' Quadrangle is considered low. Inasmuch as recovery factors have not been established for the underground development of coal beds in this quadrangle, reserves are not calculated for coal beds that occur more than 500 feet (152 m) beneath the surface. Table 2 sets forth the estimated coal resources in tons per coal bed.

In-Situ Gasification Coal Development Potential. The evaluation of subsurface coal deposits for in-situ gasification potential relates to the occurrence of coal beds more than 5 feet (1.5 m) thick buried from 500 to 3000 feet (152 to 914 m) beneath the surface. This categorization is as follows:

1. Low development potential relates to: 1) a total coal section less than 100 feet (30 m) thick that lies 500 feet (152 m) to 3000 feet (914 m) beneath the surface, or 2) coal beds 5 feet (1.5 m) or more in thickness that lie 500 feet (152 m) to 1000 feet (305 m) beneath the surface.
2. Moderate development potential is assigned to a total coal section from 100 to 200 feet (30 to 61 m) thick, and buried from 1000 to 3000 feet (305 to 914 m) beneath the surface.
3. High development potential involves 200 feet (61 m) or more of total coal thickness buried from 1000 to 3000 feet (305 to 914 m).

The coal development potential for in-situ gasification within the Northwest Quarter of Betty Reservoir 15' Quadrangle is low, hence no CDP map is generated for this map series. The coal resource tonnage for in-situ gasification with low development potential totals approximately 2.8 billion tons (2.5 billion metric tons) (Table 3). None of the coal beds in the Northwest Quarter of Betty Reservoir 15' Quadrangle qualify for a moderate or high development potential rating.

Table 1.--Strippable Coal Reserve Base Data (in short tons) for Federal Coal Lands in the Northwest Quarter of Betty Reservoir 15' Quadrangle, Converse and Campbell Counties, Wyoming.

Development potentials are based on mining ratios (cubic yards of overburden/ton of recoverable coal).

Coal Bed	High Development Potential (0-10:1 Mining Ratio)	Moderate Development Potential (10:1-15:1 Mining Ratio)	Low Development Potential (> 15:1 Mining Ratio)	Total
Middle				
Wyodak	765,100,000	200,470,000	30,780,000	996,360,000
Lower				
Wyodak	43,970,000	74,960,000	221,240,000	340,170,000
TOTAL	808,070,000	275,430,000	252,020,000	1,336,520,000

Table 2.--Coal Resource Base and Hypothetical Resources Data (in short tons) for Underground Mining Methods for Federal Coal Lands in the Northwest Quarter of Betty Reservoir 15' Quadrangle, Converse and Campbell Counties, Wyoming.

Coal Bed Name	High Development Potential	Moderate Development Potential	Low Development Potential	Total
<u>RESOURCE BASE TONNAGE:</u>				
Lower Wyodak	-----	-----	30,490,000	30,490,000
Wildcat-Moyer	-----	-----	2,542,460,000	2,542,460,000
TOTAL	-----	-----	2,572,950,000	2,572,950,000
<u>HYPOTHETICAL RESOURCE TONNAGE:</u>				
Wildcat-Moyer	-----	-----	239,370,000	239,370,000
TOTAL	-----	-----	239,370,000	239,370,000
GRAND TOTAL	-----	-----	2,812,320,000	2,812,320,000

Table 3.--Coal Resource Base Data (in short tons) for In-Situ Gasification for Federal Coal Lands in the Northwest Quarter of Betty Reservoir 15' Quadrangle, Converse and Campbell Counties, Wyoming.

Coal Bed Name	High Development Potential	Moderate Development Potential	Low Development Potential	Total
<u>RESOURCE BASE TONNAGE:</u>				
Lower Wyodak	-----	-----	30,490,000	30,490,000
Wildcat-Moyer	-----	-----	2,542,460,000	2,542,460,000
TOTAL	-----	-----	2,572,950,000	2,572,950,000
<u>HYPOTHETICAL RESOURCE TONNAGE:</u>				
Wildcat-Moyer	-----	-----	239,370,000	239,370,000
TOTAL	-----	-----	239,370,000	239,370,000
GRAND TOTAL	-----	-----	2,812,320,000	2,812,320,000

SELECTED REFERENCES

- Baker, A. A., 1929, The northward extension of the Sheridan coal field, Big Horn and Rosebud Counties, Montana: U. S. Geol. Survey Bull. 806-B, p. 15-67.
- Bass, N. W., 1932, The Ashland coal field, Rosebud, Powder River, and Custer Counties, Montana: U. S. Geol. Survey Bull. 831-B, p. 19-105.
- Brown, R. W., 1958, Fort Union Formation in the Powder River Basin, Wyoming: Wyo. Geol. Assoc. Guidebook, Thirteenth Annual Field Conf., p. 111-113.
- Denson, N. H., Dover, J. H., and Osmonson, L. M., 1978, Structure contour and isopach maps of the Wyodak-Anderson coal bed in the Reno Junction-Antelope Creek Area, Campbell and Converse Counties, Wyoming: U. S. Geol. Survey Misc. Field Studies Map MF-961, scale 1:125,000.
- Dobbin, C. E., and Barnett, V. H., 1927, The Gillette coal field, northeastern Wyoming, with a chapter on the Minturn district and northwestern part of the Gillette field by W. T. Thom, Jr.: U. S. Geol. Survey Bull. 796-A, p. 1-50
- Glass, G. B., 1975, Review of Wyoming coal field, 1975; Wyoming Geol. Survey Public Information circ. 4, p. 10.
- IntraSearch Inc., 1978, Coal resource occurrence and coal development potential of the Rocky Butte Quadrangle, Campbell County, Wyoming: U. S. Geol. Survey Open-File Report 78-830, 22 p.
- _____, 1979, Coal resource occurrence and coal development potential of the Larey Draw Quadrangle, Campbell County, Wyoming: U. S. Geol. Survey Open-File Report 79-023, 29 p.

- Jacob, A. F., 1973, Depositional environments of Paleocene Tongue River Formation: Am. Assoc. of Petroleum Geologists Bull, vol. 56, no. 6, p. 1038-1052.
- Lingley, Leslie, 1976, Preliminary coal resource occurrence map of the Betty Reservoir NW Quadrangle, Converse and Campbell Counties, Wyoming: U. S. Geol. Survey unpublished report, scale 1:24,000.
- McKay, E. J., 1974, Preliminary geologic map of the Bertha 2 NW (Rocky Butte) Quadrangle, Campbell County, Wyoming: U. S. Geol. Survey Open-File Report 74-173, scale 1:24,000.
- Olive, W. W., 1957, The Spotted Horse coal field, Sheridan and Campbell Counties, Wyoming: U. S. Geol. Survey Bull. 1050, 83 p.
- Schell, E. M., and Mowat, G. D., 1972, Reconnaissance map showing some coal and clinker beds in the Fort Union and Wasatch Formations in the eastern Powder River Basin, Campbell and Converse Counties, Wyoming: U. S. Geol. Survey Open-File Report, scale 1:63,360.
- Taff, J. A., 1909, The Sheridan coal field, Wyoming: U. S. Geol. Survey Bull. 341-B, p. 123-150.
- U. S. Bureau of Mines and U. S. Geological Survey, 1976, Coal Resource classification system of the U. S. Bureau of Mines and U. S. Geol. Survey: U.S. Geol. Survey Bull. 1450-B, 7 p.
- U. S. Geological Survey and Montana Bureau of Mines and Geology, 1976, Preliminary report of coal drill-hole data and chemical analyses of coal beds in Campbell, Converse, and Sheridan Counties of Wyoming; and Big Horn, Richland, and Dawson Counties, Montana: U. S. Geol. Survey Open-File Report 76-450, 382 p.
- Warren, W. C., 1959, Reconnaissance geology of the Birney-Broadus coal field, Rosebud and Powder River Counties, Montana: U. S. Geol. Survey Bull. 1072-J, p. 561-585.

Weimer, R. J., 1977, Stratigraphy and tectonics of western coals, in Geology of Rocky Mountain Coal, A Symposium, 1976: Colorado Geol. Survey Resource Series 1, p. 9-27.