

EXPLANATION

—10—
ISOPACHS OF COAL BED—Showing thickness in feet, interval 5 feet.

•14
DRILL HOLE—Showing coal thickness in feet.


—A—↑
TRACE OF COAL BED OUTCROP—Showing coal thickness in feet. Arrow points toward the coal-bearing area.

—SL—↑
STRIPPING LIMIT LINE—500 foot overburden isopach boundary for surface mining of coal. Arrow indicates area suitable for surface mining.

—35—
MINING RATIO CONTOUR—Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in area suitable for surface mining within the stripping limit.


To convert feet to meters multiply feet by 0.3048.

This outcrop mapping is derived and enlarged from a 1:62,500 scale publication from Sharp and Gibbons (1964, Plate 1). Numerous irregularities in outcrop elevations and the areal geology-topographic map relationship emphasize that this map presents a generalized configuration of the coal bed outcrop. Horizontal accuracy of outcrop location is estimated at ± 1000 feet (305 m).



MAP SHOWING LOCATION OF THE SW¼ HIGHLAND FLATS 15' QUADRANGLE AND THE POWDER RIVER BASIN KNOWN RECOVERABLE COAL RESOURCE AREA (STIPPLED) WYOMING

This report has not been edited for conformity with U. S. Geological Survey editorial standards or stratigraphic nomenclature.



COAL RESOURCE OCCURRENCE MAP OF THE SW¼ HIGHLAND FLATS 15' QUADRANGLE, CONVERSE COUNTY, WYOMING
BY
IntraSearch
1979

PLATE 4
ISOPACH AND MINING RATIO
MAP OF
ANDERSON COAL BED