

Text to Accompany:

OPEN-FILE REPORT 79-495

1985

FEDERAL COAL RESOURCE OCCURRENCE AND FEDERAL COAL DEVELOPMENT

POTENTIAL MAPS OF THE
PANAMA 7.5-MINUTE QUADRANGLE
LE FLORE COUNTY, OKLAHOMA
(Report includes 11 plates)

Prepared for
UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

By

GEOLOGICAL SERVICES OF TULSA, INC.

TULSA, OKLAHOMA

B. T. BRADY

U.S. GEOLOGICAL SURVEY, DENVER, COLORADO

and

J. L. QUERRY

BUREAU OF LAND MANAGEMENT, TULSA, OKLAHOMA

This report was prepared under contract to the U.S. Geological Survey, and has not been edited for conformity with Geological Survey editorial standards or stratigraphic nomenclature. Opinions expressed herein do not necessarily represent those of the Geological Survey.

CONTENTS

	<u>Page</u>
Introduction	
Purpose	1
Location	1
Accessibility	2
Physiography	2
Climate and vegetation	3
Land status	3
 General Geology	
Previous work	4
Stratigraphy	5
Structure	10
 Coal Geology	
Hartshorne coal bed and upper and lower splits	11
Stigler (Lower McAlester) and Upper McAlester coal beds.....	11
Chemical analyses of coal	12
 Coal Resources	13
 Coal Development Potential	
Development potential for surface mining methods	18
Development potential for subsurface mining and in situ coal gasification methods	19
 References	21
 Appendix I. Source and reliability of data used on Plate 1 ...	AI-1
 Appendix II. Tables of oil and gas test holes	AII-1

TABLES

	<u>Page</u>
Table 1. Average chemical analyses for coal in the Panama quadrangle, Le Flore County, Oklahoma.....	14
Table 2. Coal Reserve Base data for surface mining methods Federal coal land (in short tons) in the Panama quadrangle, Le Flore County, Oklahoma.....	20
Table 3. Coal Reserve Base data for subsurface mining and in-situ gasification methods for Federal coal land (in short tons) in the Panama quadrangle, Le Flore County, Oklahoma.....	21

ILLUSTRATIONS

(Plates are in pocket)

Plates 1-11. Federal Coal Resource Occurrence and Federal Coal Development Potential maps:

1. Coal Data Map
2. Boundary and Coal Data Map
3. Coal Data Sheet
4. Isopach Map of the Hartshorne Coal Bed and Upper and Lower Splits
5. Structure Contour Map of the Hartshore Coal Bed and Upper and Lower Splits
6. Interburden Isopach Map of the Upper and Lower Splits of the Hartshore Coal Bed and Overburden Isopach and Mining Ratio Map of the Hartshorne Coal Bed and Upper Split
7. Overburden Isopach and Mining Ratio Map of the Lower Split of the Hartshore Coal Bed
8. Areal Distribution and Identified Resources Map of the Lower Split of the Hartshore Coal Bed
10. Coal Development Potential Map for Surface Mining Methods
11. Coal Development Potential Map for Subsurface Mining Methods and In-Situ Coal Gasification Methods.

INTRODUCTION

Purpose

This text is to be used in conjunction with the Federal Coal Resource Occurrence (FCRO) and Federal Coal Development Potential (FCDP) maps of the Panama 7.5-minute quadrangle, Le Flore County, Oklahoma.

This report was compiled to support the land-planning work of the Bureau of Land Management (BLM). The work was undertaken by Geological Services of Tulsa, Tulsa, Oklahoma, at the request of the United States Geological Survey under contract number 14-08-0001-17989. The resource information gathered for this report is in response to the Federal Coal Leasing Amendments Act of 1976 (Public Law 94-377). Published and unpublished publicly available information was used as the data base for this study. No new drilling or field mapping was done to supplement this study, nor was any confidential or proprietary data used.

Location

The 7.5-minute quadrangle is located to the north of the Howe-Wilburton coal mining district, in the eastern part of the southeastern Oklahoma coal field. All of the quadrangle is within Le Flore County. The city of McAlester is 65 miles (104 km) west of the quadrangle, and the city of Tulsa is approximately 100 miles (160 km) northwest of the quadrangle.

The town of Panama is the largest settlement in the quadrangle. Other sizeable town(s) include Shady Point in the south and Sunset Corner in the north. The western edge of the town of Spiro falls just within the quadrangle boundary in the northeast.

Accessibility

The town of Panama is located slightly south and east of the center of the quadrangle. U.S. Routes 271 and 59 run north-south through town. State Route 31 intersects with Routes 271 and 59 approximately 2 miles (3.2 km) north of the town of Panama, and heads west toward Bokoshe. Five miles (9 km) north of Panama these two routes meet State Route 9 and divide: Highway 59 heads west, and Highway 271 heads east.

Railroads serving the Panama quadrangle include Kansas City Southern and the Texas and Pacific railroads, which run through the town of Panama, and the Fort Smith and Van Buren Railroad, which joins the Kansas City Southern about a mile northeast of Panama.

Many light-duty and unimproved dirt roads provide access to almost every section in the quadrangle.

Physiography

The Panama quadrangle is in the Arkoma Basin on the northern edge of the Ouachita Mountains in the Arkansas Valley physiographic province (Hendricks, 1939). The Choctaw Fault, which essentially marks the southern edge of the Basin is approximately 18 miles south of the quadrangle.

Much of the region is hilly, due largely to the action of streams on bedrock strata with differing capacities for resisting erosion (Knechtel, 1949). The landscape is characterized by long, sinuous, nearly parallel hogbacks that generally coincide with the outcrop of sandstone members. Between the hogbacks are wide erosional valleys underlain mostly by shale (Knechtel, 1949). Folding is quite widespread, resulting in sandstone-capped synclinal mountains. Total relief in the quadrangle is only about 220 feet (61 m) from

a low elevation of about 420 feet (128 m) in the river valley to a high of about 640 feet (195 m) on the tops of hogbacks.

The Poteau River flows through the southeast quarter of the quadrangle; both the James Fork and Brazil Creek flow into the river there. Numerous other small creeks and intermittent streams also provide drainage in the quadrangle. The Arkansas River Navigation Channel is located just north of the study area.

Climate and Vegetation

The climate in southeastern Oklahoma is for the most part fairly moderate. Winters are short, and extremely cold weather is rare. Summers, however, are generally long and hot. The mean annual temperature is about 62°F (17°C), and ranges from a daily average of about 41°F (5°C) in January to about 82°F (28°C) in July though it is not unusual to have occasional periods of very hot days (Hendricks, 1939). Annual precipitation in the area averages approximately 41 in. (105 cm), with rains generally abundant in the spring, early summer, fall and winter (Hendricks, 1939).

The area supports a wide variety of vegetation, with oaks, blackjacks, hickories, elms and hackberries being most common. On the higher mountains and ridges pines can also be found. In parts of the valleys that have not been cleared for farming, thick stands of water and willow oaks, hickories, cottonwoods, willows and wild plums may be present (Hendricks, 1939).

Land Status

Federal coal lands in the Panama quadrangle total approximately 16,400 acres (6637 hectares) or 42% of the quadrangle. Of that, 3410 acres (1380

hectares), or 20% are leased (as of October 19, 1979), 3140 acres (1270 ha) or 19% are unleased, and the remaining 9,830 acres (3978 hectares) are part of the Spiro-Bokoshe Known Recoverable Coal Resources Area (KRCRA) (Plate 2).

GENERAL GEOLOGY

Previous Work

Much work has been done on the southeastern Oklahoma coal field. The first geologic study of the region was published by Chance (1890) and included a map showing the outcrops of the most important coal beds in the area. In 1897, Drake published the results of his study on the coal fields of the Indian Territory, which consisted of a map and text of the principal coal beds, general stratigraphy and structural features.

From 1899 to 1910, Taff and his associates published several reports on the Oklahoma coal lands. These included a number of investigations carried out for the United States Geological Survey on the extent and general character of local stratigraphy, including coal beds. Much of his work was a part of Senate Document 390 (1910), which represented a compilation of material collected for the purpose of determining the value and extent of coal deposits in and under the segregated coal lands of the Choctaw and Chickasaw Nations in Oklahoma.

The Oklahoma Geological Survey published a bulletin by Snider in 1914 on the geology of east-central Oklahoma, emphasizing the geologic structure and oil and gas possibilities of the area. Further studies on the southern Oklahoma coal lands were carried out by Shannon and others (1926), Moose and Searle

(1929), and Hendricks (1939). These, along with later works by Knechtel and Oakes in the 1940's, added greatly to the body of knowledge on Oklahoma coals, particularly in terms of their quality, chemical composition and extent.

A number of estimates as to original and remaining coal reserves have been published, among them are the figures published in papers by Trumbull (1957) and Friedman (1974). Non-proprietary information from coal test holes drilled in various years in the Panama quadrangle was obtained from USGS files.

In recent years a number of masters theses have been done on the Southeastern Oklahoma coal field. Craney (1978) carried out a study of the Hartshorne coals in the Panama quadrangle, and much of his work has been incorporated into this report.

Stratigraphy

The Arkoma Basin, once part of the larger Ouachita geosyncline, formed as a result of subsidence beginning in Mississippian time and continuing through Early and Middle Pennsylvanian. Strata in the basin are thought to have been deposited in a deltaic environment with sediment coming primarily from eroding highlands to the northeast, north, northwest (Branan, 1968). Evidence that the basin was becoming full is provided by coal seams in the upper Atoka and lower Desmoinesian section. Sedimentation continued until late Pennsylvanian time, when the Arbuckle Orogeny of southern Oklahoma took place (Branan, 1968). In early Permian time, Ouachita mountain building to the south of the basin compressed Arkoma Basin strata into a series of long, narrow, east-west anticlinal and synclinal folds (see section on Structure below).

All of the rock units cropping out in the Panama quadrangle are of Pennsylvanian age, and include the Atoka Formation, as well as the Hartshorne, McAlester and Savanna formations of the Lower-Desmoinesian Krebs Group. The Hartshorne and McAlester formations are coal bearing in this quadrangle. The Atoka Formation was named by Taff and Adams in 1900. It is the the oldest exposed formation in the quadrangle, and crops out in the central and northwestern section of it (Knechtel, 1949). The formation consists mostly of gray silty shale interbedded with ridge-forming brown or light gray sandstone units (Knechtel, 1949). The sandstone is highly variable in character, both from bed to bed and within a single bed. In most exposures it is fine-grained, silty and irregularly bedded; however, locally it may be coarse-grained, clean, and massive to thick-bedded. The Atoka Formation thickens somewhat across the quadrangle, from about 4000 feet (1220 m) in the northwest to 8000 feet (2440 m) in the southeast (Hendricks, 1939).

The Hartshorne Formation, which forms the basal unit of the Desmoinesian Series, crops out on the limbs of the Milton and Backbone anticlines in the Panama quadrangle (Knechtel, 1949). It is most probably conformable with the underlying Atoka formation (McDaniel, 1961, Oakes and Knechtel, 1948), although the sharp and irregular contact between the Hartshorne and Atoka formations has lead some observers to conclude that a minor unconformity separates them, at least locally (Hendricks, 1939, and Branson, 1962). The contact between the Hartshorne Formation and the overlying McAlester Formation is conformable (Hendricks, 1939).

The boundaries of the Hartshorne Formation have been modified several times since the unit was first mapped by H.M. Chance in 1890. Then called the "Tobucksy" sandstone, the formation was renamed the Hartshorne sandstone by

Taff in 1899. Early workers defined the formation such that the Upper Hartshorne coal was considered to be part of the overlying McAlester Formation. However, Oakes and Knechtel (1948) recognized a convergence of the Upper and Lower Hartshorne coals in northern LeFlore and eastern Haskell counties, and redefined the formation to include both coals. The Hartshorne coal, undivided to the north, splits into Upper and Lower Hartshorne coals along a northeast-southwest trending line. This split line cuts across the central part of the Panama quadrangle (Plate 6). The presently-used definition of the Hartshorne Formation is one proposed by McDaniel (1961), which supports the boundaries suggested by Oakes and Knechtel (1948), but formally divides the formation into Upper and Lower members where applicable (based on the above mentioned coal "split line").

The Hartshorne Formation is highly variable in character and thickness. In general, it contains interbedded sandstones and shales which tend to become discontinuous as the upper and lower coals merge. The sands are for the most part fine-grained, brown to gray, silty and micaceous, and the shales are gray and sandy. Plant fossils are abundant in the shales. The formation is roughly 300 feet (92 m) thick in the Bokoshe quadrangle.

The McAlester Formation averages 1600 feet (488 m) thick in the Panama quadrangle and thins to the north. It crops out around the axis of the Bokoshe syncline in the north-northwest, and in the southern part of the quadrangle, and lies conformably on the Hartshorne Formation. The McAlester Formation consists primarily of various unnamed shale units, but includes one shale member and several sandstone members as well. In ascending order, the McAlester Formation includes the McCurtain Shale Member, and the Warner, Lequire, Cameron, Tamaha, and Keota Sandstone members. Between each of these sandstones,

and above the Keota Sandstone Member, is an unnamed shale unit. The thickness given below of each individual member or unit has been estimated from well logs in the area.

The lowermost unit of the McAlester Formation is the McCurtain Shale Member. This is a blue to dark gray, clayey shale with numerous siderite concretions and plant material (Knechtel, 1949). It varies from 575 to 775 feet (175 to 236 m) thick in the Panama quadrangle. The McCurtain Shale contains 3 thin sandstone units overlain by thin local coals (Craney, 1978).

The most persistent sandstone of the McAlester Formation is the Warner Sandstone Member, a fine-grained, argillaceous unit which forms the first prominent escarpment stratigraphically above the Hartshorne Formation. This member forms the upper boundary of the McCurtain Shale. It is highly variable in thickness ranging from 15 to 150 feet (5 to 45 m), and has a locally persistent coal associated with it. Above the Warner Sandstone is an unnamed shale unit which is dark gray, silty and fissile, and in northern LeFlore County ranges in thickness from 120 to 300 feet (37 to 92 m) (Knechtel, 1949). Siderite concretions are common, and a few thin sandstones can be found within it.

The Lequire Sandstone Member of the McAlester Formation overlies this unnamed shale. This unit includes two lenticular sandstone beds interbedded with siltstones and shales, and can include a thin local coal. In the Panama quadrangle it crops out around the Bokoshe syncline (Knechtel, 1949). The lower Lequire is present in the southern part of the quadrangle and pinches out to the north and west, and the upper Lequire sandstone is found in the north and pinches out to the south and west (Craney, 1978). Units between the Lequire and Keota Sandstone members are highly variable in thickness and lateral extent. They include two unnamed shale units and the Cameron and Tamaha

Sandstone members.

The Cameron Sandstone in the Panama area is a buff to gray, fine grained ripple-marked sandstone. It is exposed around the Bokoshe syncline and on the north side of the Cavanal syncline, where it forms prominent ridges (Knechtel, 1949). Overlying the Cameron is an unnamed gray shale unit with siderite concretions near the base and sandstone laminal throughout (Knechtel, 1949). This shale includes the Stigler (Lower McAlester) coal, which crops out in the south of the Panama quadrangle. Virtually no specific information was available for the Stigler coal in the study area, and it has not been evaluated in this report.

The Tamaha Sandstone member averages about 20 feet (6 m) thick in the area. In general, it is buff to gray, fine-grained, micaceous, cross-bedded and hard. Like the Cameron, the Tamaha Sandstone tends to be discontinuous. In the Panama quadrangle it crops out as rounded inconspicuous to prominent ridges (Knechtel, 1949). The Keota Sandstone Member, separated from the Tamaha by a fairly thick (200 feet, 61 m) unnamed dark gray shale unit, is the uppermost sand member of the McAlester Formation. It is generally a silty, buff, fine-grained sandstone, ranging from 30 to 70 feet (9 to 21 m) thick. A dark fissile to blocky shale with siderite concretions marks the top of the McAlester Formation.

The Savanna Formation crops out in the northeast corner and in the southernmost part of the Panama quadrangle (Knechtel, 1949). At least 63 feet (19m) of the lowest unnamed sandstone unit of the formation is exposed. This is overlain by about 200 feet (61 m) of shale in the south. These sandstone beds are generally brown, dense, fine-grained and micaceous, and the interbedded shales are brown to grayish green. The Savanna is the youngest formation

exposed in the Panama quadrangle.

Quaternary deposits of alluvium cover some stream valleys and flood plains in the area.

Structure

The Panama quadrangle lies within a zone of folded Pennsylvanian rocks characterized by broad, shallow synclines and narrow anticlines (Knechtel, 1949). The axes of these structures are commonly en echelon, and in general run parallel to the frontal margin of the adjacent Ouachita salient, marked by the Choctaw Fault. The principal surface structures in the Panama quadrangle are shown on Plate 1. These include the Milton anticline, the Bokoshe syncline, the Spiro anticline, the Coal Creek syncline, the Backbone anticline and the Backbone fault.

The Milton anticline passes through the northeast corner of the Panama quadrangle, exposing rocks of the Atoka Formation. The structure of the Milton anticline is essentially that of a great elongate asymmetrical dome, with the steeper limb on the southern side. It does, however, include a number of minor flexures and faults (Knechtel, 1949). A down-to-the-south normal fault interrupts the axis of the anticline in Secs. 13 and 23 of T. 9 N., R. 24 E., offsetting Atoka strata by about 400 feet (122 m) vertical displacement (Knechtel, 1949). Other normal faulting interrupts the Hartshorne Formation, and the outcrop of the Hartshorne coal, in Sec. 18 of T. 9 N., R. 25 E.

The Bokoshe syncline extends across the Panama quadrangle from west to northeast. The deepest part of the syncline occurs northeast of the quadrangle. The Hartshorne coal reaches a depth of about 1200 feet (366 m) in the Bokoshe syncline in the northeast corner of the quadrangle. On the north

limb of the syncline of the Hartshorne coal crops out as a single seam; south of the axial trace of the structure the Upper and Lower Hartshorne coals are found.

The Spiro anticline and Coal Creek syncline are parallel structures that extend approximately 1.5 miles (2.4 km) inside the eastern boundary of the quadrangle. Both are relatively minor flexures: the Coal Creek syncline is a shallow structural depression, and the Spiro anticline is a low, westward plunging structure exposing rocks of the McAlester Formation (Knechtel, 1949).

The Backbone anticline is a long (30 miles, 48 km) westward plunging structure terminating west of the Panama area in the Bokoshe quadrangle. The anticline is broken along its crest by the Backbone fault, along which rocks on the south side have been thrust upward more than 5000 feet (1525 m) (Knechtel, 1949). Near Panama there is a local sag in the structure, west of which is an elongate dome having an apex in Sec. 7 of T. 8 N., R. 25 E. (Knechtel, 1949).

Rocks of the Atoka Formation are the oldest exposed along the Backbone anticline. On the south limb of the structure and along most of the north limb, the Atoka is bordered by narrow belts of coal-bearing Hartshorne sandstone. Farther out on both sides are broad exposures of the McAlester Formations (Knechtel, 1949).

COAL GEOLOGY

Several major coal beds have been identified in the Panama quadrangle. They include in ascending order: the Hartshorne coal bed and its lower and upper splits; an unnamed local coal; and the Stigler (Lower McAlester) and

the Upper McAlester coal beds. Due to a lack of information on the latter, only the Hartshorne coals are mapped and discussed in detail in this report.

In the Panama quadrangle there is one measurement of an unnamed local coal that exceeds the Reserve Base thickness of 1 foot (0.3 m), in data point 70 (Plate 1). This has been treated as an isolated data point.

Hartshorne Coal Bed and Upper and Lower Splits

The Hartshorne coals occur at or near the top of the Hartshorne Sandstone Formation. The split line for the Hartshorne coal bed runs through the north half of the quadrangle. The split line is defined in this report as the 1-foot interburden line (Plate 6). North of this line only one coal seam is present; south of it the seam is split into Upper and Lower Hartshorne coals. The structure on these coals is presented on Plate 5, and the thickness of the interburden between the Upper and Lower Splits is shown on Plate 6. The interburden ranges from 1 foot at the split line to more than 100 feet (31 m).

Isopach maps for the Hartshorne coals are shown on Plate 4. The Hartshorne coal in the Panama quadrangle ranges from less than 2 feet (0.6 m) to almost 7 feet thick. Across most of the northern portion of the area it averages about 4 or 5 feet (1.2 to 1.5 m) thick. The Hartshorne coal has been mined along its cropline in the northwest corner of the quadrangle.

South of the split line the Upper Hartshorne coal varies from approximately 2 feet (0.6 m) thick to an anomalously thick measurement of 9.5 feet in Sec. 12, T. 8 N., R. 24 E. Local faulting may help to explain this.

The Lower Hartshorne varies from about 1 to 4.5 feet (0.3 to 1.4 m) thick. Both it and the Upper Hartshorne have been mined, particularly in the southern portion of the quadrangle.

Stigler (Lower McAlester) and Upper McAlester Coal Beds

Crop lines for the Stigler and Upper McAlester coals have been inferred in the southern part of the Panama quadrangle (Knechtel, 1949). However, no specific information on these coals in the study area was available, and they have not been mapped in this report.

Chemical Analyses of Coal

Chemical analyses were available for all three Hartshorne coals in this quadrangle. A summary of the analyses available is presented in Table 1. Average analyses are shown here, as well as the range for all samples used to calculate each average value.

The coals are classified according to fixed carbon (FC), as determined on a dry, mineral-matter-free (mmf) basis. The "as received" FC values shown on Table 1 were converted to dry mmf FC figures according to the following formula (American Society for Testing and Materials, 1980):

$$\text{Dry mmf FC} = \frac{\text{As rec'd FC} - 0.15 \text{ S}}{[100 - (\text{M} + 1.08 \text{ A} + 0.55 \text{ S})]} \times 100$$

where M = moisture, A = ash, S = sulfur

Based on the average FC shown on Table 1, all Hartshorne coals are classified as low volatile bituminous coals, with the Upper Hartshorne having an average 81% dry mmf fixed carbon, the Lower Hartshorne having an average 83% dry mmf fixed carbon, and the Hartshorne coal having an average 82% dry mmf fixed carbon.

Isolated Data Points

In instances where single or isolated measurements of coal beds thicker than 1.0 foot (0.3 m) are encountered, the standard criteria for construction

Table 1. Average chemical analyses for coals in the Panama quadrangle, LeFlore County, Oklahoma.

ANALYSIS	Hartshorne Coal Red			Upper Hartshorne Coal			Lower Hartshorne Coal			
	Form of Analysis	# of Samples	Average	Range	# of Samples	Average	Range	# of Samples	Average	Range
PROXIMATE										
Moisture	A	5	1.5	0.9-2.0	2	2.1	---	7	3.0	2.6-3.2
	A	5	17.3	16.6-19.0	2	18.0	17.2-18.8	7	16.7	15.9-18.3
Volatile Matter	C	3	16.6	15.7-17.3	1	18.0	---	5	17.2	16.5-18.8
	A	5	71.7	56.2-78.4	2	73.0	72.1-73.9	7	75.2	73.6-77.3
Fixed Carbon	C	3	75.7	74.1-77.9	1	75.0	---	5	76.7	74.0-79.3
	A	5	9.5	4.1-23.4	2	6.9	6.8-7.0	7	5.2	3.8-6.9
Ash	C	3	7.3	6.5-7.9	1	7.0	---	5	5.8	4.2-7.1
ULTIMATE										
	A	5	1.3	0.5-2.7	2	0.8	0.8	7	0.9	0.8-1.3
Sulfur	C	3	1.7	1.3-2.3	1	0.8	---	5	1.0	0.7-1.3
	A	2	4.2	---	1	4.2	---	1	4.8	---
Hydrogen	C	2	4.2	4.1-4.2	1	4.1	---	1	4.6	---
	A	2	81.3	81-81.5	1	82.8	---	1	84.0	---
Carbon	C	2	82.0	81.7-82.3	1	84.6	---	1	86.6	---
	A	2	1.7	---	1	1.9	---	1	1.7	---
Nitrogen	C	2	1.7	---	1	1.9	---	1	1.8	---
	A	2	3.8	---	1	3.5	---	1	4.6	---
Oxygen	C	2	3.1	3.0-3.1	1	1.6	---	1	2.0	---
HEATING VALUE										
	A	0	---	---	2	7847	7844-	7	7949	7760-8078
Calories	C	0	---	---	---	---	7850	1	8322	---
BTU/lb	A	5	13,477	10,811-14,694	---	14,125	14,120-	7	14,310	13,970-
					---	---	14,130	1	14,980	14,800

Form of Analysis: A = as received, C = moisture free.
 To convert Btu/lb to Kj/Kg, multiply by 2.326
 Source of data: Knechtel, (1949) and Craney (1978).

of isopach, structure contour, mining ratio, and overburden isopach maps are not available. The lack of data concerning these beds limits the extent to which they can be reasonably projected in any direction, and usually precludes their correlation with other, better known beds. For this reason, isolated data points have been mapped on separate figures for non-isopached coal beds. These figures are not included in this report, but are kept on file at the USGS office in Denver. However, coal reserves from these isolated data points are included in tables 2 and 3, and in the Reserve Base tonnages should on Plate 2.

The only isolated data point in the Panama quadrangle is a measurement of an unnamed local coal in data point 70 (see plate 1 for location).

COAL RESOURCES

Data from drill holes, mine measured sections, outcrops, well logs and mine maps were used to construct outcrop, isopach, and structure contour maps of the various coal beds in the Panama quadrangle (see below). The source of each indexed data point shown on Plate 1 is listed in Appendix I at the end of this report.

A system for classifying coal resources has been published by the U.S. Bureau of Mines and the U.S. Geological Survey, and published in U.S. Geological Survey Bulletin 1450-B (1976). Under this system, resources are classified as either Identified or Undiscovered. Identified Resources are specific bodies of coal whose location, rank, quality and quantity are known from geologic evidence supported by specific measurements, while Undiscovered Resources are bodies of coal which are thought to exist, based on broad geologic knowledge and theory.

Identified Resources may be subdivided into three categories of reliability of occurrence, according to their distance from a known point of coal-bed measurement. In order of decreasing reliability, these categories are: measured, indicated and inferred. Measured coal is that which is located within 0.25 mile (0.4 km) from a measurement point, indicated coal extends 0.5 mile (0.8 km) beyond measured coal to a distance of 0.75 mile (1.2 km) from the measurement point, and inferred coal extends 2.25 miles (3.6 km) beyond indicated coal, or a maximum distance of 3 miles (4.8 km) from the measurement point.

Undiscovered Resources may be either hypothetical or speculative. Hypothetical Resources are those undiscovered coal resources that may reasonably be expected to exist in known coal fields under known geologic conditions. They are located beyond the outer boundary of inferred resources (see above) in areas where the coal-bed continuity is assumed, based on geologic evidence. Hypothetical resources are those more than 3 miles (4.8 km) from the nearest measurement point. There are no hypothetical resources in this quadrangle.

Speculative resources are Undiscovered Resources that may occur in favorable areas where no discoveries have yet been made. Speculative resources have not been estimated in this report.

Coal resources for the Hartshorne coal and its upper and lower were calculated using data obtained from the coal isopach maps (Plate 4). The coal-bed acreage (measured by planimeter and calculated using the trapezoidal method [modified from Hollo and Fifadara, 1980]) multiplied by the average thickness of the coal bed, and by a conversion factor of 1800 short tons of coal per acre-foot (13,238 metric tons per hectare-meter) for bituminous coal yields the coal resources in short tons. Coal resource tonnages were

calculated for Identified Resources in measured, indicated, and inferred categories for unleased Federal coal lands. All coal beds thicker than 1 foot (0.305 m) that lie less than 3000 feet (914 m) below the ground surface are included in these calculations. These criteria differ from those stated in U.S. Geological Survey Bulletin 1450-B, which calls for a minimum thickness of 28 inches (70 cm) and a maximum depth of 1000 feet (305 m) for bituminous coal. Narrow strips between mines where undisturbed coal is less than 75 meters from the nearest mine are considered to have no reserves and are included within mined out areas. Mine boundaries are only approximately located (as stated in the legend on Plate 1) and therefore these narrow areas may in reality not even exist. For this reason they are considered to have no reserves, and have not been planimetered.

Reserve Base and Reserve tonnages for the above mentioned coal beds are shown on Plates 8 and 9 and have been rounded to the nearest 10,000 short tons (9,072 metric tons). In this report, Reserve Base coal is the gross amount of Identified Resources that occurs in beds 1 foot (0.3 m) or more thick and under less than 3,000 feet (914 m) of overburden. Reserves are the recoverable part of the Reserve Base coal. In the southeastern Oklahoma coal field, a recovery factor of 80 percent is applied toward surface-minable coal, and a recovery factor of 50 percent is applied toward subsurface-minable coal. No recovery factor is applicable for in-situ coal gasification methods.

The total tonnage per section for Reserve Base coal, including both surface and subsurface-minable coal, is shown in the northwest corner of the Federal coal land in each section on Plate 2. All values shown on Plate 2 are rounded to the nearest 10,000 short tons (9,072 metric tons), and total approximately 132.91 million short tons (120.58 million metric tons) for the entire

quadrangle, including tonnages in the isolated data points. Reserve Base and hypothetical tonnages from the various development potential categories for surface and subsurface mining and in-situ coal gasification methods are shown in tables 2 and 3.

The authors have not made any determination of economic recoverability for any of the coal beds described in this report.

COAL DEVELOPMENT POTENTIAL

Coal development potential areas are drawn to coincide with the boundaries of the smallest legal land subdivisions shown on Plate 2. In sections or parts of sections where no land subdivisions have been surveyed by the BLM, approximate 40-acre (16-hectare) parcels have been used to show to limits of the high, moderate, or low development potentials. A constraint imposed by the BLM specifies that the highest development potential affecting any part of a 40-acre (16-ha) lot, tract, or parcel be applied to that entire lot, tract, or parcel. For example, if 5 acres (2 hectare) within a parcel meet the criteria for a high development potential; 25 acres (10 hectare), a moderate development potential; and 10 acres (4 hectare), a low development potential; then the entire 40 acres (16 hectare) are assigned a high development potential. For purposes of this report, any lot or tract assigned a coal development potential contains coal in beds with a nominal minimum areal extent of 1 acre (0.4 hectare).

Development Potential for Surface Mining Methods

Areas where the coal beds of Reserve Base thickness are overlain by 150 feet (46 m) or less of overburden are considered to have potential for surface mining and are assigned a high, moderate, or low development potential

based on their mining ratios (cubic yards of overburden per ton of recoverable coal). The formula used to calculate mining ratios for surface mining of coal is as follows:

$$MR = \frac{t_o (cf)}{t_c (rf)} \quad \text{where MR} = \text{mining ratio}$$

t_o = thickness of overburden in feet
 t_c = thickness of coal in feet
rf = recovery factor (80 percent for this quadrangle)
cf = conversion factor to yield MR value in terms of cubic yards of overburden per short tons of recoverable coal:

0.896 for bituminous coal

Note: To convert mining ratio to cubic meters of overburden per metric ton of recoverable coal, multiply MR by 0.8428.

Areas of high, moderate, and low development potential for surface mining methods are defined as areas underlain by coal beds having respective mining ratio values of 0 to 10, 10 to 15, and greater than 15. These mining ratio values for each development potential category are based on economic and technological criteria and were provided by the U.S. Geological Survey.

Areas where the coal data are absent or extremely limited between the 150-foot (46 m) overburden line and the coal outcrop are assigned unknown development potential for surface mining methods. This applies to areas where coal beds 1.0 foot (0.305 m) or more thick are not known but may occur, and to those areas influenced by isolated data points. Limited knowledge pertaining to the areal distribution, thickness, depth and attitude of the coals in these areas prevents accurate evaluation of development potential in the high, moderate, or low categories. The areas influenced by isolated data points in this quadrangle contain no coal available

Table 2. Coal Reserve Base data for surface mining methods for Federal Coal Land (in short tons) in the Panama Quadrangle, Le Flore County, Oklahoma

Coal Bed or Coal Zone	High Development Potential	Moderate Development Potential	Low Development Potential	Unknown Development Potential	Total
Upper Hartshorne	550,000	200,000	3,480,000	---	4,230,000
Hartshorne	60,000	20,000	210,000	---	290,000
Lower Hartshorne	530,000	260,000	3,610,000	---	4,400,000
Isolated Data Points	---	---	---	---	---
Total	1,140,000	480,000	7,300,000	---	8,920,000

Table 3. Coal Reserve Base data for subsurface mining and in-situ gasification methods for Federal coal land (in short tons) in the Panama quadrangle, Le Flore, County, Oklahoma.

Coal Bed or Coal Zone	High Subsurface Development Potential	Moderate Subsurface Development Potential	Low Subsurface Development Potential	Low in-Situ Development Potential	Unknown Development Potential	Total
Upper Hartshorne	25,920,000	16,640,000	--	3,240,000	--	45,800,000
Hartshorne	580,000	25,170,000	--	2,040,000	--	27,790,000
Lower Hartshorne	27,200,000	20,140,000	--	2,830,000	--	50,170,000
Isolated Data Points	--	--	--	--	230,000	230,000
TOTAL	53,700	61,950,000	--	8,110,000	230,000	123,990,000

for surface mining.

The coal development potential for surface mining methods is shown on Plate 10. All tonnage values are summarized on Table 2. Of Federal coal land not subject to currently outstanding coal lease, permit, license or preference right lease application having a known development potential for surface mining, 10 percent is rated high, 1 percent is rated moderate, and 7 percent is rated low. The remaining Federal land (82 percent) are classified as having unknown or no development potential for surface mining methods.

Development Potential for Subsurface Mining and In-Situ Coal Gasification Methods

Areas considered to have a development potential for conventional subsurface mining methods are those areas where the coal beds of Reserve Base thickness are between 150 and 3,000 feet (46 to 914 m) below the ground surface and have dips of 15° or less. Unfaulted coal beds lying between 150 and 3,000 feet (46 and 914 m) below the ground surface, dipping greater than 15°, are considered to have a development potential for in-situ coal gasification methods.

Areas of high, moderate, and low development potential for conventional subsurface mining methods are defined as areas underlain by coal beds at depths ranging from 150 to 1,000 feet (46 to 305 m), 1,000 to 2,000 feet (305 to 610 m), and 2,000 and 3,000 feet (610 to 914 m), respectively.

Areas where the coal data are absent or extremely limited between 150 and 3,000 feet (46 to 914 m) below the ground surface are assigned unknown development potentials. This applies to areas where coal beds of Reserve Base thickness are not known, but may occur, and to those areas influenced by isolated data points. The areas influenced by isolated data points in this

quadrangle contain approximately 0.23 million short tons (0.21 million metric tons) of coal available for conventional subsurface mining.

The coal development potential for conventional subsurface mining or in-situ gasification methods is shown on plate 11. A summary of all tonnage values is presented on Table 3. Of Federal coal land areas having a known development potential for these mining methods, 56 percent is rated high, 36 percent is rated moderate, and none is rated low. Four percent of the remaining Federal land in the quadrangle is classified as having unknown or no development potential for either conventional subsurface mining or in-situ gasification methods.

Based on criteria provided by the U.S. Geological Survey, coal beds of Reserve Base thickness dipping between 15° and 35° , regardless of tonnage, have a low development potential for in-situ coal gasification methods. Beds dipping from 35° to 90° , with a minimum of 50 million tons of coal in a single unfaulted bed or multiple, closely spaced, approximately parallel beds have a moderate development potential for in-situ coal gasification methods. Coal lying between the 150-foot (46 m) overburden isopach and the outcrop is not included in total coal tonnages available because it is needed for cover and containment in the in-situ process.

In the Panama quadrangle, 14% of all Federal coal land has a low development potential for in-situ gasification methods. However, 70% of this land also has development potential for conventional subsurface mining methods. There is no land with a moderate development potential for in-situ gasification.

REFERENCES

- American Society for Testing and Materials, 1980, Gaseous fuels; coal and coke; atmospheric analyses: 1980 Annual Book of ASTM Standards, Part 26, p. 225-226.
- Branan, C.B. Jr., 1968, Natural gas in Arkoma Basin of Oklahoma and Arkansas; in Natural gases of North America, American Association of Petroleum Geologists Memoir 9, p. 1616-1635.
- Branson, C.C., 1962, Pennsylvanian System of the Mid-Continent, in C.C. Branson (ed.) Pennsylvanian System in the United States: American Association of Petroleum Geologists, Symposium, p. 431-460.
- Chance, H.M., 1890, Geology of the Choctaw coal field: American Institute of Mining Engineers, Transactions Vol. 18, p. 653-660.
- Drake, N.F., 1897, A geological reconnaissance of the coal fields of the Indian Territory: American Philosophical Society Proceedings, Vol. 36, p. 326-419.
- Donica, D.R., 1978, The geology of the Hartshorne coals (Desmoinesian) in parts of the Heavener 15' Quadrangle, LeFlore County, Oklahoma: M.S. thesis, Univ. of Oklahoma, 128 p.
- Friedman, S.A., 1974, An investigation of the coal reserves in the Ozarks section of Oklahoma and their potential uses: Ozarks Regional Commission Final Report, 117 p.
- _____ 1978, A field guidebook to Desmoinesian coal deposits in part of the Arkoma Basin, eastern Oklahoma: American Association of Petroleum Geologists, National Annual Meeting, Oklahoma City, Preconvention Field Trip 2, April 8-9, 1978, 62 p.
- Hendricks, T.A., 1939, Geology and fuel resources of the southern part of the Oklahoma coal field, part 4 - the Howe-Wilburton District, Latimer and LeFlore Counties: U.S. Geological Survey Bulletin 874-D, p. 254-300.
- Hollo, R. and Fifadara, H., 1980, TI-59 Reservoir Engineering Manual: Keplinger and Associates, Inc., Houston, 220 p.
- Johnson, K.S., 1971, Reclamation of mined coal lands in eastern Oklahoma: Oklahoma Geology Notes, v. 31, no. 6, Dec. 1971, p. 111-123.
- Knechtel, M.M., 1949, Geology and coal and natural gas resources of northern LeFlore County, Oklahoma: Oklahoma Geological Survey Bulletin 68, 76 p.
- McDaniel, G., 1961, Surface stratigraphy of the Hartshorne Formation, LeFlore, Latimer and Pittsburg Counties, Oklahoma, in Arkoma Basin and north-central Ouachita Mountains of Oklahoma, Tulsa-Ft. Smith Geological Societies Field Conference, 1961, Guidebook: Tulsa Geological Society, p. 66-71.

- Moose, J.E., and Searle, V.C., 1929, A chemical study of Oklahoma coals: Oklahoma Geological Survey Bulletin 51, 112 p.
- Oakes, M.C.; and Knechtel, M.M., 1948, Geology and mineral resources of Haskell County, Oklahoma: Oklahoma Geological Survey Bulletin 67, 136 p.
- Russell, Dearl T., 1960, Geology of northern Latimer County, Oklahoma: Oklahoma Geological Survey Circular 50, 57 p.
- Snider, L.C., 1914, Geology of east-central Oklahoma: Geological Survey Bulletin 17, 25 p.
- Taff, J.A., 1899, Geology of the McAlester-Lehigh coal field, Indian Territory: U.S. Geological Survey 19th Annual Report, Part 3, p. 423-456.
- _____ 1902, The southwestern coal field: U.S. Geological Survey 22nd Annual Report, Part 3, p. 367-413.
- _____ and Adams, G.I., 1900, Geology of the eastern Choctaw coal field, Indian Territory: U.S. Geological Survey 21st Annual Report, Part 2, p. 257-311.
- _____ 1905, Progress of coal work in Indian Territory: U.S. Geological Survey Bulletin 260, p. 382-401.
- Trumbull, James V.A., 1957, Coal resources of Oklahoma: U.S. Geological Survey Bulletin 1042-J, p. 307-382.
- United States Congress Documents, 1910, Coal lands in Oklahoma: 61st Congress, 2d Session, Senate Document 390, 374 p.
- Wilson, C.W., Jr., and Newell, N.D., 1937, Geology of the Muskogee-Porum District, Muskogee and McIntosh Counties, Oklahoma: Oklahoma Geological Survey Bulletin 57, 156 p.
- Zubovic, P., and others, 1967, Distribution of minor elements in some coals in the western and southwestern regions of the Interior coal province: U.S. Geological Survey Bulletin 1117-D, 33 p.

APPENDIX I. SOURCE AND RELIABILITY OF DATA USED ON PLATE 1.

Listed below is a point by point accounting as to the source and reliability of all information shown on Plate 1. Also presented are any notes or comments pertaining to individual data points.

DATA POINT #	LOCATION	INCREASING RELIABILITY					REFERENCE	NOTES/COMMENTS
		1	2	3	4	5		
1	NE SW	Location			x		Craney, 1978, plates 8 & 9 Bore Hole	
	Section 17	Overburden		x				
2	T 9 N R 25 E	Coal Thickness			x		Craney, 1978, plates 8 & 9 Bore Hole	
	Section 18	Overburden		x				
3	T 9 N R 25 E	Coal Thickness			x		Craney, 1978, plates 8 & 9 Bore Hole	
	Section 18	Overburden		x				
4	T 9 N R 25 E	Coal Thickness			x		Craney, 1978, plates 8 & 9 Bore Hole	Hartshorne faulted out.
	Section 18	Overburden		x				
5	T 9 N R 25 E	Coal Thickness			x		Craney, 1978, plates 8 & 9 Bore Hole	
	Section 18	Overburden		x				
6	T 9 N R 25 E	Coal Thickness			x		Craney, 1978, plates 8 & 9 Bore Hole	
	Section 18	Overburden		x				
7	T 9 N R 25 E	Coal Thickness			x		Craney, 1978, plates 8 & 9 Bore Hole	Hartshorne probably faulted
	Section 18	Overburden		x				
8	T 9 N R 25 E	Coal Thickness			x		Craney, 1978, column 1, plates 8 & 9, Bore Hole	
	Section 18	Overburden		x				
9	T 9 N R 25 E	Coal Thickness			x		Craney, 1978, plates 8 & 9	
	Section 18	Overburden		x				
10	T 9 N R 24 E	Coal Thickness			x		Knechtel, 1949, Bore Hole #8	
	Section 24	Overburden		x				
11	T 9 N R 24 E	Coal Thickness			x			
	Section 24	Overburden		x				

DATE POINT #	LOCATION	INCREASING RELIABILITY					REFERENCE	NOTES/COMMENTS
		1	2	3	4	5		
	SW SE Section 24	Location			x		Craney, 1978, plates 8 & 9 Bore Hole	
12	T 9 N R 24 E	Coal Thickness			x			
	SE SE Section 24	Location			x		Craney, 1978, plates 8 & 9 Bore Hole	
13	T 9 N R 24 E	Coal Thickness			x			
	NE SE Section 24	Location			x		Knechtel, 1949, Bore Hole #7	
14	T 9 N R 24 E	Coal Thickness			x			
	SE SE Section 24	Location			x		Craney, 1978, plates 8 & 9 Bore Hole	
15	T 9 N R 24 E	Coal Thickness			x			
	NE SE Section 24	Location			x		Craney, 1978, plates 8 & 9 Bore Hole	
16	T 9 N R 24 E	Coal Thickness			x			
	NW SW Section 19	Location			x		Knechtel, 1949, Bore Hole #3	
17	T 9 N R 25 E	Coal Thickness	x					
	SW NW Section 19	Location			x		Knechtel, 1949, Bore Hole #2	
18	T 9 N R 25 E	Coal Thickness			x			
	SW NW Section 19	Location			x		Craney, 1978, plates 8 & 9 Bore Hole	
19	T 9 N R 25 E	Coal Thickness			x			
	NW NW Section 19	Location			x		Knechtel, 1949, Bore Hole #1	
20	T 9 N R 25 E	Coal Thickness			x			
	SW NW Section 19	Location			x		Craney, 1978, plates 8 & 9 Bore Hole	
21	T 9 N R 25 E	Coal Thickness			x			
	NE SW Section 19	Location			x		Craney, 1978, plates 8 & 9 Bore Hole	
22	T 9 N R 25 E	Coal Thickness			x			
	NW NE Section 19	Location			x		Craney, 1978, p. 98, Bore Hole	
23	T 9 N R 25 E	Coal Thickness			x			
	NE SE Section 19	Location			x		Craney, 1978, plates 8 & 9 Bore Hole	
24	T 9 N R 25 E	Coal Thickness			x			

DATE POINT #	LOCATION	INCREASING RELIABILITY					REFERENCE	NOTES/COMMENTS
		1	2	3	4	5		
	SE SE	Location					Craney, 1978, plates 8 & 9	
	Section 19	Overburden	x				and column 3, plate 4, Bore Hole	
25	T 9 N R 25 E	Coal Thickness		x				
	N/2 NE SW	Location				x	Pan American Petroleum Corporation, 1962, #1 Zoe Holt	Ref. datum 17' above GL. IES, G & V logs.
26	T 9 N R 25 E	Coal Thickness	x					
	NW NE	Location				x	Craney, 1978 Map, plates 8 & 9, Bore Hole	
	Section 20	Overburden		x				
27	T 9 N R 25 E	Coal Thickness			x			
	NW SE	Location				x		
	Section 20	Overburden		x				
28	T 9 N R 25 E	Coal Thickness			x			
	NW SE	Location				x	Craney, 1978, plates 8 & 9 Bore Hole	
	Section 21	Overburden		x				
29	T 9 N R 25 E	Coal Thickness	x					
	E/2 E/2 E/2	Location				x		
	Section 21	Overburden		x				
30	T 9 N R 25 E	Coal Thickness			x			
	NE SE	Location				x		
	Section 22	Overburden				x	Craney, 1978, p. 99-100, Bore Hole	Location on logs calls for NE NE. Upper and lower Hartshorne benches.
31	T 9 N R 25 E	Coal Thickness				x		
	SW NW	Location				x		
	Section 26	Overburden		x			Craney, 1978, plates 8 & 9 and column 9, plate 2, Bore Hole	
32	T 9 N R 25 E	Coal Thickness			x			
	SW NW	Location				x		
	Section 27	Overburden		x			Craney, 1978, plates 8 & 9 and column 8, plate 2, Bore Hole	
33	T 9 N R 25 E	Coal Thickness			x			
	NW SW	Location				x		
	Section 28	Overburden		x			Craney, 1978, plate 2 column 7, plates 8 & 9, Bore Hole	
34	T 9 N R 25 E	Coal Thickness			x			
	SE NE	Location				x		
	Section 30	Overburden		x			Craney, 1978, plate 2 column 6, plate 4 column 4, plates 8 & 9, Bore Hole	
35	T 9 N R 25 E	Coal Thickness			x			
	NE SE	Location				x		
	Section 25	Overburden		x			Craney, 1978, plate 2 column 5, plates 8 & 9	
36	T 9 N R 24 E	Coal Thickness			x			
	NE NW	Location				x		
	Section 25	Overburden		x			Knechtel, 1949, Bore Hole #9	
37	T 9 N R 24 E	Coal Thickness			x			

DATA POINT #	LOCATION	INCREASING RELIABILITY					REFERENCE	NOTES/COMMENTS
		1	2	3	4	5		
38	NE NW	Location					USGS files, Bore Hole #76, 1978, KRCRA Map	Note: Crop line reported for coal-assume 1+ partial coal thickness. Also on KRCRA Map.
	Section 25	Overburden						
	T 9 N R 24 E	Coal Thickness	x					
39	NE NW	Location					Knechtel, 1949, Bore Hole #10	
	Section 25	Overburden						
	T 9 N R 24 E	Coal Thickness			x			
40	NE NW	Location					USGS files, Bore Hole #77, 1978, KRCRA Map	Upper bench thickness reported only.
	Section 25	Overburden						
	T 9 N R 24 E	Coal Thickness	x					
41	NW NW	Location					USGS files, Bore Hole #75, 1978, KRCRA Map	Upper and lower Hartshorne benches.
	Section 25	Overburden						
	T 9 N R 24 E	Coal Thickness			x			
42	-----	Location					Knechtel, 1949, Measured Section #11	
	Section 25	Overburden						
	T 9 N R 24 E	Coal Thickness			x			
43	SW NW	Location					Knechtel, 1949, Bore Hole #12	Upper and lower Hartshorne benches.
	Section 25	Overburden						
	T 9 N R 24 E	Coal Thickness			x			
44	SE NE	Location					USGS files, Bore Hole #85, 1978, KRCRA Map	
	Section 26	Overburden						
	T 9 N R 24 E	Coal Thickness			x			
45	SE NE	Location					USGS files, Bore Hole #86, 1978, KRCRA Map	
	Section 26	Overburden						
	T 9 N R 24 E	Coal Thickness			x			
46	SE NE	Location					USGS files, Bore Hole #87, 1978, KRCRA Map	Hit old mine at 57 ft.
	Section 26	Overburden						
	T 9 N R 24 E	Coal Thickness			x			
47	-----	Location					Knechtel, 1949, Measured Section #13	Upper and lower Hartshorne benches. Slope mine.
	Section 26	Overburden						
	T 9 N R 24 E	Coal Thickness			x			
48	SE NE	Location					USGS files, Bore Hole #84, 1978, KRCRA Map	
	Section 26	Overburden						
	T 9 N R 24 E	Coal Thickness			x			
49	SE NE	Location					Knechtel, 1949, Bore Hole #14	Upper and lower Hartshorne benches.
	Section 26	Overburden						
	T 9 N R 24 E	Coal Thickness			x			
50	SW NE	Location					Knechtel, 1949, Bore Hole #15	Upper and lower Hartshorne benches. Knechtel and KRCRA Map overburden don't agree.
	Section 26	Overburden						
	T 9 N R 24 E	Coal Thickness			x			

DATA POINT #	LOCATION	INCREASING RELIABILITY					REFERENCE	NOTES/COMMENTS
		1	2	3	4	5		
51	SW NE	Location		x			USGS files, Bore Hole #81, 1978, KRCRA Map	
	Section 26	Overburden		x				
	T 9 N R 24 E	Coal Thickness		x				
52	NW SE	Location		x		USGS files, Bore Hole #82, 1978, KRCRA Map		
	Section 26	Overburden		x				
	T 9 N R 24 E	Coal Thickness		x				
53	NW SE	Location		x		USGS files, Bore Hole #83, 1978, KRCRA Map		
	Section 26	Overburden		x				
	T 9 N R 24 E	Coal Thickness		x				
54	-----	Location		x		Knechtel, 1949, Measured Section #16	Slope mine.	
	Section 26	Overburden	-	-	-			
	T 9 N R 24 E	Coal Thickness		x				
55	NE SW	Location		x		Knechtel, 1949, Bore Hole #17	Upper and lower Hartshorne benches.	
	Section 26	Overburden		x				
	T 9 N R 24 E	Coal Thickness		x				
56	-----	Location		x		Knechtel, 1949, Measured Section #18	Upper and lower Hartshorne benches. Slope mine.	
	Section 26	Overburden	-	-	-			
	T 9 N R 24 E	Coal Thickness		x				
57	-----	Location		x		Knechtel, 1949, Measured Section #19	Slope mine.	
	Section 27	Overburden	-	-	-			
	T 9 N R 24 E	Coal Thickness		x				
58	NW NE	Location		x		Knechtel, 1949, Bore Hole #27		
	Section 34	Overburden		x				
	T 9 N R 24 E	Coal Thickness		x				
59	SE NE	Location		x		Crane, 1978, plate 2, column 2, plates 8 & 9, Bore Hole		
	Section 34	Overburden		x				
	T 9 N R 24 E	Coal Thickness		x				
60	SW NW	Location		x		Crane, 1978, plates 8 & 9 Bore Hole		
	Section 35	Overburden		x				
	T 9 N R 24 E	Coal Thickness		x				
61	NE SW	Location		x		Athletic Mining & Smelting Company, 1952, #1 Dunn	Ref. Datum 11.5 feet above GL. IES log.	
	Section 35	Overburden		x				
	T 9 N R 24 E	Coal Thickness	-	-	-			
62	S/2 NE	Location		x		Crane, 1978, plates 8 & 9 Bore Hole		
	Section 35	Overburden		x				
	T 9 N R 24 E	Coal Thickness		x				
63	NE NE	Location		x		USGS files, 1952, Bore Hole #19		
	Section 35	Overburden		x				
	T 9 N R 24 E	Coal Thickness		x				

DATA POINT #	LOCATION	INCREASING RELIABILITY	→					REFERENCE	NOTES/COMMENTS
			1	2	3	4	5		
	NE SE	Location							
	Section 35	Overburden		x				Craney, 1978, plates 5, 7, 8 & 9, Bore Hole	
64	T 9 N R 24 E	Coal Thickness			x				
	N/2 N/2	Location				x		USGS files, 1952, Bore Hole #22	Upper and lower Hartshorne benches.
	Section 36	Overburden				x			
65	T 9 N R 24 E	Coal Thickness							
	SE NW	Location					x	Snee & Eberly, 1963, #A-1	Ref. Datum 14' above GL.
	Section 31	Overburden			x			Dee King	IG & IES (SP through Hartshorne).
66	T 9 N R 25 E	Coal Thickness		x					
	SE SW	Location					x	USGS files, 1952, Bore Hole #20	
	Section 31	Overburden					x		
67	T 9 N R 25 E	Coal Thickness							
	NW SE	Location					x	Pan American Petroleum Corporation, 1960, #1 Dee King	Ref. Datum 16' above GL.
	Section 31	Overburden			x				IES, V, C logs
68	T 9 N R 25 E	Coal Thickness		x					
	SE NE	Location					x	Craney, 1978, plates 5, 7, 8 & 9, column 4, plate 4, Bore Hole	
	Section 31	Overburden			x				
69	T 9 N R 25 E	Coal Thickness					x		
	CNE SW	Location						Pan American Petroleum Corporation, 1966, #1 Bailey	Ref. Datum 18' above GL.
	Section 34	Overburden			x				IES - IG, D, C logs.
70	T 9 N R 25 E	Coal Thickness		x					
	SE SW	Location					x	BLM Emria Project, Bore Hole #DH-AB-11, 1979	Coal not reached.
	Section 4	Overburden					x		
71	T 8 N R 25 E	Coal Thickness		-	-	-	-		
	NE SW	Location					x	Craney, 1978, p. 93, Bore Hole	
	Section 5	Overburden					x		
72	T 8 N R 25 E	Coal Thickness							
	-----	Location					x	Knechtel, 1949, Measured Section #2	Slope mine.
	Section 5	Overburden		-	-	-	-		
73	T 8 N R 25 E	Coal Thickness					x		
	NW SE	Location					x	Senate Document #390, 1910 p. 69, Bore Hole #36	No workable coal, possible faulting. Shale-289' to 404'. Dip of strata 12°
	Section 1	Overburden					x		Ref. Datum 15' above GL.
74	T 8 N R 24 E	Coal Thickness							
	CSE	Location					x	Mustang Production Company 1972, #1-1 Turman	IG log.
	Section 1	Overburden					x		
75	T 8 N R 24 E	Coal Thickness		x					
	SE SW	Location						USGS files, 1952, Bore Hole #2	
	Section 1	Overburden					x		
76	T 8 N R 24 E	Coal Thickness							

DATA POINT #	LOCATION	INCREASING RELIABILITY	↑					REFERENCE	NOTES/COMMENTS
			1	2	3	4	5		
77	SE NW	Location						Pan American Petroleum Corporation, 1966, #1 "B" Tackett	Ref. Datum 16.5 above GL. IES, G & V logs.
	Section 1	Overburden			x				
	T 8 N R 24 E	Coal Thickness	x						
78	NE SW	Location						USGS files, 1952, Bore Hole #1	
	Section 1	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			
79	NW NW	Location						USGS files, 1952, Bore Hole #3	Near split line, yet interburden greater than 1'.
	Section 1	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			
80	NE NW	Location						Craney, 1978, plate 2, column 1, plates 8 & 9, Bore Hole	Coal thickness not reported in Craney thesis.
	Section 2	Overburden		x					
	T 8 N R 24 E	Coal Thickness			x				
81	NW SW	Location						USGS files, Bore Hole #41, KRCRA Map	
	Section 11	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			
82	NW SW	Location						USGS files, Bore Hole #46, 1978, KRCRA Map	
	Section 11	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			
83	NW SW	Location						USGS files, Bore Hole #40, 1978, KRCRA Map	
	Section 11	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			
84	NE SW	Location						USGS files, Bore Hole #45, 1978, KRCRA Map	Note: 62.4 TD reported on KRCRA Map.
	Section 11	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			
85	NE SW	Location						Knechtel, 1949, Bore Hole #13	
	Section 11	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			
86	NE SW	Location						Knechtel, 1949, Bore Hole #14	3 ft. 1 in. coal; dirty, reported.
	Section 11	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			
87	NE SW	Location						Knechtel, 1949, Bore Hole #15	
	Section 11	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			
88	NE SW	Location						USGS files, Bore Hole #47, 1978, KRCRA Map	
	Section 11	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			
89	NE SW	Location						USGS files, Bore Hole #42, 1978, KRCRA Map	Interburden 23.9' on KRCRA tables.
	Section 11	Overburden			x				
	T 8 N R 24 E	Coal Thickness				x			

DATE POINT #	LOCATION	INCREASING RELIABILITY				REFERENCE	NOTES/COMMENTS	
		1	2	3	4			
90	S/2 N/2	Location				USGS files, 1952, Bore Hole #11		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						
91	SW NE	Location				USGS files, Bore Hole #26, 1978, KRCRA Map		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness	x					
92	SW NE	Location				USGS files, Bore Hole #39, 1978, KRCRA Map		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						
93	-----	Location				Knechtel, 1949, Measured Slope, Mine Section #16		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						
94	NW SE	Location				Knechtel, 1949, Measured Section #17		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						
95	SW NE	Location				Knechtel, 1949, Bore Hole #19		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						
96	SW NE	Location				USGS files, Bore Hole 43, 1978, KRCRA Map		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						
97	SW NE	Location				Knechtel, 1949, Bore Hole #18		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						
98	SE NE	Location				USGS files, Bore Hole #38, 1978, KRCRA Map		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						
99	SE NE	Location				USGS files, Bore Hole #44, 1978, KRCRA Map		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						
100	NE NE	Location				USGS files, Bore Hole #24 1978, KRCRA Map		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness	x					
101	NE NE	Location				USGS files, 1952, Bore Hole #9		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						
102	SE NE	Location				Knechtel, 1949, Measured Section #20		
	Section 11	Overburden						
	T 8 N R 24 E	Coal Thickness						

DATE POINT #	LOCATION	INCREASING RELIABILITY					REFERENCE	NOTES/COMMENTS
		1	2	3	4	5		
	SW NW	Location	x				Knechtel, 1949, Bore Hole #21	
	Section 12	Overburden			x			
103	T 8 N R 24 E	Coal Thickness			x			
	NW NW	Location			x		USGS files, Bore Hole #51, 1978, KRCRA Map	
	Section 12	Overburden			x			
104	T 8 N R 24 E	Coal Thickness			x			
	NW NW	Location			x		BLM Emria Project, 1979, Bore Hole, DH-AB-13	Coal not reached.
	Section 12	Overburden			x			
105	T 8 N R 24 E	Coal Thickness	-	-	-	-		
	NW NW	Location			x		USGS files, Bore Hole #53, 1978, KRCRA Map	
	Section 12	Overburden			x			
106	T 8 N R 24 E	Coal Thickness			x			
	NW NW	Location			x		USGS files, Bore Hole #54, 1978, KRCRA Map	
	Section 12	Overburden			x			
107	T 8 N R 24 E	Coal Thickness			x			
	NW NW	Location			x		USGS files, Bore Hole #52, 1978, KRCRA Map	Coal not reached.
	Section 12	Overburden			x			
108	T 8 N R 24 E	Coal Thickness	-	-	-	-		
	NE NW	Location			x		Knechtel, 1949, Bore Hole #22	Coal thickness anomalously high.
	Section 12	Overburden			x			
109	T 8 N R 24 E	Coal Thickness	x					
	-----	Location			x		Knechtel, 1949, Measured Section #23	Slope mine.
	Section 12	Overburden			-	-		
110	T 8 N R 24 E	Coal Thickness			x			
	NE NW	Location			x		USGS files, Bore Hole #48, 1978, KRCRA Map	Coal thickness anomalously high.
	Section 12	Overburden			x			
111	T 8 N R 24 E	Coal Thickness	x					
	NW NE	Location			x		USGS files, 1952, Bore Hole #7	
	Section 12	Overburden			x			
112	T 8 N R 24 E	Coal Thickness			x			
	SW NE	Location			x		USGS files, Bore Hole #55, 1978, KRCRA Map	
	Section 9	Overburden			x			
113	T 8 N R 25 E	Coal Thickness			x			
	SW NE	Location			x		USGS files, Bore Hole #58, 1978, KRCRA Map	
	Section 9	Overburden			x			
114	T 8 N R 25 E	Coal Thickness			x			
	SW NE	Location			x		USGS files, Bore Hole #61, 1978, KRCRA Map	
	Section 9	Overburden			x			
115	T 8 N R 25 E	Coal Thickness			x			

DATE POINT #	LOCATION	INCREASING RELIABILITY	←					REFERENCE	NOTES/COMMENTS
			1	2	3	4	5		
116	SW NE	Location					USGS files, Bore Hole #60, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness							
117	SW NE	Location					USGS files, Bore Hole #56, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness							
118	SW NE	Location					USGS files, Bore Hole #63, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness							
119	SW NE	Location					USGS files, Bore Hole #62, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness	x						
120	SW NE	Location					USGS files, Bore Hole #65, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness							
121	SW NE	Location					USGS files, Bore Hole #64, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness							
122	SW NE	Location					USGS files, Bore Hole #59, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness	x						
123	SW NE	Location					USGS files, Bore Hole #66, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness	x						
124	SW NE	Location					USGS files, Bore Hole #57, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness							
125	SE NE	Location					USGS files, Bore Hole #67, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness	x						
126	SE NE	Location					USGS files, Bore Hole #68, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness	x						
127	SE NE	Location					Craney, 1978, plates 7, 8 & 9, Bore Hole		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness							
128	SE NE	Location					USGS files, Bore Hole #69, 1978, KRCRA Map		
	Section 9	Overburden							
	T 8 N R 25 E	Coal Thickness	x						

DATE POINT #	LOCATION	INCREASING RELIABILITY					REFERENCE	NOTES/COMMENTS
		1	2	3	4	5		
129	SW NW	Location					Craney, 1978, plates 8 & 9 Bore Hole	
	Section 12	Overburden		x				
	T 8 N R 25 E	Coal Thickness			x			
130	SW NW	Location					Oklahoma Department of Mines files, 1979-1980, Bore Hole	
	Section 12	Overburden				x		
	T 8 N R 25 E	Coal Thickness				x		
131	SE SE	Location					Knechtel, 1949, Bore Hole #8	
	Section 18	Overburden				x		
	T 8 N R 25 E	Coal Thickness				x		
132	SW SE	Location					Knechtel, 1949, Bore Hole #7	
	Section 18	Overburden				x		
	T 8 N R 25 E	Coal Thickness				x		
133	SE SW	Location					Knechtel, 1949, Bore Hole #5	
	Section 18	Overburden				x		
	T 8 N R 25 E	Coal Thickness				x		
134	SE SW	Location					Knechtel, 1949, Bore Hole #6	
	Section 18	Overburden				x		
	T 8 N R 25 E	Coal Thickness				x		
135	SW SW	Location					Knechtel, 1949, Bore Hole #3	
	Section 18	Overburden				x		
	T 8 N R 25 E	Coal Thickness				x		
136	SW SW	Location					Knechtel, 1949, Bore Hole #4	
	Section 18	Overburden				x		
	T 8 N R 25 E	Coal Thickness				x		
137	SE SE	Location					Knechtel, 1949, Bore Hole #25	
	Section 13	Overburden				x		
	T 8 N R 24 E	Coal Thickness				x		
138	SE SE	Location					Knechtel, 1949, Bore Hole #24	
	Section 13	Overburden				x		
	T 8 N R 24 E	Coal Thickness				x		
139	SE SW	Location					Knechtel, 1949, Bore Hole #27	
	Section 13	Overburden				x		
	T 8 N R 24 E	Coal Thickness				x		
140	SE SW	Location					Knechtel, 1949, Bore Hole #26	
	Section 13	Overburden				x		
	T 8 N R 24 E	Coal Thickness				x		
141	SW SW	Location					Knechtel, 1949, Bore Hole #28	
	Section 13	Overburden				x		
	T 8 N R 24 E	Coal Thickness				x		

DATA POINT #	LOCATION	INCREASING RELIABILITY	↑					REFERENCE	NOTES/COMMENTS
			1	2	3	4	5		
142	SW SW	Location						Knechtel, 1949, Bore Hole #29	
	Section 13	Overburden							
	T 8 N R 24 E	Coal Thickness							
143	SW SE	Location						Knechtel, 1949, Bore Hole #30	
	Section 14	Overburden							
	T 8 N R 24 E	Coal Thickness							
144	SE SW	Location						Knechtel, 1949, Bore Hole #14	
	Section 14	Overburden							
	T 8 N R 24 E	Coal Thickness							
145	SW SW	Location						Knechtel, 1949, Bore Hole #32	
	Section 14	Overburden							
	T 8 N R 24 E	Coal Thickness							
146	NW NW	Location						Knechtel, 1949, Bore Hole #55	Cover not recorded.
	Section 23	Overburden							
	T 8 N R 24 E	Coal Thickness							
147	NE NW	Location						Knechtel, 1949, Bore Hole #56	
	Section 23	Overburden							
	T 8 N R 24 E	Coal Thickness							
148	NW NE	Location						Knechtel, 1949, Bore Hole #57	
	Section 23	Overburden							
	T 8 N R 24 E	Coal Thickness							
149	NE NE	Location						Knechtel, 1949, Bore Hole #58	
	Section 23	Overburden							
	T 8 N R 24 E	Coal Thickness							
150	NW SE	Location						USGS files, 1952, Bore Hole #H-1	
	Section 23	Overburden							
	T 8 N R 24 E	Coal Thickness							
151	NW SE	Location						Pan American Petroleum Corporation, 1965, #1 "D" Johnson	Ref. Datum 18.5' above GL. IES, C & V logs.
	Section 24	Overburden							
	T 8 N R 24 E	Coal Thickness							
152	N/2 N/2	Location						Senate Document #390, 1910 p. 67, Bore Hole #30	Last 6.2' contained a few thin coal seams. Dip of strata 120
	Section 19	Overburden							
	T 8 N R 25 E	Coal Thickness							
153	NW NE	Location						Knechtel, 1949, Bore Hole #9	
	Section 19	Overburden							
	T 8 N R 25 E	Coal Thickness							
154	-----	Location						Knechtel, 1949, Measured Section #11, Slope Mine.	Coal; top only of LH un-covered.
	Section 19	Overburden							
	T 8 N R 25 E	Coal Thickness							

DATA POINT #	LOCATION	INCREASING RELIABILITY	↑					REFERENCE	NOTES/COMMENTS
			1	2	3	4	5		
155	NW NW	Location		x			Knechtel, 1949, Bore Hole #12		
	Section 20	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
156	NW NW	Location		x			Knechtel, 1949, Bore Hole #13		
	Section 20	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
157	NE NW	Location		x			Knechtel, 1949, Bore Hole #14	Coal; dirty.	
	Section 20	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
158	NE SW	Location				x	Midwest Oil Corporation, 1974, #1 Rust	Ref. Datum 17' above GL. Gamma log (thru casing).	
	Section 20	Overburden				x			
	T 8 N R 25 E	Coal Thickness		x					
159	NW NE	Location		x			Knechtel, 1949, Bore Hole #15		
	Section 20	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
160	NE NE	Location		x			Knechtel, 1949, Bore Hole #15		
	Section 20	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
161	NE NE	Location		x			Knechtel, 1949, Bore Hole #17		
	Section 20	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
162	SE NE	Location				x	Craney, 1978, plates 8 & 9 Bore Hole		
	Section 21	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
163	SE NE	Location				x	Craney, 1978, plates 5 & 6 Bore Hole		
	Section 21	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
164	SE NW	Location				x	Craney, 1978, plates 5 & 6 Bore Hole		
	Section 22	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
165	SE NW	Location				x	Craney, 1978, plate 9, plate 3 column 6, Bore Hole		
	Section 22	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
166	SE NE	Location		x			Knechtel, 1949, Bore Hole #18		
	Section 22	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					
167	SE NE	Location		x			Knechtel, 1949, Bore Hole #19		
	Section 22	Overburden		x					
	T 8 N R 25 E	Coal Thickness		x					

DATE POINT #	LOCATION	INCREASING RELIABILITY	↑					REFERENCE	NOTES/COMMENTS
			1	2	3	4	5		
	SW NW	Location			x			Knechtel, 1949, Bore Hole #20	
	Section 23	Overburden			x				
168	T 8 N R 25 E	Coal Thickness			x				
	NW SW	Location			x			Knechtel, 1949, Bore Hole #21	
	Section 23	Overburden			x				
169	T 8 N R 25 E	Coal Thickness			x				
	NE SW	Location			x			Knechtel, 1949, Bore Hole #22	
	Section 23	Overburden			x				
170	T 8 N R 25 E	Coal Thickness			x				
	NE SW	Location			x			Knechtel, 1949, Bore Hole #23	Coal with a little dirt.
	Section 23	Overburden			x				
171	T 8 N R 25 E	Coal Thickness			x				
	SE SW	Location			x			Oklahoma Dept. of Mines files, 1978-1979, Bore Hole G-6	
	Section 23	Overburden			x				
172	T 8 N R 25 E	Coal Thickness			x				
	NE SW	Location			x			Oklahoma Dept. of Mines files, 1978-1979, Bore Hole G-4	
	Section 23	Overburden			x				
173	T 8 N R 25 E	Coal Thickness			x				
	NW SE	Location			x			Knechtel, 1949, Bore Hole #24	
	Section 23	Overburden			x				
174	T 8 N R 25 E	Coal Thickness			x				
	NE SE	Location			x			Senate Document #390, 1910 p. 66, Bore Hole #27	Stop in very hard ss causing great wear to diamond drill. Dip of strata 14°.
	Section 23	Overburden			x				
175	T 8 N R 25 E	Coal Thickness			x				
	NW SE	Location			x			Knechtel, 1949, Bore Hole #26	
	Section 23	Overburden			x				
176	T 8 N R 25 E	Coal Thickness			x				
	SW SE	Location			x			Craney, 1978, plates 5, 7, 8 & 9, Bore Hole	
	Section 23	Overburden			x				
177	T 8 N R 25 E	Coal Thickness			x				
	SE SE	Location			x			Oklahoma Dept. of Mines files, 1978-1979, Bore Hole G-1	
	Section 23	Overburden			x				
178	T 8 N R 25 E	Coal Thickness			x				
	SE SE	Location			x			Oklahoma Dept. of Mines files, 1978-1979, Bore Hole G-2	
	Section 23	Overburden			x				
179	T 8 N R 25 E	Coal Thickness			x				
	NE SE	Location			x			Knechtel, 1949, Bore Hole #27	
	Section 23	Overburden			x				
180	T 8 N R 25 E	Coal Thickness			x				

DATA POINT #	LOCATION	INCREASING RELIABILITY	→					REFERENCE	NOTES/COMMENTS
			1	2	3	4	5		
	NE SE	Location							
	Section 23	Overburden							
181	T 8 N R 25 E	Coal Thickness						Knechtel, 1949, Bore Hole #28	
	NW SW	Location							
	Section 24	Overburden							
182	T 8 N R 25 E	Coal Thickness						Knechtel, 1949, Bore Hole #30	
	NW SW	Location							
	Section 24	Overburden							
183	T 8 N R 25 E	Coal Thickness						Knechtel, 1949, Bore Hole #29	
	SW SW	Location							
	Section 24	Overburden						Oklahoma Dept. of Mines files, 1978-1979, Bore Hole #p-4	
184	T 8 N R 25 E	Coal Thickness						Craney, 1978 Map, plates 5, 7, 8 & 9, Bore Hole	
	NW SW	Location							
	Section 24	Overburden							
185	T 8 N R 25 E	Coal Thickness							
	SE NE	Location							
	Section 26	Overburden						Oklahoma Dept. of Mines files, 1978-1979, Bore Hole G-3	
186	T 8 N R 25 E	Coal Thickness						Oklahoma Dept. of Mines files, 1978, 1979, Bore Hole G-10	
	SE SE	Location							
	Section 26	Overburden							
187	T 8 N R 25 E	Coal Thickness						Craney, 1978, p. 94-95, Bore Hole	
	SE SE	Location							
	Section 26	Overburden							
188	T 8 N R 25 E	Coal Thickness							
	SW SE	Location							
	Section 26	Overburden						Oklahoma Dept. of Mines files, 1978-1979, Bore Hole G-8	
189	T 8 N R 25 E	Coal Thickness							
	SE NW	Location							
	Section 26	Overburden						Oklahoma Dept. of Mines files, 1978-1979, Bore Hole G-7	No coal reported for LH - seam thickness could not be verified.
190	T 8 N R 25 E	Coal Thickness							
	NW NE	Location							
	Section 26	Overburden						Oklahoma Dept. of Mines files, 1978-1979, Bore Hole G-9	
191	T 8 N R 25 E	Coal Thickness							
	S/2 NW	Location							
	Section 28	Overburden						Eberly & Meade, 1978, #1-28 Butler	Ref. datum 14' above GL. IES log.
192	T 8 N R 25 E	Coal Thickness							
	SE NE	Location							
	Section 30	Overburden						Craney, 1978 map, plate 9, plate 3, column 5, Bore Hole	
193	T 8 N R 25 E	Coal Thickness							

DATE POINT #	LOCATION	INCREASING RELIABILITY					REFERENCE	NOTES/COMMENTS
		1	2	3	4	5		
194	NW NE						Craney, 1978, p. 92, Bore Hole	2300' W 1300' S of NE corner.
	Section 25							
	T 8 N R 24 E							
195	NE SW						Monsanto Company, 1969, #1 Holeton	Ref. datum 15' above GL. IG log.
	Section 26							
	T 8 N R 24 E							
196	SE NW						Pan American Petroleum Corporation, 1967, #1 Masters	Ref. datum 17.8 above GL. IG log.
	Section 35							
	T 8 N R 24 E							
197	SW NE						Pan American Petroleum Corporation, 1965, #1 Davidson	Ref. datum 18' above GL. IES, G & V logs.
	Section 35							
	T 8 N R 25 E							

APPENDIX II TABLES OF OIL AND GAS TEST HOLES

Note: "Top Log Int." refers to the measured depth to the top of the interval logged by the particular sonde. Driller log total depth, referenced to K.B. or D.F., has been abbreviated to T.D. (Note: This may vary from T.D. referenced to G.L.). The measured depth at which coal is reported on the scout card appears in the column titled "Scout Card Coal". The column titled "Harts./Drill./Scout" contains the measured depths drilled to the top of the Hartshorne Sandstone, as reported by the driller logs and the scout cards.

* Logged interval stratigraphically below Hartshorne Coals.

Sec-Tn-Rg	Operator/Farm Location	Driller Logs Coal Reported Thickness & Depth	Scout Card Coal	Harts.		Top Log Int.		T.D. Year
				Drill.	Scout	Gamma Elec.	Dens. Sonic	
1-8-24	Pan Am./Tackett "B" 560 FSL 660 FEL of NW/4	C. int. 75-132 C. int. 1063-1186	NR	NR	1605	381	381	11130 1966
1-8-24	Mustang/#1-1 Turman CSE	NR	NR	NR	NR	529	529	7513 1972
2-8-24	Reserve/#2-1 H. Wegert CSE	NR	NR	NR	NR	NR	NR	7730 1979
11-8-24	Mustang/#1-11 J. D. Blair CSE SE NW	NR	NR	NR	NR	NR	NR	7000 1978
12-8-24	Mustang/#1-12 Redwine CNE	NR	NR	NR	NR	500	500	3200 1976
13-8-24	Mustang/#1-13 J. Daniel CNE	NR	NR	NR	NR	NR	NR	6600 1977
14-8-24	Mustang/#1-14 Chitwood CNE	NR	NR	NR	NR	NR	NR	10302 1973
22-8-24	Getty Reserve Oil/#1-22 Couch CSE	NR	NR	NR	NR	NR	NR	7600 1979
23-8-24	Montgomery/#1-23 Wiles C E/2 SE SW	NR	NR	988	988	950	950	6800 1979
24-8-24	Pan Am./#1 Johnson "D" C NW SE	NR	NR	NR	NR	57	57	9450 1965
26-8-26	Monsanto/#1 Holten 1933 FSL 1933 FWL	NR	NR	NR	NR	100	100	4800 7400
35-8-25	Dyco/#1 Helton CNW NW	NR	NR	2262	2262	700	700	1969 8100
35-8-25	Pan Am./#1 Masters	NR	NR	NR	NR	100	100	7892 8200
		NR	NR	2540	2540	100	100	1967

Sec-In-Rg	Operator/Farm Location	Driller Logs Coal Reported Thickness & Depth	Scout		Harts.		Top Log		Int. Dens.	T.D. Year
			Card Coal	Coal	Drill. Scout	Scout	Gamma Elec.	Sonic		
4-8-25	Snee & Eberly/Standler #1 1520 FSL 1565 FWL of SE/4	NR	NR	NR	NR	NR	NR	NR	NR	8226
5-8-25	LeFlore Gas & El./#4 McCallip CSE SE		NR	NR	NR	NR	NR	NR	NR	1977
5-8-25	Mustang/#1-5 D. Turman 2417 FSL 1320 FWL	NR	NR	NR	NR	NR	NR	NR	NR	2621
6-8-25	Galaxy I.A./#1 Daniel 2690 FSL 2465 FWL	NR	NR	NR	NR	NR	NR	NR	NR	1940
7-8-25	LeFlore Co./#P-5 Redwine WC NW SW SE	NR	NR	NR	NR	NR	NR	NR	NR	6350
7-8-25	Galaxy, I.A./#1 Redwine 100 FNL 1800 FWL	NR	NR	NR	NR	NR	NR	NR	NR	1973
8-8-25	LeFlore O & G/#2 Hickman C S/2 S/2	NR	NR	NR	NR	NR	NR	NR	NR	9675
8-8-25	LeFlore O & G/#1 Hickman NE NE SE		NR	NR	NR	NR	NR	NR	NR	1970
8-8-25	Hamon/#1 E. Hickman 1240 FSL 1400 FWL of SE/4	NR	NR	NR	NR	NR	NR	NR	NR	7000
8-8-25	Mustang/#1-8 Goins CNW	NR	NR	NR	NR	NR	NR	NR	NR	1970
9-8-25	LeFlore/Mosley #3 C S/2 S/2 N/2 N/2 SW		NR	NR	NR	NR	NR	NR	NR	2340
11-8-25	Stephens/# J. C. Sadler NE SW SW NE	NR	NR	NR	NR	NR	NR	NR	NR	1939
17-8-25	Athletic M & S/#1 Hickman 3940 FSL 1320 FWL		NR	NR	NR	NR	NR	NR	NR	5972
18-8-25	Mustang/#1-18 Kennedy CSW	NR	NR	NR	NR	NR	NR	NR	NR	1940
20-8-25	Midwest/#1 Rust NE SE NE SW	NR	NR	NR	NR	NR	NR	NR	NR	9068
21-8-25	Eberly & Meade/#1-21 Long CNE	NR	NR	NR	NR	NR	NR	NR	NR	1972
23-8-25	Pan Am./#1 Parks SW SW NE	NR	NR	NR	NR	NR	NR	NR	NR	7650
23-8-25	Wagner & Brown/#1-23 Cannon 100 FSL 330 FWL of NE/4	NR	NR	NR	NR	NR	NR	NR	NR	1952

Sec-Tn-Rg	Operator/Farm Location	Driller Logs Coal Reported Thickness & Depth	Scout		Harts. Top Log Int.			T.D. Year
			Card Coal	Scout	Drill. Scout	Gamma Elec.	Dens. Sonic	
26-8-25	Unit Drilling/#1 Johnson 2440 FSL 1320 FWL of SE/4	NR	NR	1888	1888			7574
28-8-25	Eberly & Meade/#1-28 Butler C S/2 NW	NR	NR	1365	1365	867		11292
22-9-24	Western Okla./#1 Bryn SW NW SE	NR	NR	NR	NR	F		5550
23-9-24	Western Okla./#1 Statham SE NE NE					E		5520
23-9-24	Fed. Bank Oil Co./Fee #1 SE SW NW					B		6300
24-9-24	Stephens/#1 L. G. Stroud 3540 FSL 2740 FWL	NR	NR	NR	NR	B		4965
25-9-24	Monsanto/#1 Cragon CNE SE SW	NR	NR	NR	NR	1305		5801
25-9-24	An-Son/#1 Woods CSE/4	NR	NR	1105	NR	1305	2900B	1970
26-9-24	Galaxy & I.A./#1 Fesperman 1370 FSL 1456 FEL of SE/4	NR	NR	NR	NR	1300B		6345
27-9-24	Ark. Okla./#1 G. D. Cloud SE SE NW	NR	NR	NR	NR	135B		1971
27-9-24	Western Okla./#1 Ward NW SE NW							5074
19-9-25	Whitmar Expl./Evans Coal							1970
19-9-25	Snee & Eberly/#1 R.L. White SE NW SE		NR	400900	NR	1046*	1350*	6800
20-9-25	Pan Am./#1 Zoeholt C N/2 NE SW		NR	NR	NR	524		1970
21-9-25	Pan Amer./#1 Garrett SW SW NE	NR	NR	NR	NR	524	524	8342
30-9-25	Tenneco/#1-30 L. J. Woods CSW	NR	NR	NR	NR	650	7000	1963
31-9-25	Pan Am./#1 D. King CNW SE	NR	NR	NR	NR	650	650	7600
31-9-25	Snee & Eberly/#1-A. D. King CSE NE	NR	NR	NR	NR			1965
				NR	NR			6540
				NR	NR			1971
				NR	NR			9872
				NR	NR	223	223	1961
				1048	NR	343		6820
				1047	NR	343		1963

Sec-In-Rg	Operator/Farm Location	Driller Logs Coal Reported Thickness & Depth	Scout		Harts.			Top Log Int.			T.D. Year
			Card	Coal	Drill.	Scout	Gamma	Elec.	Dens.	Sonic	
31-9-25	Galaxy/#1 Chapple SW SE NE SW	NR	NR	NR	NR	1350				6785	1972
32-9-25	Galaxy/#1 Wood NE NE SW SW	NR	NR	NR	NR					7000	1970
33-9-25	Galaxy/#1 Avery 936 FSL 100 FWL of NE/4	NR	NR	NR	NR					9231	1969
34-9-25	Pan Am./#1 Baily CNE SW	NR	NR	NR	NR	60	60	392		8625	1966
35-9-25	LeFlore 0 & G/#1 Wilson C N/2 NW	NR	1079	1087	1087					2986	1946