

repared in cooperation with the

27°45' \_\_\_

EXPLANATION Altitude of top of Floridan aquifer, in feet below mean sea level. Contour interval 20 feet. U.S. Geological Survey test well. Number is last three O 002 (TW-27-75) digits of local well number (sheet 1). Letter-number combination in parentheses is field or agency identifier; final two digits denote year drilled. Corps of Engineers test hole. Letter-number combination in O01(C26-8-54) parentheses is field or agency identifier; final two digits denote year drilled. Observation well Test hole Destroyed Note: The overlay shows altitude of top of Floridan aquifer and is based on the shallowest known occurrence of limestones of Eocene age. The contours were originally defined in 1953 (Neill, 1955), and refined in 1955-57 (Brown and others, 1962a) and 1974-76 (references, sheets 2 and 3).

## GEOHYDROLOGY

The Brevard County portion of the Fellsmere quadrangle consists of pine-palmetto flatwoods on the generally higher areas; agricultural lands, with citrus groves on the better drained areas; and scrub lowlands with many marsh areas. Surface drainage is through the swamps and constructed drainage outlets which ultimately drain the higher areas to the Indian River or the St. Johns River.

Ground water occurs under nonartesian and artesian conditions. Nonartesian conditions occur where the upper surface of the zone of saturation (water table) is free to rise and fall in direct response to local rainfall (recharge) and to discharge. Artesian conditions occur where the water in an aquifer is confined by a bed of less permeable material and will rise in a tightly cased well above the base of the confining bed. The level to which the water will rise defines the altitude of the aquifer's potentiometric surface at that location. If the potentiometric surface is above land surface, the well will flow (sheet 3). Water-level measurements in many artesian wells are used to define the configuration of the potentiometric surface over broad areas (sheet 3).

Unconsolidated sediments of Holocene,
Pleistocene, and late Miocene age constitute
the nonartesian (shallow) aquifer. These
sediments lie above the consolidated limestone
formations of Eocene age known as the Floridan
aquifer. The altitude of the top of the
Floridan aquifer is shown on sheet 2. The
middle Miocene deposits (Hawthorn Formation)
overlie and tend to confine the Floridan aquifer.
Where the confining beds are discontinuous and
limestones of Miocene age are present, there is
usually a hydraulic connection between the middle
Miocene and the Eocene deposits.

Most of the Brevard County portion of the quadrangle is an area of artesian flow for the Floridan aquifer (sheet 3), and this aquifer contains water with chloride concentrations in excess of 300 mg/L throughout the area (sheet 4). Quality of water in the shallow aquifer is not known, as this aquifer is not utilized. Water use, primarily for agricultural purposes, is from the Floridan aquifer.

## SELECTED REFERENCES


This report is 1 of 29 similar map reports prepared on the 7½-minute topographic quadrangle base to cover all of Brevard County (see index, sheet 1). A complete list of references used in preparation of the 29 reports is given below. Individual abbreviated references are noted on the various sheets, as applicable; the user may refer to the following list to obtain the formal reference.

Anderson, K. E., ed., 1973, Water well handbook:
Missouri Water Well and Pump Contractors
Association, 80 p.

Bostwick, Inc., 1950, Analysis and recommendations for the improvement of the water supply, City of Titusville, Florida: Bostwick, Inc., Daytona Beach, Florida, 52 p.

Brown, D. W., Kenner, W. E., and Brown, Eugene, 1957, Interim report on the water resources of Brevard County, Florida: Florida Geological Survey Information Circular 11, 111 p.

Brown, D. W., Kenner, W. E., Crooks, J. W., and Foster, J. B., 1962a, Water resources of Brevard County, Florida: Florida Geological Survey Report of Investigation 28, 104 p.



1962b, Water resources records for Brevard
County, Florida: Florida Geological Survey
Information Circular 32, 180 p.

Crain, L. J., Hughes, G. H., and Snell, L. J., 1975, Water resources of Indian River County, Florida: Florida Bureau of Geology Report of Investigation 80, 75 p.

Florida Department of Natural Resources, 1970, Florida water and related land resources, St. Johns River basin: Florida Department of Natural Resources, 205 p.

Healy, H. G., 1971, Water levels in artesian and nonartesian aquifers of Florida, 1967-68:
Florida Bureau of Geology Information
Circular 68, 61 p.

Knochenmus, D. D., and Beard, M. E., 1971, Evaluation of the quantity and quality of the water resources of Volusia County, Florida: Florida Bureau of Geology Report of Investigation 57, 59 p.

Laughlin, C. P., 1976, Potentiometric surface map of the Floridan aquifer in east-central Florida, May 1976: U.S. Geological Survey Open-File Report 76-813.

Lichtler, W. F., and Anderson, Warren, 1968,
Water resources of Orange County, Florida:
Florida Geological Survey Report of
Investigation 50, 150 p.

(Selected References continued to sheet 3.)

OVERLAY MAP OF THE FELLSMERE QUADRANGLE, FLORIDA; ALTITUDE OF TOP OF FLORIDAN AQUIFER AND LOCATIONS OF WELLS
FOR WHICH GEOLOGIC DATA ARE AVAILABLE

