



EXPLANATION

- 10 ————
- 11 ————
- ISOPACHS - Showing thickness of coal, in feet. Long dashed where inferred; short dashed where projected beyond coal-bearing area. Isopach interval 1 foot.
- 5.0
- DRILL HOLE - Showing thickness of coal, in feet.
- ▲ 7.6
- POINT OF MEASUREMENT - Showing thickness of coal, in feet. Includes all points of measurement other than drill holes.
- 10.2/2.9
- INTERBEDDED COAL AND ROCK - Showing total coal thickness/total rock thickness.
- BR - Bear River
- COAL BED SYMBOL AND NAME
- ▲-----BR-----
- TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Arrow points toward coal-bearing area. Short dashed where inferred by present authors.
- TRACE OF FAULT - Bar and ball on downthrown side when direction of movement is known. Dashed where inferred or approximately located.
- COAL STRIP MINE - Hachures point toward mined area. Dashed where approximately located.
- To convert feet to meters, multiply feet by 0.3048.

Base from U.S. Geological Survey, 1971

UTM GRID AND 1971 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

SCALE 1:24,000

1 MILE / 1 KILOMETER

QUADRANGLE LOCATION

Compiled in 1977/1978

COAL RESOURCE OCCURRENCE MAP OF THE MILNER QUADRANGLE, ROUTT COUNTY, COLORADO
BY DAMES & MOORE 1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.