


EXPLANATION

- 10
 9
ISOPACHS—Showing thickness of coal, in feet. Long dashed where inferred, short dashed where projected above land surface. Isopach interval 1 foot.
- 9.6
○
DRILL HOLE—Showing thickness of coal, in feet. Drill holes which do not intersect the coal or from which a coal thickness could not be determined are not shown.
- 14.3
▶
POINT OF MEASUREMENT—Showing thickness of coal, in feet. Includes all points of measurement other than drill holes.
- SL
TRACE OF COAL BED OUTCROP—Showing symbol of name of coal bed. Arrow points toward coal-bearing area.
- BURNED AND CLINKERED COAL BED—Showing area of baked and fused rock (v symbol). Dotted line indicates the inferred limit of burning.
- INSUFFICIENT DATA LINE—Coal thickness cannot be determined beyond line shown because of insufficient data.
- FAULT—Dashed where approximately located; bar and ball on downthrown side where direction of movement is known.
- UNDERGROUND COAL MINE—Hachures point to mined-out area. Dashed where approximately located.

To convert feet to meters, multiply feet by 0.3048



COAL RESOURCE OCCURRENCE MAP OF THE NORTHEAST QUARTER OF THE
WOODSIDE 15-MINUTE QUADRANGLE, EMERY AND CARBON COUNTIES, UTAH

BY
AAA ENGINEERING AND DRAFTING, INC.

1979

PLATE 4
ISOPACH MAP
OF THE
LOWER SUNNYSIDE
COAL BED