

EXPLANATION

— 7750 —

STRUCTURE CONTOURS—Drawn on top of coal bed. Solid where vertical accuracy within 25 feet; long dashed where vertical accuracy possibly not within 25 feet; short dashed where projected above land surface. Contour interval is 50 feet (15.2 m). Datum is mean sea level.

▲
7788

POINT OF MEASUREMENT—Showing altitude of top of coal bed, in feet.

— BC —

TRACE OF COAL BED OUTCROP—Showing symbol of name of coal bed. Arrow points toward coal-bearing area. Dashed where inferred by present authors.


— | —

FAULT—Dashed where approximately located; bar and ball on downthrown side; where direction of movement is known.

To convert feet to meters, multiply feet by 0.3048.

Base from U.S. Geological Survey, 1928

Compiled in 1978



**COAL RESOURCE OCCURRENCE MAP OF THE SOUTHEAST QUARTER OF THE
HIAWATHA 15-MINUTE QUADRANGLE, EMERY COUNTY, UTAH**

**BY
AAA ENGINEERING AND DRAFTING, INC.**

1979

**PLATE 5
STRUCTURE CONTOUR MAP
OF THE
BLIND CANYON COAL BED**

This report has not been edited for conformity with Geological Survey editorial standards or stratigraphic nomenclature.