




- EXPLANATION**
- 25 —
— 20 —
ISOPACHS - Showing thickness of coal, in feet. Long dashed where inferred. Isopach interval 5 feet.
 - 40
DRILL HOLE - Showing thickness of coal, in feet.
 - ▲ 4.5
POINT OF MEASUREMENT - Showing thickness of coal, in feet. Includes all points of measurement other than drill holes.
 - Av-3A - Adaville No. 3A
COAL BED SYMBOL AND NAME
 - Av-3A —
TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Arrow points toward coal-bearing area. Dashed where inferred; short dashed where inferred by present authors.
 - C.....
INFERRED LIMIT OF BURNED AND CLINKERED COAL - Arrow points toward area of baked and fused rock.
 - — — — —
TRACE OF FAULT - Arrows designate direction of movement when known. Dashed where inferred or approximately located.
 - + — — — —
TRACE OF AXIAL PLANE OF ASYMMETRIC SYNCLINE - Short arrow indicates steeper limb.
- To convert feet to meters, multiply feet by 0.3048.

Base from U.S. Geological Survey, 1965

Compiled in 1977/1978



**COAL RESOURCE OCCURRENCE MAP OF THE MEADOW DRAW
QUADRANGLE, UINTA COUNTY, WYOMING**
BY
DAMES & MOORE
1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.