UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

MEADOW DRAW QUADRANGLE
WYOMING – UINTA CO.
7.5 MINUTE SERIES (TOPOGRAPHIC)

Base from U.S. Geological Survey, 1965

Compiled in 1977/1978

SCALE 1:24 000

1 MILE — 7000 FEET — 1 KILOMETER

UTM GRID AND 1965 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

QUADRANGLE LOCATION

EXPLANATION

NON-FEDERAL COAL LAND - Land for which the Federal Government does not own the coal rights.

W 060241

AREA OF COAL LEASE ON FEDERAL LAND - Showing coal lease number.

5

ISOPACH - Showing thickness of coal, in feet. Arrow points toward area where coal bed is 5 feet or more thick.

Av-3A - Adaville No. 3A

COAL BED SYMBOL AND NAME

Av-3A

TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Arrow points toward coal-bearing area. Short dashed where inferred by present authors.

SL

STRIPPING-LIMIT LINE - Boundary for surface mining (in this quadrangle, the 200-foot-overburden isopach). Arrow points toward the area suitable for surface mining where the recovery factor is 85 percent, and away from the area suitable for subsurface mining (down dip to the 3,000-foot-overburden isopach) where the recovery factor is 50 percent.

15

SUBSURFACE MINING LIMIT - Showing areas where dips of coal beds are greater than 15° and subsurface mining by conventional methods is not considered feasible. Arrow points toward area where dips are greater than 15°.

TRACE OF FAULT - Arrows designate direction of movement when known. Dashed where inferred or approximately located.

RB	R(85%)	RB	R(50%)	
0.92	0.78	1.38	0.19	(Measured)
0.17	0.14	1.00	0.44	(Indicated)
—	—	—	—	(Inferred)

IDENTIFIED COAL RESOURCES - Showing totals for Reserve Base (RB) and Reserves (R), in millions of short tons, for each section or part of section of non-leased Federal coal land, both within and beyond the stripping-limit line. Reserve (R) tonnage is calculated by multiplying the Reserve Base (RB) tonnage by the appropriate recovery factor. Dash indicates no resource in that category. Underground Reserves have been calculated for only that part of the Reserve Base that is suitable for underground mining, and do not include Reserves for areas where the dip of the coal bed exceeds 15°. Also, Reserves have been calculated for a constant thickness of 12 feet for areas where the coal beds are more than 12 feet thick. Therefore, in some instances, underground Reserves may be less than 50 percent of the Reserve Base.



BOUNDARY LINES - Enclosing areas of measured (M), indicated (I), and inferred (Inf) coal resources.

To convert feet to meters, multiply feet by 0.3048.

To convert short tons to metric tons, multiply short tons by 0.9072.

To convert miles to kilometers, multiply miles by 1.6093.

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.

COAL RESOURCE OCCURRENCE MAP OF THE MEADOW DRAW QUADRANGLE, UINTA COUNTY, WYOMING

BY
DAMES & MOORE
1979

PLATE 17

AREAL DISTRIBUTION AND IDENTIFIED RESOURCES MAPS OF THE ADAVILLE NO. 1A AND THE ADAVILLE NO. 3A COAL BEDS