

EXPLANATION

600
OVERBURDEN ISOPACHS - Showing thickness of overburden, in feet, from surface to top of coal bed. Isopach interval is 200 feet (61 m) over strippable coal and 400 feet (122 m) beyond the stripping-limit line.

300
DRILL HOLE - Showing thickness of overburden, in feet, from surface to top of coal bed.

10
MINING-RATIO CONTOUR - Number indicates cubic yards of overburden per ton of recoverable coal by surface mining methods. Contours shown only in areas underlain by coal of Reserve Base thickness within the stripping-limit (in this quadrangle, the 200-foot-overburden isopach). To convert mining ratio to cubic meters of overburden per metric ton of recoverable coal, multiply mining ratio by 0.8428.

Av-1B - Adaville No. 1B
COAL BED SYMBOL AND NAME

-----Av-1B-----
TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Short dashed where inferred by present authors.


To convert feet to meters, multiply feet by 0.3048.

3866 1/4 NE (BROOKS)
LITTLE GALE CREEK

3866 1/4 NE (BROOKS)

3866 1/4 SE (GUILD HOLLOW)

3866 1/4 SE (GUILD HOLLOW)



**COAL RESOURCE OCCURRENCE MAP OF THE RAGAN
QUADRANGLE, UINTA COUNTY, WYOMING**
BY
DAMES & MOORE
1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.