

EXPLANATION

10

ISOPACHS - Showing thickness of coal, in feet. Long dashed where inferred. Isopach interval 5 feet.

6000
6200

STRUCTURE CONTOURS - Drawn on top of coal zone. Solid where vertical accuracy within 40 feet; long dashed where vertical accuracy possibly not within 40 feet; short dashed where projected above ground surface. Contour interval 200 feet (61 m). Datum is mean sea level.

6748
6

DRILL HOLE - Showing altitude of top of coal zone, and thickness of coal, in feet.

17/32

INTERBEDDED COAL AND ROCK - Showing total coal thickness/total rock thickness.

RS-15 - Rock Springs No. 15
COAL ZONE SYMBOL AND NAME

RS-15




TRACE OF COAL ZONE OUTCROP - Showing symbol of name of coal zone as listed above. Arrow points toward coal-bearing area. Short dashed where inferred by present authors.

TRACE OF FAULT - Bar and ball on downthrown side when direction of movement is known. Dashed where inferred or approximately located.

To convert feet to meters, multiply feet by 0.3048.

NOTE: Structure contours are not drawn beyond those shown because of insufficient data.

SCALE 1:24000



**COAL RESOURCE OCCURRENCE MAP OF THE SOUTHWEST QUARTER OF THE BOARS TUSK
15-MINUTE QUADRANGLE, SWEETWATER COUNTY, WYOMING**
BY
DAMES & MOORE
1979

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.