

EXPLANATION



- 5 —
— 6 —
- ISOPACHS - Showing thickness of coal, in feet. Long dashed where inferred. Isopach interval 1 foot.
- 6000 —
— 6200 —
- STRUCTURE CONTOURS - Drawn on top of coal bed. Solid where vertical accuracy within 40 feet; long dashed where vertical accuracy possibly not within 40 feet; short dashed where projected above ground surface. Contour interval 200 feet (61 m). Datum is mean sea level.
- 6540
4
- DRILL HOLE - Showing altitude of top of coal bed, and thickness of coal, in feet.
- RS-9 - Rock Springs No. 9
COAL BED SYMBOL AND NAME
- RS-9 ---
- TRACE OF COAL BED OUTCROP - Showing symbol of name of coal bed as listed above. Arrow points toward coal-bearing area. Short dashed where inferred by present authors.
- TRACE OF FAULT - Bar and ball on downthrown side when direction of movement is known. Dashed where inferred or approximately located.
- To convert feet to meters, multiply feet by 0.3048.

NOTE: Isopachs and structure contours are not drawn beyond dotted line because of insufficient data.

Base from U.S. Geological Survey, 1958

SCALE 1:24,000

Compiled in 1979



COAL RESOURCE OCCURRENCE MAP OF THE SOUTHWEST QUARTER OF THE BOARS TUSK
15-MINUTE QUADRANGLE, SWEETWATER COUNTY, WYOMING

BY
DAMES & MOORE
1979

PLATE 8
ISOPACH AND STRUCTURE CONTOUR
MAP OF THE ROCK SPRINGS NO. 9
COAL BED

This report has not been edited for conformity with U.S. Geological Survey editorial standards or stratigraphic nomenclature.