

A REVISED VERSION OF GRAPHIC NORMATIVE ANALYSIS PROGRAM  
(GNAP) WITH EXAMPLES OF PETROLOGIC PROBLEM SOLVING

by

J.S. Stuckless and G. VanTrump, Jr.

U.S. GEOLOGICAL SURVEY

OPEN-FILE REPORT

79-1237

1979

# CONTENTS

	PAGE
ABSTRACT . . . . .	1
INTRODUCTION . . . . .	2
PROGRAM DESCRIPTION . . . . .	4
CIPW COMPUTATIONS . . . . .	6
PROGRAM USE . . . . .	.14
TITLE CARD . . . . .	15
FLAG COMMANDS . . . . .	.16
PPS- <del>N</del> PPS . . . . .	16
WATER- <del>N</del> WATER . . . . .	16
CANCRINITE- <del>N</del> CANCRINITE . . . . .	17
BARITE- <del>N</del> BARITE and KSPAR - <del>N</del> KSPAR . . . . .	.18
SET FLAGS . . . . .	19
MODIFIED INPUT COMMANDS . . . . .	.20
<del>M</del> ODIFY <del>F</del> ORMAT . . . . .	20
<del>O</del> XIDES . . . . .	.22
ANALYSIS CARDS . . . . .	23
OUTPUT COMMANDS . . . . .	.24
Define . . . . .	.25
<del>P</del> L <del>O</del> T and <del>P</del> L <del>O</del> T(R) . . . . .	.27
TERNARY . . . . .	28
<del>C</del> ONVERT VALUES . . . . .	.29
PRINT . . . . .	31
RECALCULATE <del>N</del> ORMS . . . . .	31
DEVICE . . . . .	.32
SCALE command and user scaling with dummy cards . . . . .	32

SUMMARY . . . . .	.34
CLEAR . . . . .	.35
ERROR MESSAGES . . . . .	.37
EXAMPLES . . . . .	.41
GNAP PRØBLEM 1 . . . . .	41
GNAP PRØBLEM 2 . . . . .	46
REFERENCES . . . . .	.49
APPENDIX I-SAMPLE PROBLEMS . . . . .	50
APPENDIX II-PROGRAM LISTING . . . . .	75

## ABSTRACT

A revised version of Graphic Normative Analysis Program (GNAP) has been developed to allow maximum flexibility in the evaluation of chemical data by the occasional computer user. GNAP calculates CIPW norms, Thornton and Tuttle's differentiation index, Barth's cations, Niggli values and values for variables defined by the user. Calculated values can be displayed graphically in X-Y plots or ternary diagrams. Plotting can be done on a line printer or Calcomp plotter with either weight percent or mole percent data.

Modifications in the original program give the user some control over normative calculations for each sample. The number of user-defined variables that can be created from the data has been increased from ten to fifteen. Plotting and calculations can be based on the original data, data adjusted to sum to 100 percent, or data adjusted to sum to 100 percent without water. Analyses for which norms were previously not computable are now computed with footnotes that show excesses or deficiencies in oxides (or volatiles) not accounted for by the norm. This report contains a listing of the computer program, an explanation of the use of the program, and the two sample problems.

## INTRODUCTION

The Graphic Normative Analysis Program (GNAP) written by Roger Bowen (1971) has proved to be an extremely useful petrologic program. It offered considerable flexibility to the non-computer specialist and could provide graphic output in publishable form. The revised version of GNAP presented here, provides more flexibility, removes some of the restrictions of the original program, and provides more information to the user. This report also reviews the principles of normative calculations particularly as they apply to some special situations.

The CIPW norm was originally introduced as the basis of classification and nomenclature of igneous rocks (Cross and others, 1902). The proposed taxonomy based on normative analysis is no longer used, but the normative minerals are still used by petrologists to characterize rocks or suites of rocks (e.g. Irvine and Baragar, 1971), and the molecular approach to the calculations has formed the basis for other methods of petrologic characterizations (e.g. Niggli, 1920).

The revised version of GNAP provides a more publishable form of output and a larger degree of user control, particularly in the calculation of the norm. User controlled flags are available that allow elements to be combined in alternate forms (such as those suggested by Washington, 1917) for samples with an unusual mineralogy. Also the complete original analysis can be printed with calculations made on a water-free basis. The original analysis was important to Washington (1917) and is still important to most chemists inasmuch as the analytical sum is an indication of the accuracy and completeness of the analysis.

As a note of historical interest, Washington (1917) stated that with practice and writing down as few results as possible, one can do an average normative calculation in five minutes. He points out that ten minutes may be required for silica-deficient rocks and 15 minutes for the most complex samples. The two examples used in this report are made up of 24 samples including several samples in Washington's complex category. The computer time (CPU) needed to do both problems (including plots and other calculations that are not part of the norm) was less than 50 seconds. Additionally, the mathematical precision is far better than that of the hand calculations.

## PROGRAM DESCRIPTION

GNAP is composed of main driver, 18 subroutines and the Calcomp<sup>1</sup> software package. All coding is in standard ANSI Fortran IV with the exception of one subroutine (FILES) and parts of the Calcomp package which are in assembler language.

The functions of the main driver are the scanning of input for recognizable commands and preliminary data manipulation prior to calls to the other subroutines. Executable statements are constructed from the user-supplied input (blanks or spaces are ignored). These statements are then identified and the indicated action is performed by the appropriate subroutine.

Subroutine NØRM uses the exact formulae of Washington (1917) to calculate the CIPW norm. This computation closely parallels the computations that were first developed for the General Rock Norm program except that certain functions (normalization of oxides, Niggli values and Barth's cations) which were optional are now performed every norm calculation. Subroutine NØRM contains two additional entry points; (1) RECALC is used to recalculate a norm from previously stored oxide values; (2) CØNVER is used to convert weight percent data to molecular amounts. NØRM also employs user-supplied flag commands as discussed below.

Subroutine EVAL evaluates all arithmetic expressions, and is a Fortran version of a procedure previously developed by R.W. Bowen of the U.S.G.S. A transition matrix technique is used to parse the expression to be evaluated.

---

<sup>1</sup> Use of trade names is for descriptive purposes only and does not constitute endorsement by the U.S. Geological Survey.

Using this transition matrix subroutine PARSE creates the Reverse Polish form of the expression, which is then evaluated using a pushdown stack. EVAL has the advantage of not requiring actual comparisons to accomplish the parse, hence execution time is considerable improved over procedures using a less sophisticate technique.

Subroutine SUMPNT is used to create the summary printout. An area of output is constructed according to instructions supplied by the user. After this area has been constructed, the summary is printed.

Subroutine PRNT is used for creation of X-Y plots. A standard grid is determined from the range of values to be plotted as described below. If the Calcomp plotter is specified, calls are made to a Calcomp software package to generate a magnetic tape containing the plotter commands. Otherwise, calls to entries of PLØT2 are made which create a printer plot. Subroutine PLØT2 is used to create printer plots and is a modified version of a subroutine developed at the University of Michigan by P. Smidinger.

Subroutine TRIANG is used for creation of ternary diagrams. If the Calcomp plotter is specified, then calls are made to the Calcomp software package. Otherwise calls are made which create diagrams on the printer.

Subroutine SIDE is used to construct one annotated side of a ternary diagram when the Calcomp plotter has been specified.

The remaining subroutines provide a degree of character manipulation and conversion in Fortran. MOVE is used to move characters from one string to another. CØNV, INIT, and FIND convert data from character form to numeric form. INDEX determines the position of a given character in a given string. NØTEQ determines if two strings are equal (i.e., contain the same characters); CLEAR provides for the construction of pages of output prior to printing. FILES is used to open and close data files as necessary; this subroutine is machine-dependent, written for execution on a Honeywell 6880 computer.

## CIPW COMPUTATIONS

The CIPW norms produced by revised GNAF are computed according to the rules of Washington (1917) except that excess  $\text{CO}_2$  is cast as magnesite and then, if  $\text{CO}_2$  is still in excess, as siderite. The resulting normative minerals are reported in weight percent, but the data can be obtained in mole percent by use of the PPS or CONVERT plus SUMMARY command. Some investigators prefer reporting normative mineral mole percents because they more closely approximate modal abundances (Irvine and Baragar, 1971).

The specific methodology and mathematics of CIPW calculations can be found in Washington (1917) or Johannsen (1939), but as these publications are no longer easily available to many users, a summary of the method with modifications used by GNAF, is given here. The oxides used and the normative minerals calculated by the subroutine NØRM and the chemical formulae of the normative minerals are given in table 1.

---

Table 1 near here.

---

1. The arithmetic sum of the analyzed elements is adjusted for F and Cl because these are actually combined with some of the cations that are reported in the analysis as oxides. (Usually this adjustment changes the total by only a few tenths of a percent, and this step was omitted from the original GNAF program). No attempt is made to adjust the sum for S because such an adjustment requires assumptions about the analytical methods used for S and FeO; for most analyses the correction would be negligible. For rocks with a high content of S, the effect of this correction should be checked. The sum, corrected for F and Cl is used to normalize the analysis to 100 percent, and the adjusted oxides (and

Table 1.--List of variable names used in GNAP

Oxides and Elements

1. SiO <sub>2</sub>	12. MnO
2. Al <sub>2</sub> O <sub>3</sub>	13. ZrO <sub>2</sub>
3. Fe <sub>2</sub> O <sub>3</sub>	14. CO <sub>2</sub>
4. FeO	15. SO <sub>3</sub>
5. MgO	16. Cl
6. CaO	17. F
7. Na <sub>2</sub> O	18. S
8. K <sub>2</sub> O	19. Cr <sub>2</sub> O <sub>3</sub>
9. H <sub>2</sub> O (+, - total or	20. NiO
10. TiO <sub>2</sub>	21. BaO
11. P <sub>2</sub> O <sub>5</sub>	

Minerals

1. Q = quartz (SiO <sub>2</sub> )	20. FA = fayalite (Fe <sub>2</sub> SiO <sub>4</sub> )
2. C = corundum (Al <sub>2</sub> O <sub>3</sub> )	21. CS = calcium orthosilicate (Ca <sub>2</sub> SiO <sub>4</sub> )
3. Z = zircon (ZrSiO <sub>4</sub> )	22. MT = magnetite (Fe <sub>3</sub> O <sub>4</sub> )
4. OR = orthoclase (KAlSi <sub>3</sub> O <sub>8</sub> )	23. CM = chromite (FeCr <sub>2</sub> O <sub>4</sub> )
5. AB = albite (NaAlSi <sub>3</sub> O <sub>8</sub> )	24. HM = hematite (Fe <sub>2</sub> O <sub>3</sub> )
6. AN = anorthite (CaAl <sub>2</sub> Si <sub>2</sub> O <sub>8</sub> )	25. IL = ilmenite (FeTiO <sub>3</sub> )
7. LC = leucite (K <sub>2</sub> Al <sub>2</sub> Si <sub>4</sub> O <sub>12</sub> )	26. TN = titanite=sphene (CaTiSiO <sub>5</sub> )
8. NE = nepheline (Na <sub>2</sub> Al <sub>2</sub> Si <sub>2</sub> O <sub>8</sub> )	27. PF = perovskite (CaTiO <sub>3</sub> )
9. KP = kaliophilite (K <sub>2</sub> Al <sub>2</sub> Si <sub>2</sub> O <sub>8</sub> )	28. RU = rutile (TiO <sub>2</sub> )
10. HL = halite (NaCl)	29. AP = apatite (Ca <sub>5</sub> F(PO <sub>4</sub> ) <sub>3</sub> )
11. TH = thenardite (Na <sub>2</sub> SO <sub>4</sub> )	30. FR = fluorite (CaF <sub>2</sub> )
12. NC = sodium carbonate (Na <sub>2</sub> CO <sub>3</sub> )	31. PR = pyrite (FeS <sub>2</sub> )
13. AC = acmite (Na <sub>2</sub> Fe <sub>2</sub> Si <sub>4</sub> O <sub>12</sub> )	32. CC = calcite (CaCO <sub>3</sub> )
14. NS = sodium metasilicate (Na <sub>2</sub> SiO <sub>3</sub> )	33. MG = magnesite (MgCO <sub>3</sub> )
15. KS = potassium metasilicate (K <sub>2</sub> SiO <sub>3</sub> )	34. SD = siderite (FeCO <sub>3</sub> )
16. WO = wollastonite (CaSiO <sub>3</sub> )	35. DI = diopside (EN+FS+WØ-WØL)
17. EN = enstatite (MgSiO <sub>3</sub> )	36. HY = hypersthene (EN+FS)
18. FS = ferrosilite (FeSiO <sub>3</sub> )	37. OL = olivine (FO+FA)
19. FO = forsterite (Mg <sub>2</sub> SiO <sub>4</sub> )	

elements) are converted to molar amounts by dividing each by its molecular weight. In the following discussion, oxides should be understood as oxides and elements, and amounts as molar amounts. (Washington (1917) ignored amounts less than .002, but they are used by GNAP).

2. The amounts of MnO and NiO are added to FeO, and BaO and SrO are added to CaO. The automatic addition of BaO to CaO can be overridden by the revised version of Gnap, as described below. No standard provision is made for the input of SrO, but it can be accommodated by the use of a series of user defined commands as shown below. The addition of BaO to CaO (or K<sub>2</sub>O or Na<sub>2</sub>O) has the effect of yielding a low total for the normative minerals relative to the oxide total because the conversion of the calcium-bearing minerals from mole percent (in which they are calculated) to weight percent does not take into account the much heavier barium component of the mineral.

3. In the nine steps of rule 3, amounts of minor oxides are combined with amounts of major oxides to form trace minerals. In the earlier version of GNAP, excess of minor constituents caused termination of the calculation and generation of an error message. The revised version uses as much of the minor constituent as possible and then reports the weight percent excess in an error message. In this case, the normative total is lower than the oxide total. Minor oxides are apportioned as follows:

- 3a. CaO equal to 3.33 times P<sub>2</sub>O<sub>5</sub> is used for apatite.
- 3b. Na<sub>2</sub>O equal to 0.5 times Cl is used for halite.
- 3c. Equal amounts of Na<sub>2</sub>O and SO<sub>3</sub> are combined for thenardite.
- 3d. FeO equal to 0.5 times S is used for pyrite.
- 3e. Equal amounts of FeO and Cr<sub>2</sub>O<sub>3</sub> are used for chromite.

- 3f. Equal amounts of  $\text{FeO}$  and  $\text{TiO}_2$  are used for ilmenite.  $\text{CaO}$  equal to any excess  $\text{TiO}_2$  is provisionally allotted to titanite. (If there is not enough  $\text{CaO}$  to use up the  $\text{Al}_2\text{O}_3$  in the anorthite calculations (4d) titanite is not calculated.) Excess  $\text{TiO}_2$  is calculated as rutile.
- 3g. F equal to  $\frac{2}{3}$  the amount of apatite (3a) is considered to be contained in apatite. Any excess is used with half as much  $\text{CaO}$  for fluorite.
- 3h. If the rock contains modal cancrinite, equal amounts of  $\text{Na}_2\text{O}$  and  $\text{CO}_2$  are combined for sodium carbonate. Excess  $\text{CO}_2$  is first combined with an equal amount of  $\text{CaO}$  for calcite. Any excess  $\text{CO}_2$  is subsequently combined with equal amounts of  $\text{MgO}$  for magnesite, and then with  $\text{FeO}$  for siderite.
- 3i. Equal amounts of  $\text{SiO}_2$  and  $\text{ZrO}$  are used for zircon.
- 4. Alumina and potash are apportioned as follows:
  - 4a. Equal amounts of  $\text{K}_2\text{O}$  and  $\text{Al}_2\text{O}_3$  are used for orthoclase.
  - 4b. Excess  $\text{K}_2\text{O}$  is equal to the amount of potassium metasilicate.
  - 4c. Excess  $\text{Al}_2\text{O}_3$  is combined with an equal amount of  $\text{Na}_2\text{O}$  and is equal to the amount of albite.
  - 4d. Excess  $\text{Al}_2\text{O}_3$  is combined with an equal amount of  $\text{CaO}$  (including the  $\text{CaO}$  that had been provisionally assigned to titanite if necessary) to make anorthite.
  - 4e. Any excess  $\text{Al}_2\text{O}_3$  is equal to the amount of corundum.
- 5. Sodium oxide and ferric iron are apportioned as follows:
  - 5a.  $\text{Fe}_2\text{O}_3$  equal to the excess of  $\text{Na}_2\text{O}$  is used for acmite.
  - 5b. Any excess  $\text{Na}_2\text{O}$  is equal to the amount of sodium metasilicate.

- 5c. Excess  $\text{Fe}_2\text{O}_3$  and an equal amount of  $\text{FeO}$  are used for magnetite.
- 5d. Any excess  $\text{Fe}_2\text{O}_3$  is equal to the amount of hematite.
6. The relative proportion of any remaining  $\text{FeO}$  and  $\text{MgO}$  are determined.
7. Lime, ferrous iron and magnesia are apportioned as follows:
  - 7a.  $\text{CaO}$  equal to the sum of  $\text{FeO}$  and  $\text{MgO}$  is used for diopside.
  - 7b. Excess  $\text{CaO}$  is equal to the amount of wollastonite.
  - 7c. Excess  $\text{MgO} + \text{FeO}$  is equal to the amount of hypersthene. The proportions of enstatite and ferrosilite are the same as the  $\text{MgO-FeO}$  proportions determined in (6).
8. Silica is adjusted for the minerals calculated in steps 3 thorough 7. If there is a deficiency in silica, the silica-rich minerals are recalculated as silica-poor minerals.
  - 8a. The  $\text{SiO}_2$  remaining after (3i) is decreased by the amount of titanite, 4 times the amount of acmite, the amount of sodium metasilicate, the amount of potassium metasilicate, 6 times the amount of orthoclase, 6 times the amount of albite, the amount of wollastonite, twice the amount of anorthite, twice the amount of diopside, and the amount of hypersthene.
  - 8b. Excess  $\text{SiO}_2$  is equal to the amount of quartz.
  - 8c. If there is a silica deficiency after (8a), hypersthene is converted to olivine (forsterite and fayalite proportions are as determined in rule (6) and  $\text{SiO}_2$  is increased by  $1/2$  the amount of hypersthene. If this results in a  $\text{SiO}_2$  excess, hypersthene is increased (from zero) and olivine is decreased until  $\text{SiO}_2$  is equal to zero.

- d. If there is still a silica deficiency titanite is converted to perovskite and silica is increased by the amount of titanite.
- 8e. If there is still a silica deficiency, albite is converted to nepheline and  $\text{SiO}_2$  is increased by 3 times the amount of albite. If this results in a silica excess, albite is increased (from zero) and nepheline is decreased until  $\text{SiO}_2$  is equal to zero.
- 8f. If there is still a silica deficiency, orthoclase is converted to leucite and  $\text{SiO}_2$  is increased by  $1/3$  the amount of orthoclase. If this results in a silica excess, orthoclase is increased (from zero) and leucite is decreased until  $\text{SiO}_2$  equals zero.
- 8g. If there is still a silica deficiency, the clinopyroxenes are converted to calcium orthosilicate and olivine. Wollastonite is converted first then diopside.  $\text{SiO}_2$  is increased by twice the amount of clinopyroxene and the clinopyroxene is changed to orthosilicate. If an excess in silica results, clinopyroxene is increased from zero and orthosilicate is decreased until silica equals zero.
- 8h. If there is still a silica deficiency, leucite is converted to kaliophilite and silica is increased by the amount of leucite. If a silica excess results, leucite is increased from zero and kaliophilite is decreased until silica equals zero.
- 9. Molecular amounts of minerals are converted to weight percent by multiplying molar amounts by molecular weights.
- 10. The total normative minerals are then calculated and divided into two categories. Silic minerals include quartz, corundum, zircon, orthoclase,

albite, anorthite, leucite, nepheline, kaliophilite, halite, thenardite, and sodium carbonate. All other minerals listed in Table 1 are Femic. In the original version of GNAP, if silica was still deficient after step (8h), an error message was printed out and no output was generated. The revised version of GNAP follows the convention of Washington (1917) and reports silica deficiencies after step (8h) as excesses of MgO and FeO (in weight percent) with normative olivine decreased. This has the effect of yielding a low normative total.

The output of approximate norms and excess oxides provides sets of usable information. The approximate norm allows data from the sample to be evaluated in the same manner as samples for which an accurate norm could be calculated. The excess oxides can then be evaluated in terms of analytical error or the existence of modal minerals that are not considered in the normative calculations. For example, an analysis with a low analytical total (e.g. 98.98%) and a large excess of  $P_2O_5$  beyond that used in the norm (e.g. 0.50%) could result from abundant rare earth phosphates in the rock. Alternatively, an analytical total near 100 percent and an excess of  $P_2O_5$  beyond that used in the norm of 0.01 percent indicates that the norm is accurate within the limits of analytical uncertainty. As a second example, the analysis of a dunite may have an analytical total near 100 percent but contain a large excess of MgO beyond that used in the normative calculation. This could indicate the existence of periclase or brucite in the rock.

The only major difference in the normative calculations by GNAP and the rules proposed by Washington is in the treatment of  $CO_2$ . Washington proposed that  $CO_2$  be treated three different ways depending on petrographic results: (1) if cancrinite was present,  $CO_2$  was first used for sodium carbonate and added to the salic component with any excess  $CO_2$  used for

calcite, (2) if primary calcite was present,  $\text{CO}_2$  was calculated as calcite and added to the femic component, and (3) if secondary calcite was present,  $\text{CO}_2$  was calculated as calcite, but calcite was not used in either the femic or salic totals. The revised version of GNAP provides for a user-initiated calculation of sodium carbonate which is added to the salic component. After sodium carbonate is calculated, or if this calculation is not requested,  $\text{CO}_2$  is assigned to calcite, with excess  $\text{CO}_2$  used for magnesite, and if necessary, siderite. These three carbonates are added to the femic total regardless of whether they are primary or secondary.

## PROGRAM USE

The input for the revised version of GNAP is much more flexible than that of the original version. GNAP input now includes a series of flag commands that allow the user to control the actual normative calculations. Errors in setting or removing flags can produce an output with errors that may not be readily apparent. For this reason, it is critical that the user provide input in exactly the form necessary to create the desired output.

The general sequence of the input card is:

1. Title Card.
2. Flag commands for normative calculations.
3. Modified input commands.
4. Analysis cards.
5. Output commands.

Cards from steps 2 and 3 above affect the data cards that follow them. They can either precede all the data, or be interspersed with the analysis cards at the user's discretion. If they are to be interspersed, it is suggested that a page of output per sample be requested (as described below) so that the output can be checked carefully.

## TITLE CARD

A title card is identified by the word TITLE punched in columns 1 through 5. Title cards are the only cards that may contain TITLE in the first five columns. For example, a variable named TITLED would be illegal. All of the remaining spaces (6 through 80) can be used for any alpha-numeric characters, symbols or blanks. If the title card contains: TITLE PRØBLEM I, all pages of output generated after the title card is read will be headed by PRØBLEM I. For this reason, a title card is generally the first card in the deck, but new title cards can be used anywhere. For example, the user may wish to title a specific plot with a particular publication reference. A new title card immediately before the plot command and a different title card immediately after the plot command will accomplish labeling of a single plot. It is generally advisable to annotate any specially-created output. The phrase MØLAR DATA is automatically added to the user's title after a CØNVERT VALUES command as discussed below. If no title card is supplied, GRAPHIC NØRMATIVE ANALYSIS PRØGRAM is printed at the top of each page.

## FLAG COMMANDS

The revised version of GNAP provides pairs of flag commands that can be used to control the calculation and output of normative information. Each flag must operate in one of two modes. Each will automatically start in one mode and remain there until changed by the user. All flag commands must end with a semicolon. They can be given before and after a single data card if necessary.

### PPS-NØPPS commands

If the command PPS (page per sample) is given, a single page of output is generated for each subsequent analysis. This page of output contains: The sample number, the plotting symbol used for this sample, the original analysis in weight percent, the original total, the original total adjusted for Cl and F, the analysis adjusted to 100 weight percent and mole percent (with or without  $H_2O$  as discussed below), the normative analysis in mole and weight percent (based on the adjusted sum), the weight percent ratios of  $Al_2O_3/SiO_2$  and  $FeO/Fe_2O_3$ , the Thornton and Tuttle differentiation index, the total, femic and salic normative minerals (if  $H_2O$  is used, the total will be less than 100%), Barth's cations, and Niggli values.

The default (or normal) mode for the PPS-NØPPS pair is NØPPS. If the PPS command is not given or if the NØPPS is given following a PPS command, single-page output is not generated.

### WATER-NØWATER commands

The NØWATER command allows the user to enter  $H_2O$  as one of the analyzed oxides (either  $H_2O^+$ ,  $H_2O^-$  or the sum of the two; the latter is preferable in most cases because it preserves the original analytical total.), but to ignore  $H_2O$  as a variable in all subsequent calculations and graphic output. In the NØWATER mode, the complete analysis and the total (adjusted for F and Cl) are shown in the summary output, but all calculations and

plotting are based on a water-free analysis, normalized to 100 percent. Plots and calculations are labeled as based on adjusted oxides. Normative minerals and adjusted oxides summaries are labeled as water-free in the summary table. These labels tell the user that the NØWATER flag is set. The default (or normal) mode for the WATER-NØWATER pair is WATER.

If the NØWATER command is used for only a few samples, and if these samples are followed by a WATER command, the normative calculations for the samples between the NØWATER and WATER commands will be on a water-free basis. There will be no label on the summary table to indicate that a few samples were treated as water-free, but the samples that were treated as water-free will be identified on the page of run conditions and error messages and on the single-page output per sample. In the summary table, the water value for these samples will be blank in the adjusted oxides and their normative totals will be 100 percent. Normative totals for samples with water will be less than 100 percent (the difference being equal to the normalized weight percent water).

Once all of the data cards have been read and the norms have been calculated, the effect of the WATER-NØWATER command is to direct the output commands to the original or adjusted oxide data sets. WATER is the default (normal) mode for this command pair. If the NØWATER command is not given, or if the WATER command is given after a NØWATER command, plots and user-defined calculations are based on the original oxides. If the NØWATER command is in operation, the plots and calculations will be based on the adjusted oxides.

#### CANCRINITE-NØCANCRINITE commands

This pair of commands allows the user to treat CO<sub>2</sub> according to the method suggested by Washington (1917). The CANCRINITE command should be given for all rock analyses which have cancrinite as a modal constituent. This

causes the normative calculation to add a step to calculate sodium carbonate before any other carbonates are calculated. Sodium carbonate is added to the salic total whereas all other carbonates are added to the femic total.

If the CANCRINITE command is not given or if NØCANCINITE is given after a CANCRINITE command, the calculation of sodium carbonate is automatically skipped. If only one analyzed sample in a data set contains cancrinite, the data card for that sample can be preceded by a CANCRINITE command, and followed by a NØCANCINITE command, and sodium carbonate will be calculate for that sample only. A message will note that the sodium carbonate calculation was attempted. The default (normal) mode for the CANCRINITE-NØCANCINITE pair is NØCANCINITE.

#### BARITE-NØBARITE and KSPAR-NØKSPAR commands.

These two pairs of commands allow the user to control the use of barium in the normative calculations. In the default (normal) mode, BaO is added to CaO as suggested by Washington (1917). If a given sample is known to contain barite and if SO<sub>3</sub> is given in the analysis, the BARITE command should precede the analysis card. This command adds BaO to Na<sub>2</sub>O for the purpose of normative calculations for the next and all subsequent analyses until a NØBARITE card is encountered. This step can be important for rock in which CO<sub>2</sub> is reported, and for which barite is an important trace mineral because otherwise Ca normative minerals are increased and Na normative minerals are decreased (because of the calculation of thenardite). The NØBARITE command returns the program to the default mode and allows the program to look for the KSPAR command. The KSPAR command adds BaO to K<sub>2</sub>O for the purpose of normative calculations, and should be used if a high-barium, potassium feldspar or barium feldspar is present in the analyzed rock. This command will not override a BARITE command, and if the latter has been given, a

NØBARITE command must precede the KSPAR command. (Although a BARITE command will override a KSPAR command, it is best to set the flag to NØKSPAR after the last analysis of a barium-bearing-feldspar rock in order to avoid possible complications further on in the data set.) The addition of barium to calcium or potassium is indicated by a note on the run condition and error message page.

#### SET FLAGS command

The SET FLAGS command returns all flags to their default condition. This command would be used before a RECALCULATE NØRMS command if norms are desired by two different modes of calculation.

## MODIFIED INPUT COMMANDS

### MODIFY FORMAT command

The user may specify an input format different from the standard format indicated in figure 1. The user prescribed format must follow Fortran IV object-time specifications and may use up to three cards per sample. The format is restricted to a form of (4X,.....,5X) for each card as discussed in the Analysis card section. The format modification is expressed as:

MODIFY FORMAT= (4X,.....,5X), NCS=n;

Where the dots represent columns 5 through 75 for each card, and n is the number of cards per sample up to a maximum of 3. If n is not specified, it is assumed to be 1. A maximum of 96 characters can be used to describe the format.

The order in which oxides are read follows the order given in table 1 unless this order is overridden by an OXIDES command.

The following example of MODIFY FORMAT is from Bowen (1971). If the user wishes to specify ten oxides per card with each value having 5 digits before the decimal and 2 digits after the decimal, the data would be preceded by:

MODIFY FORMAT= (4X,10F7.2,1X,5X), NCS=3;

note that as with all commands, this one ends with a semicolon. In this modified format, each analysis requires 3 cards. Each of the three cards must start with NRM (or STØ) and plotting symbol in columns 1 through 4 and end with the sample identification in columns 75 through 80 (as discussed in the Analysis card section below). Although space is provided for 30 variables, the program will use only the first 21. If during the same run the user wishes to use data cards that are punched in the standard format, these cards would be preceded by:

MODIFY FORMAT= (4X,9F4.2,3F3.2,F2.2,F4.2,5F3.2,F2.2,F3.2,5X), NCS = 1;

[illegible]

### ØXIDES command

The ØXIDES command is usually used in conjunction with the MØDIFY FØRMAT command. The ØXIDES card must precede all analysis cards to which it refers. The ØXIDES command indicates which oxides are to be read, and in what order. (Note that for the sake of brevity, the volatile elements are included under the term oxides.) If no ØXIDES command is given, the oxides will be read in the order given in table 1. If the order of oxides has been changed, it can be returned to the standard order by:

```
ØXIDES SIØ2,AL2Ø3,FE2Ø3,FEØ,MGØ,CAØ,NA2Ø,K2Ø,H2Ø,TIØ2,P2Ø5,MNØ,  
ZRØ2,CØ2,SØ3,CL,F,S,CR2Ø3,NIØ,BAØ;
```

If any one of the oxide names is incorrectly given, an error message is printed giving a list of acceptable oxide names foillowed by the incorrect oxide name. The run is then terminated.

The ØXIDE command only allows the user to choose which of the 21 acceptable oxides (table 1) will be read and in what order. If the user has Rb, Sr, and Ba data which are to be used in plotting, they must be read in as acceptable oxides, and then defined by their correct names by use of a define command. For example, they may be read in as CR2Ø3, NIØ, and BAØ. A series of commands are needed to instruct the computer to label CR2Ø3 as RB, NIØ as Sr, and BAØ as BA (see example below).

## ANALYSIS CARDS

The analysis cards may be set in a standard format (fig. 1) or in a user-prescribed format. The analysis card (or cards if more than one card per sample is used) may contain a maximum of twenty-one variables. The first three columns must contain either NRM or STØ. NRM places all of the original and calculated variables in a data array for future use in printing, plotting, or subsequent data manipulations. STØ bypasses all normative calculations and places only the original data in storage. This command would be used most commonly for setting an evenly divisible line printer scale for X-Y type plots, or to store non-chemical data for future plotting. Only analysis cards may have NRM or STØ in the first three columns, hence a variable named NRML or STØRM would be illegal if they started in column 1. Column 4 should contain the character that is to be used in displaying the sample on X-Y and ternary plots. The characters + and - are used to delineate axes and boundaries on plots and should, therefore, be avoided as plotting symbols. The underscore is used to delineate duplicate points, and is therefore a poor choice as a plotting symbol. The user may find that some symbols (such as #, @, and &) which have special meaning for particular machines, may not print. Columns 76-80 should contain the sample identification. Any alphanumeric and symbol combination up to 5 characters in length is permissible. A maximum of 99 samples can be processed as a group.

The identification columns 76-79 can be used for a special purpose. The RECALCULATE NØRMS command uses all values in storage including those entered directly into storage by use of a STØ command. This means that cards used for the purpose of scaling of plots only may generate meaningless norms, and may have their scaling values changed during the recalculation. To avoid this problem, the user can identify cards for which a norm or normalization to 100

percent is not desired by DUMM in columns 76-79. Cards thus identified will be entered into both adjusted and original data sets exactly as coded and will not be used in any normative calculations or normalizations. They will be used for all plotting, printing and calculating commands. Cards for which data are to be stored for later normative calculations are identified by STØ in columns 1 to 3, and an identifications other than DUMM in columns 76-79.

### OUTPUT COMMANDS

The revised version of GNAF used the same ten output commands as the original version. The discussion of these commands is based on the description by Bowen (1971).

Expressions are basic to all the output commands. These are rules by which the computer obtains and uses values. Expressions are composed of variable names, arithmetic operators, constants, and the grouping symbols the left and right parenthesis. Expressions must be syntactically and semantically correct in the Fortran sense. Thus, each left parenthesis must have a matching right parenthesis. No two arithmetic operators can be used immediately adjacent to one another. All variable names must be known to the computer before evaluation of the expression is requested. For example, the computer cannot be instructed to multiple A times 2 and then told that A is silica. Reversing the order of these two instructions make the operation permissible.

Variable names may be any of the alphanumeric combinations associated with values calculated in the norm subroutine (tables 1 and 2). Note that Niggli values, Barth's cations, and Thornton and Tuttle's differentiation index cannot be addressed by their standard abbreviations except for the purpose of

a summary printout. Up to fifteen additional variable names can be provided by user-defined commands as discussed below. Variable names must start with a letter.

---

Table 2 near here

---

The four arithmetic operators are:

(1) division (e.g.  $AL203/Si02$ ), (2) multiplication (e.g.  $.8998*FE203$ ), (3) subtraction (e.g.  $SI02-40$ ), and (4) addition (e.g.  $CA0 + BA0$ ). These operators are listed in the order of the priority. Multiplication and division are performed before subtraction and addition. Operations of equal priority are performed left to right. The order of operations is changed by the use of parentheses such that operations within parentheses are done first. Hence, if variable  $A=6/3*2$ , A is equal to 4, but if  $A=6/(3*2)$ , A is equal to 1.

Constants are decimal numbers with or without a decimal point. They must be less than eight characters in length including the decimal point as a character. For example, the half-life for  $^{238}U = 4468300000$  is not a usable constant because it contains 10 characters, but  $4468300*100$  is usable because it contains only 7 characters.

#### Define command

The define command is used to create new variable names (up to a maximum of 15) or to redefine the basic names in tables 1 and 2. The define command only operates on data that are in storage. Therefore, all define command cards must be placed after the analysis cards for which they are to be used. The define command takes the form:

Variable name=expression:

Table 2.--Variable names for partitioning of normative  
clinopyroxene, orthopyroxene, and olivine

DI = diopside  $(\text{Ca}(\text{Fe},\text{Mg})(\text{SiO}_3)_2)$

DIWØ - calcium component of diopside

DIEN - magnesium component of diopside

DIFS - iron component of diopside

WØL - excess calcium clinopyroxene beyond that needed for diopside

HY = hypersthene  $(\text{Mg}, \text{Fe})\text{SiO}_3$

HYEN = magnesium component of hypersthene

HYFS = iron component of hypersthene

ØL = olivine  $(\text{Fe},\text{Mg})_2\text{SiO}_4$

ØLFØ = magnesium component of olivine

ØLFA = iron component of olivine

Note: Results are expressed as either weight percent or mole percent of the total norm and not as percent of the mineral class.

e.g.  $TOTALFE = .77732 * (FE0 + .8998 * FE2O3);$

In this example, total metallic iron (for which the variable name is TOTALFE) is defined as the converted oxides of iron. This is calculated by first calculating all the iron oxide as FeO (within the parentheses) and the multiplying the FeO by a conversion factor. An alternate way to define the same variable would be:

$$TOTALFE = .77732 * FE0 + .69943 * FE2O3;$$

Note that in both examples an arithmetic operator is between the constant and variable name for each iron oxide. (The expression .8998FE2O3 is meaningless). Also note that both commands end with a semicolon. The number of characters to the left of the equal sign must be eight or less. No operators can be used to the left of the equal sign (e.g. +, -, \*, /, ()). The number of characters to the right of the equal sign must be forty or less. If a longer expression is necessary, it must be done in steps (e.g. X= part of the expression; variable name=X + the rest of the expression). Each define command is printed when it is executed. Numbers printed for user-defined variables in the summary table are limited to the range 999.999 to 000.001. Larger numbers are printed as \*\*\*\*\* and smaller as 0.000.

#### PLØT AND PLØT(R) commands

The command PLØT and PLØT(R) are used to generate X-Y plots on either the line printer or Calcomp plotter(as described under the DEVICE command). These commands take the form:

PLØT expression 1, expression 2;

or

PLØT(R) expression 1, expresion 2;

where expression 1 and expression 2 are valid arithmetic expressions as discussed above, separated by commas and followed by a semicolon. For example:

PLØT SIØ2, AL2Ø3;

instructs the computer to construct an X-Y plot with silica on the abscissa increasing from left to right, and alumina on the ordinate increasing bottom to top. A command of PLØT(R) A, B; instructs the computer to create an X-Y plot with the abscissa values increasing from right to left and ordinate values increasing from bottom to top. The computer uses all values in storage at the time the command is given including those for which no plotting symbol is given. Although the latter will not print, they will be used to determine the minimum and maximum values for abscissa and ordinate. They may show as an underscore of a data point that has the same value or as a blank space in the axis marking. It should be noted that unless otherwise specified (e.g. by a define or CØNVERT or NØWATER command as discussed above), the oxide values used will be the weight percent values in the unadjusted input data set and the normative minerals will be in weight percent. Plots that follow a CØNVERT command will be based on adjusted mole percent data set. Plots that follow a NØWATER command will be labeled as based on adjusted oxides. These will be normalized to 100 percent and water-free if the NØWATER command preceded the data. Duplicate data points are indicated by an underscore.

One special plot command is available. This command takes the form:

PLØT HARKER;

This command instructs the computer to create a series of X-Y plots with silica on the abscissa and all other oxides with non-zero values on the ordinate.

#### TERNARY command

The ternary command instructs the computer to construct a ternary diagram for either lineprinter or Calcomp output. This command takes the form:

TERNARY expression 1, expression 2, expression 3;

where the expressions are valid as described above, separated by commas, and followed by a semicolon. For ternary plots, all expressions must be equal to or greater than zero; if the computer encounters an expression that is less than zero, it will set it equal to zero. If all expressions are zero for a particular sample, the point is plotted in the lower left apex. Expression 1 describes the upper apex; expression 2 describes the lower left apex; and expression 3 describes the lower right apex. For example:

TERNARY Q,AB,OR;

instructs the computer to construct the familiar granite system diagram of Tuttle and Bowen (1958).

The ternary command uses all values in storage, but plots a blank space if no plotting symbol is given. The command also generates a printout of values for the three expressions normalized to 100 percent on the page that precedes the plot, including those values which are plotted as a space. A list of duplicate data points is also printed. These points are indicated by an underscore on the diagram. It should be noted that the ternary plot generated by the line printer is not exactly accurate. Also note that the original and adjusted data sets produce equivalent ternary diagrams because of the normalization step taken in calculating ternary proportions.

#### CØNVERT VALUES command

The CØNVERT VALUES command changes all of the weight percent values of the variables listed in table 1 and 2 to mole percent. It is important to note that user-defined variables are not automatically converted to mole percent. Also, only one CØNVERT VALUES command can be used in each data analysis because the command only causes division of stored values by molecular weights. With the exception of user-defined variables, values which do not

convert will not print if requested by a summary command. For example, no constant exists that changes total weight to total moles. Hence, summaries after a `CONVERT VALUES` command have no totals. If the user wishes to use his defined variables in mole percent, he must redefine them by use of a `define` command that contains the appropriate conversion factors. For example, if the user defined a variable `FEOT` to include all the iron as `FeO` and then converted values by use of a `CONVERT VALUES` command, `FEOT` would still be in weight percent.

FE<sub>0</sub>T could be converted to mole percent by either

$$\text{FE}_0\text{T} = \text{FE}_0\text{T} * 0.0139086;$$

or

$$\text{FE}_0\text{T} = \text{FE}_0 + 2.0 * \text{FE}_2\text{O}_3;.$$

#### PRINT command

The PRINT command instructs the computer to evaluate and print one or more expressions. This command takes the form:

PRINT expression 1, expression 2;

where expressions 1 and 2 are valid as described above. There is no limit on the number of expressions that can be printed. Each expression will be printed with the sample number followed by the value. All expressions must be followed by a comma except the last, which must be followed by a semicolon. The PRINT command will use the original oxide values unless otherwise specified. Refer to the discussion of the PL<sub>0</sub>T command for details of the values used in printing under various flag conditions.

#### RECALCULATE N<sub>0</sub>RMS command

The RECALCULATE N<sub>0</sub>RMS command is used to recalculate norms for each sample in storage (except samples identified by DUMM in columns 76-79). This command takes the form:

RECALCULATE N<sub>0</sub>RMS;

This command allows the user to modify the stored data (e.g. by use of a define command) and to then calculate a norm on the basis of the modified data. For example, the user may wish to compare the norms of the original data with those of volatile-free analyses with all iron expressed as ferrous iron. To do this, a summary card would be placed after the analysis cards, followed by a series of define cards that set each volatile equal to zero, a define card to calculate all the iron as Fe<sub>0</sub>, a define card to set Fe<sub>2</sub>O<sub>3</sub>

equal to zero (this card cannot precede the card that redefines FeO as all the iron recalculated as ferrous iron) and finally, a RECALCULATE NØRMS command. The RECALCULATE NØRMS command cannot be used after a CØNVERT VALUES command, because the norm subroutine requires weight percent data as input, and the weight percent data are destroyed by the CØNVERT VALUES command.

#### DEVICE command

The DEVICE command is used to specify plotting on either the line printer or Calcomp plotter. If no device is specified, approximate plotting will be done on the line printer. Both line printer and Calcomp plotter can be used in a single run. The device command takes the form:

DEVICE = CALCØMP;

or

DEVICE = PRINTER;

This command affects all PLOT and TERNARY commands that follow it in the card deck until a new device command is encountered.

#### SCALE command and user scaling with dummy cards

The scale command affects only those plots which are to be produced by the Calcomp plotter. Line printer plots have a fixed size which occupies one full page of computer paper. For X-Y plots, the line printer divides the abscissa into 10 equal intervals, and the ordinate into 5 equal intervals on the basis of the minimum and maximum values in storage for each coordinate. This will generally produce axes scales that differ widely from one data set to another, and which may be difficult to interpret within any given data set. For example, if silica in a series of basalts varies from 43.2 to 49.6, and Harker variation diagrams ( $\text{SiO}_2$  versus each oxide) are requested by the plot commands, the abscissa will be divided into units of 0.46 weight percent silica. This is an inconvenient unit, and it is unlikely that it could be

used in an overlay comparison with data from other basalt suites. For these reasons, both line printer and Calcomp plots should be scaled by the user.

User scaling is most easily accomplished by use of dummy analysis cards. One, two, or three cards can be used such that the range from minimum to maximum values is divisible by 5. If plotting of adjusted or water-free oxides is anticipated, each dummy card should sum to 100 percent (water-free if need be). The dummy cards should be included with the analysis cards (usually as the last cards of the data set) with STØ in the first three columns, and the fourth column left blank. All dummy cards must have some sort of unique identification in columns 75 through 80, such as DUMM1, DUMM2, etc. The identification DUMM in columns 76 to 79 prevents attempted norm calculation and normalization of the data to 100 percent in the event a RECALCULATE NØRMS command is given.

When the Calcomp plotter is specified, the abscissa is divided into 10 equal units, and ordinate into 8 equal units. Unlike to line printer, the Calcomp scaling subroutines set the interval values equal to 1, 2, 4, 5, or  $8 \times 10^n$ , where  $n$  is a whole number. As a result of this internal scaling, the Calcomp plots may not start with the actual minimum value and end with the actual maximum value. Nonetheless, dummy cards are advisable to insure consistent scaling among data sets.

In addition to setting ranges that can be incremented by whole numbers, the user may vary the absolute size of Calcomp plots by use of a SCALE command. This command takes the form:

SCALE =  $n$ ;

where  $n$  can be any number from 0.0 to 3.0. If no SCALE command is given, ternary plots will have sides of 230.6mm (9.08 in) in length. This scale allows direct overlay of plots on Keuffel and Esser triangular coordinate

paper (K and E No. 46 4490). Two-dimensional plots will have an abscissa of 254 mm (10 in) and an ordinate of 203.2 mm (8 in) which will overlay on standard 10 divisions per inch graph paper (e.g. K and E No. 46 0702). The scale factor for standard size plots is 1.0. Scale factors between 0.0 and 1.0 decrease the size of the plots, and scale factor between 1.0 and 3.0 increase the size of plots such that 3.0 produces a plot of 762 mm (30 in) maximum width. Scale factors greater than 3.0 exceed the capabilities of the Calcomp plotter, and generate an error message. The SCALE command does not affect the size of lettering and plotting symbols which remain fixed at 3.56 mm (.14 in).

#### SUMMARY command

This command produces a summary printout for all of the samples in storage. Nine separate groups of numbers can be obtained by use of this command:

- (1) The oxides as originally entered.
- (2) Oxides normalized to 100% (with or without water).
- (3) Normative minerals.
- (4) Partitioning of normative clinopyroxene, orthopyroxene, and olivine.
- (5) Barth's cations.
- (6) Niggli values
- (7) Thornton and Tuttle's differentiation index.
- (8) The ratios  $Al_2O_3/SiO_2$  and  $FeO/Fe_2O_3$
- (9) User-defined values.

The order in which these nine categories are printed, as well as which ones are printed are under user control. Note that this is the only command that can access categories 5 through 8 without the use of a define command. The

summary values will be printed in weight percent unless the summary command has been preceded by a CONVERT VALUES command. In this case, the summary of values in categories one through four will be in mole percent; but the user-defined variables will still be in weight percent, unless converted through the use of a define command. Values in categories 5 through 8 are not converted, and will not print even if requested. This is also true of the various totals.

The SUMMARY command takes the form:

SUMMARY (list of category keywords);

where the category key words are OXIDES, ADJUSTED, MINERALS, PARTITIONS, BARTH, NIGGLI, D.I., RATIOS, and USER. The key words used must be in the order desired by the user, separated by commas, and contained within parentheses. The summary printout will automatically contain the last title, sample numbers, and plotting symbols. Zero values will be left blank. Any variables, except ratios and D.I., for which all values are zero will be omitted from the summary printout. For example, a summary of the normative minerals for 60 samples will generate five pages of printout. If NC(sodium carbonate) is zero for all 60 samples, NC will be omitted from all five pages. However, if NC is non-zero for one sample, it will be printed for all five pages even though it will have no associated values on four of the five pages.

Note that these key words are only understood in the context of a SUMMARY command. If the differentiation index is to be used for plotting it must first be defined as:

D.I. =  $Q + R + AB + NE + KP + LC$ ;

#### CLEAR STORAGE command

The CLEAR STORAGE command is used to remove all previously stored values and to reset all flags to their default mode. This command takes the form:

CLEAR STØRAGE;

Typically, this command would be used if calculations and plotting for two different data sets were desired. The clear command would be placed after the last command card for the first data set, and would be followed by all the command and analysis cards for the next data set.

## ERROR MESSAGES AND PROGRAM CONDITIONS

GNAP is designed to recover from those errors that are due to incorrect or inadequate input. The program is also designed to recover from errors that result from special case data. When an error is detected, an error message is sent to a file that prints as a summary at the end of the run, and the computer resumes scanning the input for commands to execute. In addition to errors, the program keeps track of special conditions that are imposed by the user during the run. These are printed with the error messages at the conclusion of the run. A list of messages and probable causes follows.

1. NO MORE THAN 99 NORMS MAY BE STORED. THE LAST NORM WILL BE WIPED OUT.

More than 99 analysis cards have been processed without an intervening clear command. Only the first 99 analyses are in storage.

2. NO MORE THAN 15 NAMES MAY BE DEFINED. DEFINITION IGNORED FOR NAME = ( ).

More than 15 new variable names have been given. Consider redefining variable names.

3. PLOT COMMAND ERROR ON ( ).

The two expressions for abscissa and ordinate, respectively, are not separated by a comma.

4. TERNARY COMMAND ERROR ON ( ).

The expression giving the apices of the desired ternary diagram are not separated by commas.

5. SCALE MUST BE POSITIVE AND LESS THAN OR EQUAL TO 3.0.

An illegal scale was requested, possibly due to a misplaced decimal point.

6. "DEVICE = CALCOMP" MUST BE SPECIFIED BEFORE SETTING SCALE.

A scale command has been misplaced in the deck. It has no effect on the line printer output and is recognized only by the Calcomp software.

7. STATEMENT LENGTH (160) EXCEEDED ON CARD ( ). DID YOU FORGET A SEMICOLON?

Message is generated most often by a missing semicolon after a command, but may be due to an error in a user-supplied format.

8. FORMAT COMMAND ERROR (MISSING PARENTHESES) IN ( ).

A user-defined format is lacking a parentheses.

9. ERROR IN MODIFY COMMAND GIVEN AS ( ).

The modify keyword was not followed by format or NCS (number of cards).

10. UNRECOGNIZED COMMAND GIVEN AS ( ).

The most common causes for failure to recognize commands are misspellings and errors in user-defined formats.

11. ERROR IN EXPRESSION ( ).

This message is usually caused by syntax errors such as unmatched parentheses or adjacent arithmetic operators.

12. UNDEFINED NAME ( ).

This is most often generated by a spelling error, but could be generated by reversing a definition such that the new variable is to the right of the equal sign.

13. FIRST WORD ILLEGAL IN ( ).

A key word is misspelled in the summary command or an unrecognized variable has been requested.

14. THE FOLLOWING COMMAND CONTAINS EXCESSIVE CHARACTERS. DID YOU FORGET A SEMICOLON

A semicolon is probably missing. The defined variable may not exceed 8 characters, and the definition may not exceed 40.

15. OXIDE COMMAND CONTAINS A NAME WHICH IS NOT IN THE LIST OF ACCEPTABLE OXIDES. ACCEPTABLE OXIDES ARE: ( ).

Error is most likely due to a misspelling or use of an oxide name not used in the program.

16. GRAPHIC NORMATIVE ANALYSIS PROGRAM.

This is printed in place of a title if no title is supplied.

17. MOLAR DATA.

This is appended to the users title for all output that follows a convert command.

18. SAMPLE ( ) CONTAINS AN EXCESS OF ( ) WEIGHT PERCENT ( ) BEYOND THAT USED IN NORMATIVE CALCULATIONS.

The blanks contain sample number, amount, and element name, respectively. Elements that can occur in excess are P2O5, CL, S, CR2O3, F, CO2, or ZRO.

19. SAMPLE ( ) CONTAINS TOO LITTLE SiO2 TO COMPUTE A NORM. SiO2 DEFICIENCY IS EQUIVALENT TO AN EXCESS OF MG OF ( ) WT% AND AN EXCESS OF FE OF ( ) WT%.

The reported norm is only an approximation based on the assumption that too much olivine was calculated.

20. DATA HAVE ALREADY BEEN CONVERTED TO MOLES. NORMS CANNOT BE RECALCULATED FROM DATA EXPRESSED IN MOLES.

The user converted the data and then asked for a recalculation of the norms.

21. NO SiO<sub>2</sub> GIVEN FOR HARKER SUITE OF PLOTS.

Silica is zero for all samples, and hence no plots are generated.

22. SAMPLE ( )--NA<sub>2</sub>CO<sub>3</sub> CALCULATION ATTEMPTED.

The CANCRINITE flag was set for sample ( ).

24. SAMPLE ( ) -- BaO ADDED TO K<sub>2</sub>O.

The KSPAR flag was set for sample ( ).

25. NOTE: PLOT IS BASED ON ADJUSTED OXIDES.

This is printed on plots for which the NOH<sub>2</sub>O flag was set.

26. SAMPLE ( ) --NORM COMPUTED ON WATER FREE BASIS.

The NOWATER flag was set for sample ( ).

## EXAMPLE

### GNAP PRØBLEM 1

The first problem demonstrates the use of all the flag commands and several output commands. Seven pairs of samples are entered such that the sample A computes normally and sample B generates an error message for an excess in a minor constituent or used a new loop of the program. Two rocks with too little silica for a normative computation are also included. The range of samples in this problem also uses all possible input oxides, and computes all possible output minerals.

The first page of appendix 1 is a printout of all the cards used in the first problem in the order read by the computer. The first card is a title card which causes GNAP PRØBLEM 1 to be printed at the top of each page until the CØNVERT VALUES card is encountered at which point the title is changed to GNAP PRØBLEM 1, MØLAR DATA. The second card is a PPS command which causes a single page per sample to be printed until the NØPPS is encountered (after the third sample).

Three analyses of sample MNØ6 are shown in the first three pages of output. MNØ6A and MNØ6H are identical analyses but MNØ6H is preceded by a NØWATER command. Sample MNØ6B contains more Cl than can be combined with the available  $\text{Na}_2\text{O}$  and an error statement is printed for this sample on the last page of output for the problem that shows an excess of 0.09 weight percent Cl. Note that the increased Cl in MNØ6B removes albite from the norm, increases anorthite and halite relative to MNØ6A, and decreases total minerals relative to MNØ6A. The difference in the two totals is not 0.09, but  $(0.09 - 0.23 \times 0.09)$ . This difference is due to the effect of using Cl instead of oxygen as an anion and can be seen in the totals relative to the adjusted totals of the three samples. The effect of calculating the norm with and

without water can be seen by comparing samples MN06A and MN06H. The minerals calculated do not change, but the absolute amounts are greater in the water-free analysis.

The remaining 21 samples of problem 1 are preceded by a NØPPS command which suppresses the page per sample output. Results for these and the first 3 samples are shown in the summary table for GNAØ PRØBLEM 1 (Appendix 1). Error statements and flag conditions for the last 21 samples appear on the last page of output for problem 1.

The sample pair 1201A and 1201B differs in the amounts of MgO, CaO and CO<sub>2</sub>. Sample 1201B would not have produced a norm in the original version of GNAØ, but it does not cause an error statement to be generated in the revised version because siderite is calculated to use up the excess CO<sub>2</sub> after magnesite has been calculated. Although samples 1201A and 1201B are chemically very similar, there are several differences in the normative mineralogy which could relate to several differences in their trace mineral modes.

Sample 1165 has three similar analyses (A, B, and C). Sample 1165B and 1165C are chemically identical and differ from 1165A in contents of MgO, CaO, and CO<sub>2</sub>. The three norms have several differences. Sample 1165B generates an error message of .13 weight percent excess CO<sub>2</sub> beyond that used in the norm (for calcite, magnesite, and siderite). Sample 1165C is preceded by a CANCRINITE command and all of the CO<sub>2</sub> is used to calculate thenardite. The CANCRINITE command causes sample 1165C to have a very different normative mineralogy from that of sample 1165B (the chemically identical sample). The difference in the normative totals for samples 1165A and 1165B is equal to the excess CO<sub>2</sub> (.09 wt%).

The sample pair 1101A and 1101B differs only in the F content which causes sample 1101B to generate an error message of 0.04 weight percent F in excess, removes anorthite and calcite from the norm, and adds fluorite and magnesite to the norm. The totals differ by  $(.04 - .04 * .42)$ , which is due to the difference in weight of oxygen and fluorine.

The sample pair 344 A and 344 B differ in their amounts of CaO and  $P_2O_5$ . Sample 344 B generates an error message of .09 weight percent  $P_2O_5$  which is equal to the difference in the total of the normative minerals. Although CaO was used up before the calculation of fluorite was attempted, the increase in apatite was sufficient to accommodate the F so no secondary error message was generated for excess F.

The sample pair 278 A and 278 B differs in amounts of FeO and  $Cr_2O_3$ . Sample 278#B generates an error message of .06 weight percent  $Cr_2O_3$  which is equal to the difference in the total of the normative minerals. Note that the addition of chromium to the analysis affects the amounts of all the minerals calculated after step 3e of the rules for CIPW calculations.

The sample pair 339 A and 339 B differs only in the S added to the analysis for sample 339 B. The 0.2 weight percent increase of S causes an error message to be generated which shows an excess of S of 0.09 weight percent. This amount is equal to the difference in total weight percent normative mineralogy because no attempt is made to adjust analyses for the differences in  $O^{-2}$  and  $S^{-1}$  or  $S^{-2}$  or  $SO_3^{-2}$  incorrectly reported as S. Note that the addition of S to the analysis makes only a few, generally small differences in the normative mineralogy.

Analysis EC2-9 is an unpublished analysis of an ultramafic nodule (Robert Forbes, written communication, 1973). The sample does not have a computable norm by the original version of GNAP. It contains an excess of  $P_2O_5$  and a

large excess of the olivine molecule which could be interpreted as a large analytical error or the existence of oxide minerals not considered by the normative calculations. However, spinel, which could occur in the norm as any alumino-silicate or corundum, does exist in the sample, and probably explains most of the excess iron and magnesium. The excess  $P_2O_5$  seems large relative to analytical error and may suggest the presence of a phosphate other than apatite.

The next three samples are taken from Washington (1917) and provide a comparison with hand calculated norms. Sample A2.II generates an error message of excess  $MgO$  and  $FeO$  of 1.87 and 0.52 weight percent, respectively. In his calculated norm, Washington reports an excess of 2.31 percent  $MgO$  plus  $FeO$ . The norm for sample A3.III is very similar to that reported by Washington.

The next three samples, A1.I, A1.IS, and A1.IK, demonstrate the changes in normative mineralogy that occur as a result of allocating  $BaO$  to  $CaO$ ,  $Na_2O$ , and  $K_2O$  ( $SrO$  in the original analysis has been added to  $BaO$  on the input card for the purpose of the example). Note that all of the normative totals (even with water added) are all less than 100, and that they are all different. The effects of allocating  $BaO$  in different ways is small, but could be important in special cases.

The last two samples are included because they have reported  $ZrO$  which causes the calculation of zircon and because they have excess Ca-clinopyroxene beyond that needed to equal the Fe and Mg components of diopside. This causes  $WO_4$  (wollastonite in excess of that used in diopside) to be calculated and printed. The last sample is the only sample in the problem that causes perovskite to be calculated.

The weight percent data are used to create two commonly used ternary diagrams. The first diagram which uses normative quartz, albite and

orthoclase, is commonly used for the classification of quartz-bearing plutonic rocks or to compare the chemical composition of a granite with Tuttle and Bowen's (1958) granite minimum. (It should be noted the Tuttle and Bowen's plot is a phase diagram and that the plot generated by GNAF is not.) The second ternary diagram used the input oxides to create an AMF diagram. The upper apex is the sum of the total iron as FeO (shown as the user-defined variable FEOT) plus MNØ. If a NØWATER command had been given before the ternary command, the oxides adjusted to 100 percent would have been used. This would have resulted in a slightly different diagram unless FEOT was redefined on the basis of the adjusted oxides. The ternary ratios are shown on both diagrams. In the actual computer output, these are printed on the page that precedes the ternary diagram.

The second half of the problem is carried out using molar data. This is accomplished by use of a CØNVERT VALUES command. FEOT is redefined so that it will be in moles and a new summary is created. Subsequent pages are automatically labeled with the user's title and molar data.

The molar data are used to create two ternary diagrams. The first is based on the molar quantities of nepheline, quartz, albite, hypersthene and olivine (after Irvine and Baragar, 1971) and allows the user to evaluate silica saturation. Lines that divide undersaturated, saturated, and oversaturated fields have been drawn on the computer output. The second ternary plot is based on the molar amounts of  $Al_2O_3$ , total alkalies, and CaO. This allows the user to evaluate the alumina saturation according to the classification of Shand (1951). Lines have been drawn on the output to indicate the fields of peraluminous, metaluminous, and peralkaline. The printout for the ternary ratios has been superimposed on the diagrams by hand.

These two ternary diagrams were chosen to demonstrate the advantage of plotting molar data. The superimposed lines for field boundaries could be shown on weight percent diagrams, but they would have to be calculated by hand, and they would be more difficult to locate on the line printer output. In Shand's classification (1951), peraluminous refers to analyses in which there is more aluminum than that needed to make feldspar. The molar ratio of  $K_2O$  or  $Na_2O$  to  $Al_2O_3$  in alkali feldspar (e.g.  $K_2O \cdot Al_2O_3 \cdot 6SiO_2$ ) is 1:1 or mid-point on the left side line. For anorthite ( $CaO \cdot Al_2O_3 \cdot 2SiO_2$ ) the mid-points also indicate the point at which there is an exact mixture for feldspar. Hence, peraluminous is the field above the line that joins the mid-points.

Problem 1 ends with a SET FLAGS, and a CLEAR command (page 50). This returns the flags to their default modes and clears all of the storage registers so that a new problem can be started.

#### GNAP PRØBLEM 2

The second problem demonstrates the input of data in a user-defined format, manipulation of user-defined data, X-Y plotting, and plotting with the Calcomp plotter. The samples used in this problem are cogenetic and generate a more typical number of normative minerals than the analyses used in problem 1.

The first card is again a title card (page 50) which labels every page with GNAP PRØBLEM 2. The next card gives the new format, and the following card identifies which of the 21 oxides will be read by the computer and in what order (note that all 21 oxides are not needed). The analytical data are given in the next 12 cards. The number of cards per sample is not specified in the MØDIFY FØRMAT command, and hence, 1 card per sample is assumed.

Immediately after the data and two dummy cards, three new variables are defines (BAPPM, UPPM, and THPPM). These were originally read in as BAØ, NIØ, and CR2Ø3 and were used as such in the normative calculations as can be seen in the first summary table of problem 2 ( p. 68-70). Chromite (CM) is reported for all of the samples in spite of the fact that there is no real chromium in any of the samples. In order to obtain the correct norms, BAØ (which was read in as elemental Ba) is converted to BaO by using a define command. NIØ and CR2Ø3 are set equal to zero, and the RECALCULATE NØRMS command is given. The second summary table and the storage registers now contain the true norms and correct chemical data.

BaO was added to CaO (by default) for the normative calculations. The user may wish to have a quick visual check that BaO is varying with CaO rather than K<sub>2</sub>O. This is accomplished by plotting BAØ versus K2Ø. An inverse relationship is expected, and the user may wish to have a positive slope for the plot. Therefore, K<sub>2</sub>O is plotted with values increasing to the left by the command: PLOT(R) K2Ø,BAØ;. Scaling for this and other plots in problem 2 is accomplished through the use of dummy cards. These can be seen in the input data ( page 51), but because they generated a separated page of output for the summary tables (only 12 samples are printed per page), printout for these samples has been omitted. Note that their identification is DUMM1 and DUMM2 so that the scaling factors will not be normalized to 100 percent by the recalculated command. A second X-Y plot (Th versus U) is created, this time with values along the abscissa increasing to the right.

The next command sends plotted output to the Calcomp plotter and requests plotting at 3/4 of the normal scale. The requested plot is a ternary plot of the radioelements. Superimposed manually beside the plot is the printout of the ternary ratios. Three lines that describe the commonly accepted averages

for each of the radioelement ratios are superimposed on the diagram. In this example, most of the samples vary greatly from the normal Th/U, U/K and Th/K ratios.

The last series of commands converts the stored data to mole percent. Next a new variable (PERAL) is defined (which is greater than 1 for peraluminous rocks,) and the values of PERAL are printed. Defining PERAL prior to printing is not necessary. The command:

```
PRINT AL2O3/(NA2O+K2O+CAO);
```

would have generated the same output. Defining the variable first merely places it in storage so that it could be used for purposes other than printing. For example, the user may wish to examine the peraluminous variable as a function of differentiation in an X-Y plot.

## REFERENCES

- Bowen, R. W., 1971, Graphic normative analysis program: U.S. Geol. Survey Computer Contribution No. 13, 80 p.
- Cross, C. W., Iddings, J. P., Pirsson, L. V., and Washington, H. S., 1902, Quantitative chemico-mineralogical classification and nomenclature of igneous rocks: Jour. Geol., v. 10, p. 555-690.
- Irvine, T. N., and Baragar, W. R. A., 1971, A guide to the chemical classification of the common volcanic rocks: Can. Jour. of Earth Science, v. 8, p. 523.
- Johannsen, Albert, 1939, A descriptive petrography of the igneous rocks; Vol. I Introduction, textures, classifications and glossary: Univ. Chicago Press, Chicago, 318 p.
- Niggli, Paul, 1920, Lehrbuch der mineralogie, Berline, 476 p.
- Shand, S. J., 1951, Eruptive rocks; John Wiley, New York, 488 p.
- Tuttle, O. F., and Bowen, N. L., 1958, Origin of granites in the light of experimental studies in the system  $\text{NaAlSi}_3\text{O}_8$ - $\text{KAlSi}_3\text{O}_8$ - $\text{CaAl}_2\text{Si}_2\text{O}_8$ - $\text{H}_2\text{O}$ : Geol. Soc. America Mem. 74, 153 p.
- Washington, H. S., 1917, Chemical analysis of igneous rocks: U.S. Geol. Survey Prof. Paper 99, 1201 p.

# APPENDIX 1

## SAMPLE PROBLEMS

```

TITLE GNAF PROBLEM 1
PPS;
NRM#48301480 240 910 8101000 126 012 36306801321 140 MN06A
NRM#48301480 240 910 8101000 126 012 36306801321 153 MN06B
NOWATER;
NRMS48301480 240 910 8101000 126 012 36306801321 140 MN06H
WATER;
NOPPS;
NRM#678 179 45 80 61 25 96 53 178 23 5 2 3 3 0400 1201A
NRM#678 179 45 80 30 10 96 53 178 23 5 2 60 3 0000 1201B
NRM#749 143 9 26 20 24 76 3 066 13 3 2 2062 300 1165A
NRM#749 143 9 26 10 12 76 3 066 13 3 2 40062 300 1165B
CANCRINITE;
NRMS749 143 9 26 10 12 76 3 066 13 3 2 40062 300 1165C
NOCANCRINITE;
NRM#759 138 1 68 11 18 3 7 47 14 2 5 3 100 00 1101A
NRM#759 138 1 68 11 18 3 7 47 14 2 5 3 101500 1101B
NRM#73801330 130 04 45 44 240 580 15002100802 06 02 344 A
NRM#73801330 130 04 45 22 240 580 15002102602 06 01 344 B
NRM#52101660 830 80 450 660 370 240 300170 8110 02 03 278 A
NRM#52101660 830 20 450 660 370 240 300170 8110 02 03 70 278 B
NRM#729013500190 08 36 120 360 460 85 37 1004 01 02 339 A
NRM#729013500190 08 36 120 360 460 85 37 1004 01 02 20 339 B
NRMX3751 241 133 8954859 07 05 05 13 33 1717 EC2-9
NRMW3117 625 322 964199 1776 203 251 249296169 A2.II
NRMW3498108 14221331930 43 17 542 128518 A3.III
NRMW53701116 310 121 644 346 1671116 341192175 4 006003 44 4 81A1.I
BARITE;
NRMW53701116 310 121 644 346 1671116 341192175 4 006003 44 4 81A1.IS
NOBARITE;
KSPAR;
NRMW53701116 310 121 644 346 1671116 341192175 4 006003 44 4 81A1.IK
NOKSPAR;
NRMA55902050 265 158 87 298 904 426 039076 172 013 1 11 1 25
NRMA488 177 716 18 311 684 642 364 141242 5622 1 03 11 8 46
FEOT=FE0+0.3998*FE203;
SUMMARY (OXIDES,ADJUSTED,MINERALS,PARTITIONS,USER);
TERNARY Q,AB,OR;
TERNARY FEOT+MNC,NA2O+K2O,MGO;
CONVERT VALUES;
FEOT=FE0+2*FE203;
SUMMARY (OXIDES,ADJUSTED,MINERALS,PARTITIONS,USER);
TERNARY NE+.6*AB,Q+.4*AB+.25*HY,OL+.75*HY;
TERNARY AL2O3,NA2O+K2O,CAO;
SETFLAGS;
CLEAR;
TITLE GNAF PROBLEM 2
MODIFY FORMAT (4X,9F4.2,2F3.2,5F2.2,2F6.6,F4.4,3X,5X);
OXIDES SI02,AL2O3,FE2O3,FE0,MGO,CAO,NA2O,K2O,H2O,TIO2,P2O5,MNO,CL,F,S,CO2,
NIO,CR2O3,BAO;
NRMB670 159 14 26 12 28 40 31 79 72 24 3 5 2 101 388 1840 1
NRMB685 152 18 10 10 24 36 44 50 32 140 4 3 227 454 1280 2
NRMB685 155 10 28 11 29 41 28 61 64 19 3 7 3 86 436 1490 3
NRMB709 148 11 72 56 22 42 38 66 20 110 3 1 177 292 974 4
NRMB718 141 11 11 27 91 35 50 65 15 10 2 3 8 123 643 583 5
NRMB72 145 6 13 39 74 35 50 70 20 2 5 20000 2 11 689 532 6
NRMB724 142 12 24 4 51 37 5 123 14 1 2 2 2 00 10 55 459 7
NRMB726 152 33 84 40 22 42 34 38 19 5 1 4 6 96 4671120 8
NRMB72611449 76 112 41 75 331 534 58 12 6 3 3 200 1 994 613 698 9
NRMB728 138 50 88 28 93 33 52 63 19 0502 2 692 685 513 10

```

NRMB733	135	27	23	13	97	30	57	51	10	0702	8	172	234	271	11
NRMB735	138	64	52	18	73	32	56	56	8	8 2 2	2	262	382	388	12
STO							1								DUMM1
STO							6					20	7	2	DUMM2

BAPPM=10000\*BAO;  
 UPPM=10000\*NIO;  
 THPPM=10000\*CR203;  
 SUMMARY (ADJUSTED,MINERALS,USER);  
 BAO=1.1168\*BAO;  
 NIO=0.0;  
 CR203=0.0;  
 RECALCULATE NORMS;  
 SUMMARY (OXIDES,ADJUSTED,MINERALS,D.I.,BARTH,NIGGLI,RATIOS,USER);  
 PLOT(R) K20,BAO;  
 PLOT UPPM,THPPM;  
 DEVICE= CALCOMP ;  
 TERNARY UPPM,THPPM,0.83\*K20;  
 DEVICE=PRINTER;  
 CONVERT VALUES;  
 PERAL=AL2O3/(NA2O+K2O+CAO);  
 PRINT PERAL;

SAMPLE NO. MN06A PLOTTING SYMBOL IS \*

## ORIGINAL WT.PCT. OXIDES

SI02	AL2O3	FE2O3	FE0	MG0	CA0	NA20	K20	H20	TI02	P205	MNO	ZR02	CO2	SO3	CL	F	S	CR203	NIO	BA0
48.30	14.80	2.40	9.10	8.10	10.00	1.26	0.12	3.63	0.68	0.13	0.21	0.00	0.00	0.00	1.40	0.00	0.00	0.00	0.00	0.00

SUM OF ORIGINAL OXIDES= 100.13

SUM ADJUSTED FOR F &amp; CL= 99.81

## OXIDES NORMALIZED TO 100 PERCENT :

CONSTITUENTS	SI02	AL2O3	FE2O3	FE0	MG0	CA0	NA20	K20	H20	TI02	P205	AL2O3/SI02
PERCENTAGES	48.30	14.80	2.40	9.10	8.10	10.00	1.26	0.12	3.63	0.68	0.13	0.306
MOL. AMTS.	0.8054	0.1454	0.0151	0.1269	0.2013	0.1787	0.0204	0.0013	0.2019	0.0085	0.0009	0.0009

CONSTITUENTS	MNO	ZR02	CO2	SO3	CL	F	S	CR203	NIO	BA0	FE0/FE2O3
PERCENTAGES	0.21	0.00	0.00	0.00	1.40	0.00	0.00	0.00	0.00	0.00	3.792
MOL. AMTS.	0.0030	0.0000	0.0000	0.0000	0.0396	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000

## CIPW NORM :

MINERALS	Q	C	Z	OR	AB	AN	LC	NE	KP	HL	TH	NC
MOL. AMTS.	0.1675	0.0000	0.0000	0.0013	0.0006	0.1436	0.0000	0.0000	0.0000	0.0198	0.0000	0.0000
PERCENTAGES	10.062	0.000	0.000	0.710	0.307	39.943	0.000	0.000	0.000	2.312	0.000	0.000

MINERALS	AC	NS	KS	WO	EN	FS	FO	FA	CS	MT	CM	HM
MOL. AMTS.	0.0000	0.0000	0.0000	0.0320	0.2013	0.1063	0.0000	0.0000	0.0000	0.0151	0.0000	0.0000
PERCENTAGES	0.000	0.000	0.000	3.721	20.212	14.022	0.000	0.000	0.000	3.486	0.000	0.000

MINERALS	IL	TN	PF	RU	AP	FR	PR	CC	MG	SD	TOTAL	SALIC	FEMIC
MOL. AMTS.	0.0085	0.0000	0.0000	0.0000	0.0009	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
PERCENTAGES	1.294	0.000	0.000	0.000	0.309	0.000	0.000	0.000	0.000	0.000	96.379	53.334	43.044

MINERALS	DI	DI-WO	DI-EN	DI-FS	HY	HY-EN	HY-FS	OL	OL-FO	OL-FA	WOL
MOL. AMTS.	0.0320	0.0320	0.0210	0.0111	0.2756	0.1804	0.0952	0.0000	0.0000	0.0000	0.0000
PERCENTAGES	7.286	3.721	2.105	1.460	30.669	18.107	12.562	0.000	0.000	0.000	0.000

THORNTON + TUTTLE DIFFERENTIATION INDEX = 11.079

BARTHS CATIONS	SI	AL	FE+3	FE+2	MG	CA	NA	K	H	TI	P	MN
	47.66	17.21	1.78	7.51	11.91	10.57	2.41	0.15	23.89	0.50	0.11	0.18

	ZR	C	S1	CL	F	S2	CR	NI	BA
	0.00	0.00	0.00	2.34	0.00	0.00	0.00	0.00	0.00

NIGGLI VALUES	AL*	FM*	C*	ALK*	SI	RI	P	H	K	MG	SI'	QZ
	20.57	51.10	25.27	3.06	113.91	1.21	0.13	28.55	0.06	0.56	112.25	1.67

## GNAP PROBLEM 1

SAMPLE NO. MN06B PLOTTING SYMBOL IS #

## ORIGINAL WT.PCT. OXIDES

SiO2	AL2O3	FE2O3	FeO	MgO	CaO	Na2O	K2O	H2O	TiO2	P2O5	MnO	ZrO2	CO2	SO3	CL	F	S	CR2O3	NiO	BAO
48.30	14.80	2.40	9.10	8.10	10.00	1.26	0.12	3.63	0.68	0.13	0.21	0.00	0.00	0.00	1.53	0.00	0.00	0.00	0.00	0.00

SUM OF ORIGINAL OXIDES= 100.26

SUM ADJUSTED FOR F &amp; CL= 99.91

OXIDES NORMALIZED TO 100 PERCENT :

CONSTITUENTS	SiO2	AL2O3	FE2O3	FeO	MgO	CaO	Na2O	K2O	H2O	TiO2	P2O5	AL2O3/SiO2
PERCENTAGES	48.30	14.80	2.40	9.10	8.10	10.00	1.26	0.12	3.63	0.68	0.13	0.306
MOL. AMTS.	0.8046	0.1453	0.0150	0.1268	0.2011	0.1785	0.0203	0.0013	0.2017	0.0085	0.0009	0.0009

CONSTITUENTS	MnO	ZrO2	CO2	SO3	CL	F	S	CR2O3	NiO	BAO	FE0/FE2O3
PERCENTAGES	0.21	0.00	0.00	0.00	1.53	0.00	0.00	0.00	0.00	0.00	3.792
MOL. AMTS.	0.0030	0.0000	0.0000	0.0000	0.0432	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000

CIPW NORM :

MINERALS	Q	C	Z	OR	AB	AN	LC	NE	KP	HL	TH	NC
MOL. AMTS.	0.1702	0.0000	0.0000	0.0013	0.0000	0.1440	0.0000	0.0000	0.0000	0.0203	0.0000	0.0000
PERCENTAGES	10.227	0.000	0.000	0.710	0.000	40.066	0.000	0.000	0.000	2.378	0.000	0.000

MINERALS	AC	NS	KS	WO	EN	FS	FO	FA	CS	MT	CM	HM
MOL. AMTS.	0.0000	0.0000	0.0000	0.0314	0.2011	0.1062	0.0000	0.0000	0.0000	0.0150	0.0000	0.0000
PERCENTAGES	0.000	0.000	0.000	3.649	20.192	14.008	0.000	0.000	0.000	3.483	0.000	0.000

MINEPALS	IL	TN	PF	RU	AP	FR	PR	CC	MG	SD	TOTAL	SALIC	FEMIC
MOL. AMTS.	0.0085	0.0000	0.0000	0.0000	0.0009	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
PERCENTAGES	1.293	0.000	0.000	0.000	0.308	0.000	0.000	0.000	0.000	0.000	96.314	53.381	42.933

MINERALS	DI	DI-WO	DI-EN	DI-FS	HY	HY-EN	HY-FS	OL	OL-FO	OL-FA	WOL
MOL. AMTS.	0.0314	0.0314	0.0206	0.0109	0.2759	0.1806	0.0953	0.0000	0.0000	0.0000	0.0000
PERCENTAGES	7.146	3.649	2.064	1.432	30.704	18.128	12.576	0.000	0.000	0.000	0.000

THORNTON + TUTTLE DIFFERENTIATION INDEX = 10.937

BARTHS CATIONS	SI	AL	FE+3	FE+2	Mg	CA	NA	K	H	TI	P	MN
	47.66	17.21	1.78	7.51	11.91	10.57	2.41	0.15	23.89	0.50	0.11	0.18

	ZR	C	S1	CL	F	S2	CR	NI	BA
	0.00	0.00	0.00	2.56	0.00	0.00	0.00	0.00	0.00

NIGGLI VALUES	AL*	FM*	C*	ALK*	SI	RI	P	H	K	MG	SI'	QZ
	20.57	51.10	25.27	3.06	113.91	1.21	0.13	28.55	0.06	0.56	112.25	1.67

SAMPLE NO. MNO6H PLOTTING SYMBOL IS S

ORIGINAL WT.PCT. OXIDES

SI02	AL2O3	FF2O3	FE0	MG0	CA0	NA2O	K2O	H2O	TI02	P2O5	MNO	ZR02	CO2	SO3	CL	F	S	CR2O3	NIO	BA0
48.30	14.80	2.40	0.10	8.10	10.00	1.26	0.12	3.63	0.68	0.13	0.21	0.00	0.00	0.00	1.40	0.00	0.00	0.00	0.00	0.00

SUM OF ORIGINAL OXIDES= 100.13

SUM ADJUSTED FOR F &amp; CL= 99.81

OXIDES NORMALIZED TO 100 PERCENT : (H2O FREE)

CONSTITUENTS	SI02	AL2O3	FF2O3	FE0	MG0	CA0	NA2O	K2O	H2O	TI02	P2O5	AL2O3/SI02
PERCENTAGES	50.22	15.39	2.50	9.46	8.42	10.40	1.31	0.12	0.00	0.71	0.14	0.306
MOL. AMTS.	0.8358	0.1509	0.0156	0.1317	0.2099	0.1854	0.0211	0.0013	0.0000	0.0088	0.0010	

CONSTITUENTS	MNO	ZR02	CO2	SO3	CL	F	S	CR2O3	NIO	BA0	FE0/FE2O3
PERCENTAGES	0.22	0.00	0.00	0.00	1.46	0.00	0.00	0.00	0.00	0.00	3.792
MOL. AMTS.	0.0031	0.0000	0.0000	0.0000	0.0411	0.0000	0.0000	0.0000	0.0000	0.0000	

CIPW NORM : (H2O FREE)

MINERALS	Q	C	Z	OR	AB	AN	LC	NE	KP	HL	TH	NC
MOL. AMTS.	0.1738	0.0000	0.0000	0.0013	0.0006	0.1400	0.0000	0.0000	0.0000	0.0205	0.0000	0.0000
PERCENTAGES	10.441	0.000	0.000	0.737	0.319	41.450	0.300	0.000	0.000	2.400	0.000	0.000

MINERALS	AC	NS	KS	W0	EN	FS	FO	FA	CS	MT	CM	HM
MOL. AMTS.	0.0000	0.0000	0.0000	0.0332	0.2089	0.1103	0.0000	0.0000	0.0000	0.0156	0.0000	0.0000
PERCENTAGES	0.000	0.000	0.000	3.862	20.975	14.551	0.300	0.000	0.000	3.618	0.000	0.000

MINERALS	IL	TN	PF	RU	AP	FR	DR	CC	MG	SD	TOTAL	SALIC	FEMIC
MOL. AMTS.	0.0088	0.0000	0.0000	0.0000	0.0010	0.0000	0.0000	0.0000	0.0000	0.0000	100.016	55.347	44.669
PERCENTAGES	1.343	0.000	0.000	0.000	0.320	0.000	0.000	0.000	0.000	0.000			

THORNTON + TUTTLE DIFFERENTIATION INDEX = 11.498

BARTHS CATIONS	SI	AL	FE+3	FE+2	MG	CA	NA	K	H	TI	P	MN
	47.66	17.21	1.78	7.51	11.91	10.57	2.41	0.15	0.00	0.50	0.11	0.18

NIGGLI VALUES	AL*	FM*	C*	ALK*	SI	RI	P	H	K	MG	SI*	QZ
	20.57	51.10	25.27	3.06	113.91	1.21	0.13	0.00	0.06	0.56	112.25	1.67

GNAP PROBLEM 1

FE0T DEFINED AS FF0+0.8999\*FE2O3

## GNAP PROBLEM 1

SYMBOL	MNO6A	MNO6B	MNO6H	1201A	1201B	1165A	1165B	1165C	1101A	1101B	344 A	344 B
	*	#	S	*	#	*	#	S	*	#	*	#
SI02	48.30	48.30	48.30	67.80	67.80	74.90	74.90	74.90	75.90	75.90	73.80	73.80
AL203	14.80	14.80	14.80	17.90	17.90	14.30	14.30	14.30	13.80	13.80	13.30	13.30
FE203	2.40	2.40	2.40	0.45	0.45	0.90	0.90	0.90	0.10	0.10	1.30	1.30
FE0	9.10	9.10	9.10	0.80	0.80	0.26	0.26	0.26	0.68	0.68	0.04	0.04
MGO	8.10	8.10	8.10	0.61	0.30	0.20	0.10	0.10	0.11	0.11	0.45	0.45
CA0	10.00	10.00	10.00	0.25	0.10	0.24	0.12	0.12	0.18	0.18	0.44	0.44
NA20	1.26	1.26	1.26	9.60	9.60	7.60	7.60	7.60	3.00	3.00	2.40	2.40
K20	0.12	0.12	0.12	0.53	0.53	0.30	0.30	0.30	7.00	7.00	5.80	5.80
H20	3.63	3.63	3.63	1.78	1.78	0.66	0.66	0.66	0.47	0.47	1.50	1.50
TI02	0.68	0.68	0.68	0.23	0.23	0.13	0.13	0.13	0.14	0.14	0.21	0.21
P205	0.13	0.13	0.13	0.05	0.05	0.03	0.03	0.03	0.02	0.02	0.08	0.08
MNO	0.21	0.21	0.21	0.02	0.02	0.02	0.02	0.02	0.05	0.05	0.02	0.02
ZR02												
CO2				0.03	0.60	0.02	0.40	0.40	0.03	0.03	0.06	0.06
SO3						0.62	0.62	0.62				
CL				0.03	0.03	0.03	0.03	0.03	0.01	0.01		
F	1.40		1.40	0.04							0.02	0.01
S												
CR203												
BA0												
TOTAL (-0)	99.81	99.91	99.81	100.10	100.18	100.20	100.36	100.36	101.49	101.57	99.41	99.37
ADJUSTED OXIDES												
SI02	48.39	48.34	50.22	67.73	67.68	74.75	74.63	74.63	74.79	74.72	74.24	74.27
AL203	14.83	14.81	15.39	17.88	17.87	14.27	14.25	14.25	13.60	13.59	13.38	13.38
FE203	2.40	2.40	2.50	0.45	0.45	0.90	0.90	0.90	0.10	0.10	1.31	1.31
FE0	9.12	9.11	9.46	0.80	0.80	0.26	0.26	0.26	0.67	0.67	0.04	0.04
MGO	8.12	8.11	8.42	0.61	0.30	0.20	0.10	0.10	0.11	0.11	0.45	0.45
CA0	10.02	10.01	10.40	0.25	0.10	0.24	0.12	0.12	0.18	0.18	0.44	0.44
NA20	1.26	1.26	1.31	9.59	9.58	7.58	7.57	7.57	2.96	2.95	2.41	2.41
K20	0.12	0.12	0.12	0.53	0.53	0.30	0.30	0.30	6.90	6.89	5.83	5.84
H20	3.64	3.63	3.64	1.78	1.78	0.66	0.66	0.66	0.46	0.46	1.51	1.51
TI02	0.68	0.68	0.71	0.23	0.23	0.13	0.13	0.13	0.14	0.14	0.21	0.21
P205	0.13	0.13	0.14	0.05	0.05	0.03	0.03	0.03	0.02	0.02	0.08	0.08
MNO	0.21	0.21	0.22	0.02	0.02	0.02	0.02	0.02	0.05	0.05	0.02	0.02
ZR02												
CO2				0.03	0.60	0.02	0.40	0.40	0.03	0.03	0.06	0.06
SO3						0.62	0.62	0.62				
CL				0.03	0.03	0.03	0.03	0.03	0.01	0.01		
F	1.40		1.46	0.04							0.02	0.01
S												
CR203												
BA0												

NORMATIVE MINERALS												
Q	10.062	10.227	10.441	8.623	10.058	31.752	32.372	35.317	30.381	30.639	36.676	37.292
C				1.405	1.574	1.983	2.297	3.075	1.077	1.282	2.655	3.094
Z												
OR	0.710	0.710	0.737	3.129	3.126	1.769	1.766	1.766	40.759	40.724	34.477	34.493
AB	0.307		0.319	80.933	80.863	59.904	59.809	55.059	24.940	24.919	20.428	20.438
AN	39.943	40.066	41.450	0.463		0.866		0.398	0.564		1.194	

## NORMATIVE MINERALS

q	10.062	10.227	10.441	8.623	10.058	31.752	32.372	35.317	30.381	30.639	36.676	37.292
c				1.405	1.574	1.983	2.297	3.075	1.077	1.282	2.655	3.094
z												
OR	0.710	0.710	0.737	3.129	3.126	1.769	1.766	1.766	40.759	40.724	34.477	34.493
AB	0.307		0.319	80.933	80.863	59.904	59.809	55.059	24.940	24.919	20.428	20.438
AN	39.943	40.066	41.450	0.463		0.866		0.398	0.564		1.194	
LC												
NE												
P												

HL	2.312	2.378	2.400	0.049	0.049	0.049	0.049	0.049	0.016	0.016	0.016	0.016
TH												
NC												
AC												
NS												
KS												
WO	3.721	3.649	3.862									
EN	20.212	20.192	20.975	1.518					0.270	0.202	1.127	0.990
FS	14.022	14.008	14.551	0.754					1.013	1.012		
FO												
FA												
CS												
MT	3.486	3.483	3.618	0.652	0.651	0.525			0.143	0.143		
CM												
HM												
IL	1.294	1.293	1.343	0.436	0.436	0.536	0.897	0.246	0.262	0.262	1.308	1.308
TN						0.246					0.128	0.128
PF												
KU												
AP	0.309	0.308	0.320	0.118	0.118	0.071	0.071	0.071	0.047	0.047	0.144	0.144
FR				0.073							0.191	0.398
PR											0.027	
CC				0.068	0.061	0.045	0.143	0.143	0.067	0.057	0.137	
MG					0.626		0.208	0.208				0.116
SD					0.646		0.262	0.262				
TOTAL	96.379	96.314	100.016									
SALIC	53.334	53.381	55.347	98.222	98.226	99.343	99.217	99.344	99.539	99.513	98.491	98.400
FEMIC	43.044	42.933	44.669	94.603	95.670	97.422	97.390	97.720	97.737	97.580	95.430	95.316
				3.619	2.556	1.921	1.828	1.624	1.802	1.933	3.061	3.084
DI	7.286	7.146	7.561									
DIWO	3.721	3.649	3.862									
DIEN	2.105	2.064	2.184									
DIFS	1.460	1.432	1.515									
HY	30.669	30.704	31.827	2.272	0.018	0.497			1.283	1.214	1.127	0.990
HYEN	18.107	18.128	18.791	1.518		0.497			0.270	0.202	1.127	0.990
HYFS				0.754	0.018				1.013	1.012		
GL	12.562	12.576	13.036									
OLFO												
OLFA												
WOL												

USER DEFINED VARIABLES												
FEOT	11.260	11.260	11.260	1.205	1.205	1.070	1.070	1.070	0.770	0.770	1.210	1.210


SYMBOL	278 A *	278 B #	339 A *	339 B #	EC2-9 X	A2.II W	A3.III W	A1.I W	A1.I.S W	A1.IK W	25 A	46 A
SI02	52.10	52.10	72.90	72.90	37.51	31.17	34.98	53.70	53.70	53.70	55.90	48.80
AL2O3	16.60	16.60	13.50	13.50	2.41	6.25	10.80	11.16	11.16	11.16	20.50	17.70
FE2O3	8.30	8.30	1.90	1.90	1.83	3.22	1.42	3.10	3.10	3.10	2.65	7.16
FE0	0.80	0.20	0.08	0.08	8.95	9.64	21.33	1.21	1.21	1.21	1.58	1.80
MGO	4.50	4.50	0.36	0.36	48.59	19.90	19.30	6.44	6.44	6.44	0.87	3.11
CAO	6.60	6.60	1.20	1.20	0.07	17.76	0.43	3.46	3.46	3.46	2.98	6.84
NA2O	3.70	3.70	3.60	3.60	0.05	2.03	0.17	1.67	1.67	1.67	9.04	6.42
K2O	2.40	2.40	4.60	4.60	0.05	2.51	5.42	11.16	11.16	11.16	4.26	3.64
H2O	3.00	3.00	0.85	0.85	0.13	2.49	1.28	3.41	3.41	3.41	0.39	1.41
TI02	1.70	1.70	0.37	0.37	0.33	2.96	5.18	1.92	1.92	1.92	0.76	2.42
P2O5	0.81	0.81	0.10	0.10	0.17	1.69		1.75	1.75	1.75	0.17	0.56
MNO	0.10	0.10	0.04	0.04	0.17			0.04	0.04	0.04	0.20	0.22
ZR02											0.13	0.10
CO2	0.02	0.02	0.01	0.01				0.06	0.06	0.06	0.01	0.03
SO3								0.03	0.03	0.03		
CL								0.44	0.44	0.44		
F	0.03	0.03	0.02	0.02				0.04	0.04	0.04	0.11	0.11
S								0.81	0.81	0.81		
CR2O3								100.21	100.21	100.21	0.10	0.08
BAO											99.60	100.35
TOTAL (-O)	100.65	100.75	99.52	99.72	100.26	99.62	100.31	100.21	100.21	100.21		
ADJUSTED OXIDES												
SI02	51.76	51.71	73.25	73.10	37.41	31.29	34.87	53.59	53.59	53.59	56.12	48.63
AL2O3	16.49	16.48	13.56	13.54	2.40	6.27	10.77	11.14	11.14	11.14	20.58	17.64
FE2O3	8.25	8.24	1.91	1.91	1.83	3.23	1.42	3.09	3.09	3.09	2.66	7.13
FEO	0.79	0.20	0.08	0.08	8.93	9.68	21.26	1.21	1.21	1.21	1.59	1.79
MGO	4.47	4.47	0.36	0.36	48.46	19.98	19.24	6.43	6.43	6.43	0.87	3.10
CAO	6.56	6.55	1.21	1.20	0.07	17.83	0.43	3.45	3.45	3.45	2.99	6.82
NA2O	3.68	3.67	3.62	3.61	0.05	2.04	0.17	1.67	1.67	1.67	9.08	6.40
K2O	2.38	2.38	4.62	4.61	0.05	2.52	5.40	11.14	11.14	11.14	4.28	3.63
H2O	2.98	2.98	0.85	0.85	0.13	2.50	1.28	3.40	3.40	3.40	0.39	1.41
TI02	1.69	1.69	0.37	0.37	0.33	2.97	5.16	1.92	1.92	1.92	0.76	2.41
P2O5	0.80	0.80	0.10	0.10	0.17	1.70		1.75	1.75	1.75	0.17	0.56
MNO	0.10	0.10	0.04	0.04	0.17			0.04	0.04	0.04	0.20	0.22
ZR02											0.13	0.10
CO2	0.02	0.02	0.01	0.01				0.06	0.06	0.06	0.01	0.03
SO3								0.03	0.03	0.03		
CL								0.44	0.44	0.44		
F	0.03	0.03	0.02	0.02				0.04	0.04	0.04	0.11	0.11
S								0.81	0.81	0.81		
CR2O3								100.21	100.21	100.21	0.10	0.08
BAO											99.60	100.35
NORMATIVE MINERALS												
Q	4.094	4.090	31.745	31.681			3.860					
C			0.713	0.711	2.268							
Z											0.194	0.148
OR	14.091	14.077	27.313	27.259							25.274	21.434
AB	31.107	31.076	30.609	30.547							37.860	20.994
AN	21.459	21.438	5.180	5.170							2.787	8.697
LC												
NE											21.094	17.952
KP												



THE FOLLOWING POINTS WERE NOT PLOTTED  
BECAUSE THEY WOULD HAVE FALLEN ON A  
PREVIOUSLY PLOTTED POINT:  
MN06H 1165B 1101B 344 B 278 B 339 B


TERNARY RATIOS FOR Q, AB, CR

SAMPLE	R1	R2	R3	SYMBOL
MN06A	90.81	2.77	6.41	*
MN06B	93.51	0.00	6.49	#
MN06H	90.81	2.77	6.41	S
1201A	9.30	87.32	3.38	*
1201B	10.69	85.98	3.32	#
1165A	33.99	64.12	1.89	*
1165B	34.46	63.66	1.88	#
1165C	38.33	59.75	1.92	S
1101A	31.62	25.96	42.42	*
1101B	31.82	25.88	42.30	#
344 A	40.05	22.31	37.65	*
344 B	40.44	22.16	37.40	#
278 A	8.31	63.11	28.59	*
278 B	8.31	63.11	28.59	#
339 A	35.40	34.14	30.46	*
339 B	35.40	34.14	30.46	#
EC2-9	0.00	100.00	0.00	X
A2.1I	0.00	100.00	0.00	W
A311I	0.00	100.00	0.00	W
A1.1	0.00	0.00	100.00	W
A1.1S	0.00	0.00	100.00	W
A1.1K	0.00	0.00	100.00	W
25	0.00	59.97	40.03	A
46	0.00	49.48	50.52	A



TERNARY RATIOS FOR FEOT+MNO, NA2O+K2O, MGO

SAMPLE	R1	R2	R3	SYMBOL
MN06A	54.75	6.59	38.66	*
MN06B	54.75	6.59	38.66	#
MN06H	54.75	6.59	38.66	S
1201A	10.24	84.66	5.10	*
1201B	10.51	86.92	2.57	#
1165A	11.86	85.96	2.18	*
1165B	11.99	86.91	1.10	#
1165C	11.99	86.91	1.10	S
1101A	7.50	91.49	1.01	*
1101B	7.50	91.49	1.01	#
344 A	12.45	83.00	4.55	*
344 B	12.45	83.00	4.55	#
278 A	44.12	32.16	23.72	*
278 B	42.29	33.21	24.50	#
339 A	17.61	78.92	3.46	*
339 B	17.61	78.92	3.46	#
EC2-9	18.11	0.17	81.72	X
A2.II	33.91	12.28	53.82	W
A3.II	47.60	11.77	40.63	W
A1.I	17.33	55.04	27.63	W
A1.IS	17.33	55.04	27.63	W
A1.IK	17.33	55.04	27.63	W
25	22.71	72.54	4.75	A
46	39.12	46.50	14.38	A



THE FOLLOWING POINTS WERE NOT PLOTTED  
BECAUSE THEY WOULD HAVE FALLEN ON A  
PREVIOUSLY PLOTTED POINT:  
MN06B MN06H 1165C 1101B 344 B 339 B  
A1.IS A1.IK

## GNAP PROBLEM 1, MOLAR DATA

SYMBOL	MNO6A ★	MNO6B #	MNO6H S	1201A ★	1201B #	1165A ★	1165B #	1165C S	1101A ★	1101B #	344 A ★	344 B #
SI02	0.80	0.80	0.80	1.13	1.13	1.25	1.25	1.25	1.26	1.26	1.23	1.23
AL203	0.15	0.15	0.15	0.18	0.18	0.14	0.14	0.14	0.14	0.14	0.13	0.13
FE203	0.02	0.02	0.02	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.01	0.01
FE0	0.13	0.13	0.13	0.01	0.01	0.00	0.00	0.00	0.01	0.01	0.00	0.00
MGO	0.20	0.20	0.20	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.01
CA0	0.18	0.18	0.18	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01
NA20	0.02	0.02	0.02	0.15	0.15	0.12	0.12	0.12	0.05	0.05	0.04	0.04
K20	0.00	0.00	0.00	0.01	0.01	0.00	0.00	0.00	0.07	0.07	0.06	0.06
H20	0.20	0.20	0.20	0.10	0.10	0.04	0.04	0.04	0.03	0.03	0.08	0.08
Ti02	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
P205	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
MNO	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ZR02												
CO2				0.00	0.01	0.00	0.01	0.01	0.00	0.00	0.00	0.00
SO3						0.01	0.01	0.01				
CL	0.04	0.04	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
F				0.00								
S												
CR203												
BA0												
ADJUSTED OXIDES												
SI02	0.81	0.80	0.84	1.13	1.13	1.24	1.24	1.24	1.24	1.24	1.24	1.24
AL203	0.15	0.15	0.15	0.18	0.18	0.14	0.14	0.14	0.13	0.13	0.13	0.13
FE203	0.02	0.02	0.02	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.01	0.01
FE0	0.13	0.13	0.13	0.01	0.01	0.00	0.00	0.00	0.01	0.01	0.00	0.00
MGO	0.20	0.20	0.21	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.01	0.01
MCC	0.20	0.20	0.20	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01
CA0	0.18	0.18	0.19	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01
NA20	0.02	0.02	0.02	0.15	0.15	0.12	0.12	0.12	0.05	0.05	0.04	0.04
K20	0.00	0.00	0.00	0.01	0.01	0.00	0.00	0.00	0.07	0.07	0.06	0.06
H20	0.20	0.20	0.20	0.10	0.10	0.04	0.04	0.04	0.03	0.03	0.08	0.08
Ti02	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
P205	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
MNO	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
ZR02												
CO2				0.00	0.01	0.00	0.01	0.01	0.00	0.00	0.00	0.00
SO3						0.01	0.01	0.01				
CL	0.04	0.04	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00
F				0.00								
S												
CR203												
BA0												

NORMATIVE MINERALS										
Q	0.167	0.170	0.174	0.144	0.528	0.539	0.588	0.506	0.510	0.621
C				0.014	0.019	0.023	0.030	0.011	0.013	0.030
Z										
OR	0.001	0.001	0.001	0.006	0.003	0.003	0.003	0.073	0.073	0.062
AB	0.001	0.001	0.001	0.154	0.114	0.114	0.105	0.048	0.039	0.039
AN	0.144	0.144	0.149	0.002	0.003		0.001	0.002	0.004	

	0.020	0.020	0.021	0.000	0.000	0.000
HL	0.020	0.020	0.021	0.000	0.000	0.000

[illegible]

USER DEFINED VARIABLES				
FEOT	0.157	0.157	0.017	0.017
			0.015	0.011
			0.015	0.017
			0.015	0.011
			0.017	0.017

## GNAP PROBLEM 1, MOLAR DATA

SYMBOL	278 A ★	278 B #	339 A ★	339 B #	EC2-9 X	A2.II W	A3.III W	A1.I W	A1.IS W	A1.IK W	25 A	46 A
SiO2	0.87	0.87	1.21	1.21	0.62	0.52	0.58	0.89	0.89	0.89	0.93	0.81
Al2O3	0.16	0.16	0.13	0.13	0.02	0.06	0.11	0.11	0.11	0.11	0.20	0.17
Fe2O3	0.05	0.05	0.01	0.01	0.01	0.02	0.01	0.02	0.02	0.02	0.02	0.04
FeO	0.01	0.00	0.00	0.00	0.12	0.13	0.30	0.02	0.02	0.02	0.02	0.03
MgO	0.11	0.11	0.01	0.01	1.21	0.49	0.48	0.16	0.16	0.16	0.02	0.08
CaO	0.12	0.12	0.02	0.02	0.00	0.32	0.01	0.06	0.06	0.06	0.05	0.12
Na2O	0.06	0.06	0.06	0.06	0.00	0.03	0.00	0.03	0.03	0.03	0.15	0.10
K2O	0.03	0.03	0.05	0.05	0.00	0.03	0.06	0.12	0.12	0.12	0.05	0.04
H2O	0.17	0.17	0.05	0.05	0.01	0.14	0.07	0.19	0.19	0.19	0.02	0.08
TiO2	0.02	0.02	0.00	0.00	0.00	0.04	0.06	0.02	0.02	0.02	0.01	0.03
P2O5	0.01	0.01	0.00	0.00	0.00	0.01	0.06	0.01	0.01	0.01	0.00	0.00
MnO	0.00	0.00	0.00	0.00	0.00	0.01	0.06	0.00	0.00	0.00	0.00	0.00
ZrO2	0.00	0.00	0.00	0.00	0.00	0.01	0.06	0.00	0.00	0.00	0.00	0.00
CO2	0.00	0.00	0.00	0.00				0.00	0.00	0.00	0.00	0.00
SO3								0.00	0.00	0.00		
CL	0.00	0.00	0.00	0.00				0.02	0.02	0.02	0.01	0.01
F												
S												
CR2O3		0.00		0.01				0.00	0.00	0.00	0.00	0.00
BAO								0.01	0.01	0.01		
ADJUSTED OXIDES												
SiO2	0.86	0.86	1.22	1.22	0.62	0.52	0.58	0.89	0.89	0.89	0.93	0.81
Al2O3	0.16	0.16	0.13	0.13	0.02	0.06	0.11	0.11	0.11	0.11	0.20	0.17
Fe2O3	0.05	0.05	0.01	0.01	0.01	0.02	0.01	0.02	0.02	0.02	0.02	0.04
FeO	0.01	0.00	0.00	0.00	0.12	0.13	0.30	0.02	0.02	0.02	0.02	0.02
MgO	0.11	0.11	0.01	0.01	1.20	0.50	0.48	0.16	0.16	0.16	0.02	0.08
CaO	0.12	0.12	0.02	0.02	0.00	0.32	0.01	0.06	0.06	0.06	0.05	0.12
Na2O	0.06	0.06	0.06	0.06	0.00	0.03	0.00	0.03	0.03	0.03	0.15	0.10
K2O	0.03	0.03	0.05	0.05	0.00	0.03	0.06	0.12	0.12	0.12	0.05	0.04
H2O	0.17	0.17	0.05	0.05	0.01	0.14	0.07	0.19	0.19	0.19	0.02	0.08
TiO2	0.02	0.02	0.00	0.00	0.00	0.04	0.06	0.02	0.02	0.02	0.01	0.03
P2O5	0.01	0.01	0.00	0.00	0.00	0.01	0.06	0.01	0.01	0.01	0.00	0.00
MnO	0.00	0.00	0.00	0.00	0.00	0.01	0.06	0.00	0.00	0.00	0.00	0.00
ZrO2	0.00	0.00	0.00	0.00	0.00						0.00	0.00
CO2	0.00	0.00	0.00	0.00				0.00	0.00	0.00	0.00	0.00
SO3								0.00	0.00	0.00		
CL	0.00	0.00	0.00	0.00				0.02	0.02	0.02	0.01	0.01
F												
S				0.01								
CR2O3		0.00						0.00	0.00	0.00	0.00	0.00
BAO								0.01	0.01	0.01		
NORMATIVE MINERALS												
Q	0.068	0.068	0.528	0.527	0.022		0.038					
C			0.007	0.007								
Z								0.109	0.109	0.109	0.001	0.001
OR	0.025	0.025	0.049	0.049		0.002	0.008				0.045	0.039
AB	0.059	0.059	0.058	0.058			0.048				0.072	0.040
AN	0.077	0.077	0.019	0.019			0.003				0.010	0.031
LC							0.010					
NE					0.001	0.033	0.003				0.074	0.063
XP					0.001	0.027	0.010					
HL								0.000	0.000	0.000		

[illegible]

USER DEFINED VARIABLES										
FE0T	0.115	0.107	0.025	0.025	0.147	0.175	0.315	0.056	0.055	0.115

NE+.6\*AB

THE FOLLOWING POINTS WERE NOT PLOTTED  
BECAUSE THEY WOULD HAVE FALLEN ON A  
PREVIOUSLY PLOTTED POINT:  
1101B 344 B 339 A 339 B

SAMPLE	R1	R2	R3	SYMBOL
MN06A	0.03	53.33	46.59	*
MN06B	0.00	53.62	46.38	#
MN06H	0.08	53.33	46.59	S
1201A	29.06	66.04	4.90	*
1201B	28.76	71.21	0.03	#
1165A	10.58	88.84	0.57	*
1165B	10.48	89.52	0.00	#
1165C	9.06	90.67	0.27	S
1101A	5.06	93.56	1.38	*
1101B	5.03	93.69	1.28	#
344 A	3.54	95.19	1.27	*
344 B	3.49	95.40	1.10	#
278 A	15.71	51.48	32.81	*
278 B	14.93	50.17	34.90	#
339 A	5.88	92.99	1.13	*
339 B	5.88	92.99	1.13	#
EC2-9	0.13	0.00	99.87	X
A2.11	11.24	-0.00	86.76	W
A3.11	0.78	-0.00	99.22	W
A1.1	0.00	17.51	82.49	W
A1.1S	0.00	17.84	82.16	W
A1.1K	0.00	17.84	82.16	W
25	80.28	19.72	0.00	A
46	83.05	15.25	1.70	A

OL+.75\*HY

Q+.4\*AB+.25\*HY

AL2O3

THE FOLLOWING POINTS WERE NOT PLOTTED  
BECAUSE THEY WOULD HAVE FALLEN ON A  
PREVIOUSLY PLOTTED POINT:  
MN06B MN06H 1101A 1101B 278 B 339 B  
A1.IS A1.IK

TERNARY RATIOS FOR AL2O3,NA2O+K2O,CAO

SAMPLE	R1	R2	R3	SYMBOL
MN06A	42.06	6.26	51.68	*
MN06B	42.06	6.26	51.68	#
MN06H	42.06	6.26	51.68	S
1201A	51.55	47.14	1.31	*
1201B	51.96	47.51	0.53	#
1165A	51.88	46.54	1.58	*
1165B	52.29	46.91	0.80	#
1165C	52.29	46.91	0.80	S
1101A	51.80	46.97	1.23	*
1101B	51.80	46.97	1.23	#
344 A	54.67	42.04	3.29	*
344 B	55.59	42.74	1.67	#
278 A	44.52	23.29	32.18	*
278 B	44.52	23.29	32.18	#
339 A	50.78	41.01	8.21	*
339 B	50.78	41.01	8.21	#
EC2-9	90.14	5.10	4.76	X
A2.II	14.01	13.58	72.41	W
A3.II	60.92	34.67	4.41	W
A1.I	34.58	45.93	19.49	W
A1.IS	34.58	45.93	19.49	W
A1.IK	34.58	45.93	19.49	W
25	45.15	42.91	11.93	A
46	39.65	32.49	27.86	A

NA2O+K2O

CAO

ERROR MESSAGES AND RUN CONDITIONS

SAMPLE MND6B CONTAINS AN EXCESS OF 0.09 WEIGHT PERCENT CL  
BEYOND THAT USED IN NORMATIVE CALCULATIONS

SAMPLE MND6H--NORM COMPUTED ON WATER FREE BASES.

SAMPLE 1165R CONTAINS AN EXCESS OF 0.13 WEIGHT PERCENT CO2  
BEYOND THAT USED IN NORMATIVE CALCULATIONS

SAMPLE 1165C--NA2CO3 CALCULATION ATTEMPTED.

SAMPLE 1101R CONTAINS AN EXCESS OF 0.04 WEIGHT PERCENT F  
BEYOND THAT USED IN NORMATIVE CALCULATIONS

SAMPLE 344 R CONTAINS AN EXCESS OF 0.09 WEIGHT PERCENT P2O5  
BEYOND THAT USED IN NORMATIVE CALCULATIONS

SAMPLE 279 R CONTAINS AN EXCESS OF 0.06 WEIGHT PERCENT CR2O3  
BEYOND THAT USED IN NORMATIVE CALCULATIONS

SAMPLE 339 R CONTAINS AN EXCESS OF 0.09 WEIGHT PERCENT S  
BEYOND THAT USED IN NORMATIVE CALCULATIONS

SAMPLE EC2-9 CONTAINS AN EXCESS OF 0.12 WEIGHT PERCENT P2O5  
BEYOND THAT USED IN NORMATIVE CALCULATIONS

SAMPLE EC2-9 CONTAINS TOO LITTLE SIO2 TO COMPUTE NORM  
SIO2 DEFICIENCY IS EQUIVALENT TO AN EXCESS OF MGO OF 2.71 WT %  
AND AN EXCESS OF FEO OF 0.45 WT %.

SAMPLE A2.II CONTAINS TOO LITTLE SIO2 TO COMPUTE NORM  
SIO2 DEFICIENCY IS EQUIVALENT TO AN EXCESS OF MGO OF 1.87 WT %  
AND AN EXCESS OF FEO OF 0.52 WT %.

SAMPLE A1.IS--BAO ADDED TO NA2O.

SAMPLE A1.IK--BAO ADDED TO K2O.

GNAP PROBLEM 2

BAPPV OFFINED AS 10000\*BAO

UPPM DEFINED AS 10000\*NIO

THPPM OFFINED AS 10000\*CR2O3

GNAP PROBLEM 2

SYMBOL	1 B	2 B	3 B	4 B	5 B	6 B	7 B	8 B	9 B	10 B	11 B	12 B
ADJUSTED OXIDES												
SI02	66.98	69.15	68.22	71.34	72.62	72.66	73.04	72.60	72.83	73.79	73.31	74.25
AL2O3	15.90	15.35	15.44	14.89	14.26	14.63	14.32	15.20	14.53	13.99	13.50	13.94
FE2O3	1.40	1.82	1.00	1.11	1.11	0.61	1.21	0.33	0.76	0.51	0.27	0.65
FE0	2.60	1.01	2.79	0.72	1.11	1.31	0.24	0.84	1.12	0.89	2.30	0.53
MGO	1.01	1.01	1.10	0.56	0.27	0.39	0.40	0.40	0.41	0.28	0.13	0.18
CA0	2.80	2.42	2.89	2.21	0.92	0.75	0.51	2.20	0.75	0.94	0.97	0.74
NA20	4.00	3.63	4.08	4.23	3.54	3.53	3.73	4.20	3.32	3.34	3.00	3.23
K20	3.10	4.44	2.79	3.82	5.06	5.05	5.04	3.40	5.36	5.27	5.70	5.66
H20	0.75	0.50	0.61	0.66	0.66	0.71	1.24	0.38	0.58	0.64	0.51	0.57
TIO2	0.72	0.32	0.64	0.20	0.15	0.20	0.14	0.19	0.12	0.19	0.10	0.08
P2O5	0.24	0.14	0.19	0.11	0.10	0.02	0.01	0.05	0.06	0.05	0.07	0.08
MNO	0.03		0.03		0.02	0.05	0.02	0.01	0.03	0.02	0.02	0.02
CL	0.05	0.04	0.07	0.03	0.03	0.02	0.02	0.04	0.03			0.02
F							0.02		0.02			
CO2	0.02	0.03	0.03	0.01	0.08	0.02		0.06	0.01	0.02	0.08	0.02
NIO	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
CR2O3	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.01	0.01	0.00	0.00
BA0	0.18	0.13	0.15	0.10	0.06	0.05	0.05	0.11	0.07	0.05	0.03	0.04

NORMATIVE MINERALS

Q	23.787	24.904	25.329	26.922	30.499	30.031	30.474	29.824	30.551	31.453	30.401	32.151
C	1.444	0.534	0.974	0.043	1.725	2.091	1.864	0.852	2.111	1.200	0.967	1.402
OR	18.314	26.249	16.479	22.595	29.884	29.816	29.806	20.091	31.650	31.146	33.689	33.430
AB	33.468	30.455	34.037	35.536	29.730	29.737	31.434	35.242	27.870	28.303	25.390	27.205
AN	12.527	11.140	13.173	10.373	3.501	3.543	2.429	10.411	3.295	4.312	3.899	3.074
HL	0.082	0.067	0.115	0.050	0.050	0.033	0.033	0.066	0.050			0.033
EN	2.988	2.514	2.728	1.403	0.680	0.980	1.005	0.996	1.024	0.707	0.324	0.453
FS	2.481		3.297	0.031	0.908	1.665		0.974	1.287	0.934	3.874	0.332
MT	2.025	2.311	1.444	1.605	1.613	0.878	0.431	0.478	1.105	0.735	0.392	0.937
CM	0.006	0.007	0.006	0.004	0.010	0.010	0.008	0.001	0.009	0.010	0.003	0.006
HM		0.223					0.913					
IL	1.367	0.614	1.211	0.382	0.288	0.383	0.268	0.361	0.229	0.366	0.190	0.153
AP	0.568	0.335	0.448	0.262	0.240	0.048	0.024	0.118	0.143	0.120	0.166	0.191
FR							0.040		0.030			
CC	0.045	0.069	0.068	0.023	0.184	0.046		0.136	0.023	0.046	0.182	0.046
TOTAL	99.107	99.421	99.309	99.280	99.311	99.261	98.730	99.552	99.374	99.331	99.476	99.414
SALIC	89.622	93.348	90.106	95.518	95.389	95.251	96.041	96.486	95.525	96.413	94.346	97.295
FERIC	9.485	6.073	9.203	3.761	3.922	4.011	2.689	3.065	3.849	2.918	5.131	2.119

USER DEFINED VARIABLES

BAPPM	*****	*****	*****	974.000	583.000	532.000	459.000	*****	698.000	513.000	271.000	388.000
UPPM	1.010	2.270	0.860	1.770	12.300	11.000	10.000	0.960	9.940	6.920	17.200	2.620
THPPM	38.800	45.400	43.600	29.200	64.300	68.900	55.000	4.670	61.300	68.500	23.400	38.230

GNAP PROBLEM 2

BA0 DEFINED AS 1.1168\*BA0  
Ni0 DEFINED AS 0.0  
CR203 DEFINED AS 0.0

## GNAP PROBLEM 2

SYMBOL	1	2	3	4	5	6	7	8	9	10	11	12
	B	B	B	B	B	B	B	B	B	B	B	B
SI02	67.00	68.50	68.50	70.90	71.80	72.00	72.40	72.60	72.61	72.80	73.30	73.50
AL2O3	15.90	15.20	15.50	14.80	14.10	14.50	14.20	15.20	14.49	13.80	13.50	13.80
FE2O3	1.40	1.80	1.00	1.10	1.10	0.60	1.20	0.33	0.76	0.50	0.27	0.64
FeO	2.60	1.00	2.80	0.72	1.10	1.30	0.24	0.84	1.12	0.88	2.50	0.52
MgO	1.20	1.00	1.10	0.56	0.27	0.39	0.40	0.40	0.41	0.28	0.13	0.18
CaO	2.80	2.40	2.90	2.20	0.91	0.74	0.51	2.20	0.75	0.93	0.73	0.73
Na2O	4.00	3.60	4.10	4.20	3.50	3.50	3.70	4.20	3.31	3.30	3.00	3.20
K2O	3.10	4.40	2.80	3.80	5.00	5.00	5.00	3.40	5.34	5.20	5.70	5.60
H2O	0.79	0.50	0.61	0.66	0.65	0.70	1.23	0.38	0.58	0.63	0.51	0.56
TiO2	0.72	0.32	0.64	0.20	0.15	0.20	0.14	0.19	0.12	0.19	0.10	0.08
P2O5	0.24	0.14	0.19	0.11	0.10	0.02	0.01	0.05	0.06	0.05	0.07	0.08
MnO	0.03		0.03		0.02	0.05	0.02	0.01	0.03	0.02	0.02	0.02
CL	0.05	0.04	0.07	0.03	0.03	0.02	0.02	0.04	0.03	0.02		0.02
F							0.02		0.02			
CO2	0.02	0.03	0.03	0.01	0.08	0.02		0.06	0.01	0.02	0.08	0.02
BAO	0.21	0.14	0.17	0.11	0.07	0.06	0.05	0.13	0.08	0.06	0.03	0.04
TOTAL (-O)	100.04	99.06	100.42	99.39	98.87	99.09	99.13	100.02	99.70	98.66	99.98	98.99
ADJUSTED OXIDES												
SI02	66.97	69.15	68.21	71.33	72.62	72.66	73.04	72.59	72.83	73.79	73.31	74.25
AL2O3	15.89	15.34	15.44	14.89	14.26	14.63	14.32	15.20	14.53	13.99	13.50	13.94
FE2O3	1.40	1.82	1.00	1.11	1.11	0.61	1.21	0.33	0.76	0.51	0.27	0.65
FeO	2.60	1.01	2.79	0.72	1.11	1.31	0.24	0.84	1.12	0.89	2.30	0.53
MgO	1.20	1.01	1.10	0.56	0.27	0.39	0.40	0.40	0.41	0.28	0.13	0.18
CaO	2.80	2.42	2.89	2.21	0.92	0.75	0.51	2.20	0.75	0.94	0.97	0.74
Na2O	4.00	3.63	4.08	4.23	3.54	3.53	3.73	4.20	3.32	3.34	3.00	3.23
K2O	3.10	4.44	2.79	3.82	5.06	5.05	5.04	3.40	5.36	5.27	5.70	5.66
H2O	0.79	0.50	0.61	0.66	0.66	0.71	1.24	0.38	0.58	0.64	0.51	0.57
TiO2	0.72	0.32	0.64	0.20	0.15	0.20	0.14	0.19	0.12	0.19	0.10	0.08
P2O5	0.24	0.14	0.19	0.11	0.10	0.02	0.01	0.05	0.06	0.05	0.07	0.08
MnO	0.03		0.03		0.02	0.05	0.02	0.01	0.03	0.02	0.02	0.02
CL	0.05	0.04	0.07	0.03	0.03	0.02	0.02	0.04	0.03	0.02		0.02
F							0.02		0.02			
CO2	0.02	0.03	0.03	0.01	0.08	0.02		0.06	0.01	0.02	0.08	0.02
NiO												
CR2O3												
BAO	0.21	0.14	0.17	0.11	0.07	0.06	0.05	0.13	0.08	0.06	0.03	0.04
NORMATIVE MINERALS												
Q	23.764	24.890	25.310	26.910	30.492	30.025	30.471	29.810	30.542	31.446	30.399	32.146
C	1.429	0.524	0.962	0.035	1.720	2.087	1.860	0.844	2.105	1.196	0.965	1.399
OR	18.311	26.247	16.477	22.593	29.885	29.816	29.806	20.088	31.650	31.146	33.689	33.430
AB	33.462	30.451	34.032	35.533	29.731	29.737	31.434	35.238	27.869	28.304	25.390	27.205
AN	12.564	11.166	13.202	10.393	3.513	3.554	2.439	10.434	3.310	4.323	3.905	3.082
HL	0.082	0.067	0.115	0.050	0.050	0.033	0.033	0.066	0.050	0.707	0.324	0.033
EN	2.987	2.514	2.728	1.403	0.680	0.980	1.005	0.996	1.024	0.939	3.873	0.453
FS	2.484		3.301	0.084	0.911	1.669		0.975	1.290	0.735	0.392	0.335
MT	2.029	2.317	1.444	1.605	1.613	0.878	0.437	0.478	1.105			0.937
HM	0.219						0.909					
IL	1.367	0.613	1.210	0.382	0.288	0.383	0.268	0.361	0.229	0.366	0.190	0.153
AP	0.568	0.335	0.448	0.262	0.240	0.048	0.024	0.118	0.143	0.120	0.166	0.191
FR							0.040		0.030			
CC	0.045	0.069	0.068	0.023	0.184	0.046		0.136	0.023	0.046	0.182	0.046
TOTAL	99.093	99.411	99.298	99.272	99.306	99.257	98.727	99.544	99.369	99.327	99.475	99.411

SALIC 89.613 93.344 90.099 95.514 95.390 95.253 96.044 96.479 95.525 96.415 94.348 97.295  
FEMIC 9.480 6.067 9.199 3.759 3.916 4.004 2.683 3.065 3.844 2.912 5.126 2.116

D.I. 75.537 81.588 75.819 85.036 90.107 89.578 91.711 85.136 90.061 90.896 89.479 92.780

BARTH'S CATIONS

SI 63.00 64.80 64.08 66.73 68.34 68.29 68.90 67.71 68.47 69.42 69.20 69.82  
AL 17.62 16.95 17.09 16.42 15.82 16.21 15.93 16.71 16.10 15.51 15.02 15.45  
FE+3 0.99 1.28 0.70 0.78 0.79 0.43 0.86 0.23 0.54 0.36 0.19 0.46  
FE+2 2.04 0.79 2.19 0.57 0.88 1.03 0.19 0.65 0.88 0.70 1.82 0.41  
MG 1.68 1.41 1.53 0.79 0.38 0.55 0.57 0.56 0.58 0.40 0.18 0.25  
CA 2.82 2.43 2.91 2.22 0.93 0.75 0.52 2.20 0.76 0.95 0.98 0.74  
NA 7.29 6.60 7.44 7.66 6.46 6.44 6.83 7.59 6.05 6.10 5.49 5.89  
K 3.72 5.31 3.34 4.56 6.07 6.05 6.07 4.04 6.42 6.33 6.86 6.79  
H 4.96 3.15 3.81 4.14 4.13 4.43 7.81 2.36 3.65 4.01 3.21 3.55  
TI 0.51 0.23 0.45 0.14 0.11 0.14 0.10 0.13 0.09 0.14 0.07 0.06  
P 0.19 0.11 0.15 0.09 0.08 0.02 0.01 0.04 0.05 0.04 0.06 0.06  
MN 0.02 0.04 0.02 0.01 0.02 0.04 0.02 0.01 0.02 0.02 0.02 0.02  
C 0.03 0.04 0.04 0.01 0.10 0.03 0.03 0.08 0.01 0.03 0.10 0.03  
CL 0.08 0.06 0.11 0.05 0.05 0.03 0.03 0.06 0.05 0.03 0.03 0.03  
F 0.08 0.05 0.06 0.04 0.02 0.02 0.02 0.05 0.06 0.02 0.01 0.02  
GA 0.08 0.05 0.06 0.04 0.02 0.02 0.02 0.05 0.03 0.02 0.01 0.02


NIGGLI VALUES

AL\* 40.13 41.54 40.02 43.87 46.01 47.19 48.02 46.75 47.09 47.24 44.47 48.39  
FM\* 21.60 17.07 20.65 11.39 12.00 11.94 9.85 8.12 11.83 8.98 13.07 7.15  
C\* 13.19 12.19 13.90 12.07 5.54 4.51 3.25 12.56 4.60 5.92 5.88 4.75  
ALK\* 25.08 29.20 25.24 32.67 36.45 36.35 38.88 32.57 36.48 37.85 36.58 39.71  
SI 286.97 317.68 300.10 356.62 397.59 397.67 415.44 378.93 400.43 422.93 409.78 437.32  
RI 2.32 1.12 2.11 0.76 0.62 0.83 0.60 0.75 0.50 0.83 0.42 0.36  
P 0.44 0.27 0.35 0.23 0.23 0.05 0.02 0.11 0.14 0.12 0.17 0.20  
H 11.29 7.73 8.91 11.07 12.00 12.89 23.54 6.62 10.67 12.21 9.51 11.11  
K 0.34 0.45 0.31 0.37 0.48 0.48 0.47 0.35 0.51 0.51 0.56 0.54  
MG 0.35 0.40 0.34 0.37 0.19 0.27 0.35 0.38 0.28 0.27 0.08 0.22  
SI' 200.31 216.80 200.95 230.68 245.79 245.42 255.53 230.28 245.92 251.41 246.33 258.84  
QZ 86.66 100.88 99.15 125.93 151.80 152.25 159.91 148.65 154.52 171.51 163.44 178.48


AL2O3/SIO2 0.237 0.222 0.226 0.209 0.196 0.201 0.196 0.209 0.200 0.190 0.184 0.188  
FeO/Fe2O3 1.857 0.556 2.800 0.655 1.000 2.167 0.200 2.545 1.474 1.760 8.519 0.813

USER DEFINED VARIABLES

BAPP\* \*\*\*\*\* 974.000 583.000 532.000 459.000 \*\*\*\*\* 513.003 271.000 388.000  
UPPM 1.010 2.270 0.860 1.770 12.300 11.000 10.000 0.960 9.940 6.920 17.200 2.620  
THPP\* 38.800 45.400 43.600 29.200 64.300 68.900 55.000 4.670 61.300 68.500 23.400 38.200




GNAP PROBLEM 2



TERNARY RATIOS FOR UPPM, THPPM, 0.83\*K20

SAMPLE	R1	R2	R3	SYMBOL
1	2.38	91.55	6.07	B
2	4.42	88.46	7.12	B
3	1.84	93.19	4.97	B
4	5.19	85.57	9.24	B
5	15.23	79.63	5.14	B
6	13.09	81.98	4.94	B
7	14.46	79.54	6.00	B
8	11.36	55.25	33.39	B
9	13.14	81.01	5.86	B
10	8.68	85.91	5.41	B
11	37.94	51.62	10.44	B
12	5.76	84.02	10.22	B
DUM1	0.00	0.00	100.00	
DUM2	21.06	73.70	5.24	



## GNAP PROBLEM 2, MOLAR DATA

PERAL DEFINED AS AL2O3/(NA2O+K2O+CAO)

## GNAP PROBLEM 2, MOLAR DATA

EVALUATION OF PERAL

ID	VALUE	ID	VALUE	ID	VALUE	ID	VALUE	ID	VALUE
1	1.058	2	1.010	3	1.030	4	0.985	5	1.099
7	1.143	8	1.042	9	1.151	10	1.083	11	1.049
DUMM1	0.000	DUMM2	0.000					12	1.091

## Main Program

(75)

```

53      5  5,'NOPP','S  '  '  '  '  3,'PPS  '  '  '  '  '
54      6  7,'SETE','LAGS'  '  '  '  0,'  '  '  '  '  '
55 C----- OPEN FILES * * * * *
56      CALL FILES (INPUT,2)
57      CALL FILES (LISTP,1)
58      CALL FILES (LISTTY,3)
59      CALL FILES (LISTERR,6)
60 C----- INITIALIZE CONSTANTS TO DEFAULT VALUES * * * * *
61      110 CNT=0
62      NCS=1
63      NUM=66
64      NOX=21
65      CALL MOVE(DUMMY,FARMAT,15)
66      DECODE (DEFTLE,115) (HEADG(I),I=1,80)
67      115 FORMAT (80A1)
68      DO 117 I=81,92
69      117 HEADG(I)=BLANK
70      PRINTER=.TRUE.
71      NORMAL=.TRUE.
72      STORE=.FALSE.
73      CONVTD=.FALSE.
74      DO 118 I=1,5
75      118 SWITCH(I)=.FALSE.
76      SCALE=1.0
77      DO 120 I=1,21
78      120 ORDER(I)=I
79 C----- ZERO OUT ALL VALUES CALCULATED BY SUBROUTINE NORM * * * * *
80 C      14058= 99*(1+21+81+12+21+2+2+2)= 99*142
81      DO 130 I=1,14058
82      130 AREA(I)=0.0
83      910 DEFINE = .FALSE.
84      140 LSTMT=0
85      150 PT=PT+1
86      IF (PT.LE.80) GO TO 210
87      PT=1
88      READ (INPUT,740,END=690) CARD
89      IF(NORMAL) GO TO 159
90      IF(NOTEQ(CARD,'LAST',4)) GO TO 151
91      NORMAL=.TRUE.
92      PT=80
93      GO TO 910
94      151 IF(NOTEQ(CARD,'SYMBOL ',7)) GO TO 152
95      RASSYM=CARD(8)
96      PT=80
97      GO TO 910
98      152 CNT=CNT+1
99      IF(CNT.LE. 99) GO TO 153
100     CNT= 99
101     WRITE (LISTTY,750)
102     WRITE (LISTERR,750)
103     153 SYM(CNT)=RASSYM
104     GO TO 201
105     150 IF (NOTEQ(CARD,'TITLE',5)) GO TO 170
106     DO 160 J=1,75
107     160 HEADG(J)=CARD(J+5)
108     DO 165 J=76,92
109     165 HEADG(J)=BLANK
110     PT=90
111     GO TO 910
112     170 IF (NOTEQ(CARD,'STO',3)) GO TO 180

```

```

113      STORE=.TRUE.
114      GO TO 190
115      180 IF (NOTEQ(CARD,'NRM',3)) GO TO 210
116 C----- NORM PROCESSOR * * * * *
117      190 CNT=CNT+1
118          IF (CNT.LE. 99) GO TO 200
119          CNT= 99
120          WRITE (LISTTY,750)
121          WRITE (LISTERR,750)
122      200 SYM(CNT)=CARD(4)
123      201 CALL NORM (CARD,VALUES(1,CNT),FARMAT,NCS,TTDI(CNT),RATIOS(1,CNT),
124          1 TOTALS(1,CNT),TYPES(1,CNT),PARTHS(1,CNT),NIGGLI(1,CNT),
125          2 IDENT(1,CNT),NOX,ORDER,ADJUST(1,CNT),NAMES)
126          PT=80
127          GO TO 910
128 C----- BUILD COMMAND * * * * *
129      210 NEXT=CARD(PT)
130          IF (NEXT.EQ.SEMIC) GO TO 230
131          IF (NEXT.EQ.BLANK) GO TO 150
132          LSTMT=LSTMT+1
133          IF (LSTMT.GT.160) GO TO 220
134          STMT(LSTMT)=NEXT
135          GO TO 150
136      220 WRITE (LISTERR,760) STMT
137          WRITE (LISTTY,760) STMT
138          GO TO 910
139 C----- STATEMENT BUILT. DETERMINE TYPE AND PROCESS * * * * *
140      230 IF (NOTEQ(STMT,'CLEAR',5)) GO TO 240
141 C----- CLEAR STORAGE PROCESSOR * * * * *
142          IF (LSTMT.GT.12) WRITE (LISTERR,900) (STMT(I),I=1,LSTMT)
143          CALL FILES (LISTERR,7)
144          CALL FILES (LISTERR,8)
145          CALL FILES (LISTERR,6)
146          GO TO 110
147      240 IF (NOTEQ(STMT,'SCALE=',6)) GO TO 270
148 C----- SET THE SCALE FOR THE CALCOMP PLOTTER * * * * *
149          IF (LSTMT.GT.14) WRITE (LISTERR,900) (STMT(I),I=1,LSTMT)
150          IF (PRNTER) GO TO 260
151          SCALE=CONV(STMT,7,LSTMT,0,ERR)
152          IF (ERR.OR.SCALE.GT.3.0) GO TO 250
153          CALL FACTOR (SCALE)
154          GO TO 910
155      250 WRITE (LISTERR,700)
156          WRITE (LISTTY,700)
157          GO TO 910
158      260 WRITE (LISTERR,710)
159          WRITE (LISTTY,710)
160          GO TO 910
161      270 IF (NOTEQ(STMT,'OXIDES',6)) GO TO 320
162 C----- OXIDES AND ORDER STATEMENT PROCESSOR * * * * *
163          IF (LSTMT.GT.95) WRITE (LISTERR,900) (STMT(I),I=1,LSTMT)
164          J=7
165          LSTMT=LSTMT-6
166          NOX=0
167 C----- DETERMINE LENGTH (I) OF NEXT OXIDE NAME * * * * *
168      280 I=INDEX(STMT(J),'',LSTMT)-1
169          IF (I.LT.1) I=LSTMT
170          RNAME(1)=BLANK
171          RNAME(2)=BLANK
172          I=MIN0(I,5)

```

```

173      ENCODE(RNAME,740) (STMT(J+L-1),L=1,I)
174 C      FIND NAME IN LIST OF OXIDES.
175      DO 300 L=1,21
176      300 IF (RNAME(1).EQ.NAMES(1,L).AND.RNAME(2).EQ.NAMES(2,L)) GO TO 310
177 C----- NAME NOT FOUND, PRINT ERROR MESSAGE AND TERMINATE RJN * * * * *
178      WRITE (LISTERR,890) (NAMES(1,I),NAMES(2,I),I=1,21),RNAME
179      WRITE (LISTTY,890) (NAMES(1,I),NAMES(2,I),I=1,21),RNAME
180      GO TO 690
181 C----- INCREASE NUMBER OF OXIDES AND STORE ORDER * * * * *
182      310 NOX=NOX+1
183      ORDER(NOX)=L
184      J=J+I+1
185      LSTMT=LSTMT-I-1
186      IF (LSTMT.GT.0) GO TO 280
187      GO TO 910
188 C----- NORM, H2O, BARITE, KSPAR, CANCRINITE STATEMENT PROCESSOR * * * * *
189      320 DO 325 I=1,11
190      IF (NOTEQ(STMT,COMMAND(2,I),COMMAND(1,I))) GO TO 325
191      IF (LSTMT.GT.COMMAND(1,I)+1) WRITE (LISTERR,900)(STMT(I),I=1,LSTMT)
192      IF (I.GT.10) GO TO 323
193      J=(I+1)/2
194      IF (MOD(I,2).EQ.0) SWITCH(J)=.TRUE.
195      IF (MOD(I,2).NE.0) SWITCH(J)=.FALSE.
196      GO TO 910
197      323 DO 324 J=1,5
198      324 SWITCH(J)=.FALSE.
199      GO TO 910
200      325 CONTINUE
201      IF (NOTEQ(STMT,'DEVICE',6)) GO TO 370
202 C----- PLOTTING DEVICE SELECTION COMMAND PROCESSOR * * * * *
203      IF (LSTMT.GT.14) WRITE (LISTERR,900) (STMT(I),I=1,LSTMT)
204      IF (NOTEQ(STMT(7),'CALCOMP',7).AND.NOTEQ(STMT(8),'CALCOMP',7)) GO
205      1 TO 360
206      PRNTER=.FALSE.
207      IF (SWCC) GO TO 350
208      CALL PLOTS (BUFFER,1000,15)
209      SWCC=.TRUE.
210      350 CALL PLOT (2.0,1.12,-3)
211      GO TO 910
212      360 PRNTER=.TRUE.
213      GO TO 910
214      370 IF (NOTEQ(STMT,'SUMMARY',8)) GO TO 375
215 C----- SUMMARY PRINT PROCESSOR * * * * *
216      IF (LSTMT.GT.74) WRITE (LISTERR,900) (STMT(I),I=1,LSTMT)
217      LSTMT=LSTMT-8
218      CALL SUMPNT (STMT(9),LSTMT,CNT,IDENT,NAMES,NOX,ORDER,SYM,NUM,
219      1 SWITCH(1))
220      GO TO 910
221      375 CONTINUE
222      IF (NOTEQ(STMT,'MODIFY',6)) GO TO 410
223 C----- MODIFY COMMAND PROCESSOR * * * * *
224      IF (NOTEQ(STMT(7),'FORMAT',6)) GO TO 390
225      DO 376 J=1,60
226      376 FORMAT(J)=BLANK
227      IF (NOTEQ(STMT(14),'STATPAC',7)) GO TO 378
228      DECODE(SPEMT,740) FORMAT
229      DO 377 I=1,15
230      377 FARMAT(I)=SPEMT(I)
231      NORMAL=.FALSE.
232      RASSYM=ASK

```

```

233      NCS=NOX/10
234      IF (10+NCS.NE.NOX) NCS=NCS+1
235      IF (LSTMT.FQ.20) GO TO 910
236      I=14
237      J=30
238      CALL MOVE (STMT(22),STMT(7),LSTMT-21)
239      LSTMT=LSTMT-15
240      GO TO 379
241 378 IF (INDEX (STMT,' ',-LSTMT).EQ.0) GO TO 380
242      I=INDEX (STMT,' ',LSTMT)
243      IF (I.EQ.0) GO TO 380
244      J=INDEX (STMT,' ',-LSTMT)
245      CALL MOVE (STMT(I),FORMAT,J-I+1)
246      IF (J.NF.LSTMT) GO TO 381
247      ENCODE (FARMAT,740) FORMAT
248      GO TO 910
249 381 CALL MOVE (STMT(J+2),STMT(7),LSTMT-J-1)
250      LSTMT=LSTMT-J+5
251 379 CALL MOVE (FORMAT,BUFFER,J-I+1)
252      CALL MOVE (STMT(11),FORMAT(2),LSTMT-10)
253      CALL MOVE (BUFFER,FORMAT(LSTMT-8),J-I+1)
254      FORMAT(LSTMT-7+J-I)=FORMAT(LSTMT-8+J-I)
255      ENCODE (FARMAT,740) FORMAT
256      IF (.NOT.NORMAL) GO TO 910
257      GO TO 390
258 380 WRITE (LISTERR,770) CARD
259      WRITE (LISTTY,770) CARD
260      GO TO 910
261 390 IF (NOTEQ (STMT(7),'NCS=',4)) GO TO 400
262      NCS=CONV (STMT,11,LSTMT,0,FRR)+0.1
263      IF (ERR) GO TO 400
264      GO TO 910
265 400 WRITE (LISTERR,780) CARD
266      WRITE (LISTTY,780) CARD
267      NCS=1
268      GO TO 910
269 410 I=INDEX (STMT,' ',LSTMT)
270      IF (I.EQ.0) GO TO 480
271 C----- DEFINITION PROCESSOR * * * * *
272      LSTMT=LSTMT
273      J=MIN0 (8,I-1)
274      RNAME(1)=BLANK
275      RNAME(2)=BLANK
276      ENCODE (RNAME,740) (STMT(L),L=1,J)
277      LSTMT=LSTMT-I
278      K=I+1
279      L=NUM
280      DO 430 J=1,NUM
281      IF (RNAME(1).EQ.NAMES(1,J).AND.RNAME(2).EQ.NAMES(2,J)) GO TO 450
282 430 CONTINUE
283      J=NUM+1
284      NUM=NUM+1
285      IF (J.LE.81) GO TO 440
286      NUM=81
287      WRITE (LISTERR,790) RNAME
288      WRITE (LISTTY,790) RNAME
289      GO TO 910
290 440 NAMES(1,J)=RNAME(1)
291      NAMES(2,J)=RNAME(2)
292 450 CALL PARSE (STMT(K),LSTMT,NAMES,L,ERR,LISTTY,LISTERR)

```

```

293 IF (FPR) GO TO 910
294 DO 460 I=1,CNT
295 460 VALUES(J,I)=EVAL(VALUES(1,I))
296 IF (DEFINE) GO TO 470
297 WRITE (LISTPR,TFORM) HEADG
298 DEFINE = .TRUE.
299 470 WRITE (LISTPR,720) RNAME,(STMT(I),I=K,LSTM)
300 GO TO 140
301 480 IF (NOTEQ(STMT,'RECALC',6)) GO TO 500
302 C---- NORM RECALCULATION PROCESSOR * * * * *
303 IF (LSTM.GT.16) WRITE (LISTERR,900) (STMT(I),I=1,LSTM)
304 IF (.NOT.CONVTD) GO TO 495
305 WRITE (LISTPR,930)
306 WRITE (LISTERR,930)
307 WRITE (LISTTY,930)
308 GO TO 910
309 495 DO 490 I=1,CNT
310 SYMBOL=SYM(I)
311 490 CALL RECALC (VALUES(1,I),IDENT(1,I),SYMBOL,TTDI(I),RATIOS(1,I),TOT
312 1ALS(1,I),TYPES(1,I),BARTHS(1,I),NIGGLI(1,I),ADJUST(1,I),NAMES)
313 GO TO 910
314 500 IF (NOTEQ(STMT,'PRINT',5)) GO TO 550
315 C---- PRINT PROCESSOR * * * * *
316 J=1
317 LSTM=LSTM-5
318 K=6
319 WRITE (LISTPR,TFORM) HEADG
320 510 IF (J.EQ.0) GO TO 910
321 J=INDEX(STMT(K),'',LSTM)
322 IF (J.NE.0) GO TO 520
323 LE1=LSTM
324 GO TO 530
325 520 LE1=J-1
326 LSTM=LSTM-J
327 530 CALL PARSE (STMT(K),LE1,NAMES,NUM,ERR,LISTTY,LISTERR)
328 IF (ERR) GO TO 910
329 DO 540 I=1,CNT
330 540 X(I)=EVAL(VALUES(1,I))
331 LE1=K+LE1-1
332 WRITE (LISTPR,800) (STMT(I),I=K,LE1)
333 WRITE (LISTPR,810)
334 WRITE (LISTPR,820) (IDENT(1,I),IDENT(2,I),X(I),I=1,CNT)
335 K=K+J
336 GO TO 510
337 550 IF (NOTEQ(STMT,'CONVERT',7)) GO TO 560
338 C---- VALUE CONVERT PROCESSOR * * * * *
339 IF (LSTM.GT.13) WRITE (LISTERR,900) (STMT(I),I=1,LSTM)
340 IF (.NOT.CONVTD) GO TO 555
341 WRITE (LISTTY,940)
342 WRITE (LISTERR,940)
343 GO TO 910
344 555 CALL CONVER (VALUES,ADJUST,CNT)
345 CONVTD=.TRUE.
346 DO 558 II=1,80
347 I=81-II
348 IF (HEADG(I).EQ.BLANK) GO TO 558
349 DO 557 J=1,12
350 557 HEADG(I+J)=EXTN(J)
351 GO TO 910
352 558 CONTINUE

```

```

353      GO TO 910
354      560 IF (NOTEQ(STMT,'PLOT',4)) GO TO 610
355 C----- X-Y PLOT PROCESSOR * * * * *
356      LSTMT=LSTMT-4
357      STAND=NOTEQ(STMT(5),'(R)',3)
358      K=5
359      IF (STAND) GO TO 570
360      LSTMT=LSTMT-3
361      K=9
362      570 IF (NOTEQ(STMT(K),'HARKER',6)) GO TO 579
363 C----- HARKER SUITE OF PLOTS * * * * *
364      ENCODE (RNAME,970) NAMES(1,1),NAMES(2,1)
365      DECODE (RNAME,740) NMX
366      XMIN=+1.0E+35
367      XMAX=-1.0E+35
368      DO 571 L=1,CNT
369      IF (SWITCH(1)) X(L)=ADJUST(1,L)
370      IF (.NOT.SWITCH(1)) X(L)=VALUES(1,L)
371      XMIN=AMIN1(XMIN,X(L))
372      571 XMAX=AMAX1(XMAX,X(L))
373      IF (XMAX.GT.XMIN) GO TO 572
374      WRITE (LISTTY,950)
375      WRITE (LISTERR,950)
376      GO TO 910
377      572 DO 578 LL=2,21
378      XMIN=+1.0E+35
379      XMAX=-1.0E+35
380      DO 573 L=1,CNT
381      IF (SWITCH(1)) Y(L)=ADJUST(LL,L)
382      IF (.NOT.SWITCH(1)) Y(L)=VALUES(LL,L)
383      XMIN=AMIN1(XMIN,Y(L))
384      573 XMAX=AMAX1(XMAX,Y(L))
385      IF (XMAX.LE.XMIN) GO TO 578
386      ENCODE (RNAME,970) NAMES(1,LL),NAMES(2,LL)
387      DECODE (RNAME,740) NMY
388      CALL PRNT (X,Y,SYM,CNT,NMX,NMY,5,5,STAND,PRNTER,SCALE)
389      IF (PRNTER.AND.SWITCH(1)) WRITE (LISTPR,920)
390      578 CONTINUE
391      GO TO 910
392      579 I=INDEX(STMT(K),'',LSTMT)
393      IF (I.NE.0) GO TO 580
394      WRITE (LISTERR,830) CARD
395      WRITE (LISTTY,830) CARD
396      GO TO 910
397      580 LF1=I-1
398      LF2=LSTMT-I
399      J=I+K
400      CALL PARSE (STMT(K),LF1,NAMES,NUM,ERR,LISTTY,LISTERR)
401      IF (ERR) GO TO 910
402      DO 590 I=1,CNT
403      IF (SWITCH(1)) X(I)=EVAL(ADJUST(1,I))
404      590 IF (.NOT.SWITCH(1)) X(I)=FVAL(VALUES(1,I))
405      CALL PARSE (STMT(J),LF2,NAMES,NUM,ERR,LISTTY,LISTERR)
406      IF (ERR) GO TO 910
407      DO 600 I=1,CNT
408      IF (SWITCH(1)) Y(I)=EVAL(ADJUST(1,I))
409      600 IF (.NOT.SWITCH(1)) Y(I)=FVAL(VALUES(1,I))
410      CALL PRNT (X,Y,SYM,CNT,STMT(K),STMT(J),LF1,LF2,STAND,PRNTER,SCALE)
411      IF (PRNTER.AND.SWITCH(1)) WRITE (LISTPR,920)
412      GO TO 910

```

```

413 610 IF (NOTEQ(STMT,'TERNARY',7)) GO TO 680
414 C----- TERNARY DIAGRAM PROCESSOR * * * * *
415 LSTMT=LSTMT-7
416 I=INDEX(STMT(8),'',LSTMT)
417 IF (I.NE.0) GO TO 630
418 620 WRITE (LISTERR,840) CARD
419 WRITE (LISTTY,840) CARD
420 GO TO 910
421 630 LE1=I-1
422 LSTMT=LSTMT-I
423 I=INDEX(STMT(I+8),'',LSTMT)
424 IF (I.EQ.0) GO TO 620
425 LE2=I-1
426 LE3=LSTMT-I
427 J=LE1+LE2+10
428 K=LE1+9
429 CALL PARSE (STMT(8),LE1,NAMES,NUM,ERR,LISTTY,LISTERR)
430 IF (ERR) GO TO 910
431 DO 640 I=1,CNT
432 640 Y(I)=AMAX1(0.,EVAL(VALUE(1,I)))
433 CALL PARSE (STMT(J),LE3,NAMES,NUM,ERR,LISTTY,LISTERR)
434 IF (ERR) GO TO 910
435 DO 650 I=1,CNT
436 650 X(I)=AMAX1(0.,EVAL(VALUE(1,I)))
437 CALL PARSE (STMT(K),LE2,NAMES,NUM,ERR,LISTTY,LISTERR)
438 IF (ERR) GO TO 910
439 DO 660 I=1,CNT
440 Y1=Y(I)
441 X1=X(I)
442 SUM=X1+Y1+AMAX1(0.,EVAL(VALUE(1,I)))
443 X(I)=0.0
444 Y(I)=0.0
445 IF (SUM.EQ.0.0) GO TO 660
446 Y(I)=100.0*Y1/SUM
447 X(I)=100.0*X1/SUM
448 IF (X(I).GE.0.0.AND.Y(I).GE.0.0) GO TO 660
449 X(I)=0.0
450 Y(I)=0.0
451 660 CONTINUE
452 LSTMT=LSTMT+LE1+8
453 WRITE (LISTPR,TFORM) HEADG
454 WRITE (LISTPR,850) (STMT(I),I=8,LSTMT)
455 WRITE (LISTPR,860)
456 DO 670 I=1,CNT
457 Y1=Y(I)
458 X1=X(I)
459 SUM=SIGN(1.0,Y1)*(100.0-X1-Y1)
460 670 WRITE (LISTPR,870) IDENT(1,I),IDENT(2,I),Y1,SUM,X1,SYM(I)
461 CALL TRIANG (IDENT,X,Y,CNT,LE1,LE2,LE3,SYM,STMT(8),STMT(K),STMT(J)
462 1,PRINTER,SCALE)
463 GO TO 910
464 C----- UNRECOGNIZED COMMAND * * * * *
465 680 WRITE (LISTERR,880) (STMT(I),I=1,LSTMT)
466 WRITE (LISTTY,880) (STMT(I),I=1,LSTMT)
467 GO TO 910
468 690 IF (SWCC) CALL PLOT (0.0,0.0,999)
469 CALL FILES (LISTERR,7)
470 CALL FILES (LISTERR,8)
471 CALL FILES (LISTTY,4)
472 CALL FILES (LISTPR,5)

```

```

473 CALL FILES (INPUT,5)
474 STOP
475 700 FORMAT (/ ' SCALE MUST BE POSITIVE AND LESS THAN OR EQUAL TO 3.0. ' )
476 710 FORMAT (/ ' "DEVICE=CALCOMP" MUST BE SPECIFIED BEFORE SETTING SCALE
477 1. ' )
478 720 FORMAT (/ 1X,2A4, ' DEFINED AS ',80A1)
479 740 FORMAT (80A1)
480 750 FORMAT (/ ' NO MORE THAN 99 NORMS MAY BE STORED. THE LAST NORM WILL
481 1 BE WIPE OUT. ' )
482 760 FORMAT (/ ' STATEMENT LENGTH(160) EXCEEDED ON THE FOLLOWING STATEME
483 1NT: ' / (1X,80A1 / ) , / ' DID YOU FORGET A SEMICOLON? ' )
484 770 FORMAT (/ ' FORMAT COMMAND ERROR (MISSING PARENTHESIS) IN ',80A1)
485 780 FORMAT (/ ' ERROR IN MODIFY COMMAND ON ',80A1)
486 790 FORMAT (/ ' NO MORE THAN 15 NAMES MAY BE DEFINED. DEFINITION IGNORE
487 1D FOR NAME= ',2A4)
488 800 FORMAT (/ ' EVALUATION OF ',40A1)
489 810 FORMAT (/ 6(6X, ' ID ',7X, ' VALUE ' ) / )
490 820 FORMAT (6(4X,A4,A1,F12.3))
491 830 FORMAT (/ ' PLOT COMMAND ERROR ON ',80A1)
492 840 FORMAT (/ ' TERNARY COMMAND ERROR ON ',80A1)
493 850 FORMAT (/ ' TERNARY RATIOS FOR ',100A1)
494 860 FORMAT (/ ' SAMPLE R1 ',6X, ' R2 ',6X, ' R3 SYMBOL ' / )
495 870 FORMAT (2X,A4,A1,3F8.2,4X,A1)
496 880 FORMAT (/ ' UNRECOGNIZED COMMAND GIVEN AS: ' 1X,80A1, ( / 32X,80A1 ) )
497 890 FORMAT (/ ' OXIDE COMMAND CONTAINS A NAME WHICH IS NOT IN THE LIST
498 1 OF ACCEPTABLE OXIDES. ACCEPTABLE OXIDES ARE: ' / 1X,22A4 / 1X,20A4, / / ,
499 2 ' THE UNRECOGNIZED NAME IS ',2A4)
500 900 FORMAT (/ ' THE FOLLOWING COMMAND CONTAINS EXCESSIVE CHARACTERS. ' / /
501 1 1X,20A1 / / ' DID YOU FORGET A SEMICOLON? ' )
502 920 FORMAT (/ 38X, ' NOTE: PLOT IS BASED ON ADJUSTED OXIDES. ' )
503 930 FORMAT (/ ' NORMS CANNOT BE RECALCULATED FROM DATA EXPRESSED IN MOL
504 1FS. ' )
505 940 FORMAT (/ ' DATA HAVE ALREADY BEEN CONVERTED TO MOLES. ' )
506 950 FORMAT (/ ' NO SiO2 GIVEN FOR HARKER SUITE OF PLOTS. ' )
507 970 FORMAT (20A4)
508 END

```

#### Block Data

```

509 BLOCK DATA
510 INTEGER TFORM
511 COMMON /UNITS/ HEADG(92),TFORM(4),INPUT,LISTPR,LISTTY,LISTERR
512 DATA TFORM/'(1h1','10x9','2a1/'','') ' /
513 DATA INPUT,LISTPR,LISTTY,LISTERR/4,3,0,20/
514 END

```

```

515     SUBROUTINE NORM (CARD,OUTM,FORMAT,NCS,TTDI,RATIOS,TOTALS,TYP
516     1FS,BARTHS,VIGGLI,IDENT,NOX,ORDER,ADJUST,NAMES)
517     IMPLICIT REAL(M,N)
518     LOGICAL NOH2O,BARITE,KSPAR,CANCRI,NONORM,CONVTD,STORE,NORMAL,
519     1 PRNTER
520     INTEGER CARD(80),SYM,FORMAT(15),SAM,BUFFER(60),IDENT(2),
521     1 HEADG(92),TFORM(4),RASSYM,I,TT,ORDER(21),NOX,NCS,NAMES(2,81)
522     COMMON /FLAGS/ NOH2O,BARITE,KSPAR,CANCRI,NONORM,CONVTD,STORE,
523     1 NORMAL,PRNTER
524     COMMON /UNITS/ HEADG,TFORM,INPUT,LISTPR,LISTTY,LISTERR
525     COMMON /BULKSTOR/ PAGE(132,180),RASSYM
526 C---- WC IS USED FOR THE WEIGHT COMPONENT OF THE 21 OXIDES * * * *
527     COMMON /ALIGN1/ WC1,WC2,WC3,WC4,WC5,WC6,WC7,WC8,WC9,WC10,WC11,WC12
528     1,WC13,WC14,WC15,WC16,WC17,WC18,WC19,WC20,WC21
529 C---- MM IS USED FOR THE MOLAR MINERALS 1 TO 37; 35 TO 37 ARE DI, HY,
530 C     AND OL RESPECTIVELY.
531     COMMON /ALIGN3/ MM1,MM2,MM3,MM4,MM5,MM6,MM7,MM8,MM9,MM10,MM11,MM12
532     1,MM13,MM14,MM15,MM16,MM17,MM18,MM19,MM20,MM21,MM22,MM23,MM24,MM25,
533     2MM26,MM27,MM28,MM29,MM30,MM31,MM32,MM33,MM34,MM35,MM36,MM37
534 C---- MC IS MOLAR COMPONENT (OXIDES), PM IS WT % MINERALS, PC IS WT %
535 C     COMPONENT (ADJUSTED OXIDES), NP IS THE NORMATIVE PARTITIONING FOR
536 C     CPX, OPX, AND OL.
537     REAL K,MC(21),OUTM(81),WC(21),PM(34),NP(11),MM(37),PC(21),MG,VALUE
538     1S(81, 99),RATIOS(2),TOTALS(2),TYPES(2),BARTHS(21),VIGGLI(12)
539     2 ,RM(21),WM(34),ADJUST(21),ADJ(21,99)
540     EQUIVALENCE (WC1,WC(1)), (MM1,MM(1))
541 C---- RM IS MOLECULAR CONVERSION FACTORS FOR CHEMICAL COMPONENTS * * * *
542     DATA RM /1.664314E-2,9.807652E-3,6.262047E-3,1.391858E-2,2.4806
543     188E-2,1.783186E-2,1.61345E-2,1.061533E-2,5.550825E-2,1.251583E-2,7
544     2.045002E-3,1.409694E-2,8.115645E-3,2.272213E-2,1.249029E-2,2.82063
545     36E-2,5.263601E-2,3.118762E-2,6.579372E-3,1.33852E-2,6.521481E-3/
546 C---- WM IS THE MOLECULAR CONVERSION FOR MINERALS * * * * *
547     DATA WM /60.0848,101.9612,183.3036,556.6734,524.449,278.2102,43
548     16.5038,284.1098,316.3342,116.8856,142.0412,105.989,462.0104,122.06
549     238,154.2882,116.1642,100.3962,131.9312,140.7076,203.7776,172.2436,
550     3231.5383,223.8363,159.6922,151.7449,196.063,135.9732,79.8988,336.2
551     4084,78.0768,119.975,100.0894,84.32135,115.8564/
552     IF (NORMAL) GO TO 4
553     SYM=RASSYM
554     ENCODE(IDENT,610) (CARD(I),I=73,77)
555     GO TO 8
556     4 ENCODE(IDENT,610) (CARD(I),I=76,80)
557     SYM=CARD(4)
558     8 ENCODE(BUFFER,610) CARD
559     IF (NCS.EQ.1) GO TO 20
560     READ (INPUT,10) ((BUFFER(20*(J-1)+I),I=1,20),J=2,NCS)
561     10 FORMAT(20A4)
562     20 DECODE(BUFFER,FORMAT) (PM(I),I=1,NOX)
563     DO 30 I=1,21
564     30 PC(I)=0.0
565     DO 40 I=1,NOX
566     40 J=ORDER(I)
567     40 PC(J)=PM(I)
568     IF (STORE) GO TO 90
569     DO 50 I=1,34
570     50 PM(I)=0.0
571     DO 60 I=1,11
572     60 NP(I)=0.0

```

```

573      GO TO 80
574 C----- RECALCULATE NORMS * * * * *
575      ENTRY RECALC(OUTM,IDENT,SAM,TTDI,RATIOS,TOTALS,TYPES,BARTHS,NIGGLT
576      1,ADJUST)
577      IF (IDENT(1).EQ.'DUMM') RETURN
578      SYM=SAM
579      DO 70 I=1,21
580      70 PC(I)=OUTM(I)
581      80 RATIO=0.0
582      R1=0.0
583      IF (PC(3).NE.0.0) RATIO=PC(4)/PC(3)
584      IF (PC(1).NE.0.0) R1=PC(2)/PC(1)
585      RATIOS(1)=R1
586      RATIOS(2)=RATIO
587      90 SUM=0.0
588 C----- CALCULATE ANALYTICAL SUM
589      DO 100 I=1,21
590      OUTM(I)=PC(I)
591      ADJUST(I)=PC(I)
592      100 SUM=SUM+PC(I)
593      SUM1=SUM
594 C----- ADJUST SUM FOR CL AND F
595      SUM=SUM-0.42*PC(17)-0.23*PC(16)
596      TOTALS(1)=SUM
597      IF (STORE) GO TO 570
598      IF (NOH2O) SUM=SUM-PC(9)
599      IF (NOH2O) PC(9)=0.0
600      IF (NOH2O) WRITE (LISTERR,760) IDENT
601      IF (.NOT.NONORM) GO TO 110
602      WRITE (LISTPR,TFORM) HEADG
603      WRITE (LISTPR,615) IDENT,SYM
604      WRITE (LISTPR,620) (OUTM(I),I=1,21),SUM1,TOTALS(1)
605      IF (.NOT.NOH2O) WRITE (LISTPR,625)
606      IF (NOH2O) WRITE (LISTPR,626)
607      110 SUM=100.0/SUM
608      DO 120 I=1,21
609 C----- NORMALIZE OXIDES TO 100%
610      PC(I)=SUM*PC(I)
611      ADJUST(I)=PC(I)
612 C----- CONVERT OXIDES TO MOLECULAR AMOUNTS
613      MC(I)=PC(I)*RM(I)
614      120 WC(I)=MC(I)
615      IF (.NOT.NONORM) GO TO 130
616      WRITE (LISTPR,630) (ADJUST(I),I=1,11),R1,(MC(I),I=1,11),(ADJUST(I),
617      1 I=12,21),RATIO,(MC(I),I=12,21)
618      130 DO 140 I=1,37
619      140 MM(I)=0.0
620 C----- ADD MNO AND NIO TO FEO
621      WC4=WC4+WC12+WC20
622 C----- ADD BAO TO NA2O OR K2O OR CAO
623      IF (.NOT.BARITE) GO TO 144
624      WC7=WC7+WC21
625      WRITE (LISTERR,730) IDENT
626      GO TO 147
627      144 IF (.NOT.KSPAR) GO TO 145
628      WC9=WC9+WC21
629      WRITE (LISTERR,740) IDENT
630      GO TO 147
631      145 WC6=WC6+WC21
632 C----- CALCULATE APATITE

```

```

633 147 WC6=WC6-3.33333*WC11
634 IF (WC6.GE.0.0) GO TO 150
635 PC(11)=ABS(WC6)/3.33333
636 WC11=WC11-PC(11)
637 PC(11)=PC(11)/RM(11)
638 WRITE (LISTERR,710) IDENT,PC(11),NAMES(1,11),NAMES(2,11)
639 WRITE (LISTTY,710) IDENT,PC(11),NAMES(1,11),NAMES(2,11)
640 WC6=0.0
641 150 MM29=WC11
642 C---- CALCULATE HALITE
643 WC7=WC7-0.5*WC16
644 IF (WC7.GE.0.0) GO TO 160
645 PC(16)=ABS(WC7)/0.5
646 WC16=WC16-PC(16)
647 PC(16)=PC(16)/RM(16)
648 WRITE (LISTERR,710) IDENT,PC(16),NAMES(1,16),NAMES(2,16)
649 WRITE (LISTTY,710) IDENT,PC(16),NAMES(1,16),NAMES(2,16)
650 WC7=0.0
651 160 MM10=0.5*WC16
652 C---- CALCULATE THENARDITE
653 MM11=AMIN1(WC7,WC15)
654 WC7=WC7-MM11
655 WC15=WC15-MM11
656 C---- COMBINE S AND SO3
657 WC18=WC18+WC15
658 C---- CALCULATE PYRITE
659 WC4=WC4-0.5*WC18
660 IF (WC4.GE.0.0) GO TO 170
661 PC(18)=ABS(WC4)/0.5
662 WC18=WC18-PC(18)
663 PC(18)=PC(18)/RM(18)
664 WRITE (LISTERR,710) IDENT,PC(18),NAMES(1,18),NAMES(2,18)
665 WRITE (LISTTY,710) IDENT,PC(18),NAMES(1,18),NAMES(2,18)
666 WC4=0.0
667 170 MM31=0.5*WC18
668 C---- CALCULATE CHROMITE
669 WC4=WC4-WC19
670 IF (WC4.GE.0.0) GO TO 180
671 PC(19)=ABS(WC4)
672 WC19=WC19-PC(19)
673 PC(19)=PC(19)/RM(19)
674 WRITE (LISTERR,710) IDENT,PC(19),NAMES(1,19),NAMES(2,19)
675 WRITE (LISTTY,710) IDENT,PC(19),NAMES(1,19),NAMES(2,19)
676 WC4=0.0
677 180 MM23=WC19
678 C---- CALCULATE ILMENITE
679 MM25=AMIN1(WC4,WC10)
680 WC4=WC4-MM25
681 WC10=WC10-MM25
682 C---- ADJUST F FOR APATITE
683 WC17=WC17-0.666667*MM29
684 IF (WC17.LT.0.0) WC17=0.0
685 C---- CALCULATE FLUORITE
686 WC6=WC6-0.5*WC17
687 IF (WC6.GE.0.0) GO TO 190
688 PC(17)=ABS(WC6)/0.5
689 WC17=WC17-PC(17)
690 PC(17)=PC(17)/RM(17)
691 WRITE (LISTERR,710) IDENT,PC(17),NAMES(1,17),NAMES(2,17)
692 WRITE (LISTTY,710) IDENT,PC(17),NAMES(1,17),NAMES(2,17)

```

```

693      WC6=0.0
694      190 MM30=0.5*WC17
695      IF (.NOT.CANCRI) GO TO 194
696      WRITE (LISTERR,750) IDENT
697 C----- CALCULATE SODIUM CARBONATE IF REQUESTED
698      MM12=AMIN1(WC7,WC14)
699      WC7=WC7-MM12
700      WC14=WC14-MM12
701      IF (WC14.LE.0.0) GO TO 195
702 C----- CALCULATE CALCITE
703      194 MM32=AMIN1(WC6,WC14)
704      WC6=WC6-MM32
705      WC14=WC14-MM32
706 C----- CALCULATE MAGNESITE
707      MM33=AMIN1(WC5,WC14)
708      WC5=WC5-MM33
709      WC14=WC14-MM33
710      IF (WC14.LE.0.0) GO TO 195
711 C----- CALCULATE SIDERITE
712      MM34=AMIN1(WC4,WC14)
713      WC4=WC4-MM34
714      WC14=WC14-MM34
715      IF (WC14.LE.0.0) GO TO 200
716      PC(14)=WC14/RM(14)
717      WRITE (LISTERR,710) IDENT,PC(14),NAMES(1,14),NAMES(2,14)
718      WRITE (LISTTY,710) IDENT,PC(14),NAMES(1,14),NAMES(2,14)
719 C----- ASSIGN ALL MGO TO ENSTATITE
720      195 MM17=WC5
721 C----- CALCULATE ZIRCON
722      200 WC1=WC1-WC13
723      IF (WC1.GE.0.0) GO TO 210
724      WC1=ABS(WC1)
725      WC13=WC13-WC1
726      PC(13)=WC1/RM(13)
727      WRITE (LISTERR,710) IDENT,PC(13),NAMES(1,13),NAMES(2,13)
728      WRITE (LISTTY,710) IDENT,PC(13),NAMES(1,13),NAMES(2,13)
729      WC1=0.0
730      210 MM3=WC13
731 C----- CALCULATE ORTHOCLASE
732      DIFF=WC2-WC8
733      IF (DIFF.GE.0.0) GO TO 220
734      MM4=WC2
735 C----- CALCULATE POTASSIUM METASILICATE
736      MM15=-DIFF
737      WC2=0.0
738      WC8=0.0
739      GO TO 250
740      220 MM4=WC8
741      WC2=DIFF
742 C----- CALCULATE ALBITE
743      DIFF=WC2-WC7
744      WC8=0.0
745      IF (DIFF.GE.0.0) GO TO 230
746      MM5=WC2
747      WC7=-DIFF
748      WC2=0.0
749      GO TO 250
750      230 MM5=WC7
751      WC2=DIFF
752 C----- CALCULATE ANORTHITE

```

```

753      DIFF=WC2-WC6
754      WC7=0.0
755      IF (DIFF.GE.0.0) GO TO 240
756      MM6=WC2
757      WC6=-DIFF
758      WC2=0.0
759      GO TO 250
760      240 MM6=WC6
761      C---- CALCULATE CORUNDUM
762      MM2=DIFF
763      WC2=0.0
764      WC6=0.0
765      C---- CALCULATE TITANITE (SPHENE)
766      250 DIFF=WC10-WC6
767      IF (DIFF.GE.0.0) GO TO 260
768      MM26=WC10
769      WC6=-DIFF
770      GO TO 270
771      260 MM26=WC6
772      C---- CALCULATE RUTILE
773      MM28=DIFF
774      WC6=0.0
775      C---- CALCULATE ACMITE
776      270 DIFF=WC3-WC7
777      IF (DIFF.GE.0.0) GO TO 280
778      MM13=WC3
779      C---- CALCULATE SODIUM METASILICATE
780      MM14=-DIFF
781      C---- CALCULATE FERROSILITE
782      MM18=WC4
783      GO TO 300
784      280 MM13=WC7
785      WC3=DIFF
786      WC7=0.0
787      C---- CALCULATE MAGNETITE
788      DIFF=WC3-WC4
789      IF (DIFF.GE.0.0) GO TO 290
790      MM22=WC3
791      C---- ALTERNATE CALCULATION OF FERROSILITE
792      MM18=-DIFF
793      GO TO 300
794      290 MM22=WC4
795      C---- CALCULATE HEMATITE
796      MM24=DIFF
797      300 SUMMF=MM17+MM18
798      R1=0.0
799      R2=0.0
800      IF (SUMMF.LE.0.0) GO TO 310
801      C---- DETERMINE PARTITIONING OF FEO & MGO FOR PYROXENES & OLIVINE
802      R1=MM17/SUMMF
803      R2=MM18/SUMMF
804      C---- CALCULATE WOLLASTENITE, DIOPSIDE AND HYPERSTHENE
805      310 DIFF=SUMMF-WC6
806      IF (DIFF.LT.0.0) GO TO 320
807      MM35=WC6
808      MM36=DIFF
809      GO TO 330
810      320 MM35=SUMMF
811      MM16=-DIFF
812      C---- BALANCE SILICA

```

```

813 330 WC1=WC1-MM26-4.0*MM13-MM14-MM15-6.0*(MM4+MM5)-MM16-2.0*(MM6+MM35)-
814 1MM36
815 IF (WC1.LT.0.0) GO TO 340
816 C---- EXCESS SILICA IS QUARTZ
817 MM1=WC1
818 GO TO 420
819 C---- STMTS 340 TO 410-ADJUSTS NORM FOR SILICA DEFICIENCY
820 C---- CONVERT HYPERSTHENE TO OLIVINE & SiO2
821 340 WC1=WC1+MM36
822 DIFF=2.0*WC1-MM36
823 IF (DIFF.LT.0.0) GO TO 350
824 MM37=MM36-WC1
825 MM36=DIFF
826 GO TO 420
827 350 MM37=0.5*MM36
828 MM36=0.0
829 C---- CONVERT TILANITE TO PEROSKITE & SiO2
830 WC1=WC1-MM37+MM26
831 IF (WC1.LT.0.0) GO TO 360
832 MM27=MM26-WC1
833 MM26=WC1
834 GO TO 420
835 C---- CONVERT ALBITE TO NEPHELINE & SiO2
836 360 WC1=WC1+6.0*MM5
837 MM27=MM26
838 MM26=0.0
839 DIFF=WC1-2.0*MM5
840 IF (DIFF.LT.0.0.OR.WC1.GT.6.0*MM5) GO TO 370
841 MM8=1.5*MM5-0.25*WC1
842 MM5=0.25*DIFF
843 GO TO 420
844 370 MM8=MM5
845 MM5=0.0
846 C---- CONVERT ORTHOCLASE TO LEUCITE & SiO2
847 WC1=WC1-2.0*MM8+6.0*MM4
848 DIFF=WC1-4.0*MM4
849 IF (DIFF.LT.0.0.OR.WC1.GT.6.0*MM4) GO TO 380
850 MM7=3.0*MM4-0.5*WC1
851 MM4=0.5*DIFF
852 GO TO 420
853 380 MM7=MM4
854 MM4=0.0
855 C---- CONVERT WALLATONITE TO CALCIUM ORTHOSILICATE & SiO2
856 WC1=WC1-4.0*MM7+MM16
857 DIFF1=MM16-WC1
858 DIFF2=2.0*WC1-MM16
859 IF (DIFF1.LT.0.0.OR.DIFF2.LT.0.0) GO TO 390
860 MM21=DIFF1
861 MM16=DIFF2
862 GO TO 420
863 C---- CONVERT DIOPSIDE TO CALCIUM ORTHOSILICATE & OLIVINE & SiO2
864 390 WC1=WC1+2.0*MM35
865 FAC1=2.0*(WC1-MM35)-MM16
866 FAC2=4.0*MM35+MM16-2.0*WC1
867 FAC3=FAC2+2.0*MM16
868 IF (FAC1.LT.0.0.OR.FAC2.LT.0.0.OR.FAC3.LT.0.0) GO TO 400
869 MM21=0.25*FAC3
870 MM37=MM37+0.25*FAC2
871 MM35=0.5*FAC1
872 MM16=0.0

```

```

873      GO TO 420
874 C----- CONVERT LEUCITE TO KALIOPHILITE & SiO2
875      400 MM37=MM37+0.5*MM35
876      MM21=0.5*(MM16+MM35)
877      WC1=WC1-MM35-0.5*MM16+4.0*MM7
878      MM35=0.0
879      MM16=0.0
880      DIFF1=WC1-2.0*MM7
881      DIFF2=WC1-2.0*DIFF1
882      IF (DIFF1.GE.0.0) GO TO 410
883 C----- CALCULATE AMOUNT OF SiO2 DEFICIENCY AS EXCESS OLIVINE
884      MM37=MM37+DIFF1
885      WC1=ABS(WC1)
886      WC5=2.0*R1*ABS(DIFF1)/RM(5)
887      WC4=2.0*R2*ABS(DIFF1)/RM(4)
888      WC1=0.0
889      MM9=MM7
890      MM7=0.0
891      WRITE (LISTTY,720) IDENT,WC5,WC4
892      WRITE (LISTERR,720) IDENT,WC5,WC4
893      GO TO 420
894      410 MM9=0.5*DIFF2
895      MM7=0.5*DIFF1
896 C----- CALCULATE PARTITIONINGS IN CPX, OPX AND OL * * * * *
897      420 DI=MM35
898      DIW0=DI
899      DIEN=R1*DI
900      DIFS=R2*DI
901      HY=MM36
902      HYEN=R1*HY
903      HYFS=R2*HY
904      OL=MM37
905      OLFO=R1*OL
906      MM19=OLFO
907      OLFA=R2*OL
908      MM20=OLFA
909      MM16=MM16+DIW0
910      MM17=DIEN+HYEN
911      MM18=DIFS+HYFS
912      DO 430 I=1,34
913      430 PM(I)=WM(I)*MM(I)
914      IF (.NOT.NONORM) GO TO 440
915      IF (.NOT.NOH2O) WRITE (LISTPR,635)
916      IF (NOH2O) WRITE (LISTPR,636)
917      WRITE (LISTPR,640) (MM(I),I=1,12),(PM(I),I=1,12),(MM(I),I=13,24),
918      1 (PM(I),I=13,24),(MM(I),I=25,34)
919      440 DIFF2=0.0
920      DO 450 I=1,12
921      450 DIFF2=DIFF2+PM(I)
922      DIFF1=DIFF2
923      DO 460 I=13,34
924      460 DIFF1=DIFF1+PM(I)
925      Y=DIFF1-DIFF2
926 C----- CONVERT PARTITIONINGS TO WT %
927      NP(2)=DIW0*WM(16)
928      NP(3)=DIEN*WM(17)
929      NP(4)=DIFS*WM(18)
930      NP(1)=NP(2)+NP(3)+NP(4)
931      NP(6)=HYEN*WM(17)
932      NP(7)=HYFS*WM(18)

```

```

933      NP(5)=NP(6)+NP(7)
934      NP(9)=OLFO*WM(19)
935      NP(10)=OLFA*WM(20)
936      WOL=MM16-DIW0
937      NP(11)=WOL*WM(16)
938      NP(8)=NP(9)+NP(10)
939      TOTALS(2)=DIFF1
940      TYPES(1)=DIFF2
941      TYPES(2)=Y
942      TT0I=PM(1)+PM(4)+PM(5)+AMAX1(PM(7),0.0)+PM(8)+AMAX1(PM(9),0.0)
943      IF (.NOT.NONORM) GO TO 480
944      WRITE (LISTPR,650) (PM(I),I=25,34),DIFF1,DIFF2,Y,DI,DIW0,DIEN,
945      1 DIFS,HY,HYFN,HYES,OL,OLFO,OLFA,WOL,(NP(I),I=1,11)
946      WRITE (LISTPR,660) TT0I
947 C----- CALCULATE BARTH'S CATIONS * * * * *
948      480 DO 490 I=1,21
949      490 WC(I)=MC(I)
950      WC2=2.0*WC2
951      WC3=2.0*WC3
952      WC7=2.0*WC7
953      WC8=2.0*WC8
954      WC9=2.0*WC9
955      WC11=2.0*WC11
956      WC19=2.0*WC19
957      SUM=0.0
958      DO 500 I=1,21
959      500 SUM=SUM+WC(I)
960      SUM=SUM-WC9-WC16-WC17-WC18
961      SUM=100.0/SUM
962      DO 510 I=1,21
963      WC(I)=SUM*WC(I)
964      510 BARTHS(I)=WC(I)
965      IF (.NOT.NONORM) GO TO 520
966      WRITE (LISTPR,690) WC
967 C----- NIGGLI'S VALUES * * * * *
968      520 DO 530 I=1,21
969      530 WC(I)=MC(I)
970      AL=WC2+WC19
971      FM=2.0*WC3+WC4+WC5+WC12+WC20
972      C=WC6+WC21
973      ALK=WC7+WC8
974      SUM=100.0/(AL+FM+C+ALK)
975      AL=SUM*AL
976      NIGGLI(1)=AL
977      FM=SUM*FM
978      NIGGLI(2)=FM
979      C=SUM*C
980      NIGGLI(3)=C
981      ALK=SUM*ALK
982      NIGGLI(4)=ALK
983      SI=SUM*WC1
984      NIGGLI(5)=SI
985      TI=SUM*WC10
986      NIGGLI(6)=TI
987      P=SUM*WC11
988      NIGGLI(7)=P
989      H=SUM*WC9
990      NIGGLI(8)=H
991      K=0.0
992      DIFF1=WC7+WC8

```

```

993      IF (DIFF1.NE.0.0) K=WCR/DIFF1
994      MG=0.0
995      SIP=100.0+4.0*ALK
996      IF (FM.NE.0.0) MG=SUM*WCS/FM
997      IF (ALK.GT.AL) SIP=100.0+3.0*AL+ALK
998      Q7=SI-SIP
999      NIGGLI(9)=K
1000     NIGGLI(10)=MG
1001     NIGGLI(11)=SIP
1002     NIGGLI(12)=Q7
1003     IF (.NOT.NONORM) GO TO 540
1004     WRITE (LISTPR,700) AL,FM,C,ALK,SI,TI,P,H,K,MG,SIP,QZ
1005 540 DO 550 I=1,34
1006     550 OUTM(I+21)=PM(I)
1007     DO 560 I=1,11
1008     560 OUTM(I+55)=NP(I)
1009     570 STORE=.FALSE.
1010     RETURN
1011 C---- CONVERT VALUES TO MOLAR DATA * * * * *
1012     ENTRY CONVER (VALUES,ADJ,TT)
1013     DO 600 I=1,TT
1014     DO 580 J=1,21
1015     VALUES(J,I)=VALUES(J,I)*RM(J)
1016 580 ADJ(J,I)=ADJ(J,I)*RM(J)
1017     DO 590 J=22,55
1018 590 VALUES(J,I)=VALUES(J,I)/WM(J-21)
1019     X1=VALUES(57,I)/WM(16)
1020     VALUES(57,I)=X1
1021     Y1=VALUES(58,I)/WM(17)
1022     VALUES(58,I)=Y1
1023     SUM=VALUES(59,I)/WM(18)
1024     VALUES(59,I)=SUM
1025     VALUES(56,I)=X1+Y1+SUM
1026     X1=VALUES(61,I)/WM(17)
1027     VALUES(61,I)=X1
1028     Y1=VALUES(62,I)/WM(18)
1029     VALUES(62,I)=Y1
1030     VALUES(60,I)=X1+Y1
1031     X1=VALUES(64,I)/WM(19)
1032     VALUES(64,I)=X1
1033     Y1=VALUES(65,I)/WM(20)
1034     VALUES(65,I)=Y1
1035     VALUES(63,I)=X1+Y1
1036 600 VALUES(66,I)=VALUES(66,I)/WM(16)
1037     RETURN
1038 610 FORMAT (80A1)
1039 615 FORMAT (' SAMPLE NO. ',A4,A1,10X,'PLOTING SYMBOL IS ',A1/)
1040 620 FORMAT (' ORIGINAL WT.PCT. OXIDES'/'0 SI02 AL2O3 FE2O3 FEO ',
1041 1'MGO CAO NA2O K2O H2O TI02 P2O5 MNO ZRO2 CO2 ','SO
1042 23 CL F S CR2O3 NIO BAO'/1X,21F6.2// ' SUM OF ORIGINA
1043 3L OXIDES= ',F6.2// ' SUM ADJUSTED FOR F & CL=',F6.2)
1044 625 FORMAT (' OXIDES NORMALIZED TO 100 PERCENT : ')
1045 626 FORMAT (' OXIDES NORMALIZED TO 100 PERCENT : (H2O FREE)')
1046 630 FORMAT (' CONSTITUENTS SI02 AL2O3 FE2O3 FEO',6X,'MGO
1047 1 CAO',6X,'NA2O K2O',6X,'H2O',6X,'TI02',5X,'P2O5 AL2O3/SI02'
1048 2/' PERCENTAGES',11F9.2,F10.3/' MOL. AMTS. ',11F9.4// ' CONSTITUENTS
1049 3 MNO',6X,'ZRO2 CO2',6X,'SO3',7X,'CL',6X,'F',8X,'S',6X,'CR2O3
1050 4 NIO BAO',12X,'FEO/FE2O3'/' PERCENTAGES',10F9.2,F19.3/' MO
1051 5L AMTS. ',10F9.4)
1052 635 FORMAT (' CIPW NORM : ')

```

```

1053 636 FORMAT (/ ' CIPW NORM : (H2O FREE) ' )
1054 640 FORMAT (/ ' MINERALS ' , 9X , ' Q ' , 8X , ' C ' , 8X , ' Z ' , 8X , ' OR ' , 7X , ' AB ' , 7X , ' AN ' ,
1055 17X , ' LC ' , 7X , ' NF ' , 7X , ' KP ' , 7X , ' HL ' , 7X , ' TH ' , 7X , ' NC ' / ' MOL. AMTS. ' , 12F
1056 20.4 / ' PERCENTAGES ' , 12F0.3 / ' OMINERALS ' , 9X , ' AC ' , 7X , ' VS ' , 7X , ' KS ' , 7X ,
1057 3WO ' , 7X , ' FN ' , 7X , ' FS ' , 7X , ' FO ' , 7X , ' FA ' , 7X , ' CS ' , 7X , ' MT ' , 7X , ' CM ' , 7X , ' HM
1058 4 ' / ' MOL. AMTS. ' , 12F0.4 / ' PERCENTAGES ' , 12F0.3 / ' OMINERALS ' , 9X , ' IL ' ,
1059 57X , ' TN ' , 7X , ' PF ' , 7X , ' RU ' , 7X , ' AP ' , 7X , ' FR ' , 7X , ' PR ' , 7X , ' CC ' , 7X , ' MG
1060 6 SD TOTAL SALIC FEMIC / ' MOL. AMTS. ' , 12F0.4 )
1061 650 FORMAT ( ' PERCENTAGES ' , 13F0.3 / ' OMINERALS ' , 9X , ' DI DI-WO ' , 4X , ' DI
1062 1-EN DI-FS HY HY-EN HY-FS OL OL-FO ' , 4X , ' OL-
1063 2FA WOL ' / ' MOL. AMTS. ' , 11F0.4 / ' PERCENTAGES ' , 11F9.3 )
1064 660 FORMAT (/ ' THORNTON + TUTTLE DIFFERENTIATION INDEX = ' , F7.3 )
1065 690 FORMAT ( ' ORBARTHS CATIONS SI AL FF+3 FE+2 MG ' , 6X ,
1066 1 ' CA NA ' , 7X , ' K ' , 7X , ' H ' , 6X , ' TI ' , 7X , ' P ' , 6X , ' MN ' / 1X , 13X , 12F8.2 , / '
1067 20 ' , 25X , ' ZP ' , 7X , ' C ' , 6X , ' S1 ' , 6X , ' CL ' , 7X , ' F ' , 6X , ' S2 ' , 6X , ' CR ' , 6X , ' NI ' ,
1068 36X , ' BA ' / ' ' , 21X , 9F8.2 )
1069 700 FORMAT ( ' ONIGGLI VALUES AL* FM* C* ALK* SI ' , 6X ,
1070 1 ' RI ' , 7X , ' P ' , 7X , ' H ' , 7X , ' K ' , 6X , ' MG ' , 6X , 3HSI ' , 5X , ' OZ ' / ' ' , 13X , 12F8.2 )
1071 710 FORMAT (/ ' SAMPLE ' , A4 , A1 , ' CONTAINS AN EXCESS OF ' , F6.2 , ' WEIGHT P
1072 1ERCENT ' , A4 , A1 / 4X , ' BEYOND THAT USED IN NORMATIVE CALCULATIONS ' )
1073 720 FORMAT (/ ' SAMPLE ' , A4 , A1 , ' CONTAINS TOO LITTLE SiO2 TO COMPUTE NO
1074 1RM ' , / 4X , ' SiO2 DEFICIENCY IS EQUIVALENT TO AN EXCESS OF MgO OF ' ,
1075 2F7.2 , ' WT % ' / 4X , ' AND AN EXCESS OF FeO OF ' , F7.2 , ' WT % . ' )
1076 730 FORMAT (/ ' SAMPLE ' , A4 , A1 , ' --BAO ADDED TO Na2O . ' )
1077 740 FORMAT (/ ' SAMPLE ' , A4 , A1 , ' --BAO ADED TO K2O . ' )
1078 750 FORMAT (/ ' SAMPLE ' , A4 , A1 , ' --NA2CO3 CALCULATION ATTEMPTED . ' )
1079 760 FORMAT (/ ' SAMPLE ' , A4 , A1 , ' --NORM COMPUTED ON WATER FREE BASES . ' )
1080 END

```

```

1081 SUBROUTINE SUMPNT (STMT,LSTMT,CNT,IDENT,NAMES,NOX,ORDER,SYM,NUM)
1082 EXTERNAL SAW (descriptors)
1083 COMMON /FLAGS/ NOH2O,PAD1(4),CONVTD,PAD2(3)
1084 COMMON /UNITS/ HEADG,TFORM,INPUT,LISTPR,LISTTY,LISTERR
1085 COMMON /BULKSTOR/ PAGE,RASSYM
1086 COMMON /MASK/TTDI,ADJUST,VALUES,NIGGLI,BARTHS,RATIOS,TOTALS,TYPES
1087 LOGICAL NOH2O,CONVTD,NOTER
1088 INTEGER STM(160),STMT(LSTMT),RPAREN,SYM(1),NAMER(21),NAMEN(12),
1089 1 HEADG(92),TFORM(4),PAD(2),CNT,ORDER(1),IDENT(2,99),NAMES(2,81),
1090 2 PAGE(132,180)
1091 REAL VALUES(81,99),NIGGLI(12,99),TTDI(99),RATIOS(2,99),
1092 1 TOTALS(2,99),TYPES(2,99),BARTHS(21,99),ADJUST(21,99)
1093 DATA NAMER/'SI','AL','FE+3','FE+2','MG','CA','NA','K','H',
1094 1 'TI','P','MN','ZP','C','S1','CL','F','S2','CR','NI','BA'/
1095 DATA NAMEN/'AL*','FM*','C*','ALK*','SI','RI','P','H','K','MG',
1096 1 'HSI','QZ'//,RPAREN/')'//
1097 K=-12
1098 10 K=K+12
1099 IF (K.GE.CNT) RETURN
1100 CALL MOVE (STMT,STM,LSTMT)
1101 LSTM=LSTMT
1102 LAST=12
1103 IF (K+LAST.GT.CNT) LAST=CNT-K
1104 CALL CLEAR
1105 WRITE (LISTPR,TFORM)HEADG
1106 LENGTH=1
1107 CALL SAW(2,1,'SYMBOL',6)
1108 DO 20 J=1, LAST
1109 PAGE(10*J+ 5,2)=SYM(K+J)
1110 20 CALL SAW (1, 2+10*J,IDENT(1,K+J),5)
1111 25 IF (NOTER(STM,''),1)) GO TO 31
1112 30 CALL OUTPUT (LENGTH)
1113 GO TO 10
1114 31 IF (NOTER(STM,'OXID',4)) GO TO 70
1115 C----- WRITE THE OXIDES * * * * *
1116 I=INDEX(STM,'',LSTM)
1117 IF (I.EQ.0) STM(1)=RPAREN
1118 LSTM=LSTM-I
1119 CALL MOVE (STM(I + 1),STM,LSTM)
1120 LENGTH=LENGTH+2
1121 DO 50 L=1,NOX
1122 I=ORDER(L)
1123 DO 51 N=1,CNT
1124 IF (ABS(VALUES(I,N)) .GT. 1.0E-5) GO TO 52
1125 51 CONTINUE
1126 GO TO 50
1127 52 LENGTH=LENGTH+1
1128 CALL SAW (LENGTH,1,NAMES(1,I),5)
1129 DO 40 J=1, LAST
1130 Z=VALUES(I,K+J)
1131 IF (ABS(Z) .LT. 1.0E-5) GO TO 40
1132 CALL RSW (LENGTH,2 + 10*J,Z,'(F5.2)',5)
1133 40 CONTINUE
1134 50 CONTINUE
1135 IF (CONVTD) GO TO 25
1136 LENGTH=LENGTH+1
1137 CALL SAW (LENGTH,1,'TOTAL(-0)',9)
1138 DO 60 J=1, LAST

```

```

1139      60 CALL RSW (LENGTH, 2+10*J, TOTALS(1,K+J), '(F6.2)', 6)
1140      GO TO 25
1141      70 CONTINUE
1142      IF (NOTEQ(STM, 'BART', 4)) GO TO 100
1143 C----- WRITE BARTH'S CATIONS * * * * *
1144      I=INDEX(STM, ' ', LSTM)
1145      IF (I.EQ.0) STM(1)=RPAREN
1146      LSTM=LSTM-I
1147      CALL MOVE (STM(I + 1), STM, LSTM)
1148      IF (CONVTD) GO TO 25
1149      LENGTH=LENGTH+2
1150      CALL SAW (LENGTH, 1, 15HBARTH'S CATIONS, 15)
1151      DO 90 I=1, 21
1152      DO 71 N=1, CNT
1153      IF (ABS(BARTHS(I, N)) .GT. 1.0E-5) GO TO 72
1154      71 CONTINUE
1155      GO TO 90
1156      72 LENGTH=LENGTH+1
1157      CALL SAW (LENGTH, 1, NAMEP(I), 4)
1158      DO 80 J=1, LAST
1159      Z=BARTHS(I, K+J)
1160      IF (ABS(Z) .LT. 1.0E-5) GO TO 80
1161      CALL RSW (LENGTH, 2 + 10*J, Z, '(F6.2)', 6)
1162      80 CONTINUE
1163      90 CONTINUE
1164      GO TO 25
1165      100 CONTINUE
1166      IF (NOTEQ(STM, 'NIGG', 4)) GO TO 130
1167 C----- WRITE NIGGLI VALUES * * * * *
1168      I=INDEX(STM, ' ', LSTM)
1169      IF (I.EQ.0) STM(1)=RPAREN
1170      LSTM=LSTM-I
1171      CALL MOVE (STM(I + 1), STM, LSTM)
1172      IF (CONVTD) GO TO 25
1173      LENGTH=LENGTH+2
1174      CALL SAW (LENGTH, 1, 'NIGGLI VALUES', 13)
1175      DO 120 I=1, 12
1176      DO 101 N=1, CNT
1177      IF (ABS(NIGGLI(I, N)) .GT. 1.0E-5) GO TO 102
1178      101 CONTINUE
1179      GO TO 120
1180      102 LENGTH=LENGTH+1
1181      CALL SAW (LENGTH, 1, NAMEI(I), 4)
1182      DO 110 J=1, LAST
1183      Z=NIGGLI(I, K+J)
1184      IF (ABS(Z) .LT. 1.0E-5) GO TO 110
1185      CALL RSW (LENGTH, 2 + 10*J, Z, '(F7.2)', 7)
1186      110 CONTINUE
1187      120 CONTINUE
1188      GO TO 25
1189      130 CONTINUE
1190      IF (NOTEQ(STM, 'RATI', 4)) GO TO 160
1191 C----- WRITE THE RATIOS * * * * *
1192      I=INDEX(STM, ' ', LSTM)
1193      IF (I.EQ.0) STM(1)=RPAREN
1194      LSTM=LSTM-I
1195      CALL MOVE (STM(I + 1), STM, LSTM)
1196      IF (CONVTD) GO TO 25
1197      LENGTH=LENGTH+3
1198      CALL SAW (LENGTH, 1, 'AL2O3/SIO2', 10)

```

```

1199      DO 140 J=1, LAST
1200      IF (ABS(RATIOS(1,K+J)).LT.1.0E-5) GO TO 140
1201      CALL RSW (LENGTH, 2+10*J, RATIOS(1,K+J), '(F6.3)', 6)
1202 140 CONTINUE
1203      LENGTH=LENGTH+1
1204      CALL SAW (LENGTH, 1, 'FF0/FE203', 9)
1205      DO 150 J=1, LAST
1206      IF (ABS(RATIOS(2,K+J)).LT.1.0E-5) GO TO 150
1207      CALL RSW (LENGTH, 2+10*J, RATIOS(2,K+J), '(F6.3)', 6)
1208 150 CONTINUE
1209      GO TO 25
1210 160 CONTINUE
1211      IF (NOTEQ(STM, 'ADJUST', 6)) GO TO 300
1212 C----- WRITE THE ADJUSTED OXIDES * * * * *
1213      I=INDEX(STM, ',', LSTN)
1214      IF (I.EQ. 0) STM(1)=RPAREN
1215      LSTN=LSTN-I
1216      CALL MOVE (STM(I+1), STM, LSTN)
1217      LENGTH=LENGTH+2
1218      IF (.NOT. NOH2O) CALL SAW(LENGTH, 1, 'ADJUSTED OXIDES', 15)
1219      IF (NOH2O) CALL SAW(LENGTH, 1, 'ADJUSTED OXIDES - H2O FREE', 26)
1220      DO 301 L=1, NOX
1221      I=ORDER(L)
1222      DO 302 N=1, CNT
1223      IF (ABS(ADJUST(I,N)) .GT. 1.0E-5) GO TO 303
1224 302 CONTINUE
1225      GO TO 301
1226 303 LENGTH=LENGTH+1
1227      CALL SAW(LENGTH, 1, NAMES(1,I), 5)
1228      DO 304 J=1, LAST
1229      Z=ADJUST(I, J+K)
1230      IF (ABS(Z) .LE. 1.0E-5) GO TO 304
1231      CALL RSW(LENGTH, 2+10*J, Z, '(F5.2)', 5)
1232 304 CONTINUE
1233 301 CONTINUE
1234      GO TO 25
1235 300 CONTINUE
1236      IF (NOTEQ(STM, 'D.I.', 4)) GO TO 180
1237 C----- WRITE THORNTON AND TUTTLE'S DIFFERENTIATION INDEX * * * * *
1238      I=INDEX(STM, ',', LSTN)
1239      IF (I.EQ. 0) STM(1)=RPAREN
1240      LSTN=LSTN-I
1241      CALL MOVE (STM(I + 1), STM, LSTN)
1242      IF (CONVTD) GO TO 25
1243      LENGTH=LENGTH+3
1244      CALL SAW (LENGTH, 1, 'D.I.', 4)
1245      DO 170 J=1, LAST
1246      IF (ABS(TTDI(K+J)).LT.1.0E-5) GO TO 170
1247      CALL RSW (LENGTH, 2+10*J, TTDI(K+J), '(F6.3)', 6)
1248 170 CONTINUE
1249      GO TO 25
1250 180 CONTINUE
1251      IF (NOTEQ(STM, 'PART', 4)) GO TO 210
1252 C----- WRITE THE PARTITIONING OF DI, HY AND OL * * * * *
1253      I=INDEX(STM, ',', LSTN)
1254      IF (I.EQ. 0) STM(1)=RPAREN
1255      LSTN=LSTN-I
1256      CALL MOVE (STM(I + 1), STM, LSTN)
1257      LENGTH=LENGTH+2
1258      DO 200 I=56, 66

```

```

1259      DO 181 N=1,CNT
1260      IF (ABS (VALUES (I,N)) .GT. 1.0E-5) GO TO 182
1261 181 CONTINUE
1262      GO TO 200
1263 182 LENGTH=LENGTH+1
1264      J=2
1265      IF (I.EQ.56 .OR. I.EQ.60 .OR. I.EQ.63 .OR. I.EQ.66) J=1
1266      CALL SAW (LENGTH,J,NAMES(1,I),5)
1267      DO 190 J=1, LAST
1268      Z=VALUES (I,K+J)
1269      IF (ABS (Z) .LT. 1.0E-5) GO TO 190
1270      CALL RSW (LENGTH,2 + 10*J,7,'(F6.3)',6)
1271 190 CONTINUE
1272 200 CONTINUE
1273      GO TO 25
1274 210 CONTINUE
1275      IF (NOTEQ (STM,'MINE',4)) GO TO 250
1276 C---- WRITE THE MINERALS * * * * *
1277      I=INDEX (STM,' ',LSTM)
1278      IF (I.EQ.0) STM(1)=RPAREN
1279      LSTM=LSTM-I
1280      CALL MOVE (STM(I + 1),STM,LSTM)
1281      LENGTH=LENGTH+2
1282      IF (.NOT. NOH2O) CALL SAW (LENGTH,1,'NORMATIVE MINERALS',18)
1283      IF (NOH2O) CALL SAW (LENGTH,1,'NORMATIVE MINERALS - H2O FREE',29)
1284      DO 230 I=22,55
1285      DO 211 N=1,CNT
1286      IF (ABS (VALUES (I,N)) .GT. 1.0E-5) GO TO 212
1287 211 CONTINUE
1288      GO TO 230
1289 212 LENGTH=LENGTH+1
1290      CALL SAW (LENGTH,1,NAMES(1,I),5)
1291      DO 220 J=1, LAST
1292      Z=VALUES (I,K+J)
1293      IF (ABS (Z) .LT. 1.0E-5) GO TO 220
1294      CALL RSW (LENGTH,2 + 10*J,7,'(F6.3)',6)
1295 220 CONTINUE
1296 230 CONTINUE
1297      IF (CONVTD) GO TO 25
1298      LENGTH=LENGTH+1
1299      CALL SAW (LENGTH,1,'TOTAL',5)
1300      DO 240 J=1, LAST
1301      IF (ABS (TOTALS (2,K+J)) .LT. 1.0E-5) GO TO 240
1302      CALL RSW (LENGTH,2+10*J,TOTALS (2,K+J),'(F7.3)',7)
1303 240 CONTINUE
1304      LENGTH=LENGTH+1
1305      CALL SAW (LENGTH,2,'SALIC',5)
1306      DO 241 J=1, LAST
1307      IF (ABS (TYPES (1,K+J)) .LT. 1.0E-5) GO TO 241
1308      CALL RSW (LENGTH,2+10*J,TYPES (1,K+J),'(F7.3)',7)
1309 241 CONTINUE
1310      LENGTH=LENGTH+1
1311      CALL SAW (LENGTH,2,'FFMIC',5)
1312      DO 242 J=1, LAST
1313      IF (ABS (TYPES (2,K+J)) .LT. 1.0E-5) GO TO 242
1314      CALL RSW (LENGTH,2+10*J,TYPES (2,K+J),'(F7.3)',7)
1315 242 CONTINUE
1316      GO TO 25
1317 250 CONTINUE
1318      IF (NOTEQ (STM,'USER',4)) GO TO 280

```

```

1319 C---- WRITE THE USER DEFINED VARIABLES * * * * *
1320      I=INDEX(STM,',',LSTM)
1321      IF (I.EQ. 0) STM(1)=RPAREN
1322      LSTM=LSTM-I
1323      CALL MOVE(STM(I+1),STM,LSTM)
1324      IF (NUM.LE. 66) GO TO 25
1325      LENGTH=LENGTH+3
1326      CALL SAW(LENGTH,1,'USER DEFINED VARIABLES',22)
1327      DO 272 I=67,NUM
1328      DO 273 N=1,CNT
1329      IF (ABS(VALUES(I,N)) .GT. 1.0E-5) GO TO 274
1330 273 CONTINUE
1331      GO TO 272
1332 274 LENGTH=LENGTH+1
1333      CALL SAW(LENGTH,1,NAMES(1,I),8)
1334      DO 271 J=1, LAST
1335      Z=VALUES(I,K+J)
1336      IF (ABS(Z) .LT. 1.E-5) GO TO 271
1337      CALL RSX(LENGTH, 2+10*J,Z,'(F7.3)',7)
1338 271 CONTINUE
1339 272 CONTINUE
1340      GO TO 25
1341 280 CONTINUE
1342      WRITE (LISTERR,270) (STM(I),I=1,LSTM)
1343      WRITE (LISTTY,270) (STM(I),I=1,LSTM)
1344      I=INDEX(STM,',',LSTM)
1345      IF (I.EQ.0) GO TO 30
1346      LSTM=LSTM-I
1347      CALL MOVE (STM(I + 1),STM,LSTM)
1348      GO TO 25
1349 270 FORMAT (' FIRST WORD ILLEGAL IN ',80A1)
1350      END

```

#### Function conv

```

1351      FUNCTION CONV (A,N1,N2,F,ERR)
1352      INTEGER A(1),D,E,DIGITS(12),CHARS(17),CODES(17)
1353      LOGICAL ERR,CALLED
1354      DATA DIGITS/'0','1','2','3','4','5','6','7','8','9','.',' ','/,'
1355      1 CALLED/.FALSE./
1356      IF(CALLED) GO TO 5
1357      CALLED=.TRUE.
1358      CALL INIT(CHARS,CODES,17,DIGITS,12)
1359      5 VALUE=0.0
1360      D=E
1361      FRP=.FALSE.
1362      DO 20 I=N1,N2
1363      CALL FIND(940,A(I),INDEX,CHARS,CODES,17)
1364      IF (INDEX-11) 14,10,12
1365      10 D=I-N2
1366      GO TO 20
1367      12 INDEX=1
1368      14 VALUE=10.*VALUE+INDEX-1.
1369      20 CONTINUE
1370      30 CONV=VALUE*10.0**D
1371      RETURN
1372      40 ERR=.TRUE.
1373      VALUE=0.0
1374      GO TO 30
1375      END

```

## Function index

```

1376      FUNCTION INDEX (STRING,CHAR,N)
1377      INTEGER STRING(N),CHAR(1),TANK
1378      DECODE (CHAR,5) TANK
1379      5  FORMAT (A1)
1380      IF (N.LT.0) GO TO 30
1381      DO 10 I=1,N
1382      IF (STRING(I).EQ.TANK) GO TO 20
1383      10 CONTINUE
1384      I=0
1385      20 INDEX=I
1386      RETURN
1387      30 N=-N
1388      DO 40 II=1,N
1389      I=N+1-II
1390      IF (STRING(I).EQ.TANK) GO TO 50
1391      40 CONTINUE
1392      I=0
1393      50 INDEX=I
1394      RETURN
1395      END

```

## Subroutine move

```

1396      SUBROUTINE MOVE (A,B,N)
1397      INTEGER A(1),B(1)
1398      DO 10 I=1,N
1399      10 B(I)=A(I)
1400      RETURN
1401      END

```

## Function noteq

```

1402      LOGICAL FUNCTION NOTEQ(A,B,N)
1403      INTEGER A(1),B(2),TANK(30)
1404      DECODE(B,5) (TANK(I),I=1,N)
1405      5  FORMAT(30A1)
1406      DO 10 I=1,N
1407      IF(A(I).NE.TANK(I)) GO TO 30
1408      10 CONTINUE
1409      NOTEQ=.FALSE.
1410      20 RETURN
1411      30 NOTEQ=.TRUE.
1412      RETURN
1413      END

```

```

1414 SUBROUTINE PRNT (X,Y,SYM,CNT,F1,E2,LE1,LE2,STAND,PRNTER,SIZE)
1415 LOGICAL PRNTER,STAND
1416 INTEGER SYM(1),E1(LE1),E2(LE2),CNT
1417 DIMENSION X(1),Y(1)
1418 IF (PRNTER) GO TO 5
1419 I=-1
1420 IF (STAND) I=1
1421 CALL SCALE(X,10.0,CNT,I)
1422 XMIN=X(CNT+1)
1423 XMAX=X(CNT+2)
1424 CALL SCALE(Y,8.0,CNT,1)
1425 YMIN=Y(CNT+1)
1426 YMAX=Y(CNT+2)
1427 GO TO 40
1428 5 XMAX=X(1)
1429 XMIN=XMAX
1430 YMAX=Y(1)
1431 YMIN=YMAX
1432 DO 10 I=2,CNT
1433 XT=X(I)
1434 YT=Y(I)
1435 IF (XT.LT.XMIN) XMIN=XT
1436 IF (XT.GT.XMAX) XMAX=XT
1437 IF (YT.LT.YMIN) YMIN=YT
1438 IF (YT.GT.YMAX) YMAX=YT
1439 10 CONTINUE
1440 30 IF (STAND) GO TO 40
1441 XT=XMAX
1442 XMAX=XMIN
1443 XMIN=XT
1444 40 CALL PLOT2 (XMAX,XMIN,YMAX,YMIN,PRNTER,SIZE)
1445 DO 50 I=1,CNT
1446 50 CALL PLOT3 (SYM(I),X(I),Y(I))
1447 CALL PLOT4 (LE2,E2,LE1,E1)
1448 RETURN
1449 END

```

```

1450      SUBROUTINE TRIANG(IDENT,X,Y,CNT,LE1,LE2,LE3,SYM,E1,E2,E3,
1451      X PRINTER,SIZE)
1452      EXTERNAL SAW (descriptors)
1453      COMMON /UNITS/ HEADG,TFORM,INPUT,LISTPR,LISTTY,LISTERR
1454      COMMON /BULKSTOR/ PAGE,RASSYM
1455      DIMENSION X(1),Y(1)
1456      INTEGER E1(LE1),E2(LE2),SYM(1),STAR,BLNK,MORE(2),CNT,IDENT(2,99),
1457      1 RAD(2,36),E3(1),ZERO,USCORE,HEADG(92),TFORM(4),PAD(2),
1458      2 PE1(15),PE2(15),PE3(15),PAGE(132,180)
1459      LOGICAL PRINTER,MOD5,UNDERS(51)
1460      DATA BLNK,ZERO,STAR,USCORE,MORE/' ','+', '- ','_','+MOR','E'/
1461      IF (PRINTER) GO TO 70
1462 C----- CONSTRUCT TRIANGLE ON CALCOMP PLOTTER
1463      CALL PACK(E1,PE1,LF1)
1464      CALL PACK(E2,PE2,LE2)
1465      CALL PACK(E3,PE3,LE3)
1466      X1=-0.12*LE2
1467      CALL SYMBOL (X1,-0.3,0.21,PE2,0.0,LE2)
1468      CALL SIDE (0.0,0.0,0.0)
1469      X1=9.08-0.12*LE3
1470      CALL SYMBOL (X1,-0.3,0.21,PE3,0.0,LE3)
1471      CALL SIDE (120.0,9.08,0.0)
1472      X1=4.54-0.12*LE1
1473      CALL SYMBOL (X1,7.96,0.21,PE1,0.0,LE1)
1474      CALL SIDE (-120.0,4.54,7.86)
1475 C----- PLOT POINTS
1476      DO 60 I=1,CNT
1477      Y1=7.864E-2*Y(I)
1478      X1=9.08E-2*X(I)+Y1/1.7321
1479      IF (X1.NE.0.0.OR.Y1.NE.0.0) CALL SYMBOL (X1-0.05,Y1-0.07,0.14/SIZE
1480      X ,SYM(I),0.0,1)
1481      60 CONTINUE
1482      CALL PLOT (15.0,0.0,-3)
1483      RETURN
1484 C----- SUPERIMPOSE TRIANGLE ONTO THE PLOTTING SURFACE PAGE(.).
1485      70 DO 100 I=2,50
1486      LF=51-I
1487      DO 80 J=1,LF
1488      80 PAGE(J,I)=BLNK
1489      LF=LF+1
1490      PAGE(LF,I)=STAR
1491      MOD5=MOD(I-1,5).EQ.0
1492      IF (MOD5) PAGE(LF,I)=ZERO
1493      M=2*I-3
1494      DO 90 J=1,M
1495      LF=LF+1
1496      90 PAGE(LF,I)=BLNK
1497      LF=LF+1
1498      PAGE(LF,I)=STAR
1499      IF (MOD5) PAGE(LF,I)=ZERO
1500      LF=LF+1
1501      DO 100 J=LF,101
1502      100 PAGE(J,I)=BLNK
1503      DO 110 J=1,101
1504      PAGE(J,51)=BLNK
1505      110 PAGE(J,1)=BLNK
1506      PAGE(1,51)=STAR
1507      PAGE(51,1)=STAR

```

```

1508      DO 120 J=3,99,2
1509      PAGE(J,51)=STAR
1510 120 IF (MOD(J,10).EQ.1) PAGE(J,51)=ZERO
1511      PAGE(101,51)=STAR
1512      K=0
1513      DO 121 J=52,100
1514      UNDERS(J-51)=.FALSE.
1515      DO 121 I=1,101
1516 121 PAGE(I,J)=RLNK
1517 C----- START PLOTTING THE POINTS.
1518      DO 150 I=1,CNT
1519      XT=X(I)
1520      YT=Y(I)
1521      IF (XT.EQ.0.0.AND.YT.EQ.0.0) GO TO 150
1522      J=0.5*YT+0.5
1523      J=51-J
1524      IX=XT+0.5*YT+1.5
1525      IF (XT.LT.1.0.OR.YT.LT.1.0.OR.XT+YT.GT.99.0) GO TO 140
1526      NPT=PAGE(IX,J)
1527      IF (NPT.EQ.RLNK) GO TO 140
1528      IF(NPT .EQ. STAR) GO TO 140
1529      IF(NPT .EQ. USCORE) GO TO 140
1530      K=K+1
1531      UNDERS(J)=.TRUE.
1532      PAGE(IX,J+51)=USCORE
1533      IF (K.LE.35) GO TO 130
1534      K=36
1535      BAD(1,36)=MORE(1)
1536      BAD(2,36)=MORE(2)
1537      GO TO 150
1538 130 BAD(1,K)=IDENT(1,I)
1539      BAD(2,K)=IDENT(2,I)
1540      GO TO 150
1541 140 PAGE(IX,J)=SYM(I)
1542 150 CONTINUE
1543      IF (K.EQ.0) GO TO 170
1544      CALL SAW(1,1,'THE FOLLOWING POINTS WERE NOT PLOTTED',37)
1545      CALL SAW(2,1,'BECAUSE THEY WOULD HAVE FALLEN ON A',35)
1546      CALL SAW(3,1,'PREVIOUSLY PLOTTED POINT:',25)
1547      M=3
1548      DO 160 I=1,K
1549      J=MOD(I-1,6)
1550      IF (J.EQ.0) M=M+1
1551      LF=6*J+1
1552 160 CALL SAW(M,LF,BAD(1,I),5)
1553 170 WRITE (LISTPR,TFORM)HEADG
1554      WRITE (LISTPR,180) (E1(I),I=1,LE1)
1555      DO 210 J=1,51
1556      WRITE (LISTPR,190) (PAGE(I,J),I=1,101)
1557      IF(UNDERS(J)) WRITE (LISTPR,201) (PAGE(I,J+51),I=1,101)
1558 210 CONTINUE
1559      WRITE (LISTPR,190) (E2(I),I=1,LE2)
1560      WRITE (LISTPR,200) (E3(I),I=1,LE3)
1561      RETURN
1562 180 FORMAT (' ',55X,40A1)
1563 190 FORMAT (' ',5X,101A1)
1564 200 FORMAT ('+',105X,27A1)
1565 201 FORMAT('+',5X,101A1)
1566      END

```

```

1567      FUNCTION EVAL(VALUE$)
1568      INTEGER TYPE(41),TOP
1569      DIMENSION VALUES(1),STACK(41),POLISH(41)
1570      COMMON /EVALPR/ TYPE,ICT,POLISH
1571      COMMON /UNITS/ PAD(98),LISTTY,LISTERR
1572      I=ICT
1573      TOP=0
1574      DO 340 J=1,I
1575      INDEX=TYPE(J)
1576      IF(INDEX) 290,285,280
1577 280 TOP=TOP+1
1578      STACK(TOP)=VALUES(INDEX)
1579      GO TO 340
1580 285 TOP=TOP+1
1581      STACK(TOP)=POLISH(J)
1582      GO TO 340
1583 290 INDEX=5+INDEX
1584      IF(INDEX.EQ. 0) GO TO 295
1585      VT=STACK(TOP)
1586      TOP=TOP-1
1587      GO TO (310,300,330,320),INDEX
1588 295 STACK(TOP)=-STACK(TOP)
1589      GO TO 340
1590 300 STACK(TOP)=STACK(TOP)*VT
1591      GO TO 340
1592 310 IF(VT.NE. 0.0) GO TO 315
1593      WRITE (LISTTY,312)
1594      WRITE (LISTERR,312)
1595 312 FORMAT('/ DIVIDE BY ZERO ATTEMPTED, HENCE')
1596      GO TO 360
1597 315 STACK(TOP)=STACK(TOP)/VT
1598      GO TO 340
1599 320 STACK(TOP)=STACK(TOP)+VT
1600      GO TO 340
1601 330 STACK(TOP)=STACK(TOP)-VT
1602 340 CONTINUE
1603      IF (TOP.NE.1) GO TO 360
1604      EVAL=STACK(1)
1605 350 RETURN
1606 360 EVAL=0.0
1607      RETURN
1608      END

```

```
1609      SUBROUTINE PACK(FROM,TO,LENGTH)
1610      INTEGER FROM(LENGTH),TO(LENGTH),WORD(1)
1611      IPT=0
1612      N=LENGTH/4
1613      LAST=LENGTH-4*N
1614      IF (N.EQ.0) GO TO 10
1615      DO 5 J=1,N
1616      ENCODE (WORD,1) (FROM(IPT+I),I=1,4)
1617      1 FORMAT(4A1)
1618      TO(J)=WORD(1)
1619      5 IPT=IPT+4
1620      10 IF (LAST.EQ.0) GO TO 20
1621      WORD(1)=' '
1622      ENCODE (WORD,1) (FROM(IPT+I),I=1,LAST)
1623      TO(N+1)=WORD(1)
1624      20 RETURN
1625      END
```

```

1626      SUBROUTINE PARSE(EXPR,L,NAMES,N,ERR,LISTTY,LISTERR)
1627      LOGICAL ERR,POP,NUM,CALLED
1628      INTEGER EXPR(1),NAME(8),BLANK,TM(3,9),SYMBOL(44),TOP,ROW,COLUMN,C,
1629      1ELEMNT,SWITCH,INDEX,TYPE(41),COLS(44),NAMES(2,81),VARBLE(2),
1630      2CHARS(47),CODES(47)
1631      COMMON /FVALPR/ TYPE,ICT,POLISH
1632      DIMENSION POLISH(41),STACK(41)
1633      DATA TM/12,32,0,81,2*41,0,2*51,0,2*61,0,2*71,101,3*0,92,93
1634      1,21,22,23,113,32,33/,UNARY,DIV,PROD,DIFF,PLUS/-5.,-4.,-3.,-2.,-1./
1635      DATA COLS/26*1,11*9,8,3,2,5,4,6,7/,SYMBOL/'A','B','C','D',
1636      1 'F','F','G','H','I','J','K','L','M','N','O','P','Q','R','S',
1637      2 'T','U','V','W','X','Y','Z','0','1','2','3','4','5','6','7',
1638      3 '8','9',',','.',',','+','-','*','/','(',')','/','PAREN,CALLED/0...FALSE./
1639      4 ,BLANK/' '/
1640 C      INITIALIZATION
1641      IF(CALLED) GO TO 20
1642      CALLED=.TRUE.
1643      CALL INIT(CHARS,CODES,47,SYMBOL,44)
1644      20 ERR=.FALSE.
1645          ROW=1
1646          TOP=0
1647          I=0
1648          C=0
1649 C      CONSTRUCT POLISH FORM VIA TRANSITION MATRIX TM
1650      30 C=C+1
1651 C      ARE THERE MORE CHARACTERS TO PROCESS IN EXPR ?
1652          IF (C.LE.L) GO TO 50
1653          IF(ROW.EQ.1) GO TO 460
1654          IF (POP) GO TO 250
1655          IF (NUM) GO TO 40
1656          SWITCH=1
1657 C      GO FIND VALUE AND INSERT IN POLISH STRING
1658          GO TO 370
1659      40 SWITCH=2
1660 C      GO EVALUATE CONSTANT AND INSERT IN POLISH STRING
1661          GO TO 420
1662 C      GET THE CHARACTER. DETERMINE TASK (JOB) AND NEXT-STATE (ROW).
1663      50 NEXT=EXPR(C)
1664          CALL FIND($485,NEXT,J,CHARS,CODES,47)
1665          COLUMN=COLS(J)
1666          ELEMNT=TM(ROW,COLUMN)
1667          JOB=ELEMNT/10
1668          ROW=MOD(ELEMNT,10)
1669          GO TO (60,30,70,130,140,150,160,170,180,230,240), JOB
1670          GO TO 485
1671 C      START AN ITEM
1672      60 NAME(1)=NEXT
1673          NCHAR=1
1674          POP=.FALSE.
1675          NUM=.FALSE.
1676          GO TO 30
1677 C      ADD CURRENT CHARACTER TO PARTIALLY BUILT ITEM
1678      70 NCHAR=NCHAR+1
1679          NAME(NCHAR)=NEXT
1680          GO TO 30
1681      80 IF (POP) GO TO 100
1682          POP=.TRUE.
1683          IF (NUM) GO TO 90

```

```

1684          SWITCH=3
1685 C        GO FIND VALUE AND INSERT IN POLISH STRING
1686          GO TO 370
1687      90 SWITCH=4
1688 C        GO EVALUATE CONSTANT AND INSERT IN POLISH STRING
1689          GO TO 420
1690      100 IF (TOP.EQ.0) GO TO 120
1691          IF (CODE.LT.STACK(TOP)) GO TO 120
1692          SWITCH=5
1693          VALUE=STACK(TOP)
1694          INDEX=VALUE
1695          GO TO 470
1696      110 TOP=TOP-1
1697          GO TO 100
1698      120 TOP=TOP+1
1699          STACK(TOP)=CODE
1700          GO TO 30
1701 C        SET CODE FOR OPERATOR AND GO PROCESS ITEM
1702      130 CODE=DIFF
1703          GO TO 80
1704      140 CODE=PLUS
1705          GO TO 80
1706      150 CODE=DIV
1707          GO TO 80
1708      160 CODE=PROD
1709          GO TO 80
1710      170 CODE=UNARY
1711          GO TO 120
1712 C        RIGHT PAREN SENSED. INSERT ITEM IN POLISH AND POP STACK
1713      180 IF (POP) GO TO 200
1714          POP=.TRUE.
1715          IF (NUM) GO TO 190
1716          SWITCH=6
1717 C        GO FIND VALUE AND INSERT IN POLISH STRING
1718          GO TO 370
1719      190 SWITCH=7
1720 C        GO EVALUATE CONSTANT AND INSERT IN POLISH STRING
1721          GO TO 420
1722      200 IF (TOP.EQ.0) GO TO 460
1723          IF (PAREN.EQ.STACK(TOP)) GO TO 220
1724          SWITCH=8
1725          VALUE=STACK(TOP)
1726          INDEX=VALUE
1727          GO TO 470
1728      210 TOP=TOP-1
1729          GO TO 200
1730      220 TOP=TOP-1
1731          GO TO 30
1732 C        LEFT PAREN SENSED. INSERT IN STACK
1733      230 TOP=TOP+1
1734          STACK(TOP)=PAREN
1735          GO TO 30
1736      240 NAME(1)=NEXT
1737          NCHAR=1
1738          NUM=.TRUE.
1739          POP=.FALSE.
1740          GO TO 30
1741      250 IF (TOP.EQ.0) GO TO 510
1742          SWITCH=9
1743          VALUE=STACK(TOP)

```

```

1744         IF(VALUE.EQ.PAREN) GO TO 460
1745         INDEX=VALUF
1746         GO TO 470
1747     260 TOP=TOP-1
1748         GO TO 250
1749 C         GET INDEX ASSOCIATED WITH NAME
1750     370 NCHAR=NCHAR+1
1751         IF (NCHAR.GT.8) GO TO 390
1752 C         PAD NAME WITH BLANKS
1753         DO 380 J=NCHAR,8
1754     380 NAME(J)=BLANK
1755     390 ENCODE(VARBLE,395) NAME
1756     395 FORMAT(8A1)
1757         DO 400 J=1,N
1758         IF (VARBLE(1).EQ.NAMES(1,J).AND.VARBLE(2).EQ.NAMES(2,J)) GO TO 410
1759     400 CONTINUE
1760         WRITE (LISTTY,490) VARBLE
1761         WRITE (LISTERR,490) VARBLE
1762         GO TO 460
1763     410 INDEX=J
1764         GO TO 470
1765 C         EVALUATE A CONSTANT
1766     420 VALUE=CONV(NAME,1,NCHAR,0,FRR)
1767         INDEX=0
1768         IF (ERR) GO TO 460
1769     470 I=I+1
1770         POLISH(I)=VALUE
1771         TYPE(I)=INDEX
1772         GO TO (250,250,100,100,110,200,200,210,260), SWITCH
1773     460 ERR=.TRUE.
1774 C         PARSE=0.0
1775     485 WRITE (LISTTY,480)(EXPR(J),J=1,L)
1776         WRITE (LISTERR,480)(EXPR(J),J=1,L)
1777     510 ICT=I
1778         RETURN
1779     480 FORMAT (/ ' ERROR IN EXPRESSION ',80A1)
1780     490 FORMAT (/ ' UNDEFINED NAME ',2A4)
1781         END

```

# Subroutine plot2

```

1782     SUBROUTINE PLOT2(XMAX,XMIN,YMAX,YMIN,WPRNT,SIZE)
1783     LOGICAL KNHOR,WPLOT,UNDERS(51),WPRNT
1784     INTEGER LABEL(1),XLAR(1),PLAR(15),PXLAR(15),CH,WL,USCORE,HEADG,
1785     1 TFORM,HC,BL
1786     DIMENSION ARNOS(11)
1787     COMMON /UNITS/ HEADG(92),TFORM(4),INPUT,LISTPR,LISTTY,LISTERR
1788     COMMON /BULKSTOR/ IMAGE(23760),PASSYM
1789     COMMON /PLOTS/ XMIN1,YMIN1,DV,DH,WPLOT,SCALE,UNDERS,VMX,ARNOS
1790     DATA HC,NC,BL,USCORE/'-','+',',','_','/'
1791     WPLOT=WPRNT
1792     IF (WPRNT) GO TO 130
1793     SCALE=SIZE
1794     XMIN1=XMIN
1795     YMIN1=YMIN
1796     DV=XMAX
1797     DH=YMAX
1798     IF (ABS(DV-XMIN1).LT.1.E-6) DV=XMIN1+1.0
1799     IF (ABS(DH-YMIN1).LT.1.E-6) DH=YMIN1+1.0
1800     RETURN
1801 130 VMX=YMAX
1802     DV=(XMAX-XMIN)/100.
1803     DH=(YMAX-YMIN)/50.
1804     DO 140 I=1,11
1805 140 ARNOS(I)=(XMIN+FLOAT((I-1)*10)*DV)
1806     DO 150 I=1,10302
1807 150 IMAGE(I)=BL
1808     DO 180 I=1,51
1809     UNDERS(I)=.TRUE.
1810     I2=I*101
1811     I1=I2-100
1812     KNHOR=MOD(I-1,10).NE.0
1813     IF (KNHOR) GO TO 170
1814     DO 160 J=I1,I2
1815 160 IMAGE(J)=HC
1816 170 CONTINUE
1817     DO 180 J=I1,I2,10
1818     IF (KNHOR) GO TO 180
1819     IMAGE(J)=NC
1820 180 CONTINUE
1821     XMIN1=XMIN-DV/2.
1822     YMIN1=YMIN-DH/2.
1823     RETURN
1824     ENTRY PLOT3(CH,X,Y)
1825     DUM1=(X-XMIN1)/DV
1826     DUM2=(Y-YMIN1)/DH
1827     IF (WPLOT) GO TO 190
1828     CALL SYMBOL (DUM1-0.05,DUM2-0.07,0.14/SCALE,CH,0.0,1)
1829     RETURN
1830 190 J=(51-INT(DUM2)-1)*101+INT(DUM1)+1
1831     NPT=IMAGE(J)
1832     IF (NPT.EQ. BL) GO TO 191
1833     IF (NPT.EQ. HC) GO TO 191
1834     IF (NPT.EQ. NC) GO TO 191
1835     I=(J-1)/101+1
1836     UNDERS(I)=.FALSE.
1837     IMAGE(J+5151)=USCORE
1838 191 IMAGE(J)=CH
1839     RETURN

```

```

1840 ENTRY PLOT4(NL,LABEL,NXL,XLAB)
1841 IF (WPLOT) GO TO 200
1842 CALL PACK(LABEL,PLAB,NL)
1843 CALL PACK(XLAB,PXLAR,NXL)
1844 CALL AXIS (0.0,0.0,PLAB,NL,7.0,90.0,YMIN1,DH)
1845 CALL AXIS (0.0,0.0,PXLAR,-NXL,10.0,0.0,XMIN1,DV)
1846 CALL PLOT(15.0,0.0,-3)
1847 RETURN
1848 200 WRITE (LISTPR,TFORM)HEADG
1849 DO 220 I=1,51
1850 WL=RL
1851 IF (I.LE.NL) WL=LABEL(I)
1852 I2=I*101
1853 I1=I2-100
1854 IF (MOD(I-1,10).EQ.0) GO TO 210
1855 WRITE (LISTPR,205) WL,(IMAGE(J),J=I1,I2)
1856 205 FORMAT(1X,A1,9X,121A1)
1857 GO TO 221
1858 210 CONTINUE
1859 ORDNO=(YMX-FLOAT(I-1)*DH)
1860 WRITE (LISTPR,215) WL,ORDNO,(IMAGE(J),J=I1,I2)
1861 215 FORMAT(1X,A1,F8.3,1X,121A1)
1862 221 IF(UNDERS(I)) GO TO 220
1863 I1=I1+5151
1864 I2=I2+5151
1865 WRITE (LISTPR,222)(IMAGE(J),J=I1,I2)
1866 222 FORMAT(' ',10X,121A1)
1867 220 CONTINUE
1868 WRITE (LISTPR,225) (ABNOS(J),J=1,11)
1869 225 FORMAT(1HOF14.3,10F10.3)
1870 WRITE (LISTPR,240) (XLAB(J),J=1,NXL)
1871 RETURN
1872 240 FORMAT (' ',50X,70A1//)
1873 END

```

#### Subroutine clear

```

1874 SUBROUTINE CLEAR
1875 INTEGER COLUMN,WIDTH,SIZE,AREA(4),BLANK,PAD(86)
1876 INTEGER PAGE(132,180),FORMAT(1),STRING(33)
1877 COMMON /UNITS/ HEADG(92),TFORM(4),INPUT,LISTPR,LISTTY,LISTERR
1878 COMMON /BULKSTOR/ PAGE,RASSYM
1879 DATA BLANK/' '/
1880 DO 10 J=1,180
1881 DO 10 I=1,132
1882 10 PAGE(I,J)=BLANK
1883 GO TO 50
1884 ENTRY RSW(LINE,COLUMN,RS,FORMAT,SIZE)
1885 ENCODE(AREA,FORMAT) RS
1886 DECODE(AREA,15) (PAGE(COLUMN+I-1,LINE),I=1,SIZE)
1887 15 FORMAT(132A1)
1888 GO TO 50
1889 ENTRY SAW(LINE,COLUMN,STRING,SIZE)
1890 DECODE(STRING,15) (PAGE(COLUMN+I-1,LINE),I=1,SIZE)
1891 GO TO 50
1892 ENTRY OUTPUT(LENGTH)
1893 DO 30 J=1,LENGTH
1894 30 WRITE (LISTPR,40)(PAGE(I,J),I=1,132)
1895 40 FORMAT(' ',132A1)
1896 50 RETURN
1897 END

```

## Subroutine init

```

1898      SUBROUTINE INIT(CHARS, CODES, M, SYMBOL, N)
1899      INTEGER FILLER, CHARS(1), CODES(1), SYMBOL(1)
1900      DATA FILLER/'VOID'/
1901      DO 10 I=1, M
1902 10    CHARS(I)=FILLER
1903      DO 40 ICODE=1, N
1904      ICHAR=SYMBOL(ICODE)
1905      L=IABS(ICCHAR)
1906      J=L/M
1907      I=L-M+J
1908      IF (MOD(J, M).EQ.0) J=1
1909 20    IF (CHARS(I+1).EQ.FILLER) GO TO 30
1910      I=MOD(I+J, M)
1911      GO TO 20
1912 30    CHARS(I+1)=ICCHAR
1913 40    CODES(I+1)=ICODE
1914      RETURN
1915      END

```

---

## Subroutine find

```

1916      SUBROUTINE FIND(*, ISYMBL, KODE, CHARS, CODES, M)
1917      INTEGER CHARS(1), CODES(1), FILLER
1918      DATA FILLER/'VOID'/
1919      L=IABS(ISYMBL)
1920      J=L/M
1921      I=L-M+J
1922      IF (MOD(J, M).EQ.0) J=1
1923 50    ICHAR=CHARS(I+1)
1924      IF (ICCHAR.EQ.ISYMBL) GO TO 60
1925      IF (ICCHAR.EQ.FILLER) RETURN 1
1926      I=MOD(I+J, M)
1927      GO TO 50
1928 60    KODE=CODES(I+1)
1929      RETURN
1930      END

```

## Subroutine side

```

1931      SUBROUTINE SIDE (T, X, Y)
1932      CT=COS(1.74533E-2*T)
1933      ST=SIN(1.74533E-2*T)
1934      DO 10 I=0, 9
1935      AL=0.908*I
1936      BL=AL+0.908
1937      IH=2
1938      IF (I.EQ.0) IH=3
1939      CALL PLOT(X+AL*CT-0.086603*ST-0.05*CT, Y+AL*ST+0.086603*CT-0.05*ST,
1940 X 3)
1941      CALL PLOT(X+AL*CT, Y+AL*ST, IH)
1942      CALL PLOT(X+BL*CT, Y+BL*ST, 2)
1943      IF (I.NE.9) CALL PLOT(X+BL*CT-0.086603*ST+0.05*CT,
1944 X Y+BL*ST+0.05*ST+0.086603*CT, 2)
1945 10    CONTINUE
1946      RETURN
1947      END

```

# Subroutine files

```

1948      SUBROUTINE FILES (IN,N)
1949      EXTERNAL SCC(descriptors),DELETE(descriptors)
1950      INTEGER ANSWER,LINFS(32),HEADG,TFORM
1951      CHARACTER TAPEPT*6,INFILE*32,PRFILE*32,BLANK*32
1952      COMMON /UNITS/ HEADG(92),TFORM(4),INPUT,LISTPR,LISTTY,LISTERR
1953      DATA BLANK/" "/
1954      GO TO (30,10,50,70,40,90,100,140),N
1955 C----- OPEN INPUT FILE.
1956      10 PRINT 15
1957      15 FORMAT (/ 'Enter Input File : ',%)
1958      READ 20,INFILE
1959      20 FORMAT (A32)
1960      IF (INFILE.EQ.BLANK) STOP
1961      OPEN (INPUT,FILE=INFILE,FORM="formatted",MODE="in",ERR=18)
1962      RETURN
1963      18 PRINT 19,INFILE
1964      19 FORMAT (/ 'Cannot attach to file ',a32)
1965      CLOSE (INPUT)
1966      GO TO 10
1967 C----- OPEN PRINTER FILE.
1968      30 PRINT 35
1969      35 FORMAT (/ 'Enter Printer File : ',%)
1970      READ 20,PRFILE
1971      OPEN (LISTPR,FILE=PRFILE,FORM="formatted",CARRIAGE=.TRUE.,
1972      1 DEFER=.TRUE.,MODE="out")
1973      RETURN
1974 C----- CLOSE FILE.
1975      40 CLOSE (IN)
1976      RETURN
1977 C----- OPEN TAPE UNIT FOR CALCOMP PLOT, IF NEEDED.
1978      50 PRINT 55
1979      55 FORMAT (/ 'Is any portion of this run going to plot tape ? ',%)
1980      READ 21,ANSWER
1981      21 FORMAT(A3)
1982      IF (ANSWER.NE."yes ") RETURN
1983      PRINT 23
1984      23 FORMAT (/ 'Enter 6-character plot tape number : ',%)
1985      READ 22,TAPEPT
1986      22 FORMAT(A6)
1987      CALL SCC('-un','15','-tp','-nm',TAPEPT)
1988      RETURN
1989 C----- RESET STATUS OF CALCOMP.
1990      70 IF (ANSWER.EQ."yes ") CALL SCC('-reset')
1991      RETURN
1992 C----- OPEN SCRATCH FILE FOR LISTING ERRORS.
1993      90 OPEN (LISTERR,FILE="ERRORS.list",FORM="formatted",MODE="inout")
1994      RETURN
1995 C----- COPY ERRORS FROM SCRATCH FILE TO PRINTER FILE.
1996      100 REWIND LISTERR
1997      ISW=0
1998      110 READ (LISTERR,120,END=130) LINES
1999      120 FORMAT (33A4)
2000      IF (ISW.NE.0) GO TO 125
2001      ISW=1
2002      WRITE (LISTPR,TFORM) HEADG
2003      WRITE (LISTPR,126)
2004      126 FORMAT (/5X,'ERROR MESSAGES AND RUN CONDITIONS'//)
2005      125 WRITE (LISTPR,120) LINES

```

2006 GO TO 110  
2007 130 REWIND LISTERR  
2008 RETURN  
2009 C---- CLOSE AND DELETE SCRATCH FILE.  
2010 140 CLOSE (LISTERR)  
2011 CALL DELETE ("ERRORS.list")  
2012 RETURN  
2013 END