

U.S. Geological Survey
OPEN FILE MAP 79-1314 (D-6)

Photointerpretation and field check 1976
This map has not been edited or reviewed
for conformity with Geological Survey
standards and nomenclature.

NOTE
Information shown is intended as a general guide to ground conditions as of the date of field check. Additional landslides and rockfalls should be anticipated in all map units. The map unit depicts the dominant condition in the area delineated and variations in slope stability may occur at any point in the unit. This map is suitable for general planning purposes and as a supplement to more detailed studies for site selection. The map cannot be used as a substitute for detailed geologic and engineering investigations to establish design and construction criteria of specific sites. Some details may not appear on this map because the description is applicable to a series of maps.

Strip mines (combination of letter symbols indicates complex formed of more than one type of strip mine)

pe	of strip mine)
sh	bench with high wall (in Allegheny County benches and furrows are shown by sh).
sf	furrowed with high wall
sd	multiple furrows and multiple benches
ss	hilltop removed
srg	reclaimed by grading
sru	reclaimed by secondary use
sh/r	regraded in part, high wall remains


Coal refuse banks
r identified on aerial photographs;
not classified in field check


```
rbb  burnt
rbd  burning
rbs  sludge
```

Quarries	
q	quarry site
qub	spoil bank, quarry waste


Gravel pits	g	site of gravel pit
Slides in man-made features	af	earth flow in fill
	a/s	earth flow in strip castings
	a/r	earth flow in coal refuse

PITTSBURGH 1° X 2° SHEET



 AREAS SUSCEPTIBLE TO DEBRIS FLOWS AND DEBRIS
 AVALANCHES

Primarily shallow, narrow ravines and chutes with accumulation of stony colluvium generally 10-ft. (3 m) or less in thickness; susceptible to rapid movement during intense rainfall. Most ravines and chutes designated show evidence of former debris flows and avalanches. Symbol Δ designates historical debris flow or debris avalanche.

 AREAS SUSCEPTIBLE TO ROCKFALL

Steep, locally vertical, natural and man-made slopes and cliffs, 15 ft. (4.5 m) or more high; formed dominantly of sandstone, limestone, sandy shale, mudstone and claystone. Interbedded mudstone, claystone and shale weather rapidly leaving sandstone and limestone rock faces unsupported.


SOIL AND ROCK SUSCEPTIBLE TO LANDSLIDING
Soil and rock similar to that involved in landslides elsewhere in map area; primarily areas underlain by claystone, mudstone and shale associated with other rock types. Rock weathers rapidly on exposure forming clayey soil highly susceptible to sliding. Includes coves (U-shaped, as in low valleys) and cone layers of clayey soil that are very susceptible to sliding where excavation breaks continuity of slope and where overloaded by artificial fill.


☐ AREAS LEAST PRONE TO LANDSLIDES

Map areas in which no patterns or symbols are shown; primarily valley floors, ridge tops and broad benches; modification by excavation and fill may lead to local landslides.

Includes slopes where landslides are sparse

The first five digits of the open file number designate the specific 1:250,000 scale map sheet of which this quadrangle is a part. The last two digits designate the position of the quadrangle in a subdivision of the 1:250,000 scale map based on rows and tiers shown in the diagram to the right. The location of this quadrangle is shown by the black square.

 **ACTIVE OR RECENTLY ACTIVE LANDSLIDE**
Complex landslide composed of earthflow, debris slide, earth- and rock slump. Identified from historical records, and from scars, debris and other field evidence. Ground extremely unstable; sliding accelerated by excavation, loading and changes in drainage conditions. May include areas with several active slides too small to be shown separately. Questioned where doubtful.

 OLD LANDSLIDE

Area of extensive hummocky ground caused by earthflow and earth and rock slump. Lacks clear evidence of active sliding. Relatively stable in natural, undisturbed state, generally not affected by small structures properly sited in areas away from the edge of the toe; can be reactivated by extensive, rapid excavation, loading, and changes in ground water and surface water conditions. Area of old landslide probably includes recent ones not identified from field evidence or otherwise documented. Upslope boundary of landslide generally defined by modified scarp, but downslope (toe) may be gradational and not well defined. Questioned where doubtful.

 COMBINATION LANDSLIDE
Area of recent and old slides in which individual slides are not identified.

V COLLUVIAL SLOPE Valley wall along major streams with slope as steep as 40° (85%); stony, clayey silt soil up to 50 ft. (15 m) thick; commonly buttressed by a terrace or bench at the toe of the slope; very susceptible to sliding by cutting of toe area, removal of terrace or bench, and overloading; slide commonly activated without apparent cause.

SCREE
Residual accumulations of coarse rock material lying on quartzite slopes of the Valley and Ridge province. Generally stable except where subjected to extreme rainfall.