UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COMMONWEALTH OF PENNSYLVANIA
DEPARTMENT OF ENVIRONMENTAL RESOURCES
TOPOGRAPHIC AND GEOLOGIC SURVEY

PLUMVILLE QUADRANGLE
PENNSYLVANIA
7.5 MINUTE SERIES (TOPOGRAPHIC)

Mapped, edited, and published by the Geological Survey

Control by USGS, USC&GS, and USCE

Topography by photogrammetric methods from aerial photographs taken 1967. Field checked 1968

Polyconic projection. 1927 North American datum
10,000-foot grid based on Pennsylvania coordinate system, south zone
1000-meter Universal Transverse Mercator grid ticks, zone 17, shown in blue

UTM GRID AND 1973 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

SCALE 1:24 000

1 MILE
1000 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 KILOMETER

CONTOUR INTERVAL 20 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929

ROAD CLASSIFICATION

Secondary highway, all weather. Light duty road, all weather, hard surface — improved surface
Unimproved road, fair or dry weather
State Route

PENNSYLVANIA
QUADRANGLE LOCATION

PLUMVILLE, PA.
N4045—W7907.5/7.5
1968
PHOTOREVISED 1973

LANDSLIDES AND RELATED FEATURES

OF THE PLUMVILLE, PA. QUADRANGLE

by
John S. Pomeroy
1979

U.S. Geological Survey

OPEN FILE MAP 79-1314 (G-7)

Landslides and related features interpreted from aerial photographs: 1:40,000 (black and white) 1974

Photointerpretation and field check 1976
This map has not been edited or reviewed for conformity with Geological Survey standards and nomenclature.

ACTIVE OR RECENTLY ACTIVE LANDSLIDE
Complex landslide composed of earthflow, debris slide, earth and rock slump. Identified from historical records, and from scarps, debris and other field evidence. Ground extremely unstable; sliding accelerated by excavation, loading and changes in drainage conditions. May include areas with several active slides too small to be shown separately. Questioned where doubtful.

OLD LANDSLIDE
Area of extensive hummocky ground caused by earthflow and earth and rock slump. Lacks clear evidence of active sliding. Relatively stable in natural, undisturbed state, generally not affected by small structures properly sited in areas away from the edge of the toe; can be reactivated by extensive, rapid excavation, loading, and changes in ground water and surface water conditions. Area of old landslide probably includes recent ones not identified from field evidence or otherwise documented. Upslope boundary of landslide generally defined by modified scarps, but downslope (toe) may be gradational and not well defined. Questioned where doubtful.

COMBINATION LANDSLIDE
Area of recent and old slides in which individual slides are not identified.

COLLUVIAL SLOPE
Valley wall along major streams with slope as steep as 40° (85%); stony, clayey silt soil up to 50 ft. (15 m) thick; commonly buttressed by a terrace or bench at the toe of the slope; very susceptible to sliding by cutting of toe area, removal of terrace or bench, and overloading; slide commonly activated without apparent cause.

SCREE
Residual accumulations of coarse rock material lying on quartzite slopes of the Valley and Ridge province. Generally stable except where subjected to extreme rainfall.

COLLUVIAL SLOPES WITH LANDSLIDES
Landslides too small or obscure to map individually.

AREAS SUSCEPTIBLE TO DEBRIS FLOWS AND DEBRIS AVALANCHES
Primarily shallow, narrow ravines and chutes with accumulation of stony colluvium generally 10 ft. (3 m) or less in thickness; susceptible to rapid movement during intense rainfall. Most ravines and chutes designated show evidence of former debris flows and avalanches. Symbol designates historical debris flow or debris avalanche.

AREAS SUSCEPTIBLE TO ROCKFALL
Steep, locally vertical, natural and man-made slopes and cliffs, 15 ft. (4.5 m) or more high; formed dominantly of sandstone, limestone, sandy shale, mudstone and claystone. Interbedded mudstone, claystone and shale weather rapidly leaving sandstone and limestone rock faces unsupported.

SOIL AND ROCK SUSCEPTIBLE TO LANDSLIDING
Soil and rock similar to that involved in landslides elsewhere in map area; primarily areas underlain by claystone, mudstone and shale associated with other rock types. Rock weathers rapidly on exposure forming clayey soil highly susceptible to sliding. Includes coves (U-shaped, shallow valleys) containing thick layers of clayey soil that are very susceptible to sliding where excavation breaks continuity of slope and where overloaded by artificial fill.

AREAS LEAST PRONE TO LANDSLIDES
Map areas in which no patterns or symbols are shown; primarily valley floors, ridge tops and broad benches; modification by excavation and fill may lead to local landslides.
Includes slopes where landslides are sparse.

The first five digits of the open file number designate the specific 1:250,000 scale map sheet of which this quadrangle is a part. The last two digits designate the position of the quadrangle in a subdivision of the 1:250,000 scale map based on rows and tiers shown in the diagram to the right. The location of this quadrangle is shown by the black square.

NOTE

Information shown is intended as a general guide to ground conditions as of the date of field check. Additional landslides and rockfalls should be anticipated in all map units. The map unit depicts the dominant condition in the area delineated and variations in slope stability may occur at any point in the unit. This map is suitable for general planning purposes and as a supplement to more detailed studies for site selection. The map cannot be used as a substitute for detailed geologic and engineering investigations to establish design and construction criteria of specific sites. Some symbols may not appear on this map because the description is applicable to a series of maps.

MAN-MADE FEATURES

Strip mines (combination of letter symbols indicates complex formed of more than one type of strip mine)
- sh — bench with high wall (in Allegheny County benches and furrows are shown by sh).
- sf — furrowed with high wall
- sd — multiple furrows and multiple benches
- ss — hilltop removed
- srg — reclaimed by grading
- sru — reclaimed by secondary use
- sh/r — regraded in part, high wall remains

Coal refuse banks
- r — identified on aerial photographs; not classified in field check
- rb — not burnt nor on fire
- rbb — burnt
- rbd — burning
- rbs — sludge

Quarries
- q — quarry site
- qub — spoil bank, quarry waste

Gravel pits
- g — site of gravel pit

Slides in man-made features
- af — earth flow in fill
- a/s — earth flow in strip castings
- a/r — earth flow in coal refuse

PITTSBURGH 1° X 2° SHEET